



NOTES.—ALL RESISTORS IN OHMS $\frac{1}{2}$ W 10% UNLESS OTHERWISE SPECIFIED

- ALL CAPACITORS IN MFD. & 400V UNLESS OTHERWISE SPECIFIED

- DC VOLTAGE READINGS WITH NO SIGNAL APPLIED USING A 200000A PER VOLT VOLTMETER

-DC VOLTAGE READINGS WITH NO SIGNAL APPLIED USING
-MEMBERS IN PARENTHESES REFER TO ANREG'S PART NO.

- NUMBERS IN PARENTHESES REFER TO AMPEGS PART NO.
- PARTS DESIGNATED BY # ARE IN ZADK MODELS ONLY. THE

- PARTS DESIGNATED BY * ARE IN 240V MODELS ONLY. THE P.T. FOR 240V MODELS HAS BLACK WIRE CONNECTED TO BLUE WIRE.

- D.C. VOLTAGE READINGS ARE POSITIVE WITH RESPECT TO CHASSIS GROUND UNLESS OTHERWISE SPECIFIED.

- CIRCUIT OF CHASSIS MAY VARY SLIGHTLY FROM THAT SHOWN HERE DUE TO NORMAL PRODUCTION CHANGES.

- DYNAC ARE SILICON AXI TYPE 1 AMP 1400 VOLTS DIODES.

Digitized by srujanika@gmail.com



MODEL
V2

U.S. PATENT PENDING.

卷之三十一

BORN BY DATE ID#G. NO. PART NO. RE.

64 671 106.800 14010268 B