




MICROWAVE LO DRIVER 5104C



Microwave LO driver 5104C



Applications

Satellite transmission is a growing medium of communications. It has been necessary to develop new transmission methods to take advantage of this new medium. One of the newest, the NBTDMA (Narrow Band Time Division Multiple Access) combines the advantage of the old methods (high performances, adaptability to transmission speed) with increased access capability.

The transmission/reception equipment from the signal multiplexer up to the microwave antenna must meet these new performance requirements.

The 5104C has been developed to cope with these new applications.

Its frequency range (80 MHz - 130 MHz) and its spectral purity preserve the signal quality up to 11/14 GHz and up to 30 GHz for future applications.

Analog transmissions

- FDMA/SCPC
Frequency stability : 18 Hz/day at 6 GHz
Phase noise : -114 dBc at 100 Hz/Fc

Digital transmissions

- SMS/IBS
Phase noise meets Eutelsat/Intelsat specifications
Spurious \leq -76 dBc
- TDMA (narrow band, broad band)
Phase noise : -105 dBc à 10 Hz/Fc
Low microphony

Satellite positioning

- Ranging
Phase noise : -136 dBc à 100 KHz/Fc
phase stability : \leq 0.3°/h (option 01)
standard BCD programmable
(optional IEEE 488)

Main specifications

High spectral purity :

- -105 dBc at 10 Hz from the carrier
- -136 dBc at 100 kHz from the carrier

Long term frequency stability :

- 1.10^{-8} day after 3 days of uninterrupted operation with a constant temperature.

Long term phase stability :



- $\leq 0.3\%$ /hour after 3 days of uninterrupted operation with a constant temperature (option 01)

Low microphony

Reliability :

- MTBF > 15 000 hours

BCD programming standard, optional IEEE 488



Microwave LO driver

5104C

Specifications

Frequency

Range : 80 to 129,9 MHz

Resolution : 10 Hz

Stability

- 1×10^{-8} per day after 3 days of uninterrupted operation with a constant temperature
- 3×10^{-9} per day after 3 months of uninterrupted operation with a constant temperature
- External time base (quasi integral sampling loop)
- Input : 5, 10 MHz
- Output : 10 MHz
- Level : 0.2 to 1 Vrms/50 Ohms
- Built-in crystal adjusted by front panel potentiometer

Phase stability

$\leq 0,3^\circ/\text{h}$ after 3 days of uninterrupted operation with a constant temperature (option 01 only)

Output level

BNC socket on the rear panel
+ 13 dBm ± 2 dB/50 Ohms

Adjustable by potentiometer:
from + 6 to + 17 dBm/50 Ohms
Regulation :
 ± 1 dB de 0°C à 50°C (T° ref. : 25°C)

Spectral purity

SSB phase noise specified in a 1 Hz band-width for $80 \text{ MHz} < F_c < 128 \text{ MHz}$:

Offset/Fc	10 Hz	100 Hz	1 kHz	10 kHz	100 kHz	300 kHz
Standard (dBc)	- 90	- 106	- 120	- 123	- 133	- 144
Option 01 (dBc)	- 105	- 114	- 124	- 127	- 136	- 148

Spurious signals

- Harmonics : $\leq - 26$ dBc (+ 13 dBm)
- Mains spurious : $\leq - 75$ dBc
- Spurious : $\leq - 76$ dBc (+ 13 dBm)

Remote programming

Settling time ≤ 30 ms
BCD :

- 1 – 2 – 4 – 8 TTL
- "1" level : + 2/+ 5 V 0.1 mA
- "0" level : 0/0.7 V 0.2 mA
- Impedance : 2.2 KOhms
- Optional IEEE 488
- External device
- Talker (L1, LEØ)
- Listener (L2, LEØ)

Power supply

- Mains : 100-120/220-240V (+5% – 10%)
- Frequency : 50/400 Hz
- Consumption : 25 VA

Dimensions

- Height : Front panel : 126 mm (5")
Cabinet : 110 mm (4 1/3")
- Width : 203 mm (8")
- Depth : 410 mm (16 1/8")
- Weight : 6,5 kg (14.3 lbs)

Accessories

Housing : Cabinet for 1 or 2 instruments 19" rack mounting (option 15)

Options

- 01 : High spectral purity
High phase stability
- 03 : External IEEE 488 interface
(5104 B compatible)

The specifications in this document may be changed without notice

Schlumberger Instruments
Victoria Road, FARNBOROUGH
HAMPSHIRE - GO14 7 PW, ENGLAND
Tel.: (0252) 54 44 33
Telex: 858 245 Solfar G

Schlumberger Instruments
50, avenue Jean-Jaurès - BP 630
92542 MONTROUGE Cx - FRANCE
Tél. : 33.1. 47 46 67 00
Télex : 631468 F

Schlumberger Meßgeräte GmbH
Ingolstädter Straße 67 a
D-8000 MÜNCHEN 46-WEST GERMANY
Tel.: 089/31 88 9-0
Telex: 5 215 015 smg d.