


**8-STAGE STATIC BIDIRECTIONAL PARALLEL/SERIAL  
INPUT/OUTPUT BUS REGISTER**


- BIDIRECTIONAL PARALLEL DATA INPUT
- PARALLEL OR SERIAL INPUTS/PARALLEL OUTPUTS
- ASYNCHRONOUS OR SYNCHRONOUS PARALLEL DATA LOADING
- PARALLEL DATA-INPUT ENABLE ON "A" DATA LINES (3-state output)
- DATA RECIRCULATION FOR REGISTER EXPANSION
- MULTIPACKAGE REGISTER EXPANSION
- FULLY STATIC OPERATIONAL DC-TO-5MHz (typ.) AT  $V_{DD} = 10V$
- QUIESCENT CURRENT SPECIFIED TO 20V FOR HCC DEVICE
- 5V, 10V, AND 15V PARAMETRIC RATINGS
- INPUT CURRENT OF 100nA AT 18V AND 25°C FOR HCC DEVICE
- 100% TESTED FOR QUIESCENT CURRENT
- MEETS ALL REQUIREMENTS OF JEDEC TENTATIVE STANDARD N° 13A, "STANDARD SPECIFICATIONS FOR DESCRIPTION OF "B" SERIES CMOS DEVICES"

**DESCRIPTION**

The **HCC4034B** (extended temperature range) and **HCF4034B** (intermediate temperature range) are monolithic integrated circuits, available in 24-lead dual in-line package or ceramic package and plastic micro package. The **HCC/HCF4034B** is a static eight-stage parallel-or serial-input parallel-output register. It can be used to : 1) bidirectionally transfer parallel information between two buses ; 2) convert serial data to parallel form and direct the parallel data to either of two buses ; 3) store (recirculate) parallel data, or 4) accept parallel data from either of two buses and convert that data to serial form. Inputs that control the operations include a single-phase CLOCK (CL), A DATA ENABLE (AE), ASYNCHRONOUS/SYNCHRONOUS (A/S), A-BUS-TO-B-BUS/B-BUS-TO-A-BUS (A/B), and PARALLEL/SERIAL (P/S). Data inputs include 16 bidirectional parallel data lines of which the eight A data lines are inputs (3-state outputs) and the B data lines are outputs (inputs) depending on the signal level on the A/B input. In addition, an input for SERIAL DATA is also provided. All register stages are D-type master-slave flip-flops with separate master and slave clock



**EY**  
(Plastic Package)



**F**  
(Ceramic Frit Seal Package)




**M1**  
(Micro Package)

**ORDER CODES :**

HCC4034BF      HCF4034BEY  
HCC4034BM1      HCF4034BM1

**PIN CONNECTIONS**



S-1461


inputs generated internally to allow synchronous or asynchronous data transfer from master to slave. Isolation from external noise and the effects of loading is provided by output buffering.

**PARALLEL OPERATION** – A high P/S input signal allows data transfer into the register via the parallel data lines synchronously with the positive transition of the clock provided the A/S input is low. If the A/S input is high the transfer is independent of the clock. The direction of data flow is controlled by the A/B input. When this signal is high the A data lines are inputs (and B data lines are outputs) ; a low A/B signal reverses the direction of data flow. The AE-input is an additional feature which allows many registers to feed data to a common bus. The A DATA lines are

enabled only when this signal is high. Data storage through recirculation of data in each register stage is accomplished by making the A/B signal high and the AE signal low.

**SERIAL OPERATION** – A low P/S signal allows serial data to transfer into the register synchronously with the positive transition of the clock. The A/S input is internally disabled when the register is in the serial mode (asynchronous serial operation is not allowed). The serial data appears as output data on either the B lines (when A/B is high) or the A lines (when A/B is low and the AE signal is high). Register expansion can be accomplished by simply cascading **HCC/HCF4034B** packages.

## FUNCTIONAL DIAGRAM



## ABSOLUTE MAXIMUM RATINGS

| Symbol     | Parameter                                                                                                                   | Value                          | Unit     |
|------------|-----------------------------------------------------------------------------------------------------------------------------|--------------------------------|----------|
| $V_{DD}^*$ | Supply Voltage : <b>HCC</b> Types<br><b>HCF</b> Types                                                                       | – 0.5 to + 20<br>– 0.5 to + 18 | V<br>V   |
| $V_i$      | Input Voltage                                                                                                               | – 0.5 to $V_{DD} + 0.5$        | V        |
| $I_i$      | DC Input Current (any one input)                                                                                            | $\pm 10$                       | mA       |
| $P_{tot}$  | Total Power Dissipation (per package)<br>Dissipation per Output Transistor<br>for $T_{op}$ = Full Package-temperature Range | 200<br>100                     | mW<br>mW |
| $T_{op}$   | Operating Temperature : <b>HCC</b> Types<br><b>HCF</b> Types                                                                | – 55 to + 125<br>– 40 to + 85  | °C<br>°C |
| $T_{stg}$  | Storage Temperature                                                                                                         | – 65 to + 150                  | °C       |


Stresses above those listed under "Absolute Maximum Ratings" may cause permanent damage to the device. This is a stress rating only and functional operation of the device at these or any other conditions above those indicated in the operational sections of this specification is not implied. Exposure to absolute maximum rating conditions for external periods may affect device reliability.

## RECOMMENDED OPERATING CONDITIONS

| Symbol   | Parameter                         | Value         | Unit |
|----------|-----------------------------------|---------------|------|
| $V_{DD}$ | Supply Voltage : HCC Types        | 3 to 18       | V    |
|          | HCF Types                         | 3 to 15       | V    |
| $V_I$    | Input Voltage                     | 0 to $V_{DD}$ | V    |
| $T_{op}$ | Operating Temperature : HCC Types | - 55 to + 125 | °C   |
|          | HCF Types                         | - 40 to + 85  | °C   |


## LOGIC DIAGRAMS

## STEERING LOGIC



## LOGIC DIAGRAM AND TRUTH TABLE

## REGISTER STAGE (1 of 8 stages)




## FOR REGISTER INPUT-LEVELS AND RESULTING REGISTER OPERATION

| "A" Enable | P/S | A/B | A/S | Operation*                                                                                               |
|------------|-----|-----|-----|----------------------------------------------------------------------------------------------------------|
| 0          | 0   | 0   | X   | Serial Mode ; Synch. Serial Data Input, "A" Parallel Data Outputs Disabled                               |
| 0          | 0   | 1   | X   | Serial Mode ; Synch. Serial Data Input, "B" Parallel Data Output                                         |
| 0          | 1   | 0   | 0   | Parallel Mode ; "B" Synch. Parallel Data Inputs, "A" Parallel Data Outputs Disabled                      |
| 0          | 1   | 0   | 1   | Parallel Mode ; "B" Asynch. Parallel Data Inputs, "A" Parallel Data Outputs Disabled                     |
| 0          | 1   | 1   | 0   | Parallel Mode ; "A" Parallel Data Inputs Disabled, "B" Parallel Data Outputs, Synch. Data Recirculation  |
| 0          | 1   | 1   | 1   | Parallel Mode ; "A" Parallel Data Inputs Disabled, "B" Parallel Data Outputs, Asynch. Data Recirculation |
| 1          | 0   | 0   | X   | Serial Mode ; Synch. Serial Data Input, "A" Parallel Data Output                                         |
| 1          | 0   | 1   | X   | Serial Mode ; Synch. Serial Data Input, "B" Parallel Data Output                                         |
| 1          | 1   | 0   | 0   | Parallel Mode ; "B" Synch. Parallel Data Input, "A" Parallel Data Output                                 |
| 1          | 1   | 0   | 1   | Parallel Mode ; "B" Asynch. Parallel Data Input, "A" Parallel Data Output                                |
| 1          | 1   | 1   | 0   | Parallel Mode ; "A" Synch. Parallel Data Input, "B" Parallel Data Output                                 |
| 1          | 1   | 1   | 1   | Parallel Mode ; "A" Asynch. Parallel Data Input, "B" Parallel Data Output                                |

\* Outputs change at positive transition of clock in the serial mode and when the A/S control inputs is "low" in the parallel mode.

## TIMING DIAGRAM



## STATIC ELECTRICAL CHARACTERISTICS (over recommended operating conditions)

| Symbol                            | Parameter                      |           | Test Conditions       |                       |                          |                        | Values             |       |        |                   |       |                     | Unit  |      |
|-----------------------------------|--------------------------------|-----------|-----------------------|-----------------------|--------------------------|------------------------|--------------------|-------|--------|-------------------|-------|---------------------|-------|------|
|                                   |                                |           | V <sub>I</sub><br>(V) | V <sub>O</sub><br>(V) | I <sub>O</sub>  <br>(μA) | V <sub>DD</sub><br>(V) | T <sub>Low</sub> * |       | 25°C   |                   |       | T <sub>High</sub> * |       |      |
|                                   |                                |           |                       |                       |                          |                        | Min.               | Max.  | Min.   | Typ.              | Max.  | Min.                |       | Max. |
| I <sub>L</sub>                    | Quiescent Current              | HCC Types | 0/ 5                  |                       |                          | 5                      |                    | 5     |        | 0.04              | 5     |                     | 150   | μA   |
|                                   |                                |           | 0/10                  |                       |                          | 10                     |                    | 10    |        | 0.04              | 10    |                     | 300   |      |
|                                   |                                |           | 0/15                  |                       |                          | 15                     |                    | 20    |        | 0.04              | 20    |                     | 600   |      |
|                                   |                                |           | 0/20                  |                       |                          | 20                     |                    | 100   |        | 0.08              | 100   |                     | 3000  |      |
|                                   |                                | HCF Types | 0/ 5                  |                       |                          | 5                      |                    | 20    |        | 0.04              | 20    |                     | 150   |      |
|                                   |                                |           | 0/10                  |                       |                          | 10                     |                    | 40    |        | 0.04              | 40    |                     | 300   |      |
|                                   |                                |           | 0/15                  |                       |                          | 15                     |                    | 80    |        | 0.04              | 80    |                     | 600   |      |
| V <sub>OH</sub>                   | Output High Voltage            | 0/ 5      |                       | < 1                   | 5                        | 4.95                   |                    | 4.95  |        |                   | 4.95  |                     | V     |      |
|                                   |                                | 0/10      |                       | < 1                   | 10                       | 9.95                   |                    | 9.95  |        |                   | 9.95  |                     |       |      |
|                                   |                                | 0/15      |                       | < 1                   | 15                       | 14.95                  |                    | 14.95 |        |                   | 14.95 |                     |       |      |
| V <sub>OL</sub>                   | Output Low Voltage             | 5/0       |                       | < 1                   | 5                        |                        | 0.05               |       |        | 0.05              |       | 0.05                | V     |      |
|                                   |                                | 10/0      |                       | < 1                   | 10                       |                        | 0.05               |       |        | 0.05              |       | 0.05                |       |      |
|                                   |                                | 15/0      |                       | < 1                   | 15                       |                        | 0.05               |       |        | 0.05              |       | 0.05                |       |      |
| V <sub>IH</sub>                   | Input High Voltage             |           | 0.5/4.5               | < 1                   | 5                        | 3.5                    |                    | 3.5   |        |                   | 3.5   |                     | V     |      |
|                                   |                                |           | 1/9                   | < 1                   | 10                       | 7                      |                    | 7     |        |                   | 7     |                     |       |      |
|                                   |                                |           | 1.5/13.5              | < 1                   | 15                       | 11                     |                    | 11    |        |                   | 11    |                     |       |      |
| V <sub>IL</sub>                   | Input Low Voltage              |           | 4.5/0.5               | < 1                   | 5                        |                        | 1.5                |       |        | 1.5               |       | 1.5                 | V     |      |
|                                   |                                |           | 9/1                   | < 1                   | 10                       |                        | 3                  |       |        | 3                 |       | 3                   |       |      |
|                                   |                                |           | 13.5/1.5              | < 1                   | 15                       |                        | 4                  |       |        | 4                 |       | 4                   |       |      |
| I <sub>OH</sub>                   | Output Drive Current           | HCC Types | 0/ 5                  | 2.5                   |                          | 5                      | − 2                |       | − 1.6  | − 3.2             |       | − 1.15              |       | mA   |
|                                   |                                |           | 0/ 5                  | 4.6                   |                          | 5                      | − 0.64             |       | − 0.51 | − 1               |       | − 0.36              |       |      |
|                                   |                                |           | 0/10                  | 9.5                   |                          | 10                     | − 1.6              |       | − 1.3  | − 2.6             |       | − 0.9               |       |      |
|                                   |                                |           | 0/15                  | 13.5                  |                          | 15                     | − 4.2              |       | − 3.4  | − 6.8             |       | − 2.4               |       |      |
|                                   |                                | HCF Types | 0/ 5                  | 2.5                   |                          | 5                      | − 1.53             |       | − 1.36 | − 3.2             |       | − 1.1               |       |      |
|                                   |                                |           | 0/ 5                  | 4.6                   |                          | 5                      | − 0.52             |       | − 0.44 | − 1               |       | − 0.36              |       |      |
|                                   |                                |           | 0/10                  | 9.5                   |                          | 10                     | − 1.3              |       | − 1.1  | − 2.6             |       | − 0.9               |       |      |
|                                   |                                |           | 0/15                  | 13.5                  |                          | 15                     | − 3.6              |       | − 3.0  | − 6.8             |       | − 2.4               |       |      |
| I <sub>OL</sub>                   | Output Sink Current            | HCC Types | 0/ 5                  | 0.4                   |                          | 5                      | 0.64               |       | 0.51   | 1                 |       | 0.36                |       | mA   |
|                                   |                                |           | 0/10                  | 0.5                   |                          | 10                     | 1.6                |       | 1.3    | 2.6               |       | 0.9                 |       |      |
|                                   |                                |           | 0/15                  | 1.5                   |                          | 15                     | 4.2                |       | 3.4    | 6.8               |       | 2.4                 |       |      |
|                                   |                                | HCF Types | 0/ 5                  | 0.4                   |                          | 5                      | 0.52               |       | 0.44   | 1                 |       | 0.36                |       |      |
|                                   |                                |           | 0/10                  | 0.5                   |                          | 10                     | 1.3                |       | 1.1    | 2.6               |       | 0.9                 |       |      |
|                                   |                                |           | 0/15                  | 1.5                   |                          | 15                     | 3.6                |       | 3.0    | 6.8               |       | 2.4                 |       |      |
| I <sub>IH</sub> , I <sub>IL</sub> | Input Leakage Current          | HCC Types | 0/18                  | Any Input             |                          | 18                     |                    | ± 0.1 |        | ±10 <sup>−5</sup> | ± 0.1 |                     | ± 1   | μA   |
|                                   |                                | HCF Types | 0/15                  |                       |                          | 15                     |                    | ± 0.3 |        | ±10 <sup>−5</sup> | ± 0.3 |                     | ± 1   |      |
| I <sub>OH</sub>                   | 3-State Output Leakage Current | HCC Types | 0/18                  | 0/18                  |                          | 18                     |                    | ± 0.4 |        | ±10 <sup>−4</sup> | ± 0.4 |                     | ± 12  | μA   |
|                                   |                                | HCF Types | 0/15                  | 0/15                  |                          | 15                     |                    | ± 1.0 |        | ±10 <sup>−4</sup> | ± 1.0 |                     | ± 7.5 |      |
| C <sub>I</sub>                    | Input Capacitance              |           |                       | Any Input             |                          |                        |                    |       |        | 5                 | 7.5   |                     |       | pF   |


\* T<sub>Low</sub> = - 55°C for HCC device : - 40°C for HCF device.\* T<sub>High</sub> = + 125°C for HCC device : + 85°C for HCF device.The Noise Margin for both "1" and "0" level is : 1V min. with V<sub>DD</sub> = 5V, 2V min. with V<sub>DD</sub> = 10V, 2.5V min. with V<sub>DD</sub> = 15V.

**DYNAMIC ELECTRICAL CHARACTERISTICS** ( $T_{amb} = 25^{\circ}\text{C}$ ,  $C_L = 50\text{pF}$ ,  $R_L = 200\text{k}\Omega$ ,  
typical temperature coefficient for all  $V_{DD}$  values is  $0.3\%/^{\circ}\text{C}$ , all input rise and fall times =  $20\text{ns}$ )


| Symbol                                         | Parameter                                                                        | Test Conditions |              | Value |      |      | Unit          |
|------------------------------------------------|----------------------------------------------------------------------------------|-----------------|--------------|-------|------|------|---------------|
|                                                |                                                                                  |                 | $V_{DD}$ (V) | Min.  | Typ. | Max. |               |
| $t_{PHL}$ , $t_{PLH}$                          | Propagation Delay Time :<br>A (B) Parallel Data in to<br>B (A) Parallel Data Out |                 | 5            |       | 350  | 700  | ns            |
|                                                |                                                                                  |                 | 10           |       | 120  | 240  |               |
|                                                |                                                                                  |                 | 15           |       | 85   | 170  |               |
| $t_{PLZ}$ , $t_{PHZ}$<br>$t_{PZL}$ , $t_{PZH}$ | 3-state Propagation Delay Time<br>A/B or AE to "A" OUT                           |                 | 5            |       | 200  | 400  | ns            |
|                                                |                                                                                  |                 | 10           |       | 80   | 160  |               |
|                                                |                                                                                  |                 | 15           |       | 60   | 120  |               |
| $t_{THL}$ , $t_{TLH}$                          | Transition Time                                                                  |                 | 5            |       | 100  | 200  | ns            |
|                                                |                                                                                  |                 | 10           |       | 50   | 100  |               |
|                                                |                                                                                  |                 | 15           |       | 40   | 80   |               |
| $t_{setup}$                                    | Data Setup Time Serial Data to<br>Clock                                          |                 | 5            |       | 80   | 160  | ns            |
|                                                |                                                                                  |                 | 10           |       | 30   | 60   |               |
|                                                |                                                                                  |                 | 15           |       | 20   | 40   |               |
|                                                | Parallel Data to Clock                                                           |                 | 5            |       | 25   | 50   | ns            |
|                                                |                                                                                  |                 | 10           |       | 15   | 30   |               |
|                                                |                                                                                  |                 | 15           |       | 10   | 20   |               |
| $t_w$                                          | High-level Pulse Width, AE, P/S,<br>A/S                                          |                 | 5            |       | 175  | 350  | ns            |
|                                                |                                                                                  |                 | 10           |       | 70   | 140  |               |
|                                                |                                                                                  |                 | 15           |       | 40   | 80   |               |
| $f_{CL}$                                       | Maximum Clock Frequency                                                          |                 | 5            | 2     | 4    |      | MHz           |
|                                                |                                                                                  |                 | 10           | 5     | 10   |      |               |
|                                                |                                                                                  |                 | 15           | 7     | 14   |      |               |
| $t_w$                                          | Clock Pulse Width                                                                |                 | 5            |       | 125  | 250  | ns            |
|                                                |                                                                                  |                 | 10           |       | 50   | 100  |               |
|                                                |                                                                                  |                 | 15           |       | 35   | 70   |               |
| $t_r$ , $t_f^*$                                | Clock Input Rise or Fall Time                                                    |                 | 5,10,15      |       |      | 15   | $\mu\text{s}$ |

\* If more than one unit is cascaded.  $t_r$  should be made less than or equal to the sum of the transition time and the fixed propagation delay of the output of the driving stage for the estimated capacitive load.


Typical Output Low (sink) Current Characteristics.




Minimum Output Low (sink) Current Characteristics.



Typical Output High (source) Current Characteristics.




Minimum Output High (source) Current Characteristics.




## TYPICAL APPLICATIONS

16-BIT PARALLEL IN/PARALLEL OUT PARALLEL IN/SERIAL OUT, SERIAL IN/PARALLEL OUT, SERIAL IN/SERIAL OUT REGISTER.




## TYPICAL APPLICATIONS (continued)


## 16-BIT SERIAL IN/GATED PARALLEL OUT REGISTER



## FREQUENCY AND PHASE COMPARATOR.




## TIMING DIAGRAM



## TYPICAL APPLICATIONS (continued)

## SHIFT RIGHT/SHIFT LEFT WITH PARALLEL INPUTS




A "High" ("Low") on the Shift Left/Shift Right input allows serial data on the Shift Left Input (Shift Right Input) to enter the register on the positive transition of the clock signal. A "high" on the "A" Enable Input disables the "A" parallel data lines on Reg. 1 and 2 and enables the "A" data lines on registers 3 and 4 and allows parallel data into registers 1 and 2. Other

logic schemes may be used in place of registers 3 and 4 for parallel loading. When parallel inputs are not used Reg. 3 and 4 and associated logic are not required.


\* Shift Left input must be disabled during parallel entry.

## N-STAGE REGISTER WITH FIXED SERIAL OUTPUT LINE




## TYPICAL APPLICATIONS (continued)

## SAMPLE AND HOLD REGISTER-SERIAL/PARALLEL IN-PARALLEL OUT




## SINGLE-AND DOUBLE-BUS SYSTEMS




The "A" enable (AE) and A/B signals control all combinations of transfer between the registers and bus systems.

## TEST CIRCUITS


### Quiescent Device Current.



### Noise Immunity.




### Input Leakage Current.




## Plastic DIP24 (0.25) MECHANICAL DATA

| DIM. | mm   |       |       | inch  |       |       |
|------|------|-------|-------|-------|-------|-------|
|      | MIN. | TYP.  | MAX.  | MIN.  | TYP.  | MAX.  |
| a1   |      | 0.63  |       |       | 0.025 |       |
| b    |      | 0.45  |       |       | 0.018 |       |
| b1   | 0.23 |       | 0.31  | 0.009 |       | 0.012 |
| b2   |      | 1.27  |       |       | 0.050 |       |
| D    |      |       | 32.2  |       |       | 1.268 |
| E    | 15.2 |       | 16.68 | 0.598 |       | 0.657 |
| e    |      | 2.54  |       |       | 0.100 |       |
| e3   |      | 27.94 |       |       | 1.100 |       |
| F    |      |       | 14.1  |       |       | 0.555 |
| l    |      | 4.445 |       |       | 0.175 |       |
| L    |      | 3.3   |       |       | 0.130 |       |



## Ceramic DIP24 MECHANICAL DATA


| DIM. | mm                    |       |       | inch  |       |       |
|------|-----------------------|-------|-------|-------|-------|-------|
|      | MIN.                  | TYP.  | MAX.  | MIN.  | TYP.  | MAX.  |
| A    |                       |       | 32.3  |       |       | 1.272 |
| B    | 13.05                 |       | 13.36 | 0.514 |       | 0.526 |
| C    | 3.9                   |       | 5.08  | 0.154 |       | 0.200 |
| D    | 3                     |       |       | 0.118 |       |       |
| E    | 0.5                   |       | 1.78  | 0.020 |       | 0.070 |
| e3   |                       | 27.94 |       |       | 1.100 |       |
| F    | 2.29                  |       | 2.79  | 0.090 |       | 0.110 |
| G    | 0.4                   |       | 0.55  | 0.016 |       | 0.022 |
| I    | 1.17                  |       | 1.52  | 0.046 |       | 0.060 |
| L    | 0.22                  |       | 0.31  | 0.009 |       | 0.012 |
| M    | 1.52                  |       | 2.49  | 0.060 |       | 0.098 |
| N1   | 4° (min.), 15° (max.) |       |       |       |       |       |
| P    | 15.4                  |       | 15.8  | 0.606 |       | 0.622 |
| Q    |                       |       | 5.71  |       |       | 0.225 |



P058C

## SO24 MECHANICAL DATA

| DIM. | mm         |       |       | inch  |       |       |
|------|------------|-------|-------|-------|-------|-------|
|      | MIN.       | TYP.  | MAX.  | MIN.  | TYP.  | MAX.  |
| A    |            |       | 2.65  |       |       | 0.104 |
| a1   | 0.10       |       | 0.20  | 0.004 |       | 0.007 |
| a2   |            |       | 2.45  |       |       | 0.096 |
| b    | 0.35       |       | 0.49  | 0.013 |       | 0.019 |
| b1   | 0.23       |       | 0.32  | 0.009 |       | 0.012 |
| C    |            | 0.50  |       |       | 0.020 |       |
| c1   | 45° (typ.) |       |       |       |       |       |
| D    | 15.20      |       | 15.60 | 0.598 |       | 0.614 |
| E    | 10.00      |       | 10.65 | 0.393 |       | 0.420 |
| e    |            | 1.27  |       |       | 0.05  |       |
| e3   |            | 13.97 |       |       | 0.55  |       |
| F    | 7.40       |       | 7.60  | 0.291 |       | 0.299 |
| L    | 0.50       |       | 1.27  | 0.19  |       | 0.050 |
| S    | 8° (max.)  |       |       |       |       |       |



Information furnished is believed to be accurate and reliable. However, SGS-THOMSON Microelectronics assumes no responsibility for the consequences of use of such information nor for any infringement of patents or other rights of third parties which may result from its use. No license is granted by implication or otherwise under any patent or patent rights of SGS-THOMSON Microelectronics. Specifications mentioned in this publication are subject to change without notice. This publication supersedes and replaces all information previously supplied. SGS-THOMSON Microelectronics products are not authorized for use as critical components in life support devices or systems without express written approval of SGS-THOMSON Microelectronics.

© 1994 SGS-THOMSON Microelectronics - All Rights Reserved

SGS-THOMSON Microelectronics GROUP OF COMPANIES

Australia - Brazil - France - Germany - Hong Kong - Italy - Japan - Korea - Malaysia - Malta - Morocco - The Netherlands -  
Singapore - Spain - Sweden - Switzerland - Taiwan - Thailand - United Kingdom - U.S.A