



LC86F1216A

8-Bit Single Chip Microcontroller with 16K-Byte ROM and 1220-Byte RAM On Chip

Preliminary

Overview

The LC86F1216A is an 8-bit single chip microcontroller with the following on-chip functional blocks:

- CPU: Operable at a minimum bus cycle time of 0.5μs
 - On-chip Flash EEPROM capacity: 144 Kbytes
 - On-chip RAM capacity: 1222 bytes
 - Dot matrix liquid crystal display controller / driver
 - 16-bit timer/counter (or two channels × 8-bit timer)
 - 16-bit timer/PWM (or two channels × 8-bit timer)
 - Serial interface circuit
- All of the above functions are fabricated on a single chip.

Features

- | | | |
|---------------------------------|--|--|
| (1)Flash EEPROM: | 64K × 8 bits: | (program/data area) + 64K × 8 bits (data area) |
| | 16K × 8 bits: | (program area) |
| (2) Mask ROM: | 4K × 8 bits: | (4K: BIOS program area) |
| (3) Random Access Memory (RAM): | 512 × 8 bits (calculation area) + 512 × 8 bits | |
| | 198 × 8 bits (display area) | |
| (4) Bus Cycle Time | | |

Bus Cycle Time	Cycle Time	System Clock Oscillation	Oscillation Frequency	Voltage	Notes
0.5μs	1.0μs	Ceramic	6MHz	3.15–3.85V	OCR7 = 1
3.8μs	7.5μs	External RC	600kHz		OCR7 = 1
93μs	183μs	X'tal	32.768kHz		OCR7 = 1

Note: Bus cycle time means cycle time of reading ROM. OCR7: Bit 7 of the oscillation control register

- (5) Ports
- Input / Output Ports: 2 ports (16 terminals)
 - Input port: 1 port (4 terminals)

- Any and all SANYO products described or contained herein do not have specifications that can handle applications that require extremely high levels of reliability, such as life-support systems, aircraft's control systems, or other applications whose failure can be reasonably expected to result in serious physical and/or material damage. Consult with your SANYO representative nearest you before using any SANYO products described or contained herein in such applications.
- SANYO assumes no responsibility for equipment failures that result from using products at values that exceed, even momentarily, rated values (such as maximum ratings, operating condition ranges, or other parameters) listed in products specifications of any and all SANYO products described or contained herein.

- (6) Dot matrix liquid crystal display controller / driver
 - Display duty: 1/33 duty
 - Display bias: 1/5 bias
 - LCD power supply (max. 6V)
 - LCD driver (max. 1584 dots capability)
 - Common output ports: 33 ports
 - Segment output ports: 48 ports
 - Externally boosted clock
- (7) Serial interfaces
 - Synchronous 8-bit serial interface × 2 (with 8-bit baud rate generator)
- (8) Timers
 - Timer 0 (T0H/T0L)
 - 16-bit timer/counter
 - Timer 1 (T1H/T1L)
 - 16-bit timer/PWM
- (9) Interrupts
 - 13 sources 10 vectored interrupts
- (10) Sub-routine stack level
 - A maximum of 128 levels (stack is built in the internal RAM)
- (11) 3 oscillation circuits
 - External RC oscillation circuit / CF oscillation circuit / X'tal oscillation circuit
- (12) Power voltage
 - VDD = 3.15V – 3.85V
- (13) Shipping form
 - Chip or SQFP144
- (14) Flash memory
 - Erasing block unit size: 128 bytes
 - Erasing / writing voltage range: 3.15V – 5.5V
 - Maximum number of erase-write cycle: 50,000 times (Ta = +25°C) (with memory management program)


Note

The microcontroller will malfunction if the power supply voltage is less than the specified operable supply voltage. To prevent a malfunction, the low voltage detect circuit should be connected externally, and the voltage should always be set to the proper level. If the power supply voltage becomes lower than the voltage which is detected by the low voltage detect reset IC, then the microcontroller should be reset to restore stable operation. Use the low voltage detect reset IC which detects the lowest specification voltage of the power supply.

We cannot ensure the integrity of the block data, if the microcontroller is reset while writing to the flash memory. Therefore, in such a case, we recommend disabling any flash writing operation by user's program when the voltage decreases to a level just above the voltage which is detected by the low voltage detect reset IC.

Pin Assignment


SQFP144




Package Dimension

(unit : mm)

3214



SANYO : SQFP-144



Pad Name and Coordinates Table

PAD No.	Pin Name	X-cord	Y-cord	SQFP-144	PAD No.	Pin Name	X-cord	Y-cord	SQFP-144	PAD No.	Pin Name	X-cord	Y-cord	SQFP-144
1	NCEXT	-2965	-3540	1	47	C32	3333	-698	49	93	S18	-1139	3539	97
2	SUPCLK	-2791	-3540	2	48	C31	3333	-524	50	94	S17	-1313	3539	98
3	VDD	-2617	-3540	3	49	C30	3333	-350	51	95	S16	-1486	3539	99
4	NCTE	-2443	-3540	4	50	C29	3333	-176	52	96	S15	-1660	3539	100
5	NCTD	-2269	-3540	5	51	C28	3333	-2	53	97	S14	-1834	3539	101
6	NCTC	-2096	-3540	6	52	C27	3333	171	54	98	S13	-2008	3539	102
7	RCOUT	-1922	-3540	7	53	C26	3333	345	55	99	S12	-2182	3539	103
8	RCIN	-1748	-3540	8	54	C25	3333	519	56	100	S11	-2356	3539	104
9	NCT2	-1574	-3540	9	55	C24	3333	693	57	101	S10	-2530	3539	105
10	NCT1	-1400	-3540	10	56	C23	3333	867	58	102	S9	-2703	3539	106
11	TEST1	-1226	-3540	11	57	C22	3333	1041	59	103	S8	-2877	3539	107
12	TEST2	-1052	-3540	12	58	C21	3333	1215	60	104	S7	-3333	2992	110
13	RES#	-879	-3540	13	59	C20	3333	1388	61	105	S6	-3333	2818	111
14	VDD	-705	-3540	14	60	C19	3333	1562	62	106	S5/A11	-3333	2644	112
15	XT1	-531	-3540	15	61	C18	3333	1736	63	107	S4/A9	-3333	2470	113
16	XT2	-357	-3540	16	62	C17	3333	1910	64	108	S3/A8	-3333	2296	114
17	VSS	-183	-3540	17	63	S48	3333	2084	65	109	S2/A13	-3333	2122	115
18	CF1	-9	-3540	18	64	S47	3333	2258	66	110	S1/A14	-3333	1949	116
19	CF2	165	-3540	19	65	S46	3333	2432	67	111	WE#	-3333	1749	117
20	VDD	338	-3540	20	66	S45	3333	2605	68	112	VDD	-3333	1549	118
21	P70	512	-3540	21	67	S44	3333	2779	69	113	EP	-3333	1375	119
22	P71	686	-3540	22	68	S43	3333	2953	70	114	F/MSEL	-3333	1202	120
23	P72	860	-3540	23	69	S42	3333	3127	71	115	C1/A17	-3333	1010	121
24	P73	1034	-3540	24	70	S41	2860	3539	74	116	C2/A16	-3333	836	122
25	P30	1208	-3540	25	71	S40	2686	3539	75	117	C3/A15	-3333	662	123
26	P31	1382	-3540	26	72	S39	2512	3539	76	118	C4/A12	-3333	488	124
27	P32	1556	-3540	27	73	S38	2339	3539	77	119	C5/A7	-3333	314	125
28	P33	1729	-3540	28	74	S37	2165	3539	78	120	C6/A6	-3333	140	126
29	P34/A3	1903	-3540	29	75	S36	1991	3539	79	121	C7/A5	-3333	-34	127
30	P35/A2	2077	-3540	30	76	S35	1817	3539	80	122	C8/A4	-3333	-207	128
31	P36/A1	2251	-3540	31	77	S34	1643	3539	81	123	C9	-3333	-381	129
32	P37/A0	2425	-3540	32	78	S33	1469	3539	82	124	C10	-3333	-555	130
33	P10/DQ0	2599	-3540	33	79	S32	1295	3539	83	125	C11	-3333	-729	131
34	P11/DQ1	2773	-3540	34	80	S31	1122	3539	84	126	C12	-3333	-903	132
35	P12/DQ2	2946	-3540	35	81	S30	948	3539	85	127	C13	-3333	-1077	133
36	VSS	3333	-2756	39	82	S29	774	3539	86	128	C14	-3333	-1251	134
37	VSS	3333	-2582	39	83	S28	600	3539	87	129	C15	-3333	-1425	135
38	P13/DQ3	3333	-2408	40	84	S27	426	3539	88	130	C16	-3333	-1598	136
39	P14/DQ4	3333	-2234	41	85	S26	252	3539	89	131	VSS	-3333	-1772	137
40	P15/DQ5	3333	-2061	42	86	S25	78	3539	90	132	V1	-3333	-1946	138
41	P16/DQ6	3333	-1887	43	87	S24	-95	3539	91	133	V2	-3333	-2120	139
42	P17/DQ7	3333	-1713	44	88	S23	-269	3539	92	134	V3	-3333	-2294	140
43	CE#	3333	-1539	45	89	S22	-443	3539	93	135	V4	-3333	-2468	141
44	A10	3333	-1365	46	90	S21	-617	3539	94	136	V5	-3333	-2642	142
45	OE#	3333	-1191	47	91	S20	-791	3539	95	137	VLCD	-3333	-2815	143
46	C33	3333	-872	48	92	S19	-965	3539	96					


Continued.

Terminal	Pin No.	Pad No.	Input/ Output	Function Description
NCT1, NCT2, NCTC, NCTD, NCTE	10,9, 6,5 4	10,9 6,5 4	-	·Test terminal Leave open circuit.
$\overline{CE}$, $\overline{OE}$, $\overline{WE}$	45,47,117	43,45	I	·Memory test terminal Pull up to VDD.
EP, A10	119,46	113,44	I	·Memory test terminal Leave open circuit.
F/M_SEL	120	114	I	·Connect to VDD.
NC	36,37,38, 72,73,108, 109,144		-	·Unused terminal Leave open circuit.
NCEXT	1	1	I	·Test terminal Connect this terminal to VSS.

*Initial Port Status

Terminal	Input/Output	Pull-up Resistor Status
Port1	I	Programmable pull-up resistor: OFF
Port3	I	Programmable pull-up resistor: OFF

System Block Diagram



1. Absolute Maximum Ratings at Ta=+25°C, VSS=0V

Parameter		Symbol	Pins	Conditions	VDD[V]	Ratings			Unit
						Min.	Typ.	Max.	
Supply voltage		VDDMAX	VDD			-0.3	to	+6.0	V
Input voltage		VI(1)	Port 71, 72, 73 RES			-0.3	to	VDD+0.3	
		VI(2)	VLCD			-0.3	to	+6.5	
Output voltage		VO(1)	C1 to C33 S1 to S48			-0.3	to	VLCD+0.3	
		VO(2)	TEST1, TEST2, SUPCK			-0.3	to	VDD+0.3	
Input/output voltage		VIO(1)	Port 1, 3 Port 70 TEST1			-0.3	to	VDD+0.3	
High level output current	Peak output current	IOPH(1)	Port 1, 3 TEST1, TEST2, SUPCK	·CMOS output ·For each pin		-4			mA
	Total output current	ΣIOAH(1)	Port 3 C1 to C33, S1 to S48 TEST1, TEST2, SUPCK	Total of all pins		-25			
		ΣIOAH(2)	Port 1	Total of all pins		-25			
Low level output current	Peak output current	IOPL(1)	Port 1, 3 TEST1, TEST2, SUPCK	For each pin				20	
		IOPL(2)	Port 70	For each pin				15	
	Total output current	ΣIOAL(1)	Port 1	Total of all pins				40	
		ΣIOAL(2)	TEST1, TEST2, SUPCK	Total of all pins				40	
		ΣIOAL(3)	Port 70	Total of all pins				15	
		ΣIOAL(4)	C1 to C33, S1 to S48	Total of all pins				30	
		ΣIOAL(5)	Port 70	Total of all pins				15	
Maximum power consumption		Pdmax	SQFP144	Ta = 0°C to +50°C				400	mW
Operating temperature range		Topr				0		+50	°C
Storage temperature range		Tstg				-55		+125	

2. Recommended Operating Range at Ta=0°C to +50°C, VSS=0V

Parameter	Symbol	Pins	Conditions	Ratings				Unit
				VDD[V]	Min.	Typ.	Max.	
Operating supply voltage range	VDD(1)	VDD	98μs≤tCYC≤400μs		3.15		3.85	V
Hold voltage	VHD	VDD	RAM and register data are kept in HOLD mode.		2.0		3.85	
LCD voltage	VLCD	VLCD		3.15-3.85	VDD		6.0	
High level input voltage	VIH(1)	·Port 1, 3 ·Port 72, 73 (schmitt)	Output disable	3.15-3.85	0.7VDD		VDD	
	VIH(2)	·P70 port input/interrupt ·P71 <u>RES</u> (schmitt)	Output N-ch Tr.: OFF	3.15-3.85	0.7VDD		VDD	
Low level input voltage	VIL(1)	·Port 1, 3 ·Port 72, 73 (schmitt)	Output disable	3.15-3.85	VSS		0.3VDD	
	VIL(2)	·P70 port input/interrupt ·P71 <u>RES</u> (schmitt)	Output N-ch Tr.: OFF	3.15-3.85	VSS		0.3VDD	
Operation cycle time	tCYC			3.15-3.85	0.98		400	μs

3. Electrical Characteristics at Ta=0°C to +50°C, VSS=0V

Parameter	Symbol	Pins	Conditions	VDD[V]	Ratings			Unit
					Min.	Typ.	Max.	
High level input current	IIH(1)	Port 1, 3	·Output disable ·Pull-up MOS Tr.: OFF ·VIN=VDD (including OFF state leak current of output Tr.)	3.15–3.85			1	μ A
	IIH(2)	Port 7 without pull-up MOS Tr.	·Output N-ch Tr.: OFF ·VIN=VDD (including OFF state leak current of output Tr.)	3.15–3.85			1	
	IIH(3)	$\overline{\text{RES}}$	VIN=VDD	3.15–3.85			1	
	IIH(4)	$\overline{\text{CE}}, \overline{\text{OE}}, \overline{\text{WE}}$	VIN=VDD	3.15–3.85			1	
Low level input current	IIL(1)	Port 1,3	·Output disable ·Pull-up MOS Tr.: OFF ·VIN=VSS (including OFF state leak current of output Tr.)	3.15–3.85	-1			
	IIL(2)	Port 7 without pull-up MOS Tr.	·Output N-ch Tr.: OFF ·VIN=VSS (including OFF state leak current of output Tr.)	3.15–3.85	-1			
	IIL(3)	$\overline{\text{RES}}$	VIN=VSS	3.15–3.85	-1			
	IIL(4)	A10, EP, F/M_SEL $\overline{\text{CE}}, \overline{\text{OE}}, \overline{\text{WE}}$	VIN=VSS	3.15–3.85	-1			
High level output voltage	VOH(1)	Port 0, 1, 3: CMOS output TEST1, TEST2, SUPCK	IOH=-0.1mA	3.15–3.85	VDD-0.5			V
Low level output voltage	VOL(1)	Port 1,3 TEST1, TEST2, SUPCK	·IOL=1mA ·IOL at any single pin is not over 1mA.	3.15–3.85			0.4	
	VOL(2)	Port 70	IOL=0.5mA	3.15–3.85			0.4	
Pull-up MOS Tr. resistance	Rpu	Port 1, 3, Port 7	VOH=0.9VDD	3.15–3.85	20	60	120	k Ω
Pull-down MOS Tr. resistance	Rpd	A10, EP, F/M_SEL	VOL=0.1VDD	3.15–3.85	25	50	100	
Hysteresis voltage	VHIS	Port 1, 3 Port 7 $\overline{\text{RES}}$	Output disable	3.15–3.85		0.1VDD		V
Pin capacitance	CP	All pins	·f=1MHz ·Every other terminal is connected to VSS. ·Ta=+25°C	3.15–3.85		10		pF

4. Serial Input/Output Characteristics at Ta=0°C to +50°C, VSS=0V

Parameter		Symbol	Pins	Conditions	VDD[V]	Ratings			Unit
						Min.	Typ.	Max.	
Serial clock	Input clock	Cycle	SCK0, SCK1	Refer to figure 5.	3.15-3.85	2			tCYC
		Low level pulse width			3.15-3.85	1			
		High level pulse width			3.15-3.85	1			
	Output clock	Cycle	SCK0, SCK1	Refer to figure 5.	3.15-3.85	2			
		Low level pulse width			3.15-3.85		1/2tCYC		
		High level pulse width			3.15-3.85		1/2tCYC		
Serial input	Data set-up time	tICK	·SI0, SI1 ·SB0, SB1	·Data set-up to SCK0 and SCK1	3.15-3.85	0.4			μs
	Data hold time	tCKI		·Refer to figure 5.	3.15-3.85	0.4			
Serial output	Output delay time (Using external clock)	tCKO(1)	·SO0, SO1 ·SB0, SB1	·Data hold from SCK0 and SCK1 ·Refer to figure 5.	3.15-3.85			7/12tCYC +1	μs
	Output delay time (Using internal clock)	tCKO(2)		·Data hold from SCK0 and SCK1 ·Refer to figure 5.	3.15-3.85			1/3tCYC +1	

5. Pulse Input Conditions at Ta=0°C to +50°C, VSS=0V

Parameter	Symbol	Pins	Conditions	VDD[V]	Ratings			Unit
					Min.	Typ.	Max.	
High/low level pulse width	tPIH(1) tPIL(1)	·INT0, INT1 ·INT2/T0IN ·Refer to figure 6.	·Interrupt acceptable ·Timer 0-countable	3.15-3.85	1			tCYC
	tPIH(2) tPIL(2)	·INT3/T0IN (1/1 is selected for noise rejection clock.) ·Refer to figure 6.	·Interrupt acceptable ·Timer 0-countable	3.15-3.85	2			
	tPIH(3) tPIL(3)	·INT3 (1/64 is selected for noise rejection clock.) ·Refer to figure 6.	·Interrupt acceptable	3.15-3.85	128			
	tPIL(4)	·RES ·Refer to figure 6.	·Reset acceptable	3.15-3.85	200			μs

6. Sample Current Consumption Characteristics at Ta=0°C to +50°C, VSS=0V

The sample current consumption characteristics are the measurement result of Sanyo provided evaluation board.
The currents through the output transistors and the pull-up MOS transistors are ignored.

• Flash Memory Operation

Parameter	Symbol	Pins	Conditions	OCR7	VDD[V]	Ratings			Unit
						Min.	Typ.	Max.	
Current consumption during normal operation (Note 1)	IDDOP(6)	VDD	·FmCF=6MHz by ceramic resonator ·FsX'tal=32.768kHz by X'tal ·System clock: CF oscillation ·RC oscillation stops.	1	3.15-3.85		8	20	mA
	IDDOP(7)		·FmCF=0Hz (No oscillation)	0			2.0	4	
	IDDOP(8)		·FsX'tal=32.768kHz by X'tal ·System clock: RC oscillation	1			2.5	5	
	IDDOP(9)		·FmCF=0Hz (No oscillation) ·FsX'tal=32.768kHz by X'tal	0	3.15-3.85		200	50	μA
	IDDOP(10)		·System clock: X'tal ·RC oscillation stops.	1			450	75	

• BIOS Program Operation

Parameter	Symbol	Pins	Conditions	OCR7	VDD[V]	Ratings			Unit
				Min.	Typ.	Max.			
Current consumption during writing to flash memory (Note 1)	IDDOP(11)	VDD	·FmCF=6MHz by ceramic resonator ·FsX'tal=32.768kHz by X'tal ·System clock: CF oscillation ·RC oscillation stops.	1	3.15-3.85		8	15	mA
	IDDOP(12)		·FmCF=0Hz (No oscillation)	0	3.15-3.85		4.5	10	
			·FsX'tal=32.768kHz by X'tal	1			5	12	
			·System clock: RC oscillation						

*OCR7: Bit 7 of the oscillation control register

• BIOS Program Operation

Parameter	Symbol	Pins	Conditions	Ratings		Min.	Typ.	Max.	Unit
				OCR7	VDD[V]				
Current consumption in HALT mode (Note 1)	IDDHALT(1)	VDD	·HALT mode ·FmCF=6MHz by ceramic resonator ·FsX'tal=32.768kHz by X'tal ·System clock: CF oscillation ·RC oscillation stops. ·Refer to figure 7.	1	3.15-3.85		2.5	5	mA
	IDDHALT(2)		·HALT mode ·FmCF=0Hz (No oscillation) ·FsX'tal=32.768kHz by X'tal ·System clock: RC oscillation ·Refer to figure 7.	0	3.15-3.85		250	600	μA
	IDDHALT(3)			1			350	700	
	IDDHALT(4)		·HALT mode ·FmCF=0Hz (No oscillation) ·FsX'tal=32.768kHz by X'tal ·System clock: X'tal ·RC oscillation stops. ·Refer to figure 7.	0	3.15-3.85		15	50	μA
	IDDHALT(5)			1			20	70	
Current consumption in HOLD mode (Note 1)	IDDHOLD(1)	VDD	·HOLD mode ·Refer to figure 7.		3.15-3.85		0.05	30	

• Flash Memory Operation

Parameter	Symbol	Pins	Conditions	Ratings		Min.	Typ.	Max.	Unit
				OCR7	VDD[V]				
Current consumption in HALT mode (Note 1)	IDDHALT(6)	VDD	·HALT mode ·FmCF=6MHz by ceramic resonator ·FsX'tal=32.768kHz by X'tal ·System clock: CF oscillation ·RC oscillation stops. ·Refer to figure 7.	1	3.15-3.85		2.5	5	mA
	IDDHALT(7)		·HALT mode ·FmCF=0Hz (No oscillation) ·FsX'tal=32.768kHz by X'tal ·System clock: RC oscillation ·Refer to figure 7.	0	3.15-3.85		200	500	μA
	IDDHALT(8)			1			400	800	
	IDDHALT(9)		·HALT mode ·FmCF=0Hz (No oscillation) ·FsX'tal=32.768kHz by X'tal ·System clock: X'tal ·RC oscillation stops. ·Refer to figure 7.	0	3.15-3.85		15	50	μA
	IDDHALT(10)			1			20	70	

Note 1: The current through the output transistors, the pull-up MOS transistors, and the bleeder resistors for the display power supply are ignored.

7. LCD Driver Characteristics at Ta=0°C to +50°C, VSS=0V

Parameter	Symbol	Pins, Conditions	Ratings				Unit
			VDD[V]	Min.	Typ.	Max.	
Voltage drop between Vx and Ci (x: 1-5) (i: 1-33)	VD1	·-15μA (only on Ci terminal) ·LCD: ON ·1/5 bias ·V5=VDD	3.3			120	mV
Voltage drop between Vx and Ci (x: 1-5) (i: 1-33)	VD2	·+15μA (only on Ci terminal) ·LCD: ON ·1/5 bias ·V5=VDD	3.3	-120			
Voltage drop between Vx and Si (x: 1-5) (i: 1-48)	VD3	·-15μA (only on Si terminal) ·LCD: ON ·1/5 bias ·V5=VDD	3.3			120	
Voltage drop between Vx and Si (x: 1-5) (i: 1-48)	VD4	·+15μA (only on Si terminal) ·LCD: ON ·1/5 bias ·V5=VDD	3.3	-120			
V4 output voltage	VV4	·LCD clock frequency=0Hz ·LCD: ON ·1/5 bias ·V5=VDD ·Refer to figure 9.	3.3	0.75VDD	0.8VDD	0.85VDD	V
V3 output voltage	VV3		3.3	0.55VDD	0.6VDD	0.65VDD	
V2 output voltage	VV2		3.3	0.35VDD	0.4VDD	0.45VDD	
V1 output voltage	VV1		3.3	0.15VDD	0.2VDD	0.25VDD	

Sample LCD Power Supply Characteristics at Ta=0°C to +50°C, VSS=0V

The sample current consumption characteristics are the measurement result of Sanyo provided evaluation board.

Parameter	Symbol	Pins, Conditions		VDD[V]	Ratings			Unit
					Min.	Typ.	Max.	
LCD Power supply	ILCD1	·LCD: ON ·1/5 bias ·VLCD=VDD ·V1-V5: open ·Refer to figure 8.	20kΩmode	3.3	15	29	60	μA

VCCR: LCD contrast control register

- Notes:
- Since the circuit pattern affects the oscillation frequency, place the oscillation-related parts as close to the oscillation pins as possible with the shortest possible pattern length.
 - When using the ceramic resonator or the X'tal, please contact with the oscillator manufacturer for the circuit parameters.




Figure 1 Ceramic Oscillation Circuit.




Figure 2 X'tal Oscillation Circuit.




Figure 3 RC Oscillation Circuit.

Recommended Oscillation Circuit and Characteristics

The oscillation circuit characteristics in the table below are based on the following conditions:

- Recommended circuit parameters are verified by an oscillator manufacturer using a Sanyo provided oscillation evaluation board.
- The characteristics are the results of the evaluation with the recommended circuit parameters connected externally.

Recommended Oscillation Circuit Parameters and Characteristics (Ta = 0°C to +50°C)

Frequency	Manufacturer	Oscillator	Recommended circuit parameter	Operating supply voltage range	Oscillation stabilizing time (*)	
					Typ.	Max.
6MHz	MURATA MANUFACTURING CO., LTD.	CSA6.00MG	C1=33pF C2=33pF	3.15-3.85V	TmsCF	
					0.02ms	0.2ms
32.768kHz	CITIZEN WATCH CO., LTD.	CFS-308	C3=20pF C4=20pF	3.15-3.85V	TssX'tal	
					1.00s	3.00s

(*) Note: The oscillation stabilizing time period is the time until the oscillation becomes stable after the VDD becomes higher than the minimum operating voltage.

The oscillation circuit characteristics may differ by applications. For further assistance, please contact with the oscillator manufacturer with the following notes in your mind.

- Since the oscillation frequency precision is affected by wiring capacity of the application board, etc., adjust the oscillation frequency on the production board.

Since the oscillation circuit characteristics are affected by the noise, wiring capacity, etc., refer to the following notices.

- The distance between the clock I/O terminal and external parts should be as short as possible.
- The capacitors' VSS should be allocated close to the microcontroller's GND terminal and be away from other GND.
- The signal lines with rapid state changes or the signal line with large amplitude such as middle withstand voltage port or LCD driver output should be allocated away from the clock oscillation circuit.
- The signal lines with large current should be allocated away from the oscillation circuit.




Figure 3 Oscillation Stabilizing Time.





Figure 4 Reset Circuit.



AC Timing Measurement Point




Figure 5 Serial Input Test Condition.




Figure 6 Pulse Input Timing Condition.




Figure 7 Current Consumption Measurement Circuit.




Figure 8 LCD Current Measurement Circuit.




Figure 9 V1 - V4 Terminal Output Voltage Measurement Circuit.

- Evaluation Sample

The evaluation sample of LC86F1216 is provided in QIC144 (package). Take note that the package size will be a little different from the one made in mass-production.

- Specifications of any and all SANYO products described or contained herein stipulate the performance, characteristics, and functions of the described products in the independent state, and are not guarantees of the performance, characteristics, and functions of the described products as mounted in the customer's products or equipment. To verify symptoms and states that cannot be evaluated in an independent device, the customer should always evaluate and test devices mounted in the customer's products or equipment.
- SANYO Electric Co., Ltd. strives to supply high-quality high-reliability products. However, any and all semiconductor products fail with some probability. It is possible that these probabilistic failures could give rise to accidents or events that could endanger human lives, that could give rise to smoke or fire, or that could cause damage to other property. When designing equipment, adopt safety measures so that these kinds of accidents or events cannot occur. Such measures include but are not limited to protective circuits and error prevention circuits for safe design, redundant design, and structural design.
- In the event that any or all SANYO products(including technical data,services) described or contained herein are controlled under any of applicable local export control laws and regulations, such products must not be exported without obtaining the export license from the authorities concerned in accordance with the above law.
- No part of this publication may be reproduced or transmitted in any form or by any means, electronic or mechanical, including photocopying and recording, or any information storage or retrieval system, or otherwise, without the prior written permission of SANYO Electric Co., Ltd.
- Any and all information described or contained herein are subject to change without notice due to product/technology improvement, etc. When designing equipment, refer to the "Delivery Specification" for the SANYO product that you intend to use.
- Information (including circuit diagrams and circuit parameters) herein is for example only ; it is not guaranteed for volume production. SANYO believes information herein is accurate and reliable, but no guarantees are made or implied regarding its use or any infringements of intellectual property rights or other rights of third parties.

This catalog provides information as of September, 2000. Specifications and information herein are subject to change without notice.