



# LC86P5032

## 8-Bit Single-Chip Microcontroller

## Overview

The LC86P5032 microcontroller, a new addition to the LC865000 series, is a 8-bit single chip CMOS microcontroller with one-time PROM.

This microcontroller has the same function and pin assignment as for the LC865000 series mask ROM version, and a 32K-byte PROM.

The same DIP/QFP packages as for the LC865000 series are available for shipment. It is suitable for setting up the first release, for prototyping and developing and testing applications.

## Features

- (1) Option switching using PROM data  
The optional functions of the LC865000 series can be specified using PROM data.  
The functions of the trial products can be evaluated using a mass production board.
- (2) Internal one-time PROM capacity : 32768 bytes
- (3) Internal RAM capacity : 512 bytes

Mask ROM version	PROM capacity	RAM capacity
LC865032	32512 bytes	512 bytes
LC865028	28672 bytes	512 bytes
LC865024	24576 bytes	512 bytes
LC865020	20480 bytes	384 bytes
LC865016	16384 bytes	384 bytes
LC865012	12288 bytes	384 bytes
LC865008	8192 bytes	384 bytes

- |   |   |
|---|---|
| (4) Operating supply voltage                              | : 4.5 to 6.0 V  |
| (5) Instruction cycle time                                | : 0.98 to 400 $\mu$ s   |
| (6) Operating temperature range                           | : -30°C to +70°C  |
| (7) Pins and package compatible with the mask ROM version |   |
| (8) Applicable mask version                               | : LC865032/LC865028/LC865024/LC865020/LC865016/LC865012, LC865008 |
| (9) Factory shipment                                      | : DIP-64S<br>OFP-64E  |


### Programming service

We offer various services at nominal charges. These include ROM writing, ROM reading, and package stamping and screening. Contact our local representatives for further information.

## Package Dimensions


unit : mm

# 3071-DIP64S



unit : mm

**3159-QFP64E**



SANYO : QFP64E

## Usage Notes

When using, please take note of the following.

### (1) Differences between the LC86P5032 and the LC865000 series

Item	LC86P5032	LC865032/28/24/20/16/12/08
Port status at reset	Please refer to "Port status at reset" on the next page.	
Operation after releasing reset	The option is specified by degrees within 3 ms after applying a 'H' level to the reset pin. The program located at 00H is executed.	The program located at 00H is executed immediately after applying a 'H' level to the reset pin.
Operating voltage range (V <sub>DD</sub> )	4.5 to 6.0 V	2.7 to 6.0 V
Total output current [ $\Sigma I_{OAH}(1)$ ] [ $\Sigma I_{OAH}(1)$ ]	Refer to 'Electrical Characteristics' on the semiconductor news.	
Current drain [ I <sub>DDOP</sub> (1) ] [ I <sub>DDOP</sub> (2) ] [ I <sub>DDOP</sub> (3) ] [ I <sub>DDOP</sub> (4) ]		

### • LC86P5032 Options

Option	Pins, Circuits	Option Settings
Configuration of input/output ports	Port 0 (Can be specified for each bit.)	1. Input : No pull-up MOS transistor Output : N-channel open drain 2. Input : Pull-up MOS transistor Output : CMOS
	Ports 1, 2 (Can be specified for each bit.)	1. Input : No programmable pull-up MOS transistor Output : N-channel open drain 2. Input : Programmable pull-up MOS transistor Output : CMOS
	Ports 3, 4, 5 (Can be specified for each bit.)	1. Input : No programmable pull-up MOS transistor Output : N-channel open drain 2. Input : Programmable pull-up MOS transistor Output : CMOS
Port 7 pull-up MOS transistor	Port 7 (Can be specified for each bit.)	1. Pull-up MOS transistor not provided 2. Pull-up MOS transistor provided *P74 has no pull-up resistor option.

The port operation related to the option is different at reset. Please refer to the next table.

## LC86P5032

### • Port configuration at reset


Pin	Option settings	LC86P5032	LC865032/28/24/20/16/12/08
P0	Input : No pull-up MOS transistor Output : N-channel open drain	(Same as for the mask version)	Input mode without pull-up MOS transistor (Output is OFF)
	Input : Pull-up MOS transistor Output : CMOS	Input mode • The Pull-up MOS transistor is not present during reset or several hundred microseconds after releasing reset. After that, the pull-up MOS transistor is present. (Output is OFF)	Input mode with pull-up MOS transistor (Output is OFF)
P1, P2	Input : Programmable pull-up MOS transistor Output : N-channel open drain	(Same as for the mask version)	Input mode without pull-up MOS transistor (Output is OFF)
	Input : Programmable pull-up MOS transistor Output : CMOS	(Same as for the mask version)	Input mode without pull-up MOS transistor (Output is OFF)
P3, P4, P5	Input : Non-Programmable pull-up MOS transistor Output : N-channel open drain	(Same as for the mask version)	Input mode without pull-up MOS transistor (Output is OFF)
	Input : Programmable pull-up MOS transistor Output : CMOS	(Same as for the mask version)	Input mode without pull-up MOS transistor (Output is OFF)
P7	Pull-up MOS transistor not provided	(Same as for the mask version)	Input mode without pull-up MOS transistor
	Pull-up MOS transistor provided	Input mode • The pull-up MOS transistor is not present during reset or several hundred microseconds after releasing reset. After that, the pull-up MOS transistor is present.	Input mode with pull-up MOS transistor

### (2) Option

The LC86P5032 uses 256 bytes addressed 7F00H to 7FFFH in program memory as option data area. This area does not affect the execution of the program but means that the LC865032 program memory is 32512 bytes addressed 0000H to 7EFFFH.

The option data is written using the option specifying program "SU865000. EXE". The option data is linked to the program area by linkage loader "L865000. EXE".

### (3) ROM space



## (4) Ordering information

1. When ordering identical mask ROM and PROM devices simultaneously.  
Provide an EPROM containing the target memory contents together with separate order forms for each of the mask ROM and PROM versions.
2. When ordering a PROM device.  
Provide an EPROM containing the target memory contents together with an order form.

## How to Use

### (1) Specification of options

Programming data for the LC86P5032's EPROM is required.

The debugged evaluation file (EVA file) must be converted to an INTEL-HEX formatted file (HEX file) with file converter program EVA2HEX.EXE. The HEX file is used as the programming data for the LC86P5032.

### (2) How to program the EPROM

The LC86P5032 can be programmed by an EPROM programmer with attachments W86EP5032D and W86EP5032Q.

#### • Recommended EPROM programmer

Supplier	EPROM programmer
Advantest	R4945, R4944, R4943
Andou	AF-9704
AVAL	PKW-1100, PKW-3000
Minato Electronics	MODEL 1890A

- "27512 (Vp-p = 12.5 V) Intel high-speed programming" mode available. The address must be set to "0000H to 7FFFH" and the jumper (DASEC) must be set 'OFF' at programming.

### (3) How to use the data security function


"Data security" is a function to prevent EPROM data from being read.

Instructions on using the data security function:


1. Set the jumper of attachment 'ON'.
2. Attempt to program the EPROM. The EPROM programmer will display an error. The error indication is a result of normal activity of the data-security feature. This is not a problem with the EPROM programmer chip.

## Notes

- The data security function is not carried out when the data of all addresses contain 'FF' at step 2 above.
- Data security cannot be executed when the sequential operation "BLANK=>PROGRAM=>VERIFY" is used at step 2 above.
- Set the jumper 'OFF' after execution of data security.



W86EP5032D



W86EP5032Q

# LC86P5032

## Pin Assignment


P10/SO0	<input type="checkbox"/>	1	64	<input type="checkbox"/>	P07
P11/SI0/SB0	<input type="checkbox"/>	2	63	<input type="checkbox"/>	P06
P12/SCK0	<input type="checkbox"/>	3	62	<input type="checkbox"/>	P05
P13/SO1	<input type="checkbox"/>	4	61	<input type="checkbox"/>	P04
P14/SI1/SB1	<input type="checkbox"/>	5	60	<input type="checkbox"/>	P03
P15/SCK1	<input type="checkbox"/>	6	59	<input type="checkbox"/>	P02
P16/BUZ	<input type="checkbox"/>	7	58	<input type="checkbox"/>	P01
P17/PWM	<input type="checkbox"/>	8	57	<input type="checkbox"/>	P00
TEST1	<input type="checkbox"/>	9	56	<input type="checkbox"/>	P27
RES	<input type="checkbox"/>	10	55	<input type="checkbox"/>	P26
XT1/P74	<input type="checkbox"/>	11	54	<input type="checkbox"/>	P25
XT2	<input type="checkbox"/>	12	53	<input type="checkbox"/>	P24
V <sub>SS</sub>	<input type="checkbox"/>	13	52	<input type="checkbox"/>	P23
CF1	<input type="checkbox"/>	14	51	<input type="checkbox"/>	P22
CF2	<input type="checkbox"/>	15	50	<input type="checkbox"/>	P21
V <sub>DD</sub>	<input type="checkbox"/>	16	49	<input type="checkbox"/>	P20
P80/AN0	<input type="checkbox"/>	17	48	<input type="checkbox"/>	V <sub>DD</sub> V <sub>PP</sub>
P81/AN1	<input type="checkbox"/>	18	47	<input type="checkbox"/>	V <sub>SS</sub>
P82/AN2	<input type="checkbox"/>	19	46	<input type="checkbox"/>	P51
P83/AN3	<input type="checkbox"/>	20	45	<input type="checkbox"/>	P50
P84/AN4	<input type="checkbox"/>	21	44	<input type="checkbox"/>	P47
P85/AN5	<input type="checkbox"/>	22	43	<input type="checkbox"/>	P46
P86/AN6	<input type="checkbox"/>	23	42	<input type="checkbox"/>	P45
P87/AN7	<input type="checkbox"/>	24	41	<input type="checkbox"/>	P44
P70/INT0	<input type="checkbox"/>	25	40	<input type="checkbox"/>	P43
P71/INT1	<input type="checkbox"/>	26	39	<input type="checkbox"/>	P42
P72/INT2/T0IN	<input type="checkbox"/>	27	38	<input type="checkbox"/>	P41
P73/INT3/T0IN	<input type="checkbox"/>	28	37	<input type="checkbox"/>	P40
P30	<input type="checkbox"/>	29	36	<input type="checkbox"/>	P37
P31	<input type="checkbox"/>	30	35	<input type="checkbox"/>	P36
P32	<input type="checkbox"/>	31	34	<input type="checkbox"/>	P35
P33	<input type="checkbox"/>	32	33	<input type="checkbox"/>	P34

Top view

SANYO : DIP64S

LC86P5032


Pin Assignment



Top view

SANYO : QFP64E

## System Block Diagram



# LC86P5032 Pin Description

Pin name	I/O	Function description	Option	Function in PROM mode																																			
V <sub>SS</sub>		Power supply pin(–)																																					
V <sub>DD</sub>		Power supply pin(+)																																					
V <sub>DD</sub> V <sub>PP</sub>		Power supply pin(+)		Power for programming																																			
PORT0 P00 to P07	I/O	<ul style="list-style-type: none"><li>• 8-bit input/output port</li><li>• Input for port 0 interrupt</li><li>• Input/output in nibble units</li><li>• Input for HOLD release</li></ul>	<ul style="list-style-type: none"><li>• Pull-up resistor : Present/Not present</li><li>• Output form : CMOS/ N-channel open drain.</li></ul>																																				
PORT1 P10 to P17	I/O	<ul style="list-style-type: none"><li>• 8-bit input/output port</li><li>• Data direction can be specified for each bit.</li><li>• Other pin functions<ul style="list-style-type: none"><li>P10 : SIO0 data output</li><li>P11 : SIO0 data input/bus input/output</li><li>P12 : SIO0 clock input/output</li><li>P13 : SIO1 data output</li><li>P14 : SIO1 data input/ bus input/output</li><li>P15 : SIO1 clock input/output</li><li>P16 : Buzzer output</li><li>P17 : Timer 1 output (PWM output)</li></ul></li></ul>	Output form : CMOS/ N-channel open drain	Data input/output <ul style="list-style-type: none"><li>• D0 to D7</li></ul>																																			
PORT2 P20 to P27	I/O	<ul style="list-style-type: none"><li>• 8-bit input/output port</li><li>• Data direction can be specified for each bit.</li></ul>	Output form : CMOS/ N-channel open drain																																				
PORT3 P30 to P37	I/O	<ul style="list-style-type: none"><li>• 8-bit input/output port</li><li>• Data direction can be specified for each bit</li><li>• 15 V withstand at N-ch open-drain output</li></ul>	Output form : CMOS/ N-channel open drain	Address input <ul style="list-style-type: none"><li>• A7 to A0</li></ul>																																			
PORT4 P40 to P47	I/O	<ul style="list-style-type: none"><li>• 8-bit input/output port</li><li>• Data direction can be specified for each bit</li><li>• 15 V withstand at N-ch open-drain output</li></ul>	Output form : CMOS/ N-channel open drain	Address input <ul style="list-style-type: none"><li>• A14 to A8 (*5)</li><li>• P47 : TA (*4)</li></ul>																																			
PORT5 P50 to P51	I/O	<ul style="list-style-type: none"><li>• 2-bit input/output port.</li><li>• Data direction can be specified for each bit.</li><li>• 15 V withstand at N-ch open-drain output</li></ul>	Output form : CMOS/ N-channel open drain																																				
PORT7 P70 P71 to P74	I/O  I	<ul style="list-style-type: none"><li>• 5-bit input port</li><li>• Other pin functions<ul style="list-style-type: none"><li>P70 : INT0 input/HOLD release/N-channel Tr. output for watchdog timer.</li><li>P71 : INT 1 input/HOLD release.</li><li>P72 : INT 2 input/timer 0 event input.</li><li>P73 : INT 3 input with noise filter/timer 0 event input.</li><li>P74 : Input pin XT1 for 32.768 kHz crystal oscillation</li></ul></li><li>• Interrupt received format, vector address.</li></ul> <table><thead><tr><th></th><th>Rising</th><th>Falling</th><th>Rising &amp; falling</th><th>High level</th><th>Low level</th><th>Vector</th></tr></thead><tbody><tr><td>INT0</td><td>Enable</td><td>Enable</td><td>Disable</td><td>Enable</td><td>Enable</td><td>03H</td></tr><tr><td>INT1</td><td>Enable</td><td>Enable</td><td>Disable</td><td>Enable</td><td>Enable</td><td>0BH</td></tr><tr><td>INT2</td><td>Enable</td><td>Enable</td><td>Enable</td><td>Disable</td><td>Disable</td><td>13H</td></tr><tr><td>INT3</td><td>Enable</td><td>Enable</td><td>Enable</td><td>Disable</td><td>Disable</td><td>1BH</td></tr></tbody></table>		Rising	Falling	Rising & falling	High level	Low level	Vector	INT0	Enable	Enable	Disable	Enable	Enable	03H	INT1	Enable	Enable	Disable	Enable	Enable	0BH	INT2	Enable	Enable	Enable	Disable	Disable	13H	INT3	Enable	Enable	Enable	Disable	Disable	1BH	<p>Pullup resistor : Present/Not present (P70, 71, 72, 73) * P74 has no pull-up resistor.</p>	Input of PROM control signal <ul style="list-style-type: none"><li>• DASEC (*1)</li><li>• OE (*2)</li><li>• CE (*3)</li></ul>
	Rising	Falling	Rising & falling	High level	Low level	Vector																																	
INT0	Enable	Enable	Disable	Enable	Enable	03H																																	
INT1	Enable	Enable	Disable	Enable	Enable	0BH																																	
INT2	Enable	Enable	Enable	Disable	Disable	13H																																	
INT3	Enable	Enable	Enable	Disable	Disable	1BH																																	



## LC86P5032

Pin name	I/O	Function description	Option	Function in PROM mode
PORT8 P80 to P87	I	<ul style="list-style-type: none"> <li>8-bit input port</li> <li>Other functions</li> <li>AD input port (8 port pins)</li> </ul>		
RES	I	Reset pin		
TEST1	O	Test pin Should be left open.		
XT1/P74	I	<ul style="list-style-type: none"> <li>Input pin for 32.768 kHz crystal oscillation</li> <li>Other function : Input port P74</li> </ul> When not used, connect to $V_{DD}$ .		
XT2	O	Output pin for 32.768 kHz crystal oscillation When not used, should be left open.		
CF1	I	Input pin for ceramic resonator oscillation		
CF2	O	Output pin for ceramic resonator oscillation		


- All port options can be specified in bit units.

- \*1 Memory select input for data security
- \*2 Output enable input
- \*3 Chip enable input
- \*4 TA → PROM control signal input
- \*5 A14 → Address input

- Connect as shown in the following figure to reduce noise into  $V_{DD}$  pin.

Short-circuit the  $V_{DD}$  pin to the  $V_{DD}V_{PP}$  pin.

Short-circuit the  $V_{SS}$  pin to the  $V_{SS}$  pin.



# LC86P5032

## 1. Absolute Maximum Ratings at Ta = 25°C, VSS = 0 V

Parameter		Symbol	Pins	Conditions	Ratings			Unit	
					V <sub>DD</sub> [V]	min	typ		max
Supply voltage		V <sub>DD</sub> max	V <sub>DD</sub> , V <sub>DD</sub> V <sub>PP</sub>	V <sub>DD</sub> = V <sub>DD</sub> V <sub>PP</sub>		−0.3		+7.0	V
Input voltage		V <sub>I</sub> (1)	• Ports 71, 72, 73, $\overline{74}$ • Port 8 • $\overline{RES}$			−0.3		V <sub>DD</sub> +0.3	
Input/output voltage		V <sub>IO</sub> (1)	• Ports 0, 1, 2 • Ports 3, 4, 5 of CMOS output			−0.3		V <sub>DD</sub> +0.3	
		V <sub>IO</sub> (2)	• Ports 3, 4, 5 of open-drain output			−0.3		15	
High-level output current	Peak output current	I <sub>OPH</sub> (1)	Ports 0, 1, 2, 3, 4, 5	• CMOS output • At each pin		−4			mA
	Total output current	ΣI <sub>OA</sub> H(1)	Ports 0, 1, 2	Total of all pins		−25			
		ΣI <sub>OA</sub> H(2)	Ports 3, 4, 5	Total of all pins		−20			
Low-level output current	Peak output current	I <sub>OPL</sub> (1)	Ports 0, 1, 2, 3, 4, 5	At each pin				20	
		I <sub>OPL</sub> (2)	Port 70	At each pin				15	
	Total output current	ΣI <sub>OA</sub> L(1)	Ports 0, 1, 70	Total of all pins				40	
		ΣI <sub>OA</sub> L(2)	Port 2	Total of all pins				40	
		ΣI <sub>OA</sub> L(3)	Ports 3, 4, 5	Total of all pins				80	
Power dissipation (max.)		P <sub>d</sub> max(1)	DIP64S	T <sub>a</sub> = −30°C+70°C				720	mW
		P <sub>d</sub> max(2)	QFP64E	T <sub>a</sub> = −30°C+70°C				420	
Operating temperature range		T <sub>opr</sub>				−30		70	°C
Storage temperature range		T <sub>stg</sub>				−65		150	

2. Recommended Operating Range at  $T_a = -30^{\circ}\text{C}$  to  $+70^{\circ}\text{C}$ ,  $V_{SS} = 0\text{ V}$

Parameter	Symbol	Pins	Conditions	Ratings			Unit	
				V <sub>DD</sub> [V]	min	typ		max
Operating voltage range	V <sub>DD</sub> (1)	V <sub>DD</sub>	0.98 μs ≤ tCYC tCYC ≤ 400 μs		4.5		6.0	V
HOLD voltage	V <sub>HD</sub>	V <sub>DD</sub>	RAM and registers retain their pre-HOLD mode values.		2.0		6.0	
Input high voltage	V <sub>IH</sub> (1)	Port 0 (Schmitt)	Output disabled	4.5 to 6.0	0.4V <sub>DD</sub> +0.9		V <sub>DD</sub>	
	V <sub>IH</sub> (2)	• Ports 1, 2 • Ports 72, 73 (Schmitt)	Output disabled	4.5 to 6.0	0.75V <sub>DD</sub>		V <sub>DD</sub>	
	V <sub>IH</sub> (3)	• Port 70 Port input/interrupt. • Port 71 • $\overline{\text{RES}}$ (Schmitt)	Output N-channel transistor OFF	4.5 to 6.0	0.75V <sub>DD</sub>		V <sub>DD</sub>	
	V <sub>IH</sub> (4)	Port 70 Watchdog timer	Output N-channel transistor OFF	4.5 to 6.0	0.9V <sub>DD</sub>		V <sub>DD</sub>	
	V <sub>IH</sub> (5)	• Port $\overline{74}$ • Port 8	Output N-channel transistor OFF	4.5 to 6.0	0.75V <sub>DD</sub>		V <sub>DD</sub>	
	V <sub>IH</sub> (6)	Ports 3, 4, 5 of CMOS output (Schmitt)	Output disabled	4.5 to 6.0	0.75V <sub>DD</sub>		V <sub>DD</sub>	
	V <sub>IH</sub> (7)	Ports 3, 4, 5 of open drain output (Schmitt)	Output disabled	4.5 to 6.0	0.75V <sub>DD</sub>		13.5	
Input low voltage	V <sub>IL</sub> (1)	Port 0 (Schmitt)	Output disabled	4.5 to 6.0	V <sub>SS</sub>		0.2V <sub>DD</sub>	
	V <sub>IL</sub> (2)	• Ports 1, 2, 3, 4, 5 • Ports 72, 73 (Schmitt)	Output disabled	4.5 to 6.0	V <sub>SS</sub>		0.25V <sub>DD</sub>	
	V <sub>IL</sub> (3)	• Port 70 Port input/interrupt. • Port 71 • $\overline{\text{RES}}$ (Schmitt)	N-channel transistor OFF	4.5 to 6.0	V <sub>SS</sub>		0.25V <sub>DD</sub>	
	V <sub>IL</sub> (4)	Port 70 Watchdog timer	N-channel transistor OFF	4.5 to 6.0	V <sub>SS</sub>		0.8V <sub>DD</sub> –1.0	
	V <sub>IL</sub> (5)	• Port $\overline{74}$ • Port 8	N-channel transistor OFF	4.5 to 6.0	V <sub>SS</sub>		0.25V <sub>DD</sub>	
Operation cycle time	tCYC			4.5 to 6.0	0.98		400	μs

# LC86P5032

Parameter	Symbol	Pins	Conditions	Ratings				Unit
				V <sub>DD</sub> [V]	min	typ	max	
Oscillation frequency range (Note 1)	FmCF(1)	CF1, CF2	<ul style="list-style-type: none"> <li>12 MHz (ceramic resonator oscillation).</li> <li>Refer to Figure 1.</li> </ul>	4.5 to 6.0	11.76	12	12.24	MHz
	FmCF(2)	CF1, CF2	<ul style="list-style-type: none"> <li>3 MHz (ceramic resonator oscillation).</li> <li>Refer to Figure 1.</li> </ul>	4.5 to 6.0	2.94	3	3.06	
	FmRC		RC oscillation	4.5 to 6.0	0.4	0.8	2.0	
	FsXtal	XT1, XT2	<ul style="list-style-type: none"> <li>32.768 kHz (crystal oscillation).</li> <li>Refer to Figure 2.</li> </ul>	4.5 to 6.0		32.768		kHz
Oscillation stable time period (Note 1)	tmsCF(1)	CF1, CF2	<ul style="list-style-type: none"> <li>12 MHz (ceramic resonator oscillation).</li> <li>Refer to Figure 3.</li> </ul>	4.5 to 6.0		0.03	0.5	ms
	tmsCF(2)	CF1, CF2	<ul style="list-style-type: none"> <li>3 MHz (ceramic resonator oscillation).</li> <li>Refer to Figure 3.</li> </ul>	4.5 to 6.0		0.2	2	
	tssXtal	XT1, XT2	<ul style="list-style-type: none"> <li>32.768 kHz (crystal oscillation).</li> <li>Refer to Figure 3.</li> </ul>	4.5 to 6.0		1	1.5	s

(Note 1) The oscillation constants are shown on Table 1 and Table 2.

3. Electrical Characteristics at Ta= -30°C to +70°C, V<sub>SS</sub> = 0 V

Parameter	Symbol	Pins	Conditions	V <sub>DD</sub> [V]	Ratings			Unit
				min	typ	max		
Input high current	I <sub>IH</sub> (1)	•Ports 3, 4, 5 at open-drain output	•Output disabled •V <sub>IN</sub> = 13.5 V (including off-state leak current of output transistor)	4.5 to 6.0			5	μA
	I <sub>IH</sub> (2)	•Port 0 without pull-up MOS transistor •Ports 1, 2, 3, 4, 5	•Output disabled •Pull-up MOS transistor OFF. V <sub>IN</sub> = V <sub>DD</sub> (including off-state leak current of output transistor)	4.5 to 6.0			1	
	I <sub>IH</sub> (3)	•Ports 70, 71, 72, 73 without pull-up MOS transistor •Port 8	V <sub>IN</sub> = V <sub>DD</sub>	4.5 to 6.0			1	
	I <sub>IH</sub> (4)	• $\overline{\text{RES}}$	V <sub>IN</sub> = V <sub>DD</sub>	4.5 to 6.0			1	
Input low current	I <sub>IL</sub> (1)	•Ports 1, 2, 3, 4, 5 •Port 0 without pull-up MOS transistor	•Output disabled •Pull-up MOS transistor OFF. V <sub>IN</sub> = V <sub>SS</sub> (including off-state leak current of output transistor)	4.5 to 6.0	−1			
	I <sub>IL</sub> (2)	•Ports 70, 71, 72, 73 without pull-up MOS transistor •Port 8	V <sub>IN</sub> = V <sub>SS</sub>	4.5 to 6.0	−1			
	I <sub>IL</sub> (3)	• $\overline{\text{RES}}$	V <sub>IN</sub> = V <sub>SS</sub>	4.5 to 6.0	−1			
Output high voltage	V <sub>OH</sub> (1)	•Ports 0, 1, 2, 3, 4, 5 at CMOS output	I <sub>OH</sub> = −1.0 mA	4.5 to 6.0	V <sub>DD</sub> −1			V
	V <sub>OH</sub> (2)		I <sub>OH</sub> = −0.1 mA	4.5 to 6.0	V <sub>DD</sub> −0.5			
Output low voltage	V <sub>OL</sub> (1)	Ports 0, 1, 2, 3, 4, 5	I <sub>OL</sub> = 10 mA	4.5 to 6.0			1.5	
	V <sub>OL</sub> (2)		I <sub>OL</sub> = 1.6 mA	4.5 to 6.0			0.4	
	V <sub>OL</sub> (3)	Port 70	I <sub>OL</sub> = 1 mA	4.5 to 6.0			0.4	
	V <sub>OL</sub> (4)		I <sub>OL</sub> = 0.5 mA	4.5 to 6.0			0.4	
Pull-up MOS transistor resistance	R <sub>pu</sub>	•Ports 0, 1, 2, 3, 4, 5 •Ports 70, 71, 72, 73	V <sub>OH</sub> = 0.9 V <sub>DD</sub>	4.5 to 6.0	15	40	70	kΩ
Hysteresis voltage	V <sub>HIS</sub>	•Ports 0, 1, 2, 3, 4, 5 •Ports 70, 71, 72, 73 • $\overline{\text{RES}}$	Output disable	4.5 to 6.0		0.1V <sub>DD</sub>		V
Pin capacitance	C <sub>P</sub>	All pins	•f = 1 MHz •Unmeasured input pins are set to V <sub>SS</sub> level. •Ta = 25°C	4.5 to 6.0		10		pF

#### 4. Serial Input/Output Characteristics at Ta = -30°C to +70°C, V<sub>SS</sub> = 0 V

Parameter			Symbol	Pins	Conditions	V <sub>DD</sub> [V]	Ratings			Unit
							min	typ	max	
Serial clock	Input clock	Cycle	tCKCY(1)	SCK0, SCK1	Refer to Figure 5.	4.5 to 6.0	2			tCYC
		Low-level pulse width	tCKL(1)			4.5 to 6.0	1			
		High-level pulse width	tCKH(1)			4.5 to 6.0	1			
	Output clock	Cycle	tCKCY(2)	SCK0, SCK1	• Use pullup resistor (1 k $\Omega$ ) when set to open-drain output. • Refer to Figure 5.	4.5 to 6.0	2			
		Low-level pulse width	tCKL(2)			4.5 to 6.0		1/2tCKYC		
		High-level pulse width	tCKH(2)			4.5 to 6.0		1/2tCKYC		
Serial input	Data setup time	tICK	• SI0, SI1 • SB0, SB1	• Data set-up to SCK0, 1 • Data hold from SCK0, 1 • Refer to Figure 5.	4.5 to 6.0	0.1			$\mu$ s	
	Data hold time	tCKI			4.5 to 6.0	0.1				
Serial output	Output delay time (Serial clock is external clock.)	tCKO(1)	• SO0, SO1 • SB0, SB1	• Use a pullup resistor (1 k $\Omega$ ) when set to open-drain output.	4.5 to 6.0			7/12tCYC +0.2		
	Output delay time (Serial clock is internal clock.)	tCKO(2)			4.5 to 6.0			1/3tCYC +0.2		

5. Pulse Input Conditions at  $T_a = -30^{\circ}\text{C}$  to  $+70^{\circ}\text{C}$ ,  $V_{SS} = 0\text{ V}$

Parameter	Symbol	Pins	Conditions	Ratings			Unit
				$V_{DD}$ [V]	min	typ	max
High/low-level pulse width	tPIH(1) tPIL(1)	• INT0, INT1 • INT2/T0IN • INT3	• Interrupt acceptable • Timer 0 pulse countable	4.5 to 6.0	1		tCYC
	tPIH(2) tPIL(2)	INT3 (The noise rejection clock selected to 1/1.)	• Interrupt acceptable • Timer 0 pulse countable	4.5 to 6.0	2		
	tPIH(3) tPIL(3)	INT3 (The noise rejection clock selected to 1/16.)	• Interrupt acceptable • Timer 0 pulse countable	4.5 to 6.0	32		
	tPIL(4)	$\overline{\text{RES}}$	Reset acceptable	4.5 to 6.0	200		$\mu\text{s}$

6. A/D Converter Characteristics at  $T_a = -30^{\circ}\text{C}$  to  $+70^{\circ}\text{C}$ ,  $V_{SS} = 0\text{ V}$

Parameter	Symbol	Pins	Conditions	Ratings			Unit
				$V_{DD}$ [V]	min	typ	max
Resolution	N					8	bit
Absolute precision (Note 2)	ET			4.5 to 6.0			$\pm 1/5$ LSB
Conversion time	tCAD		A/D conversion time = $16 \times \text{tCYC}$ (ADCR2 = 0) (Note 3)	4.5 to 6.0	15.68 (tCYC = 0.98 $\mu\text{s}$ )		65.28 (tCYC = 4.08 $\mu\text{s}$ )
			A/D conversion time = $32 \times \text{tCYC}$ (ADCR2 = 1) (Note 3)		31.36 (tCYC = 0.98 $\mu\text{s}$ )		130.56 (tCYC = 4.08 $\mu\text{s}$ )
Analog input voltage range	$V_{\text{AIN}}$	AN0 to AN7		4.5 to 5.5	$V_{SS}$		$V_{DD}$ V
Analog port input current	$I_{\text{AINH}}$		$V_{\text{AIN}} = V_{DD}$	4.5 to 5.5			+1 $\mu\text{A}$
	$I_{\text{AINL}}$		$V_{\text{AIN}} = V_{SS}$	4.5 to 5.5	-1		

(Note 2) Quantizing error ( $\pm 1/2$  LSB) is ignored.

(Note 3) The conversion time is the period from execution of the instruction to start conversion to the completion of shifting the A/D converted value to the register.

7. Current Drain Characteristics at  $T_a = -30^{\circ}\text{C}$  to  $+70^{\circ}\text{C}$ ,  $V_{SS} = 0\text{ V}$ 

Parameter	Symbol	Pins	Conditions	$V_{DD}$ [V]	Ratings			Unit
					min	typ	max	
Current drain during basic operation (Note 4)	$I_{DDOP(1)}$	$V_{DD}$	<ul style="list-style-type: none"> <li>• <math>F_mCF = 12\text{ MHz}</math> for ceramic resonator oscillation.</li> <li>• <math>F_sXtal = 32.768\text{ kHz}</math> for crystal oscillator.</li> <li>• System clock : CF oscillator.</li> <li>• Internal RC oscillator stopped.</li> </ul>	4.5 to 6.0		13	26	mA
	$I_{DDOP(2)}$		<ul style="list-style-type: none"> <li>• <math>F_mCF = 3\text{ MHz}</math> for ceramic resonator oscillation.</li> <li>• <math>F_sXtal = 32.768\text{ kHz}</math> for crystal oscillator.</li> <li>• System clock : CF oscillator.</li> <li>• Internal RC oscillator stopped.</li> </ul>	4.5 to 6.0		7	14	
	$I_{DDOP(3)}$		<ul style="list-style-type: none"> <li>• <math>F_mCF = 0\text{ Hz}</math> (when oscillator stops).</li> <li>• <math>F_sXtal = 32.768\text{ kHz}</math> for crystal oscillator.</li> <li>• System clock : RC oscillator.</li> </ul>	4.5 to 6.0		4	10	
	$I_{DDOP(4)}$		<ul style="list-style-type: none"> <li>• <math>F_mCF = 0\text{ Hz}</math> (when oscillator stops).</li> <li>• <math>F_sXtal = 32.768\text{ kHz}</math> for crystal oscillator.</li> <li>• System clock : crystal oscillator.</li> <li>• Internal RC oscillator stopped.</li> </ul>	4.5 to 6.0		4	8	



# LC86P5032

Parameter	Symbol	Pins	Conditions	V <sub>DD</sub> [V]	Ratings			Unit
					min	typ	max	
Current drain at HALT mode (Note 4)	I <sub>DDHALT</sub> (1)	V <sub>DD</sub>	<ul style="list-style-type: none"> <li>• HALT mode</li> <li>• FmCF = 12 MHz for ceramic resonator oscillation.</li> <li>• FsXtal = 32.768 kHz for crystal oscillator.</li> <li>• System clock : CF oscillator.</li> <li>• Internal RC oscillator stopped.</li> </ul>	4.5 to 6.0		5	10	mA
	I <sub>DDHALT</sub> (2)		<ul style="list-style-type: none"> <li>• HALT mode</li> <li>• FmCF = 3 MHz for ceramic resonator oscillation.</li> <li>• FsXtal = 32.768 kHz for crystal oscillator.</li> <li>• System clock : CF oscillator.</li> <li>• Internal RC oscillator stopped.</li> </ul>	4.5 to 6.0		2.2	4.6	
	I <sub>DDHALT</sub> (3)		<ul style="list-style-type: none"> <li>• HALT mode</li> <li>• FmCF = 0 Hz (when oscillator stops).</li> <li>• FsXtal = 32.768 kHz for crystal oscillator.</li> <li>• System clock : RC oscillator</li> </ul>	4.5 to 6.0		550	1100	μA
	I <sub>DDHALT</sub> (4)		<ul style="list-style-type: none"> <li>• HALT mode</li> <li>• FmCF = 0 Hz (when oscillator stops).</li> <li>• FsXtal = 32.768 kHz for crystal oscillator.</li> <li>• System clock : crystal oscillator.</li> <li>• Internal RC oscillator stopped.</li> </ul>	4.5 to 6.0		25	100	
Current drain at HOLD mode (Note 4)	I <sub>DDHOLD</sub> (1)	V <sub>DD</sub>	HOLD mode	4.5 to 6.0		0.05	30	
	I <sub>DDHOLD</sub> (2)			2.5 to 4.5		0.02	20	

(Note 4) The currents of output transistors and pull-up transistors are ignored.

**Table 1. Ceramic Resonator Oscillation Guaranteed Constants (Main clock)**

Oscillation type	Supplier	Oscillator	C1	C2
12 MHz ceramic resonator oscillation	Murata	CSA12.0MTZ	33 pF	33 pF
		CST12.0MTW	on chip	
	Kyocera	KBR-12.0M	33 pF	33 pF
3 MHz ceramic resonator oscillation	Murata	CSA3.00MG040	100 pF	100 pF
		CST3.00MGW040	on chip	
	Kyocera	KBR-3.0MS	47 pF	47 pF


- For both C1 and C2, the K rank ( $\pm 10\%$ ) and SL characteristics must be used.

**Table 2. Crystal Oscillation Guaranteed Constants (Sub-clock)**

Oscillation type	Supplier	Oscillator	C3	C4
32.768 kHz crystal oscillation	Kyocera	KF-38G-13P0200	18 pF	18 pF


- For both C3 and C4, the J rank ( $\pm 5\%$ ) and CH characteristics must be used.  
(If high precision is not necessary, use K rank ( $\pm 10\%$ ) and SL characteristics.)

- Notes
- Since the circuit pattern affects the oscillation frequency, place the oscillation-related parts as close to the oscillation pins as possible with the shortest possible pattern length.
  - If you use other oscillators herein, we provide no guarantee for the characteristics.



Main-clock circuit

**Figure 1 Ceramic Resonator Oscillation**



Sub-clock circuit

**Figure 2 Crystal Oscillation**





Figure 3 Oscillation Stable Time



The values of  $C_{RES}$  and  $R_{RES}$  should be determined such that reset time is at least 200  $\mu s$ , measured from the moment the power exceeds the  $V_{DD}$  lower limit.


Figure 4 Reset Circuit




## Usage Notes

- The construction of the one-time programmable microcontroller with a blank built-in PROM makes it impossible for Sanyo to completely factory-test it before shipping. To prove reliability of the programmed devices, the screening procedure shown in the following figure should always be followed.
- It is not possible to perform a writing test on the blank PROM. 100% yield, therefore, cannot be guaranteed.
- Ensure dry packaging  
The environment must be held at a temperature of 30°C or less and a humidity level of 70% or less.
- After opening the packing  
The preparation procedures shown in the following figure should always be followed prior to mounting the packages on the substrate. After opening the packing, a controlled environment must be maintained until soldering. The environment must be held at a temperature of 30°C or less and a humidity level of 70% or less. Please solder within 96 hours.

### a. Shipping with a blank PROM (Data to be programmed by customer)



### b. Shipping with programmed PROM (Data programmed by Sanyo)



- Any and all SANYO products described or contained herein do not have specifications that can handle applications that require extremely high levels of reliability, such as life-support systems, aircraft's control systems, or other applications whose failure can be reasonably expected to result in serious physical and/or material damage. Consult with your SANYO representative nearest you before using any SANYO products described or contained herein in such applications.**
- SANYO assumes no responsibility for equipment failures that result from using products at values that exceed, even momentarily, rated values (such as maximum ratings, operating condition ranges, or other parameters) listed in products' specifications of any and all SANYO products described or contained herein.**
- Specifications of any and all SANYO products described or contained herein stipulate the performance, characteristics, and functions of the described products in the independent state, and are not guarantees of the performance, characteristics, and functions of the described products as mounted in the customer's products or equipment. To verify symptoms and states that cannot be evaluated in an independent device, the customer should always evaluate and test devices mounted in the customer's products or equipment.**
- SANYO Electric Co., Ltd. strives to supply high-quality high-reliability products. However, any and all semiconductor products fail with some probability. It is possible that these probabilistic failures could give rise to accidents or events that could endanger human lives, that could give rise to smoke or fire, or that could cause damage to other property. When designing equipment, adopt safety measures so that these kinds of accidents or events cannot occur. Such measures include but are not limited to protective circuits and error prevention circuits for safe design, redundant design, and structural design.**
- In the event that any or all SANYO products (including technical data, services) described or contained herein are controlled under any of applicable local export control laws and regulations, such products must not be exported without obtaining the export license from the authorities concerned in accordance with the above law.**
- No part of this publication may be reproduced or transmitted in any form or by any means, electronic or mechanical, including photocopying and recording, or any information storage or retrieval system, or otherwise, without the prior written permission of SANYO Electric Co., Ltd.**
- Any and all information described or contained herein are subject to change without notice due to product/technology improvement, etc. When designing equipment, refer to the "Delivery Specification" for the SANYO product that you intend to use.**
- Information (including circuit diagrams and circuit parameters) herein is for example only ; it is not guaranteed for volume production. SANYO believes information herein is accurate and reliable, but no guarantees are made or implied regarding its use or any infringements of intellectual property rights or other rights of third parties.**