





## QUAD 2-INPUT OR GATE


**MC54/74F32**




**QUAD 2-INPUT OR GATE**  
**FAST™ SCHOTTKY TTL**



**J SUFFIX**  
CERAMIC  
CASE 632-08



**N SUFFIX**  
PLASTIC  
CASE 646-06



**D SUFFIX**  
SOIC  
CASE 751A-02

### ORDERING INFORMATION

MC54FXXJ Ceramic  
MC74FXXN Plastic  
MC74FXXD SOIC

### GUARANTEED OPERATING RANGES

Symbol	Parameter		Min	Typ	Max	Unit
V <sub>CC</sub>	Supply Voltage	54, 74	4.5	5.0	5.5	V
T <sub>A</sub>	Operating Ambient Temperature Range	54	-55	25	125	°C
		74	0	25	70	
I <sub>OH</sub>	Output Current — High	54, 74			-1.0	mA
I <sub>OL</sub>	Output Current — Low	54, 74			20	mA

# MC54/74F32

## DC CHARACTERISTICS OVER OPERATING TEMPERATURE RANGE (unless otherwise specified)

Symbol	Parameter	Limits			Unit	Test Conditions	
		Min	Typ	Max			
$V_{IH}$	Input HIGH Voltage	2.0			V	Guaranteed Input HIGH Voltage	
$V_{IL}$	Input LOW Voltage			0.8	V	Guaranteed Input LOW Voltage	
$V_{IK}$	Input Clamp Diode Voltage			-1.2	V	$V_{CC} = \text{MIN}$ , $I_{IN} = -18 \text{ mA}$	
$V_{OH}$	Output HIGH Voltage	54, 74	2.5		V	$I_{OH} = -1.0 \text{ mA}$	$V_{CC} = 4.50 \text{ V}$
		74	2.7		V	$I_{OH} = -1.0 \text{ mA}$	$V_{CC} = 4.75 \text{ V}$
$V_{OL}$	Output LOW Voltage			0.5	V	$I_{OL} = 20 \text{ mA}$	$V_{CC} = \text{MIN}$
$I_{IH}$	Input HIGH Current			20	$\mu\text{A}$	$V_{CC} = \text{MAX}$ , $V_{IN} = 2.7 \text{ V}$	
				0.1	mA	$V_{CC} = \text{MAX}$ , $V_{IN} = 7.0 \text{ V}$	
$I_{IL}$	Input LOW Current			-0.6	mA	$V_{CC} = \text{MAX}$ , $V_{IN} = 0.5 \text{ V}$	
$I_{OS}$	Output Short Circuit Current (Note 2)	-60		-150	mA	$V_{CC} = \text{MAX}$ , $V_{OUT} = 0 \text{ V}$	
$I_{CC}$	Power Supply Current Total, Output HIGH			9.2	mA	$V_{CC} = \text{MAX}$ , $V_{IN} = 4.5 \text{ V}$	
				15.5	mA	$V_{CC} = \text{MAX}$ , $V_{IN} = \text{GND}$	

### NOTES:

1. For conditions shown as MIN or MAX, use the appropriate value specified under recommended operating conditions for the applicable device type.
2. Not more than one output should be shorted at a time, nor for more than 1 second.

## AC CHARACTERISTICS

Symbol	Parameter	54/74F		54F		74F		Unit	
		$T_A = +25^\circ\text{C}$ $V_{CC} = +5.0 \text{ V}$ $C_L = 50 \text{ pF}$		$T_A = -55^\circ\text{C} \text{ to } +125^\circ\text{C}$ $V_{CC} = 5.0 \text{ V} \pm 10\%$ $C_L = 50 \text{ pF}$		$T_A = 0^\circ\text{C} \text{ to } 70^\circ\text{C}$ $V_{CC} = 5.0 \text{ V} \pm 10\%$ $C_L = 50 \text{ pF}$			
		Min	Max	Min	Max	Min	Max		
		3.0	5.6	3.0	7.5	3.0	6.6		
$t_{PLH}$	Propagation Delay	3.0	5.6	3.0	7.5	3.0	6.6	ns	
$t_{PHL}$	Propagation Delay	3.0	5.3	2.5	7.5	3.0	6.3	ns	