

PowerMOS transistor**PHT1N60R****GENERAL DESCRIPTION**



N-channel enhancement mode field-effect power transistor in a plastic envelope suitable for surface mounting featuring high avalanche energy capability, stable blocking voltage, fast switching and high thermal cycling performance. Intended for use in Compact Fluorescent Lights (CFL) and general purpose switching applications.

QUICK REFERENCE DATA

SYMBOL	PARAMETER	MAX.	UNIT
V_{DS}	Drain-source voltage	600	V
I_D	Drain current (DC)	0.53	A
P_{tot}	Total power dissipation	1.8	W
$R_{DS(ON)}$	Drain-source on-state resistance	16.0	Ω

PINNING - SOT223

PIN	DESCRIPTION
1	gate
2	drain
3	source
4	drain (tab)

PIN CONFIGURATION**SYMBOL****LIMITING VALUES**

Limiting values in accordance with the Absolute Maximum System (IEC 134)

SYMBOL	PARAMETER	CONDITIONS	MIN.	MAX.	UNIT
V_{DS}	Drain-source voltage		-	600	V
V_{DGR}	Drain-gate voltage		-	600	V
$\pm V_{GS}$	Gate-source voltage		-	30	V
I_D	Drain current (DC)	$R_{GS} = 20 \text{ k}\Omega$	-	0.53	A
I_{DM}	Drain current (pulse peak value)	$T_{sp} = 25^\circ\text{C}$ $T_{sp} = 100^\circ\text{C}$ $T_{sp} = 25^\circ\text{C}$	-	0.4	A
I_{DR}	Source-drain diode current (DC)	$T_{sp} = 25^\circ\text{C}$	-	2.12	A
I_{DRM}	Source-drain diode current (pulse peak value)	$T_{sp} = 25^\circ\text{C}$	-	0.53	A
P_{tot}	Total power dissipation	$T_{sp} = 25^\circ\text{C}$	-	2.12	A
T_{stg}	Storage temperature		-	1.8	W
T_j	Junction temperature		-55	150	$^\circ\text{C}$
			-	150	$^\circ\text{C}$

AVALANCHE LIMITING VALUE

SYMBOL	PARAMETER	CONDITIONS	MIN.	MAX.	UNIT
W_{DSS}	Drain-source non-repetitive unclamped inductive turn-off energy	$I_D = 2 \text{ A}$; $V_{DD} \leq 50 \text{ V}$; $V_{GS} = 10 \text{ V}$; $R_{GS} = 50 \Omega$ $T_j = 25^\circ\text{C}$ prior to surge $T_j = 100^\circ\text{C}$ prior to surge	-	20	mJ
W_{DSR}^1	Drain-source repetitive unclamped inductive turn-off energy	$I_D = 2 \text{ A}$; $V_{DD} \leq 50 \text{ V}$; $V_{GS} = 10 \text{ V}$; $R_{GS} = 50 \Omega$; $T_j \leq 150^\circ\text{C}$	-	8	mJ
			-	3.6	mJ

1. Pulse width and frequency limited by $T_{j(max)}$

PowerMOS transistor

PHT1N60R

THERMAL RESISTANCES

SYMBOL	PARAMETER	CONDITIONS	MIN.	TYP.	MAX.	UNIT
$R_{th\ j-sp}$	Thermal resistance junction to solder point		-	-	15	K/W
$R_{th\ j-a}$	Thermal resistance junction to ambient	pcb mounted; minimum footprint	-	156	-	K/W
		pcb mounted; pad area as in fig:2	-	70	-	K/W

STATIC CHARACTERISTICS

 $T_{mb} = 25\ ^\circ\text{C}$ unless otherwise specified

SYMBOL	PARAMETER	CONDITIONS	MIN.	TYP.	MAX.	UNIT
$V_{(BR)DSS}$	Drain-source breakdown voltage	$V_{GS} = 0\text{ V}; I_D = 0.25\text{ mA}$	600	-	-	V
$V_{GS(TO)}$	Gate threshold voltage	$V_{DS} = V_{GS}; I_D = 0.25\text{ mA}$	2.0	3.0	4.0	V
I_{DSS}	Drain-source leakage current	$V_{DS} = 500\text{ V}; V_{GS} = 0\text{ V}; T_j = 25\ ^\circ\text{C}$	-	1	100	μA
		$V_{DS} = 400\text{ V}; V_{GS} = 0\text{ V}; T_j = 125\ ^\circ\text{C}$	-	0.1	1.0	mA
I_{GSS}	Gate-source leakage current	$V_{GS} = \pm 35\text{ V}; V_{DS} = 0\text{ V}$	-	4	100	nA
$R_{DS(ON)}$	Drain-source on-state resistance	$V_{GS} = 10\text{ V}; I_D = 1\text{ A}$	-	-	16.0	Ω
V_{SD}	Source-drain diode forward voltage	$I_F = 2\text{ A}; V_{GS} = 0\text{ V}$	-	0.85	1.2	V

DYNAMIC CHARACTERISTICS

 $T_{mb} = 25\ ^\circ\text{C}$ unless otherwise specified

SYMBOL	PARAMETER	CONDITIONS	MIN.	TYP.	MAX.	UNIT
g_{fs}	Forward transconductance	$V_{DS} = 15\text{ V}; I_D = 1\text{ A}$	0.5	0.8	-	S
C_{iss}	Input capacitance	$V_{GS} = 0\text{ V}; V_{DS} = 25\text{ V}; f = 1\text{ MHz}$	-	75	100	pF
C_{oss}	Output capacitance		-	10	15	pF
C_{rss}	Feedback capacitance		-	5	10	pF
$Q_{g(tot)}$	Total gate charge	$V_{GS} = 10\text{ V}; I_D = 2\text{ A}; V_{DS} = 400\text{ V}$	-	5	-	nC
Q_{gs}	Gate to source charge		-	.5	-	nC
Q_{gd}	Gate to drain (Miller) charge		-	3	-	nC
t_{don}	Turn-on delay time	$V_{DD} = 30\text{ V}; I_D = 2\text{ A};$	-	5	10	ns
t_r	Turn-on rise time	$V_{GS} = 10\text{ V}; R_{GS} = 50\ \Omega;$	-	15	20	ns
t_{doff}	Turn-off delay time	$R_{GEN} = 50\ \Omega$	-	15	20	ns
t_f	Turn-off fall time		-	7	15	ns
t_{rr}	Source-drain diode Reverse recovery time	$I_F = 2\text{ A}; -dI_F/dt = 100\text{ A}/\mu\text{s};$	-	150	-	ns
Q_{rr}	Source-drain diode Reverse recovery charge	$V_{GS} = 0\text{ V}; V_R = 100\text{ V}$	-	1.5	-	μC

PowerMOS transistor

PHT1N60R

MOUNTING INSTRUCTIONS



Dimensions in mm.

Fig.1. soldering pattern for surface mounting SOT223.


PRINTED CIRCUIT BOARD

Dimensions in mm.Fig.2. PCB for thermal resistance and power rating for SOT223.
PCB: FR4 epoxy glass (1.6 mm thick), copper laminate (35 μ m thick).

PowerMOS transistor

PHT1N60R

MECHANICAL DATA

**Notes**

1. Observe the general handling precautions for electrostatic-discharge sensitive devices (ESDs) to prevent damage to MOS gate oxide.
2. Refer to surface mounting instructions for SOT223 envelope.
3. Epoxy meets UL94 V0 at 1/8".

PowerMOS transistor

PHT1N60R

DEFINITIONS

Data sheet status	
Objective specification	This data sheet contains target or goal specifications for product development.
Preliminary specification	This data sheet contains preliminary data; supplementary data may be published later.
Product specification	This data sheet contains final product specifications.
Limiting values	
Limiting values are given in accordance with the Absolute Maximum Rating System (IEC 134). Stress above one or more of the limiting values may cause permanent damage to the device. These are stress ratings only and operation of the device at these or at any other conditions above those given in the Characteristics sections of this specification is not implied. Exposure to limiting values for extended periods may affect device reliability.	
Application information	
Where application information is given, it is advisory and does not form part of the specification.	
© Philips Electronics N.V. 1998	
All rights are reserved. Reproduction in whole or in part is prohibited without the prior written consent of the copyright owner.	
The information presented in this document does not form part of any quotation or contract, it is believed to be accurate and reliable and may be changed without notice. No liability will be accepted by the publisher for any consequence of its use. Publication thereof does not convey nor imply any license under patent or other industrial or intellectual property rights.	

LIFE SUPPORT APPLICATIONS

These products are not designed for use in life support appliances, devices or systems where malfunction of these products can be reasonably expected to result in personal injury. Philips customers using or selling these products for use in such applications do so at their own risk and agree to fully indemnify Philips for any damages resulting from such improper use or sale.