

54AC11238, 74AC11238 3-LINE TO 8-LINE DECODERS/DEMULTIPLEXERS

SCAS039A – APRIL 1988 – REVISED APRIL 1993

- Designed Specifically for High-Speed Memory Decoders and Data Transmission Systems
- Noninverting Version of 'AC11138
- Incorporates 3 Enable Inputs to Simplify Cascading and/or Data Reception
- Flow-Through Architecture Optimizes PCB Layout
- Center-Pin V_{CC} and GND Configurations Minimize High-Speed Switching Noise
- EPIC™ (Enhanced-Performance Implanted CMOS) 1- μ m Process
- 500-mA Typical Latch-Up Immunity at 125°C
- Package Options Include Plastic Small-Outline Packages, Ceramic Chip Carriers, and Standard Plastic and Ceramic 300-mil DIPs

description


The 'AC11238 circuit is designed to be used in high-performance memory-decoding or data-routing applications requiring very short propagation delay times. In high-performance memory systems, this decoder can be used to minimize the effects of system decoding. When employed with high-speed memories utilizing a fast enable circuit, the delay times of this decoder and the enable time of the memory are usually less than the typical access time of the memory. This means that the effective system delay introduced by the decoder is negligible.

The conditions at the binary select inputs and the three enable inputs select one of eight input lines. Two active-low and one active-high enable inputs reduce the need for external gates or inverters when expanding. A 24-line decoder can be implemented without external inverters and a 32-line decoder requires only one inverter. An enable input can be used as a data input for demultiplexing applications.


The 54AC11238 is characterized for operation over the full military temperature range of – 55°C to 125°C. The 74AC11238 is characterized for operation from – 40°C to 85°C.

54AC11238 . . . J PACKAGE 74AC11238 . . . D OR N PACKAGE

(TOP VIEW)



54AC11238 . . . FK PACKAGE (TOP VIEW)



NC – No internal connection

EPIC is a trademark of Texas Instruments Incorporated.

PRODUCTION DATA information is current as of publication date. Products conform to specifications per the terms of Texas Instruments standard warranty. Production processing does not necessarily include testing of all parameters.

Copyright © 1993, Texas Instruments Incorporated

**TEXAS
INSTRUMENTS**

POST OFFICE BOX 655303 • DALLAS, TEXAS 75265

54AC11238, 74AC11238



3-LINE TO 8-LINE DECODERS/DEMULTIPLEXERS

SCAS039A – APRIL 1988 – REVISED APRIL 1993

FUNCTION TABLE


| ENABLE INPUTS | | | SELECT INPUTS | | | OUTPUTS | | | | | | | |
|---------------|------------------|------------------|---------------|---|---|---------|----|----|----|----|----|----|----|
| G1 | $\overline{G2A}$ | $\overline{G2B}$ | C | B | A | Y0 | Y1 | Y2 | Y3 | Y4 | Y5 | Y6 | Y7 |
| X | H | X | X | X | X | L | L | L | L | L | L | L | L |
| X | X | H | X | X | X | L | L | L | L | L | L | L | L |
| L | X | X | X | X | X | L | L | L | L | L | L | L | L |
| H | L | L | L | L | L | H | L | L | L | L | L | L | L |
| H | L | L | L | L | H | L | H | L | L | L | L | L | L |
| H | L | L | L | H | L | L | L | H | L | L | L | L | L |
| H | L | L | L | H | H | L | L | L | H | L | L | L | L |
| H | L | L | H | L | L | L | L | L | L | H | L | L | L |
| H | L | L | H | L | H | L | L | L | L | L | H | L | L |
| H | L | L | H | H | L | L | L | L | L | L | L | H | L |
| H | L | L | H | H | H | L | L | L | L | L | L | L | H |

logic symbols (alternatives)†



† These symbols are in accordance with ANSI/IEEE Std 91-1984 and IEC Publication 617-12.

logic diagram (positive logic)



Pin numbers shown are for the D, J, and N packages.

absolute maximum ratings over operating free-air temperature range (unless otherwise noted)[†]

| | |
|--|----------------------------|
| Supply voltage range, V_{CC} | –0.5 V to 7 V |
| Input voltage range, V_I (see Note 1) | –0.5 V to $V_{CC} + 0.5$ V |
| Output voltage range, V_O (see Note 1) | –0.5 V to $V_{CC} + 0.5$ V |
| Input clamp current, I_{IK} ($V_I < 0$ or $V_I > V_{CC}$) | ± 20 mA |
| Output clamp current, I_{OK} ($V_O < 0$ or $V_O > V_{CC}$) | ± 50 mA |
| Continuous output current, I_O ($V_O = 0$ to V_{CC}) | ± 50 mA |
| Continuous current through V_{CC} or GND | ± 200 mA |
| Storage temperature range | –65°C to 150°C |

[†] Stresses beyond those listed under “absolute maximum ratings” may cause permanent damage to the device. These are stress ratings only and functional operation of the device at these or any other conditions beyond those indicated under “recommended operating conditions” is not implied. Exposure to absolute-maximum-rated conditions for extended periods may affect device reliability.

NOTE 1: The input and output voltage ratings may be exceeded if the input and output current ratings are observed.

54AC11238, 74AC11238

3-LINE TO 8-LINE DECODERS/DEMULTIPLEXERS

SCAS039A – APRIL 1988 – REVISED APRIL 1993

recommended operating conditions

| | | | 54AC11238 | | | 74AC11238 | | | UNIT |
|-----------------|------------------------------------|-------------------------|-----------|-----------------|-----|-----------|-----------------|-----|------|
| | | | MIN | NOM | MAX | MIN | NOM | MAX | |
| V _{CC} | Supply voltage | | 3 | 5 | 5.5 | 3 | 5 | 5.5 | V |
| V _{IH} | High-level input voltage | V _{CC} = 3 V | 2.1 | | | 2.1 | | | V |
| | | V _{CC} = 4.5 V | 3.15 | | | 3.15 | | | |
| | | V _{CC} = 5.5 V | 3.85 | | | 3.85 | | | |
| V _{IL} | Low-level input voltage | V _{CC} = 3 V | 0.9 | | | 0.9 | | | V |
| | | V _{CC} = 4.5 V | 1.35 | | | 1.35 | | | |
| | | V _{CC} = 5.5 V | 1.65 | | | 1.65 | | | |
| V _I | Input voltage | | 0 | V _{CC} | | 0 | V _{CC} | | V |
| V _O | Output voltage | | 0 | V _{CC} | | 0 | V _{CC} | | V |
| I _{OH} | High-level output current | V _{CC} = 3 V | −4 | | | −4 | | | mA |
| | | V _{CC} = 4.5 V | −24 | | | −24 | | | |
| | | V _{CC} = 5.5 V | −24 | | | −24 | | | |
| I _{OL} | Low-level output current | V _{CC} = 3 V | 12 | | | 12 | | | mA |
| | | V _{CC} = 4.5 V | 24 | | | 24 | | | |
| | | V _{CC} = 5.5 V | 24 | | | 24 | | | |
| Δt/Δv | Input transition rise or fall rate | | 0 | 10 | | 0 | 10 | | ns/V |
| T _A | Operating free-air temperature | | −55 | 125 | | −40 | 85 | | °C |

electrical characteristics over recommended operating free-air temperature range (unless otherwise noted)

| PARAMETER | TEST CONDITIONS | V_{CC} | $T_A = 25^\circ\text{C}$ | | | 54AC11238 | | 74AC11238 | | UNIT |
|-----------|-----------------------------------|----------|--------------------------|------|-----------|-----------|---------|-----------|---------|---------------|
| | | | MIN | TYP† | MAX | MIN | MAX | MIN | MAX | |
| V_{OH} | $I_{OH} = -50\text{ }\mu\text{A}$ | 3 V | 2.9 | | | 2.9 | | 2.9 | | V |
| | | 4.5 V | 4.4 | | | 4.4 | | 4.4 | | |
| | | 5.5 V | 5.4 | | | 5.4 | | 5.4 | | |
| | $I_{OH} = -4\text{ mA}$ | 3 V | 2.58 | | | 2.4 | | 2.48 | | |
| | | 4.5 V | 3.94 | | | 3.7 | | 3.8 | | |
| | $I_{OH} = -24\text{ mA}$ | 4.5 V | 4.94 | | | 4.7 | | 4.8 | | |
| | | 5.5 V | | | | 3.85 | | | | |
| V_{OL} | $I_{OL} = 50\text{ }\mu\text{A}$ | 3 V | | | 0.1 | | 0.1 | | 0.1 | V |
| | | 4.5 V | | | 0.1 | | 0.1 | | 0.1 | |
| | | 5.5 V | | | 0.1 | | 0.1 | | 0.1 | |
| | $I_{OL} = 12\text{ mA}$ | 3 V | | | 0.36 | | 0.5 | | 0.44 | |
| | | 4.5 V | | | 0.36 | | 0.5 | | 0.44 | |
| | $I_{OL} = 24\text{ mA}$ | 4.5 V | | | 0.36 | | 0.5 | | 0.44 | |
| | | 5.5 V | | | 0.36 | | 0.5 | | 0.44 | |
| I_{OL} | $I_{OL} = 50\text{ mA}^\ddagger$ | 5.5 V | | | | 1.65 | | | | V |
| | $I_{OL} = 75\text{ mA}^\ddagger$ | 5.5 V | | | | | | 1.65 | | |
| I_I | $V_I = V_{CC}$ or GND | 5.5 V | | | ± 0.1 | | ± 1 | | ± 1 | μA |
| I_{CC} | $V_I = V_{CC}$ or GND, $I_O = 0$ | 5.5 V | | | 4 | | 80 | | 40 | μA |
| C_i | $V_I = V_{CC}$ or GND | 5 V | | | 3.5 | | | | | pF |

† All typical values are at $V_{CC} = 5\text{ V}$, $T_A = 25^\circ\text{C}$.

‡ Not more than one output should be tested at a time, and the duration of the test should not exceed 10 ms.



54AC11238, 74AC11238 3-LINE TO 8-LINE DECODERS/DEMULTIPLEXERS

SCAS039A – APRIL 1988 – REVISED APRIL 1993

switching characteristics over recommended operating free-air temperature range,
 $V_{CC} = 3.3 \text{ V} \pm 0.3 \text{ V}$ (unless otherwise noted) (see Figure 1)

| PARAMETER | FROM (INPUT) | TO (OUTPUT) | $T_A = 25^\circ\text{C}$ | | | 54AC11238 | | 74AC11238 | | UNIT |
|-----------|----------------------------------|----------------|--------------------------|------|------|-----------|------|-----------|------|------|
| | | | MIN | TYP | MAX | MIN | MAX | MIN | MAX | |
| t_{PLH} | A, B, C | Any Y | 1.5 | 8.5 | 10.6 | 1.5 | 12.7 | 1.5 | 11.7 | ns |
| t_{PHL} | | | 1.5 | 9.6 | 11.9 | 1.5 | 14.3 | 1.5 | 13.3 | |
| t_{PLH} | G1 | Any Y | 1.5 | 8.2 | 10.3 | 1.5 | 12.3 | 1.5 | 11.4 | ns |
| t_{PHL} | | | 1.5 | 9.6 | 11.7 | 1.5 | 14 | 1.5 | 13 | |
| t_{PLH} | $\overline{G2A}, \overline{G2B}$ | Any Y | 1.5 | 9.1 | 11.2 | 1.5 | 13.4 | 1.5 | 12.5 | ns |
| t_{PHL} | | | 1.5 | 10.7 | 12.9 | 1.5 | 15.6 | 1.5 | 14.5 | |


switching characteristics over recommended operating free-air temperature range,
 $V_{CC} = 5 \text{ V} \pm 0.5 \text{ V}$ (unless otherwise noted) (see Figure 1)

| PARAMETER | FROM (INPUT) | TO (OUTPUT) | $T_A = 25^\circ\text{C}$ | | | 54AC11238 | | 74AC11238 | | UNIT |
|-----------|----------------------------------|----------------|--------------------------|-----|-----|-----------|------|-----------|------|------|
| | | | MIN | TYP | MAX | MIN | MAX | MIN | MAX | |
| t_{PLH} | A, B, C | Any Y | 1.5 | 5.4 | 7.3 | 1.5 | 9 | 1.5 | 8.5 | ns |
| t_{PHL} | | | 1.5 | 6.3 | 8.6 | 1.5 | 10.9 | 1.5 | 10.2 | |
| t_{PLH} | G1 | Any Y | 1.5 | 5.2 | 6.9 | 1.5 | 8.7 | 1.5 | 8.1 | ns |
| t_{PHL} | | | 1.5 | 6.5 | 8.5 | 1.5 | 10.6 | 1.5 | 9.9 | |
| t_{PLH} | $\overline{G2A}, \overline{G2B}$ | Any Y | 1.5 | 5.6 | 7.5 | 1.5 | 9.6 | 1.5 | 8.9 | ns |
| t_{PHL} | | | 1.5 | 7.2 | 9.3 | 2.5 | 11.8 | 1.5 | 11 | |

operating characteristics, $V_{CC} = 5 \text{ V}$, $T_A = 25^\circ\text{C}$

| PARAMETER | | TEST CONDITIONS | | TYP | UNIT |
|-----------|-------------------------------|---|--|-----|------|
| C_{pd} | Power dissipation capacitance | $C_L = 50 \text{ pF}$, $f = 1 \text{ MHz}$ | | 44 | pF |

PARAMETER MEASUREMENT INFORMATION




- NOTES: A. C_L includes probe and jig capacitance.
 B. Input pulses are supplied by generators having the following characteristics: $PRR \leq 10 \text{ MHz}$, $Z_O = 50 \Omega$, $t_r = 3 \text{ ns}$, $t_f = 3 \text{ ns}$.
 C. The outputs are measured one at a time with one input transition per measurement.

Figure 1. Load Circuit and Voltage Waveforms

54AC11238, 74AC11238 3-LINE TO 8-LINE DECODERS/DEMULTIPLEXERS

SCAS039A – APRIL 1988 – REVISED APRIL 1993


TYPICAL APPLICATION DATA



Pin numbers shown are for the D, J, and N packages.

Figure 2. 24-Bit Decoding Scheme

TYPICAL APPLICATION DATA



Pin numbers shown are for the D, J, and N packages.

Figure 3. 32-Bit Decoding Scheme

IMPORTANT NOTICE

Texas Instruments (TI) reserves the right to make changes to its products or to discontinue any semiconductor product or service without notice, and advises its customers to obtain the latest version of relevant information to verify, before placing orders, that the information being relied on is current.

TI warrants performance of its semiconductor products and related software to the specifications applicable at the time of sale in accordance with TI's standard warranty. Testing and other quality control techniques are utilized to the extent TI deems necessary to support this warranty. Specific testing of all parameters of each device is not necessarily performed, except those mandated by government requirements.

Certain applications using semiconductor products may involve potential risks of death, personal injury, or severe property or environmental damage ("Critical Applications").

TI SEMICONDUCTOR PRODUCTS ARE NOT DESIGNED, INTENDED, AUTHORIZED, OR WARRANTED TO BE SUITABLE FOR USE IN LIFE-SUPPORT APPLICATIONS, DEVICES OR SYSTEMS OR OTHER CRITICAL APPLICATIONS.

Inclusion of TI products in such applications is understood to be fully at the risk of the customer. Use of TI products in such applications requires the written approval of an appropriate TI officer. Questions concerning potential risk applications should be directed to TI through a local SC sales office.

In order to minimize risks associated with the customer's applications, adequate design and operating safeguards should be provided by the customer to minimize inherent or procedural hazards.

TI assumes no liability for applications assistance, customer product design, software performance, or infringement of patents or services described herein. Nor does TI warrant or represent that any license, either express or implied, is granted under any patent right, copyright, mask work right, or other intellectual property right of TI covering or relating to any combination, machine, or process in which such semiconductor products or services might be or are used.