

SN54ALVTH16543, SN74ALVTH16543 2.5-V/3.3-V 16-BIT REGISTERED TRANSCEIVERS WITH 3-STATE OUTPUTS

SCES073A – JUNE 1996 – REVISED JULY 1996

- Members of the Texas Instruments **Widebus™** Family
- High-Impedance State During Power Up and Power Down
- 5-V I/O Compatible
- High-Drive Outputs (–32 mA/64 mA)
- Typical V_{OLP} (Output Ground Bounce) < 0.8 V at $V_{CC} = 3.3$ V, $T_A = 25^\circ\text{C}$
- Auto 3-State Eliminates Bus Current Loading When Voltage at the Output Exceeds V_{CC}
- Bus-Hold Data Inputs Eliminate the Need for External Pullup/Pulldown Resistors
- Power Off Disables Inputs/Outputs, Permitting Live Insertion
- Package Options Include Plastic 300-mil Shrink Small-Outline (DL), Thin Shrink Small-Outline (DGG), Thin Very Small-Outline (DGV) Packages, and 380-mil Fine-Pitch Ceramic Flat (WD) Package

description

The 'ALVTH16543 are 16-bit registered transceivers designed for 2.5-V or 3.3-V V_{CC} operation, but with the capability to provide a TTL interface to a 5-V system environment. These devices can be used as two 8-bit transceivers or one 16-bit transceiver. Separate latch-enable (\overline{LEAB} or \overline{LEBA}), output-enable (\overline{OEAB} or \overline{OEBA}), and chip-enable (\overline{CEAB} or \overline{CEBA}) inputs are provided for each register to permit independent control in either direction of data flow.

The A-to-B enable (\overline{CEAB}) input must be low to enter data from A or to output data from B. If \overline{CEAB} is low and \overline{LEAB} is low, the A-to-B latches are transparent; a subsequent low-to-high transition of \overline{LEAB} puts the A latches in the storage mode. With \overline{CEAB} and \overline{OEAB} both low, the 3-state B outputs are active and reflect the data present at the output of the A latches. Data flow from B to A is similar but uses the \overline{CEBA} , \overline{LEBA} , and \overline{OEBA} inputs.


Active bus-hold circuitry is provided to hold unused or floating data inputs at a valid logic level.

When V_{CC} is between 0 and 1.2 V, the device is in the high-impedance state during power up or power down. However, to ensure the high-impedance state above 1.2 V, \overline{OE} should be tied to V_{CC} through a pullup resistor; the minimum value of the resistor is determined by the current-sinking capability of the driver.

The SN74ALVTH16543 is available in TI's thin very small-outline package (DGV), which provides the same I/O pin count and functionality of standard Widebus packages in less than half the printed circuit board area.

The SN54ALVTH16543 is characterized for operation over the full military temperature range of -55°C to 125°C . The SN74ALVTH16543 is characterized for operation from -40°C to 85°C .

SN54ALVTH16543 . . . WD PACKAGE
SN74ALVTH16543 . . . DGG, DGV, OR DL PACKAGE
(TOP VIEW)



PRODUCT PREVIEW



Please be aware that an important notice concerning availability, standard warranty, and use in critical applications of Texas Instruments semiconductor products and disclaimers thereto appears at the end of this data sheet.

Widebus is a trademark of Texas Instruments Incorporated.

PRODUCT PREVIEW information concerns products in the formative or design phase of development. Characteristic data and other specifications are design goals. Texas Instruments reserves the right to change or discontinue these products without notice.

**TEXAS
INSTRUMENTS**

POST OFFICE BOX 655303 • DALLAS, TEXAS 75265

Copyright © 1996, Texas Instruments Incorporated



SN54ALVTH16543, SN74ALVTH16543

2.5-V/3.3-V 16-BIT REGISTERED TRANSCEIVERS

WITH 3-STATE OUTPUTS

SCES073A – JUNE 1996 – REVISED JULY 1996

logic diagram (positive logic)



PRODUCT PREVIEW



POST OFFICE BOX 655303 • DALLAS, TEXAS 75265

SN54ALVTH16543, SN74ALVTH16543

2.5-V/3.3-V 16-BIT REGISTERED TRANSCEIVERS

WITH 3-STATE OUTPUTS

SCES073A – JUNE 1996 – REVISED JULY 1996

FUNCTION TABLE†
(each 8-bit section)

INPUTS				OUTPUT B
$\overline{\text{CEAB}}$	$\overline{\text{LEAB}}$	$\overline{\text{OEAB}}$	A	
H	X	X	X	Z
X	X	H	X	Z
L	H	L	X	B ₀ ‡
L	L	L	L	L
L	L	L	H	H

† A-to-B data flow is shown; B-to-A flow control is the same except that it uses $\overline{\text{CEBA}}$, $\overline{\text{LEBA}}$, and $\overline{\text{OEBA}}$.

‡ Output level before the indicated steady-state input conditions were established

absolute maximum ratings over operating free-air temperature range (unless otherwise noted)§

Supply voltage range, V_{CC}	–0.5 V to 4.6 V
Input voltage range, V_I (see Note 1)	–0.5 V to 7 V
Voltage range applied to any output in the high state or power-off state, V_O (see Note 1)	–0.5 V to 7 V
Output current in the low state, I_O : SN54ALVTH16543	96 mA
SN74ALVTH16543	128 mA
Output current in the high state, I_O : SN54ALVTH16543	–48 mA
SN74ALVTH16543	–64 mA
Input clamp current, I_{IK} ($V_I < 0$)	–50 mA
Output clamp current, I_{OK} ($V_O < 0$)	–50 mA
Maximum power dissipation at $T_A = 55^\circ\text{C}$ (in still air) (see Note 2): DGG package	1 W
DGV package	1 W
DL package	1.4 W
Storage temperature range, T_{stg}	–65°C to 150°C

§ Stresses beyond those listed under “absolute maximum ratings” may cause permanent damage to the device. These are stress ratings only, and functional operation of the device at these or any other conditions beyond those indicated under “recommended operating conditions” is not implied. Exposure to absolute-maximum-rated conditions for extended periods may affect device reliability.

- NOTES:
1. The input and output negative-voltage ratings may be exceeded if the input and output clamp-current ratings are observed.
 2. The maximum package power dissipation is calculated using a junction temperature of 150°C and a board trace length of 750 mils. For more information, refer to the *Package Thermal Considerations* application note in the *ABT Advanced BiCMOS Technology Data Book*.

PRODUCT PREVIEW



SN54ALVTH16543, SN74ALVTH16543

2.5-V/3.3-V 16-BIT REGISTERED TRANSCEIVERS

WITH 3-STATE OUTPUTS

SCES073A – JUNE 1996 – REVISED JULY 1996

recommended operating conditions, $V_{CC} = 2.5\text{ V} \pm 0.2\text{ V}$ (see Note 3)

		SN54ALVTH16543		SN74ALVTH16543		UNIT
		MIN	MAX	MIN	MAX	
V_{CC}	Supply voltage	2.3	2.7	2.3	2.7	V
V_{IH}	High-level input voltage	1.7		1.7		V
V_{IL}	Low-level input voltage		0.7		0.7	V
V_I	Input voltage	0	5.5	0	5.5	V
I_{OH}	High-level output current		–6		–8	mA
I_{OL}	Low-level output current		6		8	mA
	Low-level output current; current duty cycle $\leq 50\%$; $f \geq 1\text{ KHz}$		18		24	
$\Delta t/\Delta v$	Input transition rise or fall rate	Outputs enabled			10	ns/V
T_A	Operating free-air temperature	–55	125	–40	85	°C

NOTE 3: Unused control inputs must be held high or low to prevent them from floating.

recommended operating conditions, $V_{CC} = 3.3\text{ V} \pm 0.3\text{ V}$ (see Note 3)

		SN54ALVTH16543		SN74ALVTH16543		UNIT
		MIN	MAX	MIN	MAX	
V_{CC}	Supply voltage	3	3.6	3	3.6	V
V_{IH}	High-level input voltage	2		2		V
V_{IL}	Low-level input voltage		0.8		0.8	V
V_I	Input voltage	0	5.5	0	5.5	V
I_{OH}	High-level output current		–24		–32	mA
I_{OL}	Low-level output current		24		32	mA
	Low-level output current; current duty cycle $\leq 50\%$; $f \geq 1\text{ KHz}$		48		64	
$\Delta t/\Delta v$	Input transition rise or fall rate	Outputs enabled			10	ns/V
T_A	Operating free-air temperature	–55	125	–40	85	°C

NOTE 3: Unused control inputs must be held high or low to prevent them from floating.

PRODUCT PREVIEW



POST OFFICE BOX 655303 • DALLAS, TEXAS 75265

SN54ALVTH16543, SN74ALVTH16543
2.5-V/3.3-V 16-BIT REGISTERED TRANSCEIVERS
WITH 3-STATE OUTPUTS

SCES073A – JUNE 1996 – REVISED JULY 1996

**electrical characteristics over recommended operating free-air temperature range,
 $V_{CC} = 2.5\text{ V} \pm 0.2\text{ V}$ (unless otherwise noted) (see Figure 1)**

PARAMETER	TEST CONDITIONS		SN54ALVTH16543			SN74ALVTH16543			UNIT
			MIN	TYP†	MAX	MIN	TYP†	MAX	
V_{IK}	$V_{CC} = 2.3\text{ V}$, $I_I = -18\text{ mA}$				-1.2			-1.2	V
V_{OH}	$V_{CC} = 2.3\text{ V to } 2.7\text{ V}$, $I_{OH} = -100\text{ }\mu\text{A}$		$V_{CC}-0.2$			$V_{CC}-0.2$			V
	$V_{CC} = 2.3\text{ V}$	$I_{OH} = -6\text{ mA}$	1.7						
		$I_{OH} = -8\text{ mA}$				1.7			
V_{OL}	$V_{CC} = 2.3\text{ V to } 2.7\text{ V}$, $I_{OL} = 100\text{ }\mu\text{A}$				0.2			0.2	V
	$V_{CC} = 2.3\text{ V}$	$I_{OL} = 6\text{ mA}$			0.5				
		$I_{OL} = 8\text{ mA}$						0.5	
		$I_{OL} = 18\text{ mA}$			0.5				
		$I_{OL} = 24\text{ mA}$						0.5	
I_I	$V_{CC} = 2.7\text{ V}$, $V_I = \text{GND}$	Control inputs			± 1			± 1	μA
	$V_{CC} = 0\text{ or } 2.7\text{ V}$, $V_I = 2.7\text{ V}$				10			10	
	$V_{CC} = 2.7\text{ V}$	$V_I = V_{CC}$ $V_I = 0$	A or B ports		10			10	
					-5			-5	
I_{off}	$V_{CC} = 0$, $V_I\text{ or } V_O = 0\text{ to } 4.5\text{ V}$				± 100			± 100	μA
$I_{I(\text{hold})}$	$V_{CC} = 2.3\text{ V}$	$V_I = 0.7\text{ V}$	A or B ports		90			90	μA
		$V_I = 1.7\text{ V}$			75			75	
	$V_{CC} = 2.7\text{ V}^\ddagger$, $V_I = 0\text{ to } 2.7\text{ V}$								
I_{EX}^\S	$V_{CC} = 2.3\text{ V}$, $V_O = 3.6\text{ V}$								μA
$I_{OZ(\text{PU/PD})}^\P$	$V_{CC} \leq 1.2\text{ V}$, $V_I = \text{GND or } V_{CC}$, $V_O = 0.5\text{ V to } V_{CC}$, $\text{OE} = \text{don't care}$				± 100			± 100	μA
I_{CC}	$V_{CC} = 2.7\text{ V}$, $I_O = 0$, $V_I = V_{CC}\text{ or GND}$	Outputs high		0.04	0.09		0.04	0.09	mA
		Outputs low		2.3	4.5		2.3	4.5	
		Outputs disabled		0.04	0.09		0.04	0.09	
C_i	$V_{CC} = 2.5\text{ V}$, $V_I = 2.5\text{ V or } 0$				3			3	pF
C_{io}	$V_{CC} = 2.5\text{ V}$, $V_O = 2.5\text{ V or } 0$				9			9	pF

† All typical values are at $V_{CC} = 2.5\text{ V}$, $T_A = 25^\circ\text{C}$.

‡ This is the bus-hold maximum dynamic current required to switch the input from one state to another.

§ Current into an output in the high state when $V_O > V_{CC}$

¶ High-impedance state during power up/high-impedance state during power down

PRODUCT PREVIEW

SN54ALVTH16543, SN74ALVTH16543

2.5-V/3.3-V 16-BIT REGISTERED TRANSCEIVERS

WITH 3-STATE OUTPUTS

SCES073A – JUNE 1996 – REVISED JULY 1996

electrical characteristics over recommended operating free-air temperature range,
 $V_{CC} = 3.3 \text{ V} \pm 0.3 \text{ V}$ (unless otherwise noted) (see Figure 2)

PARAMETER	TEST CONDITIONS		SN54ALVTH16543			SN74ALVTH16543			UNIT
			MIN	TYP†	MAX	MIN	TYP†	MAX	
V_{IK}	$V_{CC} = 3 \text{ V}$, $I_I = -18 \text{ mA}$				-1.2			-1.2	V
V_{OH}	$V_{CC} = 3 \text{ V to } 3.6 \text{ V}$, $I_{OH} = -100 \mu\text{A}$		$V_{CC}-0.2$			$V_{CC}-0.2$			V
	$V_{CC} = 3 \text{ V}$	$I_{OH} = -24 \text{ mA}$	2						
		$I_{OH} = -32 \text{ mA}$				2			
V_{OL}	$V_{CC} = 3 \text{ V to } 3.6 \text{ V}$, $I_{OL} = 100 \mu\text{A}$				0.2			0.2	V
	$V_{CC} = 3 \text{ V}$	$I_{OL} = 16 \text{ mA}$						0.4	
		$I_{OL} = 24 \text{ mA}$			0.5				
		$I_{OL} = 32 \text{ mA}$						0.5	
		$I_{OL} = 48 \text{ mA}$			0.55				
		$I_{OL} = 64 \text{ mA}$						0.55	
I_I	$V_{CC} = 3.6 \text{ V}$, $V_I = V_{CC} \text{ or GND}$	Control inputs			± 1			± 1	μA
	$V_{CC} = 0 \text{ or } 3.6 \text{ V}$, $V_I = 5.5 \text{ V}$				10			10	
	$V_{CC} = 3.6 \text{ V}$	$V_I = 5.5 \text{ V}$			20			20	
		$V_I = V_{CC}$			10			10	
		$V_I = 0$			-5			-5	
I_{off}	$V_{CC} = 0$, $V_I \text{ or } V_O = 0 \text{ to } 4.5 \text{ V}$				± 100			± 100	μA
$I_{I(hold)}$	$V_{CC} = 3 \text{ V}$	$V_I = 0.8 \text{ V}$	A or B ports		75			75	μA
		$V_I = 2 \text{ V}$			-75			-75	
	$V_{CC} = 3.6 \text{ V}^\ddagger$, $V_I = 0 \text{ to } 3.6 \text{ V}$				± 500			± 500	
I_{EX}^\S	$V_{CC} = 3 \text{ V}$, $V_O = 5.5 \text{ V}$				125			125	μA
$I_{OZ(PU/PD)}^\P$	$V_{CC} \leq 1.2 \text{ V}$, $V_I = \text{GND or } V_{CC}$, $\overline{OE} = \text{don't care}$				± 100			± 100	μA
I_{CC}	$V_{CC} = 3.6 \text{ V}$, $I_O = 0$, $V_I = V_{CC} \text{ or GND}$	Outputs high		0.07	0.09		0.07	0.09	mA
		Outputs low		3.2	5		3.2	5	
		Outputs disabled		0.07	0.09		0.07	0.09	
$\Delta I_{CC}^\#$	$V_{CC} = 3 \text{ V to } 3.6 \text{ V}$, One input at $V_{CC} - 0.6 \text{ V}$, Other inputs at V_{CC} or GND				0.2			0.2	mA
C_i	$V_{CC} = 3.3 \text{ V}$, $V_I = 3.3 \text{ V or } 0$				3			3	pF
C_{io}	$V_{CC} = 3.3 \text{ V}$, $V_O = 3.3 \text{ V or } 0$				9			9	pF

† All typical values are at $V_{CC} = 3.3 \text{ V}$, $T_A = 25^\circ\text{C}$.

‡ This is the bus-hold maximum dynamic current required to switch the input from one state to another.

§ Current into an output in the high state when $V_O > V_{CC}$

¶ High-impedance state during power up/high-impedance state during power down

This is the increase in supply current for each input that is at the specified TTL voltage level rather than V_{CC} or GND.

PRODUCT PREVIEW



POST OFFICE BOX 655303 • DALLAS, TEXAS 75265

SN54ALVTH16543, SN74ALVTH16543
2.5-V/3.3-V 16-BIT REGISTERED TRANSCEIVERS
WITH 3-STATE OUTPUTS

SCES073A – JUNE 1996 – REVISED JULY 1996

timing requirements over recommended operating free-air temperature range, $V_{CC} = 2.5\text{ V} \pm 0.2\text{ V}$ (unless otherwise noted) (see Figure 1)

				SN54ALVTH16543		SN74ALVTH16543		UNIT
				MIN	MAX	MIN	MAX	
t _w	Pulse duration, \overline{LEAB} or \overline{LEBA} low				1.5		1.5	ns
t _{su}	Setup time	A or B before $\overline{LEAB}\uparrow$ or $\overline{LEBA}\uparrow$	Data high	–0.2		–0.2	ns	
			Data low	0.8		0.8		
		A or B before $\overline{CEAB}\uparrow$ or $\overline{CEBA}\uparrow$	Data high	2		2		
			Data low	1.5		1.5		
t _h	Hold time	A or B after $\overline{LEAB}\uparrow$ or $\overline{LEBA}\uparrow$	Data high	0.8		0.8	ns	
			Data low	1.7		1.7		
		A or B after $\overline{CEAB}\uparrow$ or $\overline{CEBA}\uparrow$	Data high	0.5		0.5		
			Data low	–0.4		–0.4		

timing requirements over recommended operating free-air temperature range, $V_{CC} = 3.3\text{ V} \pm 0.3\text{ V}$ (unless otherwise noted) (see Figure 2)

				SN54ALVTH16543		SN74ALVTH16543		UNIT
				MIN	MAX	MIN	MAX	
t _w	Pulse duration, \overline{LEAB} or \overline{LEBA} low			1.5		1.5		ns
t _{su}	Setup time	A or B before $\overline{LEAB}\uparrow$ or $\overline{LEBA}\uparrow$	Data high	0.0		0.0		ns
			Data low	0.7		0.7		
		A or B before $\overline{CEAB}\uparrow$ or $\overline{CEBA}\uparrow$	Data high	0.7		0.7		
			Data low	1.1		1.1		
t _h	Hold time	A or B after $\overline{LEAB}\uparrow$ or $\overline{LEBA}\uparrow$	Data high	0.7		0.7		ns
			Data low	1.5		1.5		
		A or B after $\overline{CEAB}\uparrow$ or $\overline{CEBA}\uparrow$	Data high	0.3		0.3		
			Data low	0.7		0.7		

PRODUCT PREVIEW



SN54ALVTH16543, SN74ALVTH16543 2.5-V/3.3-V 16-BIT REGISTERED TRANSCEIVERS WITH 3-STATE OUTPUTS

SCES073A – JUNE 1996 – REVISED JULY 1996

switching characteristics over recommended operating free-air temperature range, $C_L = 50 \text{ pF}$, $V_{CC} = 2.5 \text{ V} \pm 0.2 \text{ V}$ (unless otherwise noted) (see Figure 1)

PARAMETER	FROM (INPUT)	TO (OUTPUT)	SN54ALVTH16543		SN74ALVTH16543			UNIT
			MIN	MAX	MIN	TYP†	MAX	
t_{pd}	A or B	B or A	1	4.4	1	2.1	4	ns
	\overline{LE}	A or B	1.5	6.7	1.5	2.9	6.1	
t_{en}	\overline{OE}	A or B	2	6.7	2	3.1	6.1	ns
t_{dis}	\overline{OE}	A or B	2	6.2	2	3.5	5.6	ns
t_{en}	\overline{CE}	A or B	2	6.9	2	3.1	6.2	ns
t_{dis}	\overline{CE}	A or B	2	7.1	2	3.7	6.4	ns

† All typical values are at $V_{CC} = 2.5 \text{ V}$, $T_A = 25^\circ\text{C}$.

switching characteristics over recommended operating free-air temperature range, $C_L = 50 \text{ pF}$, $V_{CC} = 3.3 \text{ V} \pm 0.3 \text{ V}$ (unless otherwise noted) (see Figure 2)

PARAMETER	FROM (INPUT)	TO (OUTPUT)	SN54ALVTH16543		SN74ALVTH16543			UNIT
			MIN	MAX	MIN	TYP‡	MAX	
t_{pd}	A or B	B or A	1	3.3	1	1.8	3	ns
	\overline{LE}	A or B	1.5	4.4	1.5	2.4	4	
t_{en}	\overline{OE}	A or B	1.5	4.5	1.5	2.6	4.1	ns
t_{dis}	\overline{OE}	A or B	1.5	4.7	1.5	2.7	4.3	ns
t_{en}	\overline{CE}	A or B	1.5	4.4	1.5	2.5	4	ns
t_{dis}	\overline{CE}	A or B	1.5	4.7	1.5	2.7	4.3	ns

‡ All typical values are at $V_{CC} = 3.3 \text{ V}$, $T_A = 25^\circ\text{C}$.

PRODUCT PREVIEW




POST OFFICE BOX 655303 • DALLAS, TEXAS 75265

SN54ALVTH16543, SN74ALVTH16543 2.5-V/3.3-V 16-BIT REGISTERED TRANSCEIVERS WITH 3-STATE OUTPUTS

SCES073A – JUNE 1996 – REVISED JULY 1996


PARAMETER MEASUREMENT INFORMATION

$$V_{CC} = 2.5 \text{ V} \pm 0.2 \text{ V}$$




LOAD CIRCUIT


TEST	S1
t_{pd}	Open
t_{PLZ}/t_{PZL}	2 $\times V_{CC}$
t_{PHZ}/t_{PZH}	GND




VOLTAGE WAVEFORMS
SETUP AND HOLD TIMES



VOLTAGE WAVEFORMS
PROPAGATION DELAY TIMES



VOLTAGE WAVEFORMS
PULSE DURATION



VOLTAGE WAVEFORMS
ENABLE AND DISABLE TIMES

- NOTES:
- C_L includes probe and jig capacitance.
 - Waveform 1 is for an output with internal conditions such that the output is low except when disabled by the output control. Waveform 2 is for an output with internal conditions such that the output is high except when disabled by the output control.
 - All input pulses are supplied by generators having the following characteristics: PRR $\leq 10 \text{ MHz}$, $Z_O = 50 \Omega$, $t_r \leq 2.5 \text{ ns}$, $t_f \leq 2.5 \text{ ns}$.
 - The outputs are measured one at a time with one transition per measurement.
 - t_{PLZ} and t_{PHZ} are the same as t_{dis} .
 - t_{PZL} and t_{PZH} are the same as t_{en} .
 - t_{PLH} and t_{PHL} are the same as t_{pd} .

Figure 1. Load Circuit and Voltage Waveforms

PRODUCT PREVIEW

SN54ALVTH16543, SN74ALVTH16543


2.5-V/3.3-V 16-BIT REGISTERED TRANSCEIVERS

WITH 3-STATE OUTPUTS

SCES073A – JUNE 1996 – REVISED JULY 1996


PARAMETER MEASUREMENT INFORMATION

$$V_{CC} = 3.3 \text{ V} \pm 0.3 \text{ V}$$




LOAD CIRCUIT


TEST	S1
t_{pd}	Open
t_{PLZ}/t_{PZL}	6 V
t_{PHZ}/t_{PZH}	GND




VOLTAGE WAVEFORMS
PULSE DURATION



VOLTAGE WAVEFORMS
SETUP AND HOLD TIMES



VOLTAGE WAVEFORMS
PROPAGATION DELAY TIMES
INVERTING AND NONINVERTING OUTPUTS



VOLTAGE WAVEFORMS
ENABLE AND DISABLE TIMES
LOW- AND HIGH-LEVEL ENABLING

- NOTES:
- C_L includes probe and jig capacitance.
 - Waveform 1 is for an output with internal conditions such that the output is low except when disabled by the output control. Waveform 2 is for an output with internal conditions such that the output is high except when disabled by the output control.
 - All input pulses are supplied by generators having the following characteristics: $PRR \leq 10 \text{ MHz}$, $Z_O = 50 \Omega$, $t_r \leq 2.5 \text{ ns}$, $t_f \leq 2.5 \text{ ns}$.
 - The outputs are measured one at a time with one transition per measurement.
 - t_{PLZ} and t_{PHZ} are the same as t_{dis} .
 - t_{PZL} and t_{PZH} are the same as t_{en} .
 - t_{PLH} and t_{PHL} are the same as t_{pd} .

Figure 2. Load Circuit and Voltage Waveforms

IMPORTANT NOTICE

Texas Instruments (TI) reserves the right to make changes to its products or to discontinue any semiconductor product or service without notice, and advises its customers to obtain the latest version of relevant information to verify, before placing orders, that the information being relied on is current.

TI warrants performance of its semiconductor products and related software to the specifications applicable at the time of sale in accordance with TI's standard warranty. Testing and other quality control techniques are utilized to the extent TI deems necessary to support this warranty. Specific testing of all parameters of each device is not necessarily performed, except those mandated by government requirements.

Certain applications using semiconductor products may involve potential risks of death, personal injury, or severe property or environmental damage ("Critical Applications").

TI SEMICONDUCTOR PRODUCTS ARE NOT DESIGNED, INTENDED, AUTHORIZED, OR WARRANTED TO BE SUITABLE FOR USE IN LIFE-SUPPORT APPLICATIONS, DEVICES OR SYSTEMS OR OTHER CRITICAL APPLICATIONS.

Inclusion of TI products in such applications is understood to be fully at the risk of the customer. Use of TI products in such applications requires the written approval of an appropriate TI officer. Questions concerning potential risk applications should be directed to TI through a local SC sales office.

In order to minimize risks associated with the customer's applications, adequate design and operating safeguards should be provided by the customer to minimize inherent or procedural hazards.

TI assumes no liability for applications assistance, customer product design, software performance, or infringement of patents or services described herein. Nor does TI warrant or represent that any license, either express or implied, is granted under any patent right, copyright, mask work right, or other intellectual property right of TI covering or relating to any combination, machine, or process in which such semiconductor products or services might be or are used.