

# SN54HC646, SN74HC646 OCTAL BUS TRANSCEIVERS AND REGISTERS WITH 3-STATE OUTPUTS

SCLS150B – DECEMBER 1982 – REVISED MAY 1997

- Independent Registers for A and B Buses
- Multiplexed Real-Time and Stored Data
- True Data Paths
- High-Current 3-State Outputs Can Drive up to 15 LSTTL Loads
- Package Options Include Plastic Small-Outline (DW) and Ceramic Flat (W) Packages, Ceramic Chip Carriers (FK), and Standard Plastic (NT) and Ceramic (JT) 300-mil DIPs

## description

The 'HC646 consist of bus-transceiver circuits with 3-state outputs, D-type flip-flops, and control circuitry arranged for multiplexed transmission of data directly from the input bus or from the internal registers. Data on the A or B bus is clocked into the registers on the low-to-high transition of the appropriate clock (CLKAB or CLKBA) input. Figure 1 illustrates the four fundamental bus-management functions that can be performed with the 'HC646.


Output-enable ( $\overline{OE}$ ) and direction-control (DIR) inputs control the transceiver functions. In the transceiver mode, data present at the high-impedance port may be stored in either or both registers.

The select-control (SAB and SBA) inputs can multiplex stored and real-time (transparent mode) data. DIR determines which bus receives data when  $\overline{OE}$  is active (low). In the isolation mode ( $\overline{OE}$  high), A data may be stored in one register and/or B data may be stored in the other register.


When an output function is disabled, the input function is still enabled and can be used to store and transmit data. Only one of the two buses, A or B, may be driven at a time.

The SN54HC646 is characterized for operation over the full military temperature range of  $-55^{\circ}\text{C}$  to  $125^{\circ}\text{C}$ . The SN74HC646 is characterized for operation from  $-40^{\circ}\text{C}$  to  $85^{\circ}\text{C}$ .

SN54HC646 . . . JT OR W PACKAGE  
SN74HC646 . . . DW OR NT PACKAGE  
(TOP VIEW)



SN54HC646 . . . FK PACKAGE  
(TOP VIEW)



NC – No internal connection



Please be aware that an important notice concerning availability, standard warranty, and use in critical applications of Texas Instruments semiconductor products and disclaimers thereto appears at the end of this data sheet.

UNLESS OTHERWISE NOTED this document contains PRODUCTION DATA information current as of publication date. Products conform to specifications per the terms of Texas Instruments standard warranty. Production processing does not necessarily include testing of all parameters.


 **TEXAS  
INSTRUMENTS**

POST OFFICE BOX 655303 • DALLAS, TEXAS 75265

Copyright © 1997, Texas Instruments Incorporated

# SN54HC646, SN74HC646 OCTAL BUS TRANSCEIVERS AND REGISTERS WITH 3-STATE OUTPUTS

SCLS150B – DECEMBER 1982 – REVISED MAY 1997



Pin numbers shown are for the DW, JT, NT, and W packages.

**Figure 1. Bus-Management Functions**

# SN54HC646, SN74HC646 OCTAL BUS TRANSCEIVERS AND REGISTERS WITH 3-STATE OUTPUTS


SCLS150B – DECEMBER 1982 – REVISED MAY 1997

FUNCTION TABLE

| INPUTS |     |        |        |     |     | DATA I/O       |                | OPERATION OR FUNCTION     |
|--------|-----|--------|--------|-----|-----|----------------|----------------|---------------------------|
| OE     | DIR | CLKAB  | CLKBA  | SAB | SBA | A1–A8          | B1–B8          |                           |
| X      | X   | ↑      | X      | X   | X   | Input          | Unspecified†   | Store A, B unspecified†   |
| X      | X   | X      | ↑      | X   | X   | Unspecified†   | Input          | Store B, A unspecified†   |
| H      | X   | ↑      | ↑      | X   | X   | Input          | Input          | Store A and B data        |
| H      | X   | H or L | H or L | X   | X   | Input disabled | Input disabled | Isolation, hold storage   |
| L      | L   | X      | X      | X   | L   | Output         | Input          | Real-time B data to A bus |
| L      | L   | X      | H or L | X   | H   | Output         | Input          | Stored B data to A bus    |
| L      | H   | X      | X      | L   | X   | Input          | Output         | Real-time A data to B bus |
| L      | H   | H or L | X      | H   | X   | Input          | Output         | Stored A data to B bus    |

† The data-output functions can be enabled or disabled by various signals at OE and DIR. Data-input functions are always enabled; i.e., data at the bus terminals is stored on every low-to-high transition of the clock inputs.

## logic symbol‡




‡ This symbol is in accordance with ANSI/IEEE Std 91-1984 and IEC Publication 617-12. Pin numbers shown are for the DW, JT, NT, and W packages.

# SN54HC646, SN74HC646 OCTAL BUS TRANSCEIVERS AND REGISTERS WITH 3-STATE OUTPUTS

SCLS150B – DECEMBER 1982 – REVISED MAY 1997

## logic diagram (positive logic)



Pin numbers shown are for the DW, JT, NT, and W packages.

## absolute maximum ratings over operating free-air temperature range†

|                                                                                   |                |
|-----------------------------------------------------------------------------------|----------------|
| Supply voltage range, $V_{CC}$ .....                                              | -0.5 V to 7 V  |
| Input clamp current, $I_{IK}$ ( $V_I < 0$ or $V_I > V_{CC}$ ) (see Note 1) .....  | $\pm 20$ mA    |
| Output clamp current, $I_{OK}$ ( $V_O < 0$ or $V_O > V_{CC}$ ) (see Note 1) ..... | $\pm 20$ mA    |
| Continuous output current, $I_O$ ( $V_O = 0$ to $V_{CC}$ ) .....                  | $\pm 35$ mA    |
| Continuous current through $V_{CC}$ or GND .....                                  | $\pm 70$ mA    |
| Package thermal impedance, $\theta_{JA}$ (see Note 2): DW package .....           | 81°C/W         |
| NT package .....                                                                  | 67°C/W         |
| Storage temperature range, $T_{stg}$ .....                                        | -65°C to 150°C |

† Stresses beyond those listed under "absolute maximum ratings" may cause permanent damage to the device. These are stress ratings only, and functional operation of the device at these or any other conditions beyond those indicated under "recommended operating conditions" is not implied. Exposure to absolute-maximum-rated conditions for extended periods may affect device reliability.

NOTES: 1. The input and output voltage ratings may be exceeded if the input and output current ratings are observed.

2. The package thermal impedance is calculated in accordance with JESD 51, except for through-hole packages, which use a trace length of zero.



POST OFFICE BOX 655303 • DALLAS, TEXAS 75265

# SN54HC646, SN74HC646 OCTAL BUS TRANSCEIVERS AND REGISTERS WITH 3-STATE OUTPUTS

SCLS150B – DECEMBER 1982 – REVISED MAY 1997

## recommended operating conditions

|                 |                                       | SN54HC646               |     |                 | SN74HC646 |     |                 | UNIT |
|-----------------|---------------------------------------|-------------------------|-----|-----------------|-----------|-----|-----------------|------|
|                 |                                       | MIN                     | NOM | MAX             | MIN       | NOM | MAX             |      |
| V <sub>CC</sub> | Supply voltage                        | 2                       | 5   | 6               | 2         | 5   | 6               | V    |
| V <sub>IH</sub> | High-level input voltage              | V <sub>CC</sub> = 2 V   |     | 1.5             | 1.5       |     | V               |      |
|                 |                                       | V <sub>CC</sub> = 4.5 V |     | 3.15            | 3.15      |     |                 |      |
|                 |                                       | V <sub>CC</sub> = 6 V   |     | 4.2             | 4.2       |     |                 |      |
| V <sub>IL</sub> | Low-level input voltage               | V <sub>CC</sub> = 2 V   |     | 0               | 0.5       | 0   | 0.5             | V    |
|                 |                                       | V <sub>CC</sub> = 4.5 V |     | 0               | 1.35      | 0   | 1.35            |      |
|                 |                                       | V <sub>CC</sub> = 6 V   |     | 0               | 1.8       | 0   | 1.8             |      |
| V <sub>I</sub>  | Input voltage                         | 0                       |     | V <sub>CC</sub> | 0         |     | V <sub>CC</sub> | V    |
| V <sub>O</sub>  | Output voltage                        | 0                       |     | V <sub>CC</sub> | 0         |     | V <sub>CC</sub> | V    |
| t <sub>t</sub>  | Input transition (rise and fall) time | V <sub>CC</sub> = 2 V   |     | 0               | 1000      | 0   | 1000            | ns   |
|                 |                                       | V <sub>CC</sub> = 4.5 V |     | 0               | 500       | 0   | 500             |      |
|                 |                                       | V <sub>CC</sub> = 6 V   |     | 0               | 400       | 0   | 400             |      |
| T <sub>A</sub>  | Operating free-air temperature        | -55                     |     | 125             | -40       |     | 85              | °C   |

## electrical characteristics over recommended operating free-air temperature range (unless otherwise noted)

| PARAMETER       | TEST CONDITIONS |                                                           | V <sub>CC</sub>           | T <sub>A</sub> = 25°C |       |       | SN54HC646 |      | SN74HC646 |     | UNIT |
|-----------------|-----------------|-----------------------------------------------------------|---------------------------|-----------------------|-------|-------|-----------|------|-----------|-----|------|
|                 |                 |                                                           |                           | MIN                   | TYP   | MAX   | MIN       | MAX  | MIN       | MAX |      |
| V <sub>OH</sub> |                 | V <sub>I</sub> = V <sub>IH</sub> or V <sub>IL</sub>       | I <sub>OH</sub> = -20 μA  | 2 V                   | 1.9   | 1.998 | 1.9       | 1.9  | V         |     |      |
|                 |                 |                                                           |                           | 4.5 V                 | 4.4   | 4.499 | 4.4       | 4.4  |           |     |      |
|                 |                 |                                                           |                           | 6 V                   | 5.9   | 5.999 | 5.9       | 5.9  |           |     |      |
|                 |                 |                                                           | I <sub>OH</sub> = -6 mA   | 4.5 V                 | 3.98  | 4.3   | 3.7       | 3.84 |           |     |      |
|                 |                 |                                                           | I <sub>OH</sub> = -7.8 mA | 6 V                   | 5.48  | 5.8   | 5.2       | 5.34 |           |     |      |
| V <sub>OL</sub> |                 | V <sub>I</sub> = V <sub>IH</sub> or V <sub>IL</sub>       | I <sub>OL</sub> = 20 μA   | 2 V                   | 0.002 | 0.1   | 0.1       | 0.1  | V         |     |      |
|                 |                 |                                                           |                           | 4.5 V                 | 0.001 | 0.1   | 0.1       | 0.1  |           |     |      |
|                 |                 |                                                           |                           | 6 V                   | 0.001 | 0.1   | 0.1       | 0.1  |           |     |      |
|                 |                 |                                                           | I <sub>OL</sub> = 6 mA    | 4.5 V                 | 0.17  | 0.26  | 0.4       | 0.33 |           |     |      |
|                 |                 |                                                           | I <sub>OL</sub> = 7.8 mA  | 6 V                   | 0.15  | 0.26  | 0.4       | 0.33 |           |     |      |
| I <sub>I</sub>  | Control inputs  | V <sub>I</sub> = V <sub>CC</sub> or 0                     | 6 V                       | ±0.1                  | ±100  | ±1000 | ±1000     | nA   |           |     |      |
| I <sub>OZ</sub> | A or B          | V <sub>O</sub> = V <sub>CC</sub> or 0                     | 6 V                       | ±0.01                 | ±0.5  | ±10   | ±5        | μA   |           |     |      |
| I <sub>CC</sub> |                 | V <sub>I</sub> = V <sub>CC</sub> or 0, I <sub>O</sub> = 0 | 6 V                       |                       | 8     | 160   | 80        | μA   |           |     |      |
| C <sub>i</sub>  | Control inputs  |                                                           | 2 V to 6 V                | 3                     | 10    | 10    | 10        | pF   |           |     |      |

PRODUCT PREVIEW information concerns products in the formative or design phase of development. Characteristic data and other specifications are design goals. Texas Instruments reserves the right to change or discontinue these products without notice.



**SN54HC646, SN74HC646**  
**OCTAL BUS TRANSCEIVERS AND REGISTERS**  
**WITH 3-STATE OUTPUTS**

SCLS150B – DECEMBER 1982 – REVISED MAY 1997

timing requirements over recommended operating free-air temperature range (unless otherwise noted)

|                                                                | V <sub>CC</sub> | T <sub>A</sub> = 25°C |     | SN54HC646 |     | SN74HC646 |     | UNIT |
|----------------------------------------------------------------|-----------------|-----------------------|-----|-----------|-----|-----------|-----|------|
|                                                                |                 | MIN                   | MAX | MIN       | MAX | MIN       | MAX |      |
| f <sub>clock</sub> Clock frequency                             | 2 V             | 0                     | 6   | 0         | 4.3 | 0         | 5.5 | MHz  |
|                                                                | 4.5 V           | 0                     | 31  | 0         | 22  | 0         | 27  |      |
|                                                                | 6 V             | 0                     | 36  | 0         | 25  | 0         | 31  |      |
| t <sub>w</sub> Pulse duration, CLKBA or CLKAB high or low      | 2 V             | 80                    |     | 115       |     | 95        |     | ns   |
|                                                                | 4.5 V           | 16                    |     | 23        |     | 19        |     |      |
|                                                                | 6 V             | 14                    |     | 20        |     | 16        |     |      |
| t <sub>su</sub> Setup time, A before CLKAB↑ or B before CLKBA↑ | 2 V             | 100                   |     | 150       |     | 125       |     | ns   |
|                                                                | 4.5 V           | 20                    |     | 30        |     | 25        |     |      |
|                                                                | 6 V             | 17                    |     | 26        |     | 21        |     |      |
| t <sub>h</sub> Hold time, A after CLKAB↑ or B after CLKBA↑     | 2 V             | 5                     |     | 5         |     | 5         |     | ns   |
|                                                                | 4.5 V           | 5                     |     | 5         |     | 5         |     |      |
|                                                                | 6 V             | 5                     |     | 5         |     | 5         |     |      |

PRODUCT PREVIEW information concerns products in the formative or design phase of development. Characteristic data and other specifications are design goals. Texas Instruments reserves the right to change or discontinue these products without notice.



POST OFFICE BOX 655303 • DALLAS, TEXAS 75265

# SN54HC646, SN74HC646 OCTAL BUS TRANSCEIVERS AND REGISTERS WITH 3-STATE OUTPUTS

SCLS150B – DECEMBER 1982 – REVISED MAY 1997

switching characteristics over recommended operating free-air temperature range,  $C_L = 50$  pF (unless otherwise noted) (see Figure 2)

| PARAMETER | FROM (INPUT)    | TO (OUTPUT) | $V_{CC}$ | $T_A = 25^\circ\text{C}$ |     |     | SN54HC646 |     | SN74HC646 |     | UNIT |
|-----------|-----------------|-------------|----------|--------------------------|-----|-----|-----------|-----|-----------|-----|------|
|           |                 |             |          | MIN                      | TYP | MAX | MIN       | MAX | MIN       | MAX |      |
| $f_{max}$ |                 |             | 2 V      | 6                        | 11  |     | 4.4       |     | 5.5       | MHz |      |
|           |                 |             | 4.5 V    | 31                       | 54  |     | 22        |     | 27        |     |      |
|           |                 |             | 6 V      | 36                       | 64  |     | 25        |     | 31        |     |      |
| $t_{pd}$  | CLKBA or CLKAB  | A or B      | 2 V      |                          | 65  | 180 |           | 270 |           | 225 | ns   |
|           |                 |             | 4.5 V    |                          | 18  | 36  |           | 54  |           | 45  |      |
|           |                 |             | 6 V      |                          | 14  | 31  |           | 46  |           | 38  |      |
|           | A or B          | B or A      | 2 V      |                          | 50  | 135 |           | 205 |           | 170 |      |
|           |                 |             | 4.5 V    |                          | 14  | 27  |           | 41  |           | 34  |      |
|           |                 |             | 6 V      |                          | 11  | 23  |           | 35  |           | 29  |      |
|           | SBA or SAB†     | A or B      | 2 V      |                          | 70  | 190 |           | 285 |           | 240 |      |
|           |                 |             | 4.5 V    |                          | 20  | 38  |           | 57  |           | 48  |      |
|           |                 |             | 6 V      |                          | 16  | 32  |           | 48  |           | 41  |      |
| $t_{en}$  | $\overline{OE}$ | A or B      | 2 V      |                          | 85  | 245 |           | 370 |           | 305 | ns   |
|           |                 |             | 4.5 V    |                          | 25  | 49  |           | 74  |           | 61  |      |
|           |                 |             | 6 V      |                          | 20  | 42  |           | 63  |           | 52  |      |
| $t_{dis}$ | $\overline{OE}$ | A or B      | 2 V      |                          | 85  | 245 |           | 370 |           | 305 | ns   |
|           |                 |             | 4.5 V    |                          | 25  | 49  |           | 74  |           | 61  |      |
|           |                 |             | 6 V      |                          | 20  | 42  |           | 63  |           | 52  |      |
| $t_{en}$  | DIR             | A or B      | 2 V      |                          | 80  | 245 |           | 370 |           | 305 | ns   |
|           |                 |             | 4.5 V    |                          | 25  | 49  |           | 74  |           | 61  |      |
|           |                 |             | 6 V      |                          | 20  | 42  |           | 63  |           | 52  |      |
| $t_{dis}$ | DIR             | A or B      | 2 V      |                          | 80  | 245 |           | 370 |           | 305 | ns   |
|           |                 |             | 4.5 V    |                          | 25  | 49  |           | 74  |           | 61  |      |
|           |                 |             | 6 V      |                          | 20  | 42  |           | 63  |           | 52  |      |
| $t_t$     |                 | Any         | 2 V      |                          | 28  | 60  |           | 90  |           | 75  | ns   |
|           |                 |             | 4.5 V    |                          | 8   | 12  |           | 18  |           | 15  |      |
|           |                 |             | 6 V      |                          | 6   | 10  |           | 15  |           | 13  |      |

† These parameters are measured with the internal output state of the storage register opposite that of the bus input.

**SN54HC646, SN74HC646**  
**OCTAL BUS TRANSCEIVERS AND REGISTERS**  
**WITH 3-STATE OUTPUTS**

SCLS150B – DECEMBER 1982 – REVISED MAY 1997

switching characteristics over recommended operating free-air temperature range,  $C_L = 150 \text{ pF}$   
(unless otherwise noted) (see Figure 2)

| PARAMETER | FROM (INPUT)    | TO (OUTPUT) | $V_{CC}$ | $T_A = 25^\circ\text{C}$ |     |     | SN54HC646 |     | SN74HC646 |     | UNIT |
|-----------|-----------------|-------------|----------|--------------------------|-----|-----|-----------|-----|-----------|-----|------|
|           |                 |             |          | MIN                      | TYP | MAX | MIN       | MAX | MIN       | MAX |      |
| $t_{pd}$  | CLKBA or CLKAB  | A or B      | 2 V      |                          | 90  | 265 |           | 400 |           | 330 | ns   |
|           |                 |             | 4.5 V    |                          | 24  | 53  |           | 80  |           | 66  |      |
|           |                 |             | 6 V      |                          | 20  | 46  |           | 68  |           | 57  |      |
|           | A or B          | B or A      | 2 V      |                          | 70  | 220 |           | 335 |           | 280 |      |
|           |                 |             | 4.5 V    |                          | 20  | 44  |           | 67  |           | 56  |      |
|           |                 |             | 6 V      |                          | 15  | 38  |           | 57  |           | 49  |      |
|           | SBA or SAB†     | A or B      | 2 V      |                          | 80  | 275 |           | 415 |           | 345 |      |
|           |                 |             | 4.5 V    |                          | 24  | 55  |           | 83  |           | 69  |      |
|           |                 |             | 6 V      |                          | 20  | 47  |           | 70  |           | 60  |      |
| $t_{en}$  | $\overline{OE}$ | A or B      | 2 V      |                          | 113 | 330 |           | 500 |           | 410 | ns   |
|           |                 |             | 4.5 V    |                          | 33  | 66  |           | 100 |           | 82  |      |
|           |                 |             | 6 V      |                          | 27  | 57  |           | 85  |           | 71  |      |
|           | DIR             | A or B      | 2 V      |                          | 113 | 330 |           | 500 |           | 410 |      |
|           |                 |             | 4.5 V    |                          | 33  | 66  |           | 100 |           | 82  |      |
|           |                 |             | 6 V      |                          | 27  | 57  |           | 85  |           | 71  |      |
| $t_t$     |                 | Any         | 2 V      |                          | 45  | 210 |           | 315 |           | 265 | ns   |
|           |                 |             | 4.5 V    |                          | 17  | 42  |           | 63  |           | 53  |      |
|           |                 |             | 6 V      |                          | 13  | 36  |           | 53  |           | 43  |      |

† These parameters are measured with the internal output state of the storage register opposite that of the bus input.

**operating characteristics,  $T_A = 25^\circ\text{C}$**


| PARAMETER                              | TEST CONDITIONS | TYP | UNIT |
|----------------------------------------|-----------------|-----|------|
| $C_{pd}$ Power dissipation capacitance | No load         | 50  | pF   |

PRODUCT PREVIEW information concerns products in the formative or design phase of development. Characteristic data and other specifications are design goals. Texas Instruments reserves the right to change or discontinue these products without notice.







POST OFFICE BOX 655303 • DALLAS, TEXAS 75265

PARAMETER MEASUREMENT INFORMATION



| PARAMETER         | $R_L$        | $C_L$           | S1     | S2     |
|-------------------|--------------|-----------------|--------|--------|
| $t_{en}$          | 1 k $\Omega$ | 50 pF or 150 pF | Open   | Closed |
|                   |              |                 | Closed | Open   |
| $t_{dis}$         | 1 k $\Omega$ | 50 pF           | Open   | Closed |
|                   |              |                 | Closed | Open   |
| $t_{pd}$ or $t_t$ | —            | 50 pF or 150 pF | Open   | Open   |



- NOTES: A.  $C_L$  includes probe and test-fixture capacitance.  
 B. Waveform 1 is for an output with internal conditions such that the output is low except when disabled by the output control. Waveform 2 is for an output with internal conditions such that the output is high except when disabled by the output control.  
 C. Phase relationships between waveforms were chosen arbitrarily. All input pulses are supplied by generators having the following characteristics:  $PRR \leq 1$  MHz,  $Z_O = 50 \Omega$ ,  $t_r = 6$  ns,  $t_f = 6$  ns.  
 D. For clock inputs,  $f_{max}$  is measured when the input duty cycle is 50%.  
 E. The outputs are measured one at a time with one input transition per measurement.  
 F.  $t_{PLZ}$  and  $t_{PHZ}$  are the same as  $t_{dis}$ .  
 G.  $t_{PZL}$  and  $t_{PZH}$  are the same as  $t_{en}$ .  
 H.  $t_{PLH}$  and  $t_{PHL}$  are the same as  $t_{pd}$ .

Figure 2. Load Circuit and Voltage Waveforms

## **IMPORTANT NOTICE**

Texas Instruments (TI) reserves the right to make changes to its products or to discontinue any semiconductor product or service without notice, and advises its customers to obtain the latest version of relevant information to verify, before placing orders, that the information being relied on is current.

TI warrants performance of its semiconductor products and related software to the specifications applicable at the time of sale in accordance with TI's standard warranty. Testing and other quality control techniques are utilized to the extent TI deems necessary to support this warranty. Specific testing of all parameters of each device is not necessarily performed, except those mandated by government requirements.

Certain applications using semiconductor products may involve potential risks of death, personal injury, or severe property or environmental damage ("Critical Applications").

**TI SEMICONDUCTOR PRODUCTS ARE NOT DESIGNED, INTENDED, AUTHORIZED, OR WARRANTED TO BE SUITABLE FOR USE IN LIFE-SUPPORT APPLICATIONS, DEVICES OR SYSTEMS OR OTHER CRITICAL APPLICATIONS.**

Inclusion of TI products in such applications is understood to be fully at the risk of the customer. Use of TI products in such applications requires the written approval of an appropriate TI officer. Questions concerning potential risk applications should be directed to TI through a local SC sales office.

In order to minimize risks associated with the customer's applications, adequate design and operating safeguards should be provided by the customer to minimize inherent or procedural hazards.

TI assumes no liability for applications assistance, customer product design, software performance, or infringement of patents or services described herein. Nor does TI warrant or represent that any license, either express or implied, is granted under any patent right, copyright, mask work right, or other intellectual property right of TI covering or relating to any combination, machine, or process in which such semiconductor products or services might be or are used.