


# SN10KHT5538 OCTAL ECL-TO-TTL TRANSLATOR WITH OPEN-COLLECTOR OUTPUTS

SDZS012 – MARCH 1990

- 10KH Compatible
- Open-Collector Outputs Drive Bus Lines or Buffer Memory Address Registers
- ECL and TTL Control Inputs
- Flow-Through Architecture Optimizes PCB Layout
- Center-Pin  $V_{CC}$ ,  $V_{EE}$ , and GND Configurations Minimize High-Speed Switching Noise
- Package Options Include “Small Outline” Packages and Standard Plastic 300-mil DIPs

DW OR NT PACKAGE  
(TOP VIEW)




## description

This octal ECL-to-TTL translator is designed to provide efficient translation between a 10KH signal environment and a TTL signal environment. This device is designed specifically to improve the performance and density of ECL-to-TTL CPU/bus oriented functions such as memory address drivers, clock drivers, and bus-oriented receivers and transmitters while eliminating the need for three-state overlap protection.

Two output enables,  $\overline{OE1}$  and  $\overline{OE2}$ , are provided. These enable inputs are ANDed together with  $\overline{OE1}$  being ECL-compatible and  $\overline{OE2}$  being TTL-compatible. This offers the choice of controlling the outputs of the device from either a TTL or ECL signal environment.

The SN10KHT5538 is characterized for operation from 0°C to 75°C.

## logic symbol



† This symbol is in accordance with ANSI/IEEE Std 91-1984 and IEC Publication 617-12.

FUNCTION TABLE

OUTPUT ENABLE		DATA INPUT A	OUTPUT (TTL) Y
$\overline{OE1}$	$\overline{OE2}$		
H	X	X	H
X	H	X	H
L	L	L	H
L	L	H	L


# SN10KHT5538

## OCTAL ECL-TO-TTL TRANSLATOR

### WITH OPEN-COLLECTOR OUTPUTS

SDZS012 – MARCH 1990

#### logic diagram (positive logic)



#### absolute maximum ratings over operating free-air temperature range (unless otherwise noted)<sup>†</sup>

Supply voltage range, $V_{CC}$	–0.5 V to 7 V
Supply voltage range, $V_{EE}$	–8 V to 0 V
Input voltage range (TTL) (see Note 1)	–1.2 V to 7 V
Input voltage range (ECL)	$V_{EE}$ to 0 V
Input current range (TTL)	–30 mA to 5 mA
Current into any output in the low state	96 mA
Voltage applied to any output in the high state	–0.5 V to $V_{CC}$
Operating temperature range	0°C to 75°C
Storage temperature range	–65°C to 150°C

<sup>†</sup> Stresses beyond those listed under “absolute maximum ratings” may cause permanent damage to the device. These are stress ratings only and functional operation of the device at these or any other conditions beyond those indicated under “recommended operating conditions” is not implied. Exposure to absolute-maximum-rated conditions for extended periods may affect device reliability.

NOTE 1: The TTL input voltage ratings may be exceeded provided the input current ratings are observed.

**recommended operating conditions**

		MIN	NOM	MAX	UNIT
$V_{CC}$	TTL supply voltage	4.5	5	5.5	V
$V_{EE}$	ECL supply voltage	-4.94	-5.2	-5.46	V
$V_{IH}$	TTL high-level input voltage	2			V
$V_{IL}$	TTL low-level input voltage			0.8	V
$V_{IH}$	ECL high-level input voltage (see Note 2)	0°C	-1170	-840	mV
		25°C	-1130	-810	mV
		75°C	-1070	-735	mV
$V_{IL}$	ECL low-level input voltage (see Note 2)	0°C	-1950	-1480	mV
		25°C	-1950	-1480	mV
		75°C	-1950	-1450	mV
$V_{OH}$	TTL high-level output voltage			5.5	V
$I_{OL}$	TTL low-level output current			48	mA
$I_{IK}$	TTL input clamp current			-18	mA
$T_A$	Operating free-air temperature	0		75	°C

NOTE 2: The algebraic convention, in which the least positive (most negative) value is designated minimum, is used in this data sheet for logic levels only.

**electrical characteristics over recommended operating free-air temperature range (unless otherwise noted)**

PARAMETER		TEST CONDITIONS			MIN	TYP†	MAX	UNIT
$I_{IK}$	OE2 only	$V_{CC} = 4.5\text{ V}$ , $V_{EE} = -4.94\text{ V}$ , $I_I = -18\text{ mA}$					-1.2	V
$I_I$	OE2 only	$V_{CC} = 5.5\text{ V}$ , $V_{EE} = -5.46\text{ V}$ , $V_I = 7\text{ V}$					0.1	mA
$I_{IH}$	OE2 only	$V_{CC} = 5.5\text{ V}$ , $V_{EE} = -5.46\text{ V}$ , $V_I = 2.7\text{ V}$					20	μA
$I_{IL}$	OE2 only	$V_{CC} = 5.5\text{ V}$ , $V_{EE} = -5.46\text{ V}$ , $V_I = 0.5\text{ V}$					-0.5	mA
$I_{IH}$	A inputs and $\overline{OE}1$	$V_{CC} = 5.5\text{ V}$ , $V_{EE} = -5.46\text{ V}$ , $V_I = -840\text{ V}$	0°C				350	μA
		$V_{CC} = 5.5\text{ V}$ , $V_{EE} = -5.46\text{ V}$ , $V_I = -810\text{ V}$	25°C				350	
		$V_{CC} = 5.5\text{ V}$ , $V_{EE} = -5.46\text{ V}$ , $V_I = -735\text{ V}$	75°C				350	
$I_{IL}$	A inputs and $\overline{OE}1$	$V_{CC} = 5.5\text{ V}$ , $V_{EE} = -5.46\text{ V}$ , $V_I = -1950\text{ V}$	0°C		0.5			μA
			25°C		0.5			
			75°C		0.5			
$I_{OH}$		$V_{CC} = 4.5\text{ V}$ , $V_{EE} = -4.94\text{ V}$ , $V_{OH} = 5.5\text{ V}$					250	μA
$V_{OL}$		$V_{CC} = 4.5\text{ V}$ , $V_{EE} = -5.2\text{ V} \pm 5\%$ , $I_{OL} = 48\text{ mA}$			0.38	0.55		V
$I_{CCH}$		$V_{CC} = 5.5\text{ V}$ , $V_{EE} = -5.46\text{ V}$				66	95	mA
$I_{CCL}$		$V_{CC} = 5.5\text{ V}$ , $V_{EE} = -5.46\text{ V}$				79.5	114	mA
$I_{EE}$		$V_{CC} = 5.5\text{ V}$ , $V_{EE} = -5.46\text{ V}$				-23	-33	mA
$C_i$		$V_{CC} = 5.5\text{ V}$ , $V_{EE} = -5.2\text{ V}$				5		pF
$C_o$		$V_{CC} = 5.5\text{ V}$ , $V_{EE} = -5.2\text{ V}$				5		pF

† All typical values are at  $V_{CC} = 5\text{ V}$ ,  $V_{EE} = -5.2\text{ V}$ ,  $T_A = 25^\circ\text{C}$ .

# SN10KHT5538

## OCTAL ECL-TO-TTL TRANSLATOR

### WITH OPEN-COLLECTOR OUTPUTS


SDZS012 – MARCH 1990

switching characteristics over recommended ranges of supply voltage and operating free-air temperature (unless otherwise noted) (see Figure 1)


PARAMETER	FROM (INPUT)	TO (OUTPUT)	$C_L = 50 \text{ pF}$ , $R_1 = 500 \Omega$ , $R_2 = 500 \Omega$			UNIT
			MIN	TYP†	MAX	
$t_{PLH}$	Any A	Y	6.4	9.1	11.7	ns
$t_{PHL}$			2.7	4.9	7.2	
$t_{PLH}$	OE1 (ECL)	Y	7	10.1	13.3	ns
$t_{PHL}$			3.6	6.2	8.8	
$t_{PLH}$	OE2 (TTL)	Y	6.5	9.1	11.6	ns
$t_{PHL}$			2.8	5.3	7.9	

† All typical values are at  $V_{CC} = 5 \text{ V}$ ,  $V_{EE} = -5.2 \text{ V}$ ,  $T_A = 25^\circ\text{C}$ .


## PARAMETER MEASUREMENT INFORMATION



LOAD CIRCUIT



VOLTAGE WAVEFORMS  
TTL-INPUT PROPAGATION DELAY TIMES



VOLTAGE WAVEFORMS  
ECL-INPUT PROPAGATION DELAY TIMES

NOTES: A.  $C_L$  includes probe and jig capacitance.

B. For TTL inputs, input pulses are supplied by generators having the following characteristics:  $PRR \leq 10 \text{ MHz}$ ,  $Z_0 = 50 \Omega$ ,  $t_r \leq 2.5 \text{ ns}$ ,  $t_f \leq 2.5 \text{ ns}$ .

C. For ECL inputs, input pulses are supplied by generators having the following characteristics:  $PRR \leq 10 \text{ MHz}$ ,  $Z_0 = 50 \Omega$ ,  $t_r \leq 1.5 \text{ ns}$ ,  $t_f \leq 1.5 \text{ ns}$ .

D. The outputs are measured one at a time with one transition per measurement.

Figure 1. Load Circuit and Voltage Waveforms

## **IMPORTANT NOTICE**

Texas Instruments (TI) reserves the right to make changes to its products or to discontinue any semiconductor product or service without notice, and advises its customers to obtain the latest version of relevant information to verify, before placing orders, that the information being relied on is current.

TI warrants performance of its semiconductor products and related software to the specifications applicable at the time of sale in accordance with TI's standard warranty. Testing and other quality control techniques are utilized to the extent TI deems necessary to support this warranty. Specific testing of all parameters of each device is not necessarily performed, except those mandated by government requirements.

Certain applications using semiconductor products may involve potential risks of death, personal injury, or severe property or environmental damage ("Critical Applications").

**TI SEMICONDUCTOR PRODUCTS ARE NOT DESIGNED, INTENDED, AUTHORIZED, OR WARRANTED TO BE SUITABLE FOR USE IN LIFE-SUPPORT APPLICATIONS, DEVICES OR SYSTEMS OR OTHER CRITICAL APPLICATIONS.**

Inclusion of TI products in such applications is understood to be fully at the risk of the customer. Use of TI products in such applications requires the written approval of an appropriate TI officer. Questions concerning potential risk applications should be directed to TI through a local SC sales office.

In order to minimize risks associated with the customer's applications, adequate design and operating safeguards should be provided by the customer to minimize inherent or procedural hazards.

TI assumes no liability for applications assistance, customer product design, software performance, or infringement of patents or services described herein. Nor does TI warrant or represent that any license, either express or implied, is granted under any patent right, copyright, mask work right, or other intellectual property right of TI covering or relating to any combination, machine, or process in which such semiconductor products or services might be or are used.