


MC10173

Quad 2-Input Multiplexer/Latch

The MC10173 is a quad two channel multiplexer with latch. It incorporates common clock and common data select inputs. The select input determines which data input is enabled. A high (H) level enables data inputs D00, D10, D20, and D30 and a low (L) level enables data inputs D01, D11, D21, D31. Any change on the data input will be reflected at the outputs while the clock is low. The outputs are latched on the positive transition of the clock. While the clock is in the high state, a change in the information present at the data inputs will not affect the output information.

- $P_D = 275 \text{ mW typ/pkg (No Load)}$
- $t_{pd} = 2.5 \text{ ns typ}$
- $t_r, t_f = 2.0 \text{ ns typ (20\%–80\%)}$

LOGIC DIAGRAM



TRUTH TABLE


SELECT	CLOCK	$Q0_{n+1}$
H	L	D00
L	L	D01
X	H	$Q0_n$




ON Semiconductor

<http://onsemi.com>


MARKING DIAGRAMS




CDIP-16
L SUFFIX
CASE 620



PDIP-16
P SUFFIX
CASE 648




PLCC-20
FN SUFFIX
CASE 775



A = Assembly Location
WL = Wafer Lot
YY = Year
WW = Work Week

DIP PIN ASSIGNMENT



Pin assignment is for Dual-in-Line Package.
For PLCC pin assignment, see the Pin Conversion Tables on page 18 of the ON Semiconductor MECL Data Book (DL122/D).

ORDERING INFORMATION

Device	Package	Shipping
MC10173L	CDIP-16	25 Units / Rail
MC10173P	PDIP-16	25 Units / Rail
MC10173FN	PLCC-20	46 Units / Rail

MC10173

ELECTRICAL CHARACTERISTICS

Characteristic	Symbol	Pin Under Test	Test Limits							Unit
			−30°C		+25°C			+85°C		
			Min	Max	Min	Typ	Max	Min	Max	
Power Supply Drain Current	I _E	8		73			66		73	mAdc
Input Current	I _{inH}	5		470			295		295	μAdc
		6		470			295		295	
		7		400			250		250	
		9		400			250		250	
	I _{inL}	All	0.5		0.5			0.3		μAdc
Output Voltage Logic 1	V _{OH}	1	−1.060	−0.890	−0.960		−0.810	−0.890	−0.700	Vdc
		2	−1.060	−0.890	−0.960		−0.810	−0.890	−0.700	
Output Voltage Logic 0	V _{OL}	1	−1.890	−1.675	−1.850		−1.650	−1.825	−1.615	Vdc
		2	−1.890	−1.675	−1.850		−1.650	−1.825	−1.615	
Threshold Voltage Logic 1	V _{OHA}	1	−1.080		−0.980			−0.910		Vdc
		2	−1.080		−0.980			−0.910		
Threshold Voltage Logic 0	V _{OLA}	1		−1.655			−1.630		−1.595	Vdc
		2		−1.655			−1.630		−1.595	
Switching Times (50Ω Load)										ns
Propagation Delay	Data Input	t ₆₊₁₊	1	0.8	3.7	1.0	2.5	3.5	1.1	5.3
		t _{6−1−}	1	0.8	3.7	1.0	2.5	3.5	1.1	5.3
		t ₅₊₁₊	1	0.8	3.7	1.0	2.5	3.5	1.1	5.3
		t _{5−1−}	1	0.8	3.7	1.0	2.5	3.5	1.1	5.3
	Clock Input	t _{7−1+}	1	1.6	7.2	1.6	4.5	6.8	1.4	6.8
		t _{7−1−}	1	1.6	7.2	1.6	4.5	6.8	1.4	6.8
	Select Input	t ₉₊₁₊	1	1.1	6.2	1.3	3.5	5.7	1.2	6.7
		t _{9+1−}	1	1.1	6.2	1.3	3.5	5.7	1.2	6.7
		t _{9−1+}	1	1.1	6.2	1.3	3.5	5.7	1.2	6.7
		t _{9−1−}	1	1.1	6.2	1.3	3.5	5.7	1.2	6.7
	Setup Time	Data Input	t _{setup}	1	2.0		2.0	1.5		2.0
		Select Input	t _{setup}	1	3.0		3.0	2.5		3.0
Hold Time	Data Input	t _{hold}	1	2.5		2.5	0.0		2.5	
	Select Input	t _{hold}	1	1.5		1.5	−0.5		1.5	
Rise Time (20 to 80%)	t ₊	1	1.2	4.0	1.5	2.0	3.5	1.4	4.0	
Fall Time (20 to 80%)	t _−	1	1.2	4.0	1.5	2.0	3.5	1.4	4.0	

* V_{ILmin} applied to each input pin, one at a time.

MC10173

ELECTRICAL CHARACTERISTICS (continued)

@ Test Temperature			TEST VOLTAGE VALUES (Volts)					(V _{CC}) Gnd	
			V _{IH} max	V _{IL} min	V _{IH} Amin	V _{IL} Amax	V _{EE}		
			−30°C	−0.890	−1.890	−1.205	−1.500		−5.2
			+25°C	−0.810	−1.850	−1.105	−1.475		−5.2
			+85°C	−0.700	−1.825	−1.035	−1.440		−5.2
Characteristic	Symbol	Pin Under Test	TEST VOLTAGE APPLIED TO PINS LISTED BELOW						
			V _{IH} max	V _{IL} min	V _{IH} Amin	V _{IL} Amax	V _{EE}		
Power Supply Drain Current	I _E	8					8	16	
Input Current		5	5				8	16	
		6	6				8	16	
		7	7				8	16	
		9	9				8	16	
	I _{inL}	All		*			8	16	
Output Voltage Logic 1	V _{OH}	1	6, 9	7			8	16	
		2	5	7			8	16	
Output Voltage Logic 0	V _{OL}	1	9	7			8	16	
		2		7			8	16	
Threshold Voltage Logic 1	V _{OHA}	1	9	7	6		8	16	
		2		7	5		8	16	
Threshold Voltage Logic 0	V _{OLA}	1	9	7		6	8	16	
		2		7		5	8	16	
Switching Times (50Ω Load)			+1.11V	+0.31V	Pulse In	Pulse Out	−3.2 V	+2.0 V	
Propagation Delay	Data Input	t ₆₊₁₊	1	9	7	6	1	8	16
		t _{6−1−}	1	9	7	6	1	8	16
		t ₅₊₁₊	1		7	5	1	8	16
		t _{5−1−}	1		7	5	1	8	16
	Clock Input	t _{7−1+}	1			5, 7	1	8	16
		t _{7−1−}	1			5, 7	1	8	16
	Select Input	t ₉₊₁₊	1	6	7	9	1	8	16
		t _{9+1−}	1	5	7	9	1	8	16
		t _{9−1+}	1	5	7	9	1	8	16
		t _{9−1−}	1	6	7	9	1	8	16
	Setup Time	Data Input	t _{setup}	1			5, 7	1	8
Select Input		t _{setup}	1	6		7, 9	1	8	16
Hold Time	Data Input	t _{hold}	1			5, 7	1	8	16
	Select Input	t _{hold}	1	6		7, 9	1	8	16
Rise Time	(20 to 80%)	t ₊	1	5		7	1	8	16
Fall Time	(20 to 80%)	t _−	1			7	1	8	16

* V_{ILmin} applied to each input pin, one at a time.

Each MECL 10,000 series circuit has been designed to meet the dc specifications shown in the test table, after thermal equilibrium has been established. The circuit is in a test socket or mounted on a printed circuit board and transverse air flow greater than 500 linear fpm is maintained. Outputs are terminated through a 50-ohm resistor to −2.0 volts. Test procedures are shown for only one gate. The other gates are tested in the same manner.

MC10173

PACKAGE DIMENSIONS

PLCC-20
FN SUFFIX
PLASTIC PLCC PACKAGE
CASE 775-02
ISSUE C




NOTES:

- DATUMS -L-, -M-, AND -N- DETERMINED WHERE TOP OF LEAD SHOULDER EXITS PLASTIC BODY AT MOLD PARTING LINE.
- DIMENSION G1, TRUE POSITION TO BE MEASURED AT DATUM -T-, SEATING PLANE.
- DIMENSIONS R AND U DO NOT INCLUDE MOLD FLASH. ALLOWABLE MOLD FLASH IS 0.010 (0.250) PER SIDE.
- DIMENSIONING AND TOLERANCING PER ANSI Y14.5M, 1982.
- CONTROLLING DIMENSION: INCH.
- THE PACKAGE TOP MAY BE SMALLER THAN THE PACKAGE BOTTOM BY UP TO 0.012 (0.300). DIMENSIONS R AND U ARE DETERMINED AT THE OUTERMOST EXTREMES OF THE PLASTIC BODY EXCLUSIVE OF MOLD FLASH, TIE BAR BURRS, GATE BURRS AND INTERLEAD FLASH, BUT INCLUDING ANY MISMATCH BETWEEN THE TOP AND BOTTOM OF THE PLASTIC BODY.
- DIMENSION H DOES NOT INCLUDE DAMBAR PROTRUSION OR INTRUSION. THE DAMBAR PROTRUSION(S) SHALL NOT CAUSE THE H DIMENSION TO BE GREATER THAN 0.037 (0.940). THE DAMBAR INTRUSION(S) SHALL NOT CAUSE THE H DIMENSION TO BE SMALLER THAN 0.025 (0.635).

DIM	INCHES		MILLIMETERS	
	MIN	MAX	MIN	MAX
A	0.385	0.395	9.78	10.03
B	0.385	0.395	9.78	10.03
C	0.165	0.180	4.20	4.57
E	0.090	0.110	2.29	2.79
F	0.013	0.019	0.33	0.48
G	0.050 BSC		1.27 BSC	
H	0.026	0.032	0.66	0.81
J	0.020	---	0.51	---
K	0.025	---	0.64	---
R	0.350	0.356	8.89	9.04
U	0.350	0.356	8.89	9.04
V	0.042	0.048	1.07	1.21
W	0.042	0.048	1.07	1.21
X	0.042	0.056	1.07	1.42
Y	---	0.020	---	0.50
Z	2 °	10 °	2 °	10 °
G1	0.310	0.330	7.88	8.38
K1	0.040	---	1.02	---


MC10173

PACKAGE DIMENSIONS



- NOTES:
1. DIMENSIONING AND TOLERANCING PER ANSI Y14.5M, 1982.
 2. CONTROLLING DIMENSION: INCH.
 3. DIMENSION L TO CENTER OF LEAD WHEN FORMED PARALLEL.
 4. DIMENSION F MAY NARROW TO 0.76 (0.030) WHERE THE LEAD ENTERS THE CERAMIC BODY.

DIM	INCHES		MILLIMETERS	
	MIN	MAX	MIN	MAX
A	0.750	0.785	19.05	19.93
B	0.240	0.295	6.10	7.49
C	---	0.200	---	5.08
D	0.015	0.020	0.39	0.50
E	0.050 BSC		1.27 BSC	
F	0.055	0.065	1.40	1.65
G	0.100 BSC		2.54 BSC	
H	0.008	0.015	0.21	0.38
K	0.125	0.170	3.18	4.31
L	0.300 BSC		7.62 BSC	
M	0°	15°	0°	15°
N	0.020	0.040	0.51	1.01




- NOTES:
1. DIMENSIONING AND TOLERANCING PER ANSI Y14.5M, 1982.
 2. CONTROLLING DIMENSION: INCH.
 3. DIMENSION L TO CENTER OF LEADS WHEN FORMED PARALLEL.
 4. DIMENSION B DOES NOT INCLUDE MOLD FLASH.
 5. ROUNDED CORNERS OPTIONAL.

DIM	INCHES		MILLIMETERS	
	MIN	MAX	MIN	MAX
A	0.740	0.770	18.80	19.55
B	0.250	0.270	6.35	6.85
C	0.145	0.175	3.69	4.44
D	0.015	0.021	0.39	0.53
F	0.040	0.70	1.02	1.77
G	0.100 BSC		2.54 BSC	
H	0.050 BSC		1.27 BSC	
J	0.008	0.015	0.21	0.38
K	0.110	0.130	2.80	3.30
L	0.295	0.305	7.50	7.74
M	0°	10°	0°	10°
S	0.020	0.040	0.51	1.01

Notes

Notes

ON Semiconductor and  are trademarks of Semiconductor Components Industries, LLC (SCILLC). SCILLC reserves the right to make changes without further notice to any products herein. SCILLC makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does SCILLC assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. "Typical" parameters which may be provided in SCILLC data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. SCILLC does not convey any license under its patent rights nor the rights of others. SCILLC products are not designed, intended, or authorized for use as components in systems intended for surgical implant into the body, or other applications intended to support or sustain life, or for any other application in which the failure of the SCILLC product could create a situation where personal injury or death may occur. Should Buyer purchase or use SCILLC products for any such unintended or unauthorized application, Buyer shall indemnify and hold SCILLC and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that SCILLC was negligent regarding the design or manufacture of the part. SCILLC is an Equal Opportunity/Affirmative Action Employer.

PUBLICATION ORDERING INFORMATION**North America Literature Fulfillment:**

Literature Distribution Center for ON Semiconductor
P.O. Box 5163, Denver, Colorado 80217 USA
Phone: 303-675-2175 or 800-344-3860 Toll Free USA/Canada
Fax: 303-675-2176 or 800-344-3867 Toll Free USA/Canada
Email: ONlit@hibbertco.com

N. American Technical Support: 800-282-9855 Toll Free USA/Canada

EUROPE: LDC for ON Semiconductor – European Support

German Phone: (+1) 303-308-7140 (M–F 2:30pm to 5:00pm Munich Time)
Email: ONlit-german@hibbertco.com
French Phone: (+1) 303-308-7141 (M–F 2:30pm to 5:00pm Toulouse Time)
Email: ONlit-french@hibbertco.com
English Phone: (+1) 303-308-7142 (M–F 1:30pm to 5:00pm UK Time)
Email: ONlit@hibbertco.com

ASIA/PACIFIC: LDC for ON Semiconductor – Asia Support

Phone: 303-675-2121 (Tue–Fri 9:00am to 1:00pm, Hong Kong Time)
Toll Free from Hong Kong 800-4422-3781
Email: ONlit-asia@hibbertco.com

JAPAN: ON Semiconductor, Japan Customer Focus Center
4-32-1 Nishi-Gotanda, Shinagawa-ku, Tokyo, Japan 141-8549

Phone: 81-3-5740-2745
Email: r14525@onsemi.com

Fax Response Line: 303-675-2167
800-344-3810 Toll Free USA/Canada

ON Semiconductor Website: <http://onsemi.com>

For additional information, please contact your local
Sales Representative.