

# MC74LVX4053

## Product Preview

# Analog Multiplexer / Demultiplexer

## High-Performance Silicon-Gate CMOS

The MC74LVX4053 utilizes silicon-gate CMOS technology to achieve fast propagation delays, low ON resistances, and low OFF leakage currents. This analog multiplexer/demultiplexer controls analog voltages that may vary across the complete power supply range (from  $V_{CC}$  to  $V_{EE}$ ).

The LVX4053 is similar in pinout to the LVX8053, HC4053A, and the metal-gate MC14053B. The Channel-Select inputs determine which one of the Analog Inputs/Outputs is to be connected, by means of an analog switch, to the Common Output/Input. When the Enable pin is HIGH, all analog switches are turned off.

The Channel-Select and Enable inputs are compatible with standard CMOS outputs; with pull-up resistors they are compatible with LSTTL outputs.

This device has been designed so that the ON resistance ( $R_{on}$ ) is more linear over input voltage than  $R_{on}$  of metal-gate CMOS analog switches, or High-Speed CMOS analog switches.


- Fast Switching and Propagation Speeds
- Low Crosstalk Between Switches
- Analog Power Supply Range ( $V_{CC} - GND$ ) = 2.0 to 6.0 V
- Digital (Control) Power Supply Range ( $V_{CC} - GND$ ) = 2.0 to 6.0 V
- Improved Linearity and Lower ON Resistance Than Metal-Gate, HSL, or VHC Counterparts
- Low Noise
- Designed to Operate on a Single Supply with  $V_{EE} = GND$ , or Using Split Supplies up to  $\pm 3.3$  V



ON Semiconductor

<http://onsemi.com>



### MARKING DIAGRAMS




SOIC-16  
D SUFFIX  
CASE 751B



TSSOP-16  
DT SUFFIX  
CASE 948F



SOIC EIAJ-16  
M SUFFIX  
CASE 966



A = Assembly Location  
L, WL = Wafer Lot  
Y, YY = Year  
W, WW = Work Week


### ORDERING INFORMATION

Device	Package	Shipping
MC74LVX4053D	SOIC-16	48 Units/Rail
MC74LVX4053DR2	SOIC-16	2500 Units/Reel
MC74LVX4053DT	TSSOP-16	96 Units/Rail
MC74LVX4053DTR2	TSSOP-16	2500 Units/Reel
MC74LVX4053M	SOIC EIAJ-16	48 Units/Rail
MC74LVX4053MEL	SOIC EIAJ-16	2000 Units/Reel

This document contains information on a product under development. ON Semiconductor reserves the right to change or discontinue this product without notice.

# MC74LVX4053

## PIN CONNECTION AND MARKING DIAGRAM (Top View)




## FUNCTION TABLE

Control Inputs						
Enable	Select					
	C	B	A	ON Channels		
L	L	L	L	Z0	Y0	X0
L	L	L	H	Z0	Y0	X1
L	L	H	L	Z0	Y1	X0
L	L	H	H	Z0	Y1	X1
L	H	L	L	Z1	Y0	X0
L	H	L	H	Z1	Y0	X1
L	H	H	L	Z1	Y1	X0
L	H	H	H	Z1	Y1	X1
H	X	X	X	NONE		

X = Don't Care

## LOGIC DIAGRAM Triple Single-Pole, Double-Position Plus Common Off



NOTE: This device allows independent control of each switch. Channel-Select Input A controls the X-Switch, Input B controls the Y-Switch and Input C controls the Z-Switch

# MC74LVX4053

## MAXIMUM RATINGS\*

Symbol	Parameter	Value	Unit
$V_{EE}$	Negative DC Supply Voltage (Referenced to GND)	- 7.0 to + 5.0	V
$V_{CC}$	Positive DC Supply Voltage (Referenced to GND) (Referenced to $V_{EE}$ )	- 0.5 to + 7.0 - 0.5 to + 7.0	V
$V_{IS}$	Analog Input Voltage	$V_{EE} - 0.5$ to $V_{CC} + 0.5$	V
$V_{in}$	Digital Input Voltage (Referenced to GND)	- 0.5 to $V_{CC} + 0.5$	V
$I$	DC Current, Into or Out of Any Pin	$\pm 20$	mA
$P_D$	Power Dissipation in Still Air, SOIC Package† TSSOP Package†	500 450	mW
$T_{stg}$	Storage Temperature Range	- 65 to + 150	°C
$T_L$	Lead Temperature, 1 mm from Case for 10 Seconds	260	°C

This device contains protection circuitry to guard against damage due to high static voltages or electric fields. However, precautions must be taken to avoid applications of any voltage higher than maximum rated voltages to this high-impedance circuit. For proper operation,  $V_{in}$  and  $V_{out}$  should be constrained to the range  $GND \leq (V_{in} \text{ or } V_{out}) \leq V_{CC}$ . Unused inputs must always be tied to an appropriate logic voltage level (e.g., either GND or  $V_{CC}$ ). Unused outputs must be left open.

\*Maximum Ratings are those values beyond which damage to the device may occur.

Functional operation should be restricted to the Recommended Operating Conditions.

†Derating — SOIC Package: - 7 mW/°C from 65° to 125°C

TSSOP Package: - 6.1 mW/°C from 65° to 125°C

## RECOMMENDED OPERATING CONDITIONS


Symbol	Parameter	Min	Max	Unit
$V_{EE}$	Negative DC Supply Voltage (Referenced to GND)	-6.0	GND	V
$V_{CC}$	Positive DC Supply Voltage (Referenced to GND) (Referenced to $V_{EE}$ )	2.0 2.0	6.0 6.6	V
$V_{IS}$	Analog Input Voltage	$V_{EE}$	$V_{CC}$	V
$V_{in}$	Digital Input Voltage (Referenced to GND)	0	$V_{CC}$	V
$V_{IO}^*$	Static or Dynamic Voltage Across Switch		1.2	V
$T_A$	Operating Temperature Range, All Package Types	- 55	+125	°C
$t_r, t_f$	Input Rise/Fall Time (Channel Select or Enable Inputs)			ns/V
	$V_{CC} = 3.3 \text{ V} \pm 0.3 \text{ V}$ $V_{CC} = 5.0 \text{ V} \pm 0.5 \text{ V}$	0 0	100 20	

\*For voltage drops across switch greater than 1.2 V (switch on), excessive  $V_{CC}$  current may be drawn; i.e., the current out of the switch may contain both  $V_{CC}$  and switch input components. The reliability of the device will be unaffected unless the Maximum Ratings are exceeded.

The  $\theta_{JA}$  of the package is equal to 1/Derating. Higher junction temperatures may affect the expected lifetime of the device per the table and figure below.

## DEVICE JUNCTION TEMPERATURE VERSUS TIME TO 0.1% BOND FAILURES

Junction Temperature °C	Time, Hours	Time, Years
80	1,032,200	117.8
90	419,300	47.9
100	178,700	20.4
110	79,600	9.4
120	37,000	4.2
130	17,800	2.0
140	8,900	1.0



Failure Rate vs. Time Junction Temperature

# MC74LVX4053

## DC CHARACTERISTICS — Digital Section (Voltages Referenced to GND)

Symbol	Parameter	Condition	V <sub>CC</sub> V	Guaranteed Limit			Unit
				–55 to 25°C	≤85°C	≤125°C	
V <sub>IH</sub>	Minimum High-Level Input Voltage, Channel-Select or Enable Inputs	R <sub>on</sub> = Per Spec	2.0	1.50	1.50	1.50	V
			3.0	2.10	2.10	2.10	
			4.5	3.15	3.15	3.15	
			5.5	3.85	3.85	3.85	
V <sub>IL</sub>	Maximum Low-Level Input Voltage, Channel-Select or Enable Inputs	R <sub>on</sub> = Per Spec	2.0	0.5	0.5	0.5	V
			3.0	0.9	0.9	0.9	
			4.5	1.35	1.35	1.35	
			5.5	1.65	1.65	1.65	
I <sub>in</sub>	Maximum Input Leakage Current, Channel-Select or Enable Inputs	V <sub>in</sub> = V <sub>CC</sub> or GND,	5.5	± 0.1	± 1.0	± 1.0	μA
I <sub>CC</sub>	Maximum Quiescent Supply Current (per Package)	Channel Select, Enable and V <sub>IS</sub> = V <sub>CC</sub> or GND; V <sub>IN</sub> = 0 V	5.5	4	40	160	μA

## DC ELECTRICAL CHARACTERISTICS Analog Section

Symbol	Parameter	Test Conditions	V <sub>CC</sub> V	V <sub>EE</sub> V	Guaranteed Limit			Unit
					– 55 to 25°C	≤ 85°C	≤ 125°C	
R <sub>on</sub>	Maximum “ON” Resistance	V <sub>in</sub> = V <sub>IL</sub> or V <sub>IH</sub> V <sub>IS</sub> = V <sub>CC</sub> to V <sub>EE</sub>  I <sub>S</sub>   ≤ 10.0 mA (Figures 1, 2)	3.0	0	20	25	30	Ω
			4.5	0	10	15	20	
			5.5	0	7	10	15	
			3.3	–3.3	4.0	10	15	
		V <sub>in</sub> = V <sub>IL</sub> or V <sub>IH</sub> V <sub>IS</sub> = V <sub>CC</sub> or V <sub>EE</sub> (Endpoints)  I <sub>S</sub>   ≤ 10.0 mA (Figures 1, 2)	3.0	0	20	25	30	
			4.5	0	10	15	20	
			5.5	0	7	10	15	
			3.3	–3.3	4.0	10	15	
ΔR <sub>on</sub>	Maximum Difference in “ON” Resistance Between Any Two Channels in the Same Package	V <sub>in</sub> = V <sub>IL</sub> or V <sub>IH</sub> V <sub>IS</sub> = 1/2 (V <sub>CC</sub> – V <sub>EE</sub> )  I <sub>S</sub>   ≤ 10.0 mA	3.0	0	5	5	5	Ω
			4.5	0	1	1.2	1.5	
			5.5	0	1	1.2	1.5	
			3.3	–3.3	1	1.2	1.5	
I <sub>off</sub>	Maximum Off-Channel Leakage Current, Any One Channel	V <sub>in</sub> = V <sub>IL</sub> or V <sub>IH</sub> ; V <sub>IO</sub> = V <sub>CC</sub> or GND; Switch Off (Figure 3)	5.5	0	1	10	1000	nA
			3.3	–3.3	1	10	1000	
	Maximum Off-Channel Leakage Current, Common Channel	V <sub>in</sub> = V <sub>IL</sub> or V <sub>IH</sub> ; V <sub>IO</sub> = V <sub>CC</sub> or GND; Switch Off (Figure 4)	5.5	0	1	10	1000	
			3.3	–3.3	1	10	1000	
I <sub>on</sub>	Maximum On-Channel Leakage Current, Channel-to-Channel	V <sub>in</sub> = V <sub>IL</sub> or V <sub>IH</sub> ; Switch-to-Switch = V <sub>CC</sub> or GND; (Figure 5)	5.5	0	1	10	1000	nA
			3.3	–3.3	1	10	1000	
t <sub>BBM</sub>	Minimum Break-Before- Make Time§ (Figure 13)	V <sub>in</sub> = V <sub>IL</sub> or V <sub>IH</sub> V <sub>IS</sub> = 1/2 (V <sub>CC</sub> – V <sub>EE</sub> ) R <sub>L</sub> = 300 Ω, C <sub>L</sub> = 35 pF	3.0	0.0	1	TBD	TBD	ns
			4.5	0.0	0.2	TBD	TBD	
			5.5	0.0	0.2	TBD	TBD	
			3.3	–3.3	0.2	TBD	TBD	

§Guaranteed by design.

# MC74LVX4053

## AC CHARACTERISTICS (C<sub>L</sub> = 50 pF, Input t<sub>r</sub> = t<sub>f</sub> = 3 ns)

Symbol	Parameter	V <sub>CC</sub> V	V <sub>EE</sub> V	Guaranteed Limit			Unit
				−55 to 25°C	≤85°C	≤125°C	
t <sub>PLH</sub> , t <sub>PHL</sub>	Maximum Propagation Delay, Channel–Select to Analog Output (Figure 9)	2.0	0	30	35	40	ns
		3.0	0	20	25	30	
		4.5	0	15	18	22	
		5.5	0	15	18	20	
		3.3	−3.3	10	12	15	
t <sub>PLH</sub> , t <sub>PHL</sub>	Maximum Propagation Delay, Analog Input to Analog Output (Figure 10)	2.0	0	1.0	1.0	2.0	ns
		3.0	0	1.0	1.0	2.0	
		4.5	0	1.0	1.0	1.0	
		5.5	0	1.0	1.0	1.0	
		3.3	−3.3	1.0	1.0	1.0	
t <sub>PLZ</sub> , t <sub>PHZ</sub>	Maximum Propagation Delay, Enable to Analog Output (Figure 11)	2.0	0	30	35	40	ns
		3.0	0	20	25	30	
		4.5	0	15	18	22	
		5.5	0	15	18	20	
		3.3	−3.3	10	12	15	
t <sub>PZL</sub> , t <sub>PZH</sub>	Maximum Propagation Delay, Enable to Analog Output (Figure 11)	2.0	0	20	25	30	ns
		3.0	0	12	14	15	
		4.5	0	8.0	10	12	
		5.5	0	8.0	10	12	
		3.3	−3.3	5.0	8.0	10	
C <sub>in</sub>	Maximum Input Capacitance, Channel–Select or Enable Inputs			10	10	10	pF
C <sub>I/O</sub>	Maximum Capacitance (All Switches Off)	Analog I/O		35	35	35	pF
		Common O/I		50	50	50	
		Feedthrough		1.0	1.0	1.0	
C <sub>PD</sub>	Power Dissipation Capacitance (Figure 18)*	Typical @ 25°C, V <sub>CC</sub> = 5.0 V, V <sub>EE</sub> = 0V					pF
		45					

§Used to determine the no-load dynamic power consumption: P<sub>D</sub> = C<sub>PD</sub> V<sub>CC</sub><sup>2</sup>f + I<sub>CC</sub> V<sub>CC</sub>.

# MC74LVX4053

## ADDITIONAL APPLICATION CHARACTERISTICS (GND = 0 V)

Symbol	Parameter	Condition	V <sub>CC</sub> V	V <sub>EE</sub> V	Limit*	Unit
					25°C	
BW	Maximum On-Channel Bandwidth or Minimum Frequency Response (Figure 6)	$V_{IS} = \frac{1}{2} (V_{CC} - V_{EE})$ , Ref & Test Attn = 10 dB Source Amplitude = 0 dB	3.0	0.0	80	MHz
			4.5	0.0	80	
			5.5	0.0	80	
			3.3	-3.3	80	
V <sub>ISO</sub>	Off-Channel Feedthrough Isolation (Figure 7)	$V_{IS} = \frac{1}{2} (V_{CC} - V_{EE})$ , Adjust Network Analyzer output to 10 dBm on each output from the power splitter	3.0	0.0	-93	dB
			4.5	0.0	-93	
			5.5	0.0	-93	
			3.3	-3.3	-93	
V <sub>ISOC</sub>	Common-Channel Feedthrough Isolation (Figure 8)	$V_{IS} = \frac{1}{2} (V_{CC} - V_{EE})$ , Adjust Network Analyzer output to 10 dBm on each output from the power splitter	3.0	0.0	-93	dB
			4.5	0.0	-93	
			5.5	0.0	-93	
			3.3	-3.3	-93	
V <sub>ONL</sub>	Maximum Feedthrough On Loss (Figure 11)	$V_{IS} = \frac{1}{2} (V_{CC} - V_{EE})$ , Adjust Network Analyzer output to 10 dBm on each output from the power splitter	3.0	0.0	-2	dB
			4.5	0.0	-2	
			5.5	0.0	-2	
			3.3	-3.3	-2	
Q	Feedthrough Noise. Channel-Select Input to Common I/O (Figure 9)	$V_{IN} = V_{CC}$ to $V_{EE}$ , $f_{IS} = 1$ MHz, $t_r = t_f = 3$ ns $R_{IS} = 600 \Omega$ , $C_L = 50$ pF	3.0	0.0	25	mV <sub>PP</sub>
			4.5	0.0	40	
			5.5	0.0	50	
			3.3	-3.3	60	
	Feedthrough Noise. Channel-Select Input to Common I/O (Figure 9)	$V_{IN} = V_{CC}$ to $V_{EE}$ , $f_{IS} = 1$ MHz, $t_r = t_f = 3$ ns $R_{IS} = 10 \Omega$ , $C_L = 10$ pF	3.0	0.0	35	
			4.5	0.0	40	
			5.5	0.0	50	
			3.3	-3.3	60	
Q	Feedthrough Noise.† Enable Input to Common I/O (Figure 10)	$V_{IN} = V_{CC}$ to $V_{EE}$ , $f_{IS} = 1$ MHz, $t_r = t_f = 3$ ns $R_{IS} = 0 \Omega$ , $C_L = 1000$ pF, $Q = C_L \cdot \Delta V_{OUT}$	3.0	0.0	TBD	pC
			4.5	0.0	3.0	
			5.5	0.0	3.0	
			3.3	-3.3	TBD	
	Feedthrough Noise. Channel-Select Input to Common I/O (Figure 9)	$V_{IN} = V_{CC}$ to $V_{EE}$ , $f_{IS} = 1$ MHz, $t_r = t_f = 3$ ns $R_{IS} = 0 \Omega$ , $C_L = 1000$ pF, $Q = C_L \cdot \Delta V_{OUT}$	3.0	0.0	TBD	
			4.5	0.0	TBD	
			5.5	0.0	TBD	
			3.3	-3.3	TBD	
V <sub>CT</sub>	Crosstalk Between Any Two Switches (Figure 12)	$V_{IS} = \frac{1}{2} (V_{CC} - V_{EE})$ , $f_{IS} = 100$ kHz, $R_L = 50 \Omega$	3.0	0.0	-96	dB
			4.5	0.0	-96	
			5.5	0.0	-96	
			3.3	-3.3	-96	
V <sub>ΔOUT</sub>	Maximum Shift in Output Voltage of Enabled Analog Channel due to injected Current on a Disabled Channel (Figure 17)	$I_{IN} \nless 1$ mA, $R_S \leq 3.9$ K $\Omega$ $I_{IN} \nless 10$ mA, $R_S \leq 3.9$ K $\Omega$ $I_{IN} \nless 1$ mA, $R_S \leq 20$ K $\Omega$ $I_{IN} \nless 10$ mA, $R_S \leq 20$ K $\Omega$	5.0	0.0	TBD	mV
			5.0	0.0	TBD	
			5.0	0.0	TBD	
			5.0	0.0	TBD	
THD	Total Harmonic Distortion  THD = THD <sub>MEASURED</sub> - THD <sub>SOURCE</sub>  (Figure 19)	$f_{IS} = 1$ MHz, $R_L = 10$ K $\Omega$ , $C_L = 50$ pF, $V_{IS} = 2.5$ V <sub>PP</sub> sine wave $V_{IS} = 4.0$ V <sub>PP</sub> sine wave $V_{IS} = 5.0$ V <sub>PP</sub> sine wave $V_{IS} = 6.0$ V <sub>PP</sub> sine wave	3.0	0.0	0.10	%
			4.5	0.0	0.08	
			5.5	0.0	0.05	
			3.3	-3.3	0.05	

\*Limits not tested. Determined by design and verified by qualification.

†Note: Some manufacturers may refer to this specification as Charge Injection.

‡Note:  $I_{IN}$  = Total current injected into all disabled channels.

# MC74LVX4053




Figure 1a. Typical On Resistance,  $V_{CC} = 3.0\text{ V}$ ,  $V_{EE} = 0\text{ V}$




Figure 1b. Typical On Resistance,  $V_{CC} = 4.5\text{ V}$ ,  $V_{EE} = 0\text{ V}$




Figure 1c. Typical On Resistance,  $V_{CC} = 5.5\text{ V}$ ,  $V_{EE} = 0\text{ V}$






Figure 2. On Resistance Test Set-Up


# MC74LVX4053




**Figure 3. Maximum Off Channel Leakage Current, Any One Channel, Test Set-Up**



**Figure 4. Maximum Off Channel Leakage Current, Common Channel, Test Set-Up**



**Figure 5. Maximum On Channel Leakage Current, Channel to Channel, Test Set-Up**



**Figure 6. Maximum On Channel Bandwidth, Test Set-Up**






Figure 7. Maximum Off Channel Feedthrough Isolation, Test Set-Up




Figure 8. Maximum Common-Channel Feedthrough Isolation Test Set-Up




Figure 9. Feedthrough Noise, Channel Select to Common Out, Test Set-Up






Figure 10. Feedthrough Noise, Enable to Common Out, Test Set-Up


# MC74LVX4053




**Figure 11. Maximum On Channel Feedthrough  
On Loss Test Set-Up**



### Figure 12. Crosstalk Between Any Two Switches Test Set-Up




**Figure 13a. Break-Before-Make Test Set-Up**




**Figure 13b. Break–Before–Make Time**

# MC74LVX4053




**Figure 14a. Propagation Delays, Channel Select to Analog Out**




\*Includes all probe and jig capacitance

**Figure 14b. Propagation Delay, Test Set–Up Channel Select to Analog Out**




**Figure 15a. Propagation Delays, Analog In to Analog Out**




\*Includes all probe and jig capacitance

**Figure 15b. Propagation Delay, Test Set–Up  
Analog In to Analog Out**



### Figure 16a. Propagation Delays, Enable to Analog Out



**Figure 16b. Propagation Delay, Test Set-Up Enable to Analog Out**




Figure 17. Maximum Shift in Output Voltage of Enabled Analog Channel due to Injected Current on a Disabled Channel Test Set-Up




Figure 18. Power Dissipation Capacitance, Test Set-Up




Figure 19a. Total Harmonic Distortion Test Set-Up




Figure 19b. Plot, Harmonic Distortion

## APPLICATIONS INFORMATION

The Channel Select and Enable control pins should be at  $V_{CC}$  or GND logic levels.  $V_{CC}$  being recognized as a logic high and GND being recognized as a logic low. In this example:

$$\begin{aligned} V_{CC} &= +5V = \text{logic high} \\ \text{GND} &= 0V = \text{logic low} \end{aligned}$$

The maximum analog voltage swing is determined by the supply voltages  $V_{CC}$  and  $V_{EE}$ . The positive peak analog voltage should not exceed  $V_{CC}$ . Similarly, the negative peak analog voltage should not go below  $V_{EE}$ . In this example, the difference between  $V_{CC}$  and  $V_{EE}$  is five volts. Therefore, using the configuration of Figure 15, a maximum analog signal of five volts peak-to-peak can be controlled. Unused analog inputs/outputs may be left floating (i.e., not connected). However, tying unused analog inputs and outputs to  $V_{CC}$  or

GND through a low value resistor helps minimize crosstalk and feedthrough noise that may be picked up by an unused switch.

Although used here, balanced supplies are not a requirement. The only constraints on the power supplies are that:

$$\begin{aligned} V_{EE} - \text{GND} &= 0 \text{ to } -6 \text{ volts} \\ V_{CC} - \text{GND} &= 2 \text{ to } 6 \text{ volts} \\ V_{CC} - V_{EE} &= 2 \text{ to } 6 \text{ volts} \\ &\text{and } V_{EE} \leq \text{GND} \end{aligned}$$

When voltage transients above  $V_{CC}$  and/or below  $V_{EE}$  are anticipated on the analog channels, external Germanium or Schottky diodes ( $D_x$ ) are recommended as shown in Figure 16. These diodes should be able to absorb the maximum anticipated current surges during clipping.




Figure 20a. Application Example




Figure 20b. Application Example




Figure 21. External Germanium or Schottky Clipping Diodes

# MC74LVX4053





Figure 22. Function Diagram, LVX4053

# MC74LVX4053

## PACKAGE DIMENSIONS

SOIC-16  
D SUFFIX  
CASE 751B-05  
ISSUE J




### NOTES:

1. DIMENSIONING AND TOLERANCING PER ANSI Y14.5M, 1982.
2. CONTROLLING DIMENSION: MILLIMETER.
3. DIMENSIONS A AND B DO NOT INCLUDE MOLD PROTRUSION.
4. MAXIMUM MOLD PROTRUSION 0.15 (0.006) PER SIDE.
5. DIMENSION D DOES NOT INCLUDE DAMBAR PROTRUSION. ALLOWABLE DAMBAR PROTRUSION SHALL BE 0.127 (0.005) TOTAL IN EXCESS OF THE D DIMENSION AT MAXIMUM MATERIAL CONDITION.

DIM	MILLIMETERS		INCHES	
	MIN	MAX	MIN	MAX
A	9.80	10.00	0.386	0.393
B	3.80	4.00	0.150	0.157
C	1.35	1.75	0.054	0.068
D	0.35	0.49	0.014	0.019
F	0.40	1.25	0.016	0.049
G	1.27 BSC		0.050 BSC	
J	0.19	0.25	0.008	0.009
K	0.10	0.25	0.004	0.009
M	0°	7°	0°	7°
P	5.80	6.20	0.229	0.244
R	0.25	0.50	0.010	0.019

TSSOP-16  
DT SUFFIX  
CASE 948F-01  
ISSUE O



### NOTES:



1. DIMENSIONING AND TOLERANCING PER ANSI Y14.5M, 1982.
2. CONTROLLING DIMENSION: MILLIMETER.
3. DIMENSION A DOES NOT INCLUDE MOLD FLASH, PROTRUSIONS OR GATE BURRS. MOLD FLASH OR GATE BURRS SHALL NOT EXCEED 0.15 (0.006) PER SIDE.
4. DIMENSION B DOES NOT INCLUDE INTERLEAD FLASH OR PROTRUSION. INTERLEAD FLASH OR PROTRUSION SHALL NOT EXCEED 0.25 (0.010) PER SIDE.
5. DIMENSION K DOES NOT INCLUDE DAMBAR PROTRUSION. ALLOWABLE DAMBAR PROTRUSION SHALL BE 0.08 (0.003) TOTAL IN EXCESS OF THE K DIMENSION AT MAXIMUM MATERIAL CONDITION.
6. TERMINAL NUMBERS ARE SHOWN FOR REFERENCE ONLY.
7. DIMENSION A AND B ARE TO BE DETERMINED AT DATUM PLANE -W-.

DIM	MILLIMETERS		INCHES	
	MIN	MAX	MIN	MAX
A	4.90	5.10	0.193	0.200
B	4.30	4.50	0.169	0.177
C	---	1.20	---	0.047
D	0.05	0.15	0.002	0.006
F	0.50	0.75	0.020	0.030
G	0.65 BSC		0.026 BSC	
H	0.18	0.28	0.007	0.011
J	0.09	0.20	0.004	0.008
J1	0.09	0.16	0.004	0.006
K	0.19	0.30	0.007	0.012
K1	0.19	0.25	0.007	0.010
L	6.40 BSC		0.252 BSC	
M	0°	8°	0°	8°


# MC74LVX4053

## PACKAGE DIMENSIONS

SOIC EIAJ-16  
M SUFFIX  
CASE 966-01  
ISSUE O



DETAIL P




VIEW P

### NOTES:

1. DIMENSIONING AND TOLERANCING PER ANSI Y14.5M, 1982.
2. CONTROLLING DIMENSION: MILLIMETER.
3. DIMENSIONS D AND E DO NOT INCLUDE MOLD FLASH OR PROTRUSIONS AND ARE MEASURED AT THE PARTING LINE. MOLD FLASH OR PROTRUSIONS SHALL NOT EXCEED 0.15 (0.006) PER SIDE.
4. TERMINAL NUMBERS ARE SHOWN FOR REFERENCE ONLY.
5. THE LEAD WIDTH DIMENSION (b) DOES NOT INCLUDE DAMBAR PROTRUSION. ALLOWABLE DAMBAR PROTRUSION SHALL BE 0.08 (0.003) TOTAL IN EXCESS OF THE LEAD WIDTH DIMENSION AT MAXIMUM MATERIAL CONDITION. DAMBAR CANNOT BE LOCATED ON THE LOWER RADIUS OR THE FOOT. MINIMUM SPACE BETWEEN PROTRUSIONS AND ADJACENT LEAD TO BE 0.46 (0.018).

DIM	MILLIMETERS		INCHES	
	MIN	MAX	MIN	MAX
A	---	2.05	---	0.081
A <sub>1</sub>	0.05	0.20	0.002	0.008
b	0.35	0.50	0.014	0.020
c	0.18	0.27	0.007	0.011
D	9.90	10.50	0.390	0.413
E	5.10	5.45	0.201	0.215
e	1.27 BSC		0.050 BSC	
H <sub>E</sub>	7.40	8.20	0.291	0.323
L	0.50	0.85	0.020	0.033
L <sub>E</sub>	1.10	1.50	0.043	0.059
M	0°	10°	0°	10°
Q <sub>1</sub>	0.70	0.90	0.028	0.035
Z	---	0.78	---	0.031

ON Semiconductor and  are trademarks of Semiconductor Components Industries, LLC (SCILLC). SCILLC reserves the right to make changes without further notice to any products herein. SCILLC makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does SCILLC assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. "Typical" parameters which may be provided in SCILLC data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. SCILLC does not convey any license under its patent rights nor the rights of others. SCILLC products are not designed, intended, or authorized for use as components in systems intended for surgical implant into the body, or other applications intended to support or sustain life, or for any other application in which the failure of the SCILLC product could create a situation where personal injury or death may occur. Should Buyer purchase or use SCILLC products for any such unintended or unauthorized application, Buyer shall indemnify and hold SCILLC and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that SCILLC was negligent regarding the design or manufacture of the part. SCILLC is an Equal Opportunity/Affirmative Action Employer.

## PUBLICATION ORDERING INFORMATION

### NORTH AMERICA Literature Fulfillment:

Literature Distribution Center for ON Semiconductor  
P.O. Box 5163, Denver, Colorado 80217 USA  
Phone: 303-675-2175 or 800-344-3860 Toll Free USA/Canada  
Fax: 303-675-2176 or 800-344-3867 Toll Free USA/Canada  
Email: ONlit@hibbertco.com  
Fax Response Line: 303-675-2167 or 800-344-3810 Toll Free USA/Canada

### N. American Technical Support: 800-282-9855 Toll Free USA/Canada

### EUROPE: LDC for ON Semiconductor – European Support

German Phone: (+1) 303-308-7140 (Mon-Fri 2:30pm to 7:00pm CET)  
Email: ONlit-german@hibbertco.com  
French Phone: (+1) 303-308-7141 (Mon-Fri 2:00pm to 7:00pm CET)  
Email: ONlit-french@hibbertco.com  
English Phone: (+1) 303-308-7142 (Mon-Fri 12:00pm to 5:00pm GMT)  
Email: ONlit@hibbertco.com

### EUROPEAN TOLL-FREE ACCESS\*: 00-800-4422-3781

\*Available from Germany, France, Italy, UK, Ireland

### CENTRAL/SOUTH AMERICA:

Spanish Phone: 303-308-7143 (Mon-Fri 8:00am to 5:00pm MST)  
Email: ONlit-spanish@hibbertco.com

### ASIA/PACIFIC: LDC for ON Semiconductor – Asia Support

Phone: 303-675-2121 (Tue-Fri 9:00am to 1:00pm, Hong Kong Time)  
Toll Free from Hong Kong & Singapore:  
001-800-4422-3781  
Email: ONlit-asia@hibbertco.com

### JAPAN: ON Semiconductor, Japan Customer Focus Center

4-32-1 Nishi-Gotanda, Shinagawa-ku, Tokyo, Japan 141-0031  
Phone: 81-3-5740-2700  
Email: r14525@onsemi.com

### ON Semiconductor Website: <http://onsemi.com>

For additional information, please contact your local Sales Representative.