

FACT SHEET


MCM69C232 MCM69C432

Content Addressable Memories for High Performance Internetworking and Fully Associative Disk Drive Cache Applications


4K x 64 AND 16K x 64 CAMS:

The MCM69C232 and the MCM69C432 are flexible content-addressable memories (CAM) that can contain 4096 and 16,384 entries of 64 bits, respectively. They are implemented with standard 4-transistor SRAM cells that provide a CAM solution at a fraction of the cost of existing CAMs. The widths of the match field and the output field are programmable, and the match time is designed to be ≤ 180 nanoseconds. As a result, the MCM69C232 and the MCM69C432 are well suited for datacom applications such as Virtual Path Identifier/Virtual Circuit Identifier (VPI/VCI) translation in ATM switches up to OC12 (622 Mbps) data rates and Media Access Control (MAC) address lookup in Ethernet/Fast Ethernet bridges. CAMs are also well suited for fully associative disk drive cache and RAID applications. The match duty cycle of the MCM69C232 and the MCM69C432 is user defined, with a trade-off between the time between matches and the number of new entries added to the CAM per second.

MCM69C232 AND MCM69C432 BLOCK DIAGRAM



LINE CARD BLOCK DIAGRAM



The Product:

MCM69C232 Features:

- Production Now
- Volume Pricing < \$20
- 4096 Entries
- Programmable 12- to 64-Bit Wide Match Field
- 160 ns Match Time
- 150 ns Insertion Time if 1 of 12 Entry Queue Locations is Empty

MCM69C432 Features:

- Production Now
- Volume Pricing < \$50
- 16,384 Entries
- Programmable 14- to 64-Bit Wide Match Field
- 180 ns Match Time
- 150 ns Insertion Time if 1 of 14 Entry Queue Locations is Empty

Common Features:

- Mask Register to "Don't Care" Selected Bits
- Depth Expansion by Cascading Multiple Devices
- Programmable 0- to 32-Bit Output Value
- Separate Ports for Control and Match Operations
- 10 ms Initialization Time after Fast Insertion (at Power-Up Only)
- Single 3.3 V ± 5% Supply
- IEEE Standard 1149.1 Test Port (JTAG)
- 100-Pin TQFP Package

For additional information call 512–933–SRAM, or your local Motorola sales representative. FAX (512) 933–6809

Motorola reserves the right to make changes without further notice to any products herein. Motorola makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does Motorola assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation consequential or incidental damages. "Typical" parameters which may be provided in Motorola data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. Motorola does not convey any license under its patent rights nor the rights of others. Motorola products are not designed, intended, or authorized for use as components in systems intended for surgical implant into the body, or other applications intended to support or sustain life, or for any other application in which the failure of the Motorola product could create a situation where personal injury or death may occur. Should Buyer purchase or use Motorola products for any such unintended or unauthorized application, Buyer shall indemnify and hold Motorola and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that Motorola was negligent regarding the design or manufacture of the part. Motorola and manufacture of the part. Motor

How to reach us:

USA/EUROPE/Locations Not Listed: Motorola Literature Distribution; P.O. Box 5405. Denver. Colorado. 80217. 1-303-675-2140 or 1-800-441-2447

Mfax™: RMFAX0@email.sps.mot.com - TOUCHTONE 1-602-244-6609 Motorola Fax Back System - US & Canada ONLY 1-800-774-1848

– http://sps.motorola.com/mfax/

ASIA/I

JAPAN: Nippon Motorola Ltd.: SPD, Strategic Planning Office, 141, 4-32-1 Nishi-Gotanda, Shagawa-ku, Tokyo, Japan. 03-5487-8488

ASIA/PACIFIC: Motorola Semiconductors H.K. Ltd.; 8B Tai Ping Industrial Park, 51 Ting Kok Road, Tai Po, N.T., Hong Kong. 852-26629298

CUSTOMER FOCUS CENTER: 1-800-521-6274

MOTOROLA

HOME PAGE: http://motorola.com/sps/

© Motorola, Inc. 1998

Mfax is a trademark of Motorola. Inc.

MCM69C232FACT/D