

Appendix B – ATtiny24A/44A/84A Specification at 125°C

This document contains information specific to devices operating at temperatures up to 125°C. Only deviations are covered in this appendix, all other information can be found in the complete datasheet. The complete datasheet can be found at www.atmel.com.



8-bit AVR[®]
Microcontroller
with 2K/4K/8K
Bytes In-System
Programmable
Flash

ATtiny24A
ATtiny44A
ATtiny84A

Appendix B

Rev. 8183F - Appendix B-AVR-06/12



1. Memories

1.1 EEPROM Data Memory

The EEPROM has an endurance of at least 50,000 write/erase cycles.

2. Electrical Characteristics

2.1 Absolute Maximum Ratings*

Operating Temperature.....	-55°C to +125°C
Storage Temperature	-65°C to +150°C
Voltage on any Pin except <u>RESET</u> with respect to Ground	-0.5V to $V_{CC}+0.5V$
Voltage on <u>RESET</u> with respect to Ground.....	-0.5V to +13.0V
Maximum Operating Voltage	6.0V
DC Current per I/O Pin	40.0 mA
DC Current V_{CC} and GND Pins	200.0 mA

*NOTICE: Stresses beyond those listed under “Absolute Maximum Ratings” may cause permanent damage to the device. This is a stress rating only and functional operation of the device at these or other conditions beyond those indicated in the operational sections of this specification is not implied. Exposure to absolute maximum rating conditions for extended periods may affect device reliability.

2.2 DC Characteristics

Table 2-1. DC Characteristics. $T_A = -40^{\circ}\text{C}$ to $+125^{\circ}\text{C}$

Symbol	Parameter	Condition	Min	Typ ⁽¹⁾	Max	Units
V_{IL}	Input Low Voltage	$V_{CC} = 1.8V - 2.4V$	-0.5		$0.2V_{CC}$ ⁽³⁾	V
		$V_{CC} = 2.4V - 5.5V$	-0.5		$0.3V_{CC}$ ⁽³⁾	V
	Input Low Voltage, <u>RESET</u> Pin as Reset ⁽⁴⁾	$V_{CC} = 1.8V - 5.5$	-0.5		$0.2V_{CC}$ ⁽³⁾	
V_{IH}	Input High-voltage Except <u>RESET</u> pin	$V_{CC} = 1.8V - 2.4V$	$0.7V_{CC}$ ⁽²⁾		$V_{CC} + 0.5$	V
		$V_{CC} = 2.4V - 5.5V$	$0.6V_{CC}$ ⁽²⁾		$V_{CC} + 0.5$	V
	Input High-voltage <u>RESET</u> pin as Reset ⁽⁴⁾	$V_{CC} = 1.8V$ to $5.5V$	$0.9V_{CC}$ ⁽²⁾		$V_{CC} + 0.5$	V
V_{OL}	Output Low Voltage ⁽⁵⁾ Except <u>RESET</u> pin ⁽⁷⁾	$I_{OL} = 10\text{ mA}$, $V_{CC} = 5V$			0.6	V
		$I_{OL} = 5\text{ mA}$, $V_{CC} = 3V$			0.5	V
V_{OH}	Output High-voltage ⁽⁶⁾ Except <u>RESET</u> pin ⁽⁷⁾	$I_{OH} = -10\text{ mA}$, $V_{CC} = 5V$	4.3			V
		$I_{OH} = -5\text{ mA}$, $V_{CC} = 3V$	2.5			V
I_{LIL}	Input Leakage Current I/O Pin	$V_{CC} = 5.5V$, pin low (absolute value)		< 0.05	1 ⁽⁸⁾	μA
I_{LIH}	Input Leakage Current I/O Pin	$V_{CC} = 5.5V$, pin high (absolute value)		< 0.05	1 ⁽⁸⁾	μA
R_{PU}	Pull-up Resistor, I/O Pin	$V_{CC} = 5.5V$, input low	20		50	$k\Omega$
	Pull-up Resistor, Reset Pin	$V_{CC} = 5.5V$, input low	30		60	$k\Omega$

Table 2-1. DC Characteristics. $T_A = -40^{\circ}\text{C}$ to $+125^{\circ}\text{C}$ (Continued)


Symbol	Parameter	Condition	Min	Typ ⁽¹⁾	Max	Units
I_{CC}	Supply Current, Active Mode ⁽⁹⁾	$f = 1\text{MHz}, V_{CC} = 2\text{V}$		0.25	0.5	mA
		$f = 4\text{MHz}, V_{CC} = 3\text{V}$		1.2	2	mA
		$f = 8\text{MHz}, V_{CC} = 5\text{V}$		4.4	7	mA
	Supply Current, Idle Mode ⁽⁹⁾	$f = 1\text{MHz}, V_{CC} = 2\text{V}$		0.04	0.2	mA
		$f = 4\text{MHz}, V_{CC} = 3\text{V}$		0.25	0.6	mA
		$f = 8\text{MHz}, V_{CC} = 5\text{V}$		1.3	2	mA
	Supply Current, Power-Down Mode ⁽¹⁰⁾	WDT enabled, $V_{CC} = 3\text{V}$		4	20	μA
		WDT disabled, $V_{CC} = 3\text{V}$		0.2	10	μA

- Notes:
1. Typical values at 25°C .
 2. “Min” means the lowest value where the pin is guaranteed to be read as high.
 3. “Max” means the highest value where the pin is guaranteed to be read as low.
 4. Not tested in production.
 5. Although each I/O port can sink more than the test conditions (10 mA at $V_{CC} = 5\text{V}$, 5 mA at $V_{CC} = 3\text{V}$) under steady state conditions (non-transient), the sum of all I_{OL} (for all ports) should not exceed 60 mA. If I_{OL} exceeds the test conditions, V_{OL} may exceed the related specification. Pins are not guaranteed to sink current greater than the listed test condition.
 6. Although each I/O port can source more than the test conditions (10 mA at $V_{CC} = 5\text{V}$, 5 mA at $V_{CC} = 3\text{V}$) under steady state conditions (non-transient), the sum of all I_{OH} (for all ports) should not exceed 60 mA. If I_{OH} exceeds the test condition, V_{OH} may exceed the related specification. Pins are not guaranteed to source current greater than the listed test condition.
 7. The $\overline{\text{RESET}}$ pin must tolerate high voltages when entering and operating in programming modes and, as a consequence, has a weak drive strength as compared to regular I/O pins. See figures, for ATtiny24A, from [Figure 3-22 on page 20](#) to [Figure 3-25 on page 22](#), and for ATtiny44A, from [Figure 3-67 on page 43](#) to [Figure 3-70 on page 44](#).
 8. These are test limits, which account for leakage currents of the test environment. Actual device leakage currents are lower.
 9. Values are with external clock using methods described in “Minimizing Power Consumption”. Power reduction is enabled (PRR = 0xFF) and there is no I/O drive.
 10. BOD disabled.

2.3 Speed

The maximum operating frequency of the device depends on V_{CC} . As shown in [Figure 2-1](#), the relationship between maximum frequency and V_{CC} is linear in the region $1.8\text{V} < V_{CC} < 4.5\text{V}$.

Figure 2-1. Maximum Frequency vs. V_{CC} . $T_A = -40^{\circ}\text{C}$ to $+125^{\circ}\text{C}$



2.4 Clock Characteristics

2.4.1 Accuracy of Calibrated Internal Oscillator

It is possible to manually calibrate the internal oscillator to be more accurate than default factory calibration. Note that the oscillator frequency depends on temperature and voltage. Voltage and temperature characteristics can be found in [Figure 3-45 on page 32](#).

Table 2-2. Calibration Accuracy of Internal RC Oscillator

Calibration Method	Target Frequency	V _{CC}	Temperature	Accuracy at given voltage & temperature ⁽¹⁾
Factory Calibration	8.0 MHz	3V	25°C	±10%
User Calibration	Fixed frequency within: 7.3 – 8.1 MHz	Fixed voltage within: 1.8V – 5.5V	Fixed temperature within: -40°C to +125°C	±1%

Note: 1. Accuracy of oscillator frequency at calibration point (fixed temperature and fixed voltage).

2.5 System and Reset Characteristics

2.5.1 Power-On Reset

Table 2-3. Characteristics of Enhanced Power-On Reset. T_A = -40 to +125°C

Symbol	Parameter	Min ⁽¹⁾	Typ ⁽¹⁾	Max ⁽¹⁾	Units
V _{POR}	Release threshold of power-on reset ⁽²⁾	1.1	1.4	1.7	V
V _{POA}	Activation threshold of power-on reset ⁽³⁾	0.6	1.3	1.7	V
SR _{ON}	Power-On Slope Rate	0.01			V/ms

Notes: 1. Values are guidelines, only
2. Threshold where device is released from reset when voltage is rising
3. The Power-on Reset will not work unless the supply voltage has been below V_{POA}

2.6 ADC Characteristics

Table 2-4. ADC Characteristics, Single Ended Channels. T = -40°C to +125°C

Symbol	Parameter	Condition	Min	Typ	Max	Units
	Resolution				10	Bits
	Absolute accuracy (Including INL, DNL, and Quantization, Gain and Offset Errors)	$V_{REF} = 4V, V_{CC} = 4V,$ ADC clock = 200 kHz		2.0		LSB
		$V_{REF} = 4V, V_{CC} = 4V,$ ADC clock = 1 MHz		2.5		LSB
		$V_{REF} = 4V, V_{CC} = 4V,$ ADC clock = 200 kHz Noise Reduction Mode		1.5		LSB
		$V_{REF} = 4V, V_{CC} = 4V,$ ADC clock = 1 MHz Noise Reduction Mode		2.0		LSB
	Integral Non-Linearity (INL) (Accuracy after Offset and Gain Calibration)	$V_{REF} = 4V, V_{CC} = 4V,$ ADC clock = 200 kHz		1.0		LSB
	Differential Non-linearity (DNL)	$V_{REF} = 4V, V_{CC} = 4V,$ ADC clock = 200 kHz		0.5		LSB
	Gain Error	$V_{REF} = 4V, V_{CC} = 4V,$ ADC clock = 200 kHz		2.0		LSB
	Offset Error (Absolute)	$V_{REF} = 4V, V_{CC} = 4V,$ ADC clock = 200 kHz		1.5		LSB
	Conversion Time	Free Running Conversion	14		280	μs
	Clock Frequency		50		1000	kHz
V_{IN}	Input Voltage		GND		V_{REF}	V
	Input Bandwidth			38.5		kHz
A_{REF}	External Voltage Reference		2.0		V_{CC}	V
V_{INT}	Internal Voltage Reference		1.0	1.1	1.2	V
R_{REF}	Reference Input Resistance			32		kΩ
R_{AIN}	Analog Input Resistance			100		MΩ
	ADC Conversion Output		0		1023	LSB

Table 2-5. ADC Characteristics, Differential Channels (Unipolar Mode), $T_A = -40^{\circ}\text{C}$ to $+125^{\circ}\text{C}$

Symbol	Parameter	Condition	Min	Typ	Max	Units
	Resolution	Gain = 1x			10	Bits
		Gain = 20x			10	Bits
	Absolute accuracy (Including INL, DNL, and Quantization, Gain and Offset Errors)	Gain = 1x $V_{REF} = 4\text{V}$, $V_{CC} = 5\text{V}$ ADC clock = 50 - 200 kHz		10		LSB
		Gain = 20x $V_{REF} = 4\text{V}$, $V_{CC} = 5\text{V}$ ADC clock = 50 - 200 kHz		15		LSB
	Integral Non-Linearity (INL) (Accuracy after Offset and Gain Calibration)	Gain = 1x $V_{REF} = 4\text{V}$, $V_{CC} = 5\text{V}$ ADC clock = 50 - 200 kHz		4		LSB
		Gain = 20x $V_{REF} = 4\text{V}$, $V_{CC} = 5\text{V}$ ADC clock = 50 - 200 kHz		10		LSB
	Gain Error	Gain = 1x		10		LSB
		Gain = 20x		15		LSB
	Offset Error	Gain = 1x $V_{REF} = 4\text{V}$, $V_{CC} = 5\text{V}$ ADC clock = 50 - 200 kHz		3		LSB
		Gain = 20x $V_{REF} = 4\text{V}$, $V_{CC} = 5\text{V}$ ADC clock = 50 - 200 kHz		4		LSB
	Conversion Time	Free Running Conversion	70		280	μs
	Clock Frequency		50		200	kHz
V_{IN}	Input Voltage		GND		V_{CC}	V
V_{DIFF}	Input Differential Voltage				V_{REF}/Gain	V
	Input Bandwidth			4		kHz
A_{REF}	External Reference Voltage		2.0		$V_{CC} - 1.0$	V
V_{INT}	Internal Voltage Reference		1.0	1.1	1.2	V
R_{REF}	Reference Input Resistance			32		k Ω
R_{AIN}	Analog Input Resistance			100		M Ω
	ADC Conversion Output		0		1023	LSB

Table 2-6. ADC Characteristics, Differential Channels (Bipolar Mode), $T_A = -40^{\circ}\text{C}$ to $+125^{\circ}\text{C}$

Symbol	Parameter	Condition	Min	Typ	Max	Units
	Resolution	Gain = 1x			10	Bits
		Gain = 20x			10	Bits
	Absolute accuracy (Including INL, DNL, and Quantization, Gain and Offset Errors)	Gain = 1x $V_{REF} = 4\text{V}$, $V_{CC} = 5\text{V}$ ADC clock = 50 - 200 kHz		8		LSB
		Gain = 20x $V_{REF} = 4\text{V}$, $V_{CC} = 5\text{V}$ ADC clock = 50 - 200 kHz		8		LSB
	Integral Non-Linearity (INL) (Accuracy after Offset and Gain Calibration)	Gain = 1x $V_{REF} = 4\text{V}$, $V_{CC} = 5\text{V}$ ADC clock = 50 - 200 kHz		4		LSB
		Gain = 20x $V_{REF} = 4\text{V}$, $V_{CC} = 5\text{V}$ ADC clock = 50 - 200 kHz		5		LSB
	Gain Error	Gain = 1x		4		LSB
		Gain = 20x		5		LSB
	Offset Error	Gain = 1x $V_{REF} = 4\text{V}$, $V_{CC} = 5\text{V}$ ADC clock = 50 - 200 kHz		3		LSB
		Gain = 20x $V_{REF} = 4\text{V}$, $V_{CC} = 5\text{V}$ ADC clock = 50 - 200 kHz		4		LSB
	Conversion Time	Free Running Conversion	70		280	μs
	Clock Frequency		50		200	kHz
V_{IN}	Input Voltage		GND		V_{CC}	V
V_{DIFF}	Input Differential Voltage				V_{REF}/Gain	V
	Input Bandwidth			4		kHz
A_{REF}	External Reference Voltage		2.0		$V_{CC} - 1.0$	V
V_{INT}	Internal Voltage Reference		1.0	1.1	1.2	V
R_{REF}	Reference Input Resistance			32		k Ω
R_{AIN}	Analog Input Resistance			100		M Ω
	ADC Conversion Output		-512		511	LSB

2.7 Analog Comparator Characteristics

Table 2-7. Analog Comparator Characteristics, $T_A = -40^{\circ}\text{C}$ to $+125^{\circ}\text{C}$

Symbol	Parameter	Condition	Min	Typ	Max	Units
V_{AIO}	Input Offset Voltage	$V_{CC} = 5V, V_{IN} = V_{CC} / 2$		< 10	40	mV
I_{LAC}	Input Leakage Current	$V_{CC} = 5V, V_{IN} = V_{CC} / 2$	-0.5		0.5	μA
t_{APD}	Analog Propagation Delay (from saturation to slight overdrive)	$V_{CC} = 2.7V$		750		ns
		$V_{CC} = 4.0V$		500		
	Analog Propagation Delay (large step change)	$V_{CC} = 2.7V$		100		
		$V_{CC} = 4.0V$		75		
t_{DPD}	Digital Propagation Delay	$V_{CC} = 1.8V - 5.5$		1	2	CLK

Note: All parameters are based on simulation results and are not tested in production

2.8 Serial Programming Characteristics

Table 2-8. Serial Programming Characteristics, $T_A = -40^{\circ}\text{C}$ to $+125^{\circ}\text{C}$, $V_{CC} = 1.8 - 5.5V$
(Unless Otherwise Noted)

Symbol	Parameter	Min	Typ	Max	Units
$1/t_{CLCL}$	Oscillator Frequency	0		4	MHz
t_{CLCL}	Oscillator Period	250			ns
$1/t_{CLCL}$	Oscillator Frequency ($V_{CC} = 4.5V - 5.5V$)	0		20	MHz
t_{CLCL}	Oscillator Period ($V_{CC} = 4.5V - 5.5V$)	50			ns
t_{SHSL}	SCK Pulse Width High	$2 t_{CLCL}^{(1)}$			ns
t_{SLSH}	SCK Pulse Width Low	$2 t_{CLCL}^{(1)}$			ns
t_{OVSH}	MOSI Setup to SCK High	t_{CLCL}			ns
t_{SHOX}	MOSI Hold after SCK High	$2 t_{CLCL}$			ns

Note: 1. $2 t_{CLCL}$ for $f_{ck} < 12 \text{ MHz}$, $3 t_{CLCL}$ for $f_{ck} \geq 12 \text{ MHz}$

3. Typical Characteristics

3.1 ATtiny24A

3.1.1 Current Consumption in Active Mode

Figure 3-1. Active Supply Current vs. V_{CC} (Internal RC Oscillator, 8 MHz)




Figure 3-2. Active Supply Current vs. V_{CC} (Internal RC Oscillator, 1 MHz)





Figure 3-3. Active Supply Current vs. V_{CC} (Internal RC Oscillator, 128 kHz)



3.1.2 Current Consumption in Idle Mode

Figure 3-4. Idle Supply Current vs. V_{CC} (Internal RC Oscillator, 8 MHz)




Figure 3-5. Idle Supply Current vs. V_{CC} (Internal RC Oscillator, 1 MHz)





Figure 3-6. Idle Supply Current vs. V_{CC} (Internal RC Oscillator, 128 kHz)



3.1.3 Current Consumption in Power-down Mode

Figure 3-7. Power-down Supply Current vs. V_{CC} (Watchdog Timer Disabled)





Figure 3-8. Power-down Supply Current vs. V_{CC} (Watchdog Timer Enabled)



3.1.4 Current Consumption of Peripheral Units

Figure 3-9. Programming Current vs. V_{CC}




Figure 3-10. Brownout Detector Current vs. V_{CC} (BOD Level = 1.8V)





Figure 3-11. Watchdog Timer Current vs. V_{CC}



3.1.5 Pull-up Resistors

Figure 3-12. Pull-up Resistor Current vs. Input Voltage (I/O Pin, $V_{CC} = 1.8V$)




Figure 3-13. Pull-up Resistor Current vs. Input Voltage (I/O Pin, $V_{CC} = 2.7V$)




Figure 3-14. Pull-up Resistor Current vs. Input Voltage (I/O Pin, $V_{CC} = 5V$)




Figure 3-15. Reset Pull-up Resistor Current vs. Reset Pin Voltage ($V_{CC} = 1.8V$)




Figure 3-16. Reset Pull-up Resistor Current vs. Reset Pin Voltage ($V_{CC} = 2.7V$)





Figure 3-17. Reset Pull-up Resistor Current vs. Reset Pin Voltage ($V_{CC} = 5V$)



3.1.6 Output Driver Strength

Figure 3-18. V_{OL} : Output Voltage vs. Sink Current (I/O Pin, $V_{CC} = 1.8V$)




Figure 3-19. V_{OL} : Output Voltage vs. Sink Current (I/O Pin, $V_{CC} = 3V$)




Figure 3-20. V_{OL} : Output Voltage vs. Sink Current (I/O Pin, $V_{CC} = 5V$)




Figure 3-21. V_{OH} : Output Voltage vs. Source Current (I/O Pin, $V_{CC} = 1.8V$)




Figure 3-22. V_{OH} : Output Voltage vs. Source Current (I/O Pin, $V_{CC} = 3V$)




Figure 3-23. V_{OH} : Output Voltage vs. Source Current (I/O Pin, $V_{CC} = 5V$)




Figure 3-24. V_{OL} : Output Voltage vs. Sink Current (Reset Pin as I/O, $V_{CC} = 3V$)




Figure 3-25. V_{OL} : Output Voltage vs. Sink Current (Reset Pin as I/O, $V_{CC} = 5V$)




Figure 3-26. V_{OH} : Output Voltage vs. Source Current (Reset Pin as I/O, $V_{CC} = 3V$)





Figure 3-27. V_{OH} : Output Voltage vs. Source Current (Reset Pin as I/O, $V_{CC} = 5V$)



3.1.7 Input Threshold and Hysteresis (for I/O Ports)

Figure 3-28. V_{IH} : Input Threshold Voltage vs. V_{CC} (IO Pin, Read as '1')




Figure 3-29. V_{IL} : Input Threshold Voltage vs. V_{CC} (I/O Pin, Read as '0')




Figure 3-30. $V_{IH}-V_{IL}$: Input Hysteresis vs. V_{CC} (I/O Pin)




Figure 3-31. V_{IH} : Input Threshold Voltage vs. V_{CC} (Reset Pin as I/O, Read as '1')




Figure 3-32. V_{IL} : Input Threshold Voltage vs. V_{CC} (Reset Pin as I/O, Read as '0')





Figure 3-33. $V_{IH}-V_{IL}$: Input Hysteresis vs. V_{CC} (Reset Pin as I/O)



3.1.8 BOD, Bandgap and Reset

Figure 3-34. BOD Threshold vs. Temperature (BODLEVEL is 4.3V)




Figure 3-35. BOD Threshold vs. Temperature (BODLEVEL is 2.7V)




Figure 3-36. BOD Threshold vs. Temperature (BODLEVEL is 1.8V)




Figure 3-37. Bandgap Voltage vs. Temperature ($V_{CC} = 5V$)




Figure 3-38. V_{IH} : Input Threshold Voltage vs. V_{CC} (Reset Pin, Read as '1')




Figure 3-39. V_{IL} : Input Threshold Voltage vs. V_{CC} (Reset Pin, Read as '0')




Figure 3-40. $V_{IH}-V_{IL}$: Input Hysteresis vs. V_{CC} (Reset Pin)






Figure 3-41. Minimum Reset Pulse Width vs. V_{CC}



3.1.9 Analog Comparator Offset

Figure 3-42. Analog Comparator Offset ($V_{CC} = 5V$)



3.1.10 Internal Oscillator Speed

Figure 3-43. Watchdog Oscillator Frequency vs. V_{CC}




Figure 3-44. Watchdog Oscillator Frequency vs. Temperature




Figure 3-45. Calibrated 8 MHz RC Oscillator Frequency vs. Temperature





Figure 3-46. Calibrated 8 MHz RC Oscillator Frequency vs. OSCCAL Value ($V_{CC} = 3V$)



3.2 ATtiny44A

3.2.1 Current Consumption in Active Mode

Figure 3-47. Active Supply Current vs. V_{CC} (Internal RC Oscillator, 8 MHz)




Figure 3-48. Active Supply Current vs. V_{CC} (Internal RC Oscillator, 1 MHz)





Figure 3-49. Active Supply Current vs. V_{CC} (Internal RC Oscillator, 128 kHz)



3.2.2 Current Consumption in Idle Mode

Figure 3-50. Idle Supply Current vs. V_{CC} (Internal RC Oscillator, 8 MHz)




Figure 3-51. Idle Supply Current vs. V_{CC} (Internal RC Oscillator, 1 MHz)





Figure 3-52. Idle Supply Current vs. V_{CC} (Internal RC Oscillator, 128 kHz)



3.2.3 Current Consumption in Power-down Mode

Figure 3-53. Power-down Supply Current vs. V_{CC} (Watchdog Timer Disabled)





Figure 3-54. Power-down Supply Current vs. V_{CC} (Watchdog Timer Enabled)



3.2.4 Current Consumption of Peripheral Units

Figure 3-55. Programming Current vs. V_{CC}




Figure 3-56. Brownout Detector Current vs. V_{CC} (BOD Level = 1.8V)





Figure 3-57. Watchdog Timer Current vs. V_{CC}



3.2.5 Pull-up Resistors

Figure 3-58. Pull-up Resistor Current vs. Input Voltage (I/O Pin, $V_{CC} = 1.8V$)




Figure 3-59. Pull-up Resistor Current vs. Input Voltage (I/O Pin, $V_{CC} = 2.7V$)




Figure 3-60. Pull-up Resistor Current vs. Input Voltage (I/O Pin, $V_{CC} = 5V$)




Figure 3-61. Reset Pull-up Resistor Current vs. Reset Pin Voltage ($V_{CC} = 1.8V$)




Figure 3-62. Reset Pull-up Resistor Current vs. Reset Pin Voltage ($V_{CC} = 2.7V$)





Figure 3-63. Reset Pull-up Resistor Current vs. Reset Pin Voltage ($V_{CC} = 5V$)



3.2.6 Output Driver Strength

Figure 3-64. V_{OL} : Output Voltage vs. Sink Current (I/O Pin, $V_{CC} = 1.8V$)




Figure 3-65. V_{OL} : Output Voltage vs. Sink Current (I/O Pin, $V_{CC} = 3V$)




Figure 3-66. V_{OL} : Output Voltage vs. Sink Current (I/O Pin, $V_{CC} = 5V$)




Figure 3-67. V_{OH} : Output Voltage vs. Source Current (I/O Pin, $V_{CC} = 1.8V$)




Figure 3-68. V_{OH} : Output Voltage vs. Source Current (I/O Pin, $V_{CC} = 3V$)




Figure 3-69. V_{OH} : Output Voltage vs. Source Current (I/O Pin, $V_{CC} = 5V$)




Figure 3-70. V_{OL} : Output Voltage vs. Sink Current (Reset Pin as I/O, $V_{CC} = 3V$)




Figure 3-71. V_{OL} : Output Voltage vs. Sink Current (Reset Pin as I/O, $V_{CC} = 5V$)




Figure 3-72. V_{OH} : Output Voltage vs. Source Current (Reset Pin as I/O, $V_{CC} = 3V$)





Figure 3-73. V_{OH} : Output Voltage vs. Source Current (Reset Pin as I/O, $V_{CC} = 5V$)



3.2.7 Input Threshold and Hysteresis (for I/O Ports)

Figure 3-74. V_{IH} : Input Threshold Voltage vs. V_{CC} (IO Pin, Read as '1')




Figure 3-75. V_{IL} : Input Threshold Voltage vs. V_{CC} (I/O Pin, Read as '0')




Figure 3-76. $V_{IH}-V_{IL}$: Input Hysteresis vs. V_{CC} (I/O Pin)




Figure 3-77. V_{IH} : Input Threshold Voltage vs. V_{CC} (Reset Pin as I/O, Read as '1')




Figure 3-78. V_{IL} : Input Threshold Voltage vs. V_{CC} (Reset Pin as I/O, Read as '0')





Figure 3-79. $V_{IH}-V_{IL}$: Input Hysteresis vs. V_{CC} (Reset Pin as I/O)



3.2.8 BOD, Bandgap and Reset

Figure 3-80. BOD Threshold vs. Temperature (BODLEVEL = 4.3V)




Figure 3-81. BOD Threshold vs. Temperature (BODLEVEL = 2.7V)




Figure 3-82. BOD Threshold vs. Temperature (BODLEVEL = 1.8V)




Figure 3-83. Bandgap Voltage vs. Temperature ($V_{CC} = 5V$)




Figure 3-84. V_{IH} : Input Threshold Voltage vs. V_{CC} (Reset Pin, Read as '1')




Figure 3-85. V_{IL} : Input Threshold Voltage vs. V_{CC} (Reset Pin, Read as '0')




Figure 3-86. $V_{IH}-V_{IL}$: Input Hysteresis vs. V_{CC} (Reset Pin)






Figure 3-87. Minimum Reset Pulse Width vs. V_{CC}



3.2.9 Analog Comparator Offset

Figure 3-88. Analog Comparator Offset ($V_{CC} = 5V$)



3.2.10 Internal Oscillator Speed

Figure 3-89. Watchdog Oscillator Frequency vs. V_{CC}




Figure 3-90. Watchdog Oscillator Frequency vs. Temperature




Figure 3-91. Calibrated 8 MHz RC Oscillator Frequency vs. Temperature





Figure 3-92. Calibrated 8 MHz RC Oscillator Frequency vs. OSCCAL Value



3.3 ATtiny84A

3.3.1 Current Consumption in Active Mode

Figure 3-93. Active Supply Current vs. V_{CC} (Internal RC Oscillator, 8 MHz)




Figure 3-94. Active Supply Current vs. V_{CC} (Internal RC Oscillator, 1 MHz)





Figure 3-95. Active Supply Current vs. V_{CC} (Internal RC Oscillator, 128 kHz)



3.3.2 Current Consumption in Idle Mode

Figure 3-96. Idle Supply Current vs. V_{CC} (Internal RC Oscillator, 8 MHz)




Figure 3-97. Idle Supply Current vs. V_{CC} (Internal RC Oscillator, 1 MHz)





Figure 3-98. Idle Supply Current vs. V_{CC} (Internal RC Oscillator, 128 kHz)



3.3.3 Current Consumption in Power-down Mode

Figure 3-99. Power-down Supply Current vs. V_{CC} (Watchdog Timer Disabled)





Figure 3-100. Power-down Supply Current vs. V_{CC} (Watchdog Timer Enabled)



3.3.4 Current Consumption of Peripheral Units

Figure 3-101. Programming Current vs. V_{CC}





Figure 3-102. Brownout Detector Current vs. V_{CC} (BOD Level = 1.8V)



3.3.5 Pull-up Resistors

Figure 3-103. Pull-up Resistor Current vs. Input Voltage (I/O Pin, $V_{CC} = 1.8V$)




Figure 3-104. Pull-up Resistor Current vs. Input Voltage (I/O Pin, $V_{CC} = 2.7V$)




Figure 3-105. Pull-up Resistor Current vs. Input Voltage (I/O Pin, $V_{CC} = 5V$)




Figure 3-106. Reset Pull-up Resistor Current vs. Reset Pin Voltage ($V_{CC} = 1.8V$)




Figure 3-107. Reset Pull-up Resistor Current vs. Reset Pin Voltage ($V_{CC} = 2.7V$)





Figure 3-108. Reset Pull-up Resistor Current vs. Reset Pin Voltage ($V_{CC} = 5V$)



3.3.6 Output Driver Strength

Figure 3-109. V_{OL} : Output Voltage vs. Sink Current (I/O Pin, $V_{CC} = 3V$)




Figure 3-110. V_{OL} : Output Voltage vs. Sink Current (I/O Pin, $V_{CC} = 5V$)




Figure 3-111. V_{OH} : Output Voltage vs. Source Current (I/O Pin, $V_{CC} = 3V$)




Figure 3-112. V_{OH} : Output Voltage vs. Source Current (I/O Pin, $V_{CC} = 5V$)




Figure 3-113. V_{OL} : Output Voltage vs. Sink Current (Reset Pin as I/O, $V_{CC} = 3V$)




Figure 3-114. V_{OL} : Output Voltage vs. Sink Current (Reset Pin as I/O, $V_{CC} = 5V$)




Figure 3-115. V_{OH} : Output Voltage vs. Source Current (Reset Pin as I/O, $V_{CC} = 3V$)





Figure 3-116. V_{OH} : Output Voltage vs. Source Current (Reset Pin as I/O, $V_{CC} = 5V$)



3.3.7 Input Threshold and Hysteresis (for I/O Ports)

Figure 3-117. V_{IH} : Input Threshold Voltage vs. V_{CC} (I/O Pin, Read as '1')




Figure 3-118. V_{IL} : Input Threshold Voltage vs. V_{CC} (I/O Pin, Read as '0')




Figure 3-119. $V_{IH}-V_{IL}$: Input Hysteresis vs. V_{CC} (I/O Pin)




Figure 3-120. V_{IH} : Input Threshold Voltage vs. V_{CC} (Reset Pin as I/O, Read as '1')




Figure 3-121. V_{IL} : Input Threshold Voltage vs. V_{CC} (Reset Pin as I/O, Read as '0')





Figure 3-122. $V_{IH}-V_{IL}$: Input Hysteresis vs. V_{CC} (Reset Pin as I/O)



3.3.8 BOD, Bandgap and Reset

Figure 3-123. BOD Threshold vs. Temperature (BODLEVEL = 4.3V)




Figure 3-124. BOD Threshold vs. Temperature (BODLEVEL = 2.7V)




Figure 3-125. Bandgap Voltage vs. Temperature ($V_{CC} = 5V$)




Figure 3-126. V_{IH} : Input Threshold Voltage vs. V_{CC} (Reset Pin, Read as '1')




Figure 3-127. V_{IL} : Input Threshold Voltage vs. V_{CC} (Reset Pin, Read as '0')




Figure 3-128. $V_{IH}-V_{IL}$: Input Hysteresis vs. V_{CC} (Reset Pin)






Figure 3-129. Minimum Reset Pulse Width vs. V_{CC}



3.3.9 Analog Comparator Offset

Figure 3-130. Analog Comparator Offset ($V_{CC} = 5V$)



3.3.10 Internal Oscillator Speed

Figure 3-131. Watchdog Oscillator Frequency vs. V_{CC}




Figure 3-132. Watchdog Oscillator Frequency vs. Temperature




Figure 3-133. Calibrated 8 MHz RC Oscillator Frequency vs. V_{CC}




Figure 3-134. Calibrated 8 MHz RC Oscillator Frequency vs. Temperature





Figure 3-135. Calibrated 8 MHz RC Oscillator Frequency vs. OSCCAL Value



4. Ordering Information

4.1 ATtiny24A

Speed (MHz) ⁽¹⁾	Supply Voltage (V)	Temperature Range	Package ⁽²⁾	Ordering Code ⁽³⁾
20	1.8 – 5.5V	Industrial (-40°C to +125°C)	14S1	ATtiny24A-SSF
				ATtiny24A-SSFR
			20M1	ATtiny24A-MF
				ATtiny24A-MFR
			20M2	ATtiny24A-MM8
				ATtiny24A-MM8R

- Notes:
- For speed vs. supply voltage, see section [2.3 "Speed" on page 4](#).
 - All packages are Pb-free, halide-free and fully green and they comply with the European directive for Restriction of Hazardous Substances (RoHS).
 - Code indicators:
 - F: matte tin
 - R: tape & reel

Package Type	
14S1	14-lead, 0.150" Wide Body, Plastic Gull Wing Small Outline Package (SOIC)
20M1	20-pad, 4 x 4 x 0.8 mm Body, Quad Flat No Lead / Micro Lead Frame Package (QFN/MLF)
20M2	20-pad, 3 x 3 x 0.85 mm Body, Very Thin Quad Flat No Lead Package (VQFN)

4.2 ATtiny44A

Speed (MHz) ⁽¹⁾	Supply Voltage (V)	Temperature Range	Package ⁽²⁾	Ordering Code ⁽³⁾
20	1.8 – 5.5V	Industrial (-40°C to +125°C)	14S1	ATtiny44A-SSF
				ATtiny44A-SSFR
			20M1	ATtiny44A-MF
				ATtiny44A-MFR

- Notes:
- For speed vs. supply voltage, see section [2.3 "Speed" on page 4](#).
 - All packages are Pb-free, halide-free and fully green and they comply with the European directive for Restriction of Hazardous Substances (RoHS).
 - Code indicators:
 - F: matte tin
 - R: tape & reel

Package Type	
14S1	14-lead, 0.150" Wide Body, Plastic Gull Wing Small Outline Package (SOIC)
20M1	20-pad, 4 x 4 x 0.8 mm Body, Quad Flat No Lead / Micro Lead Frame Package (QFN/MLF)



4.3 ATtiny84A

Speed (MHz) ⁽¹⁾	Supply Voltage (V)	Temperature Range	Package ⁽²⁾	Ordering Code ⁽³⁾
20	1.8 – 5.5V	Industrial (-40°C to +125°C)	14S1	ATtiny84A-SSF
				ATtiny84A-SSFR

- Notes:
1. For speed vs. supply voltage, see section [2.3 "Speed" on page 4](#).
 2. All packages are Pb-free, halide-free and fully green and they comply with the European directive for Restriction of Hazardous Substances (RoHS).
 3. Code indicators:
 - F: matte tin
 - R: tape & reel

Package Type	
14S1	14-lead, 0.150" Wide Body, Plastic Gull Wing Small Outline Package (SOIC)

5. Revision History

Revision No.	History
8183A: Appendix B–AVR–12/10	Initial revision
8183D: Appendix B–AVR–08/11	Added tape&reel order codes
8183E: Appendix B–AVR–01/12	Added ATtiny84A
8183F: Appendix B–AVR–06/12	Updated order codes for ATtiny24A



Headquarters

Atmel Corporation

2325 Orchard Parkway
San Jose, CA 95131
USA
Tel: (+1)(408) 441-0311
Fax: (+1)(408) 487-2600

International

Atmel Asia Limited

Unit 01-5 & 16, 19F
BEA Tower, Millennium City 5
418 Kwun Tong Road
Kwun Tong, Kowloon
HONG KONG
Tel: (+852) 2245-6100
Fax: (+852) 2722-1369

Atmel Munich GmbH

Business Campus
Parking 4
D-85748 Garching b. Munich
GERMANY
Tel: (+49) 89-31970-0
Fax: (+49) 89-3194621

Atmel Japan

9F, Tonetsu Shinkawa Bldg.
1-24-8 Shinkawa
Chuo-ku, Tokyo 104-0033
JAPAN
Tel: (+81)(3) 3523-3551
Fax: (+81)(3) 3523-7581

Product Contact

Web Site

www.atmel.com

Technical Support

avr@atmel.com

Sales Contact

www.atmel.com/contacts

Literature Requests

www.atmel.com/literature

Disclaimer: The information in this document is provided in connection with Atmel products. No license, express or implied, by estoppel or otherwise, to any intellectual property right is granted by this document or in connection with the sale of Atmel products. **EXCEPT AS SET FORTH IN ATMEL'S TERMS AND CONDITIONS OF SALE LOCATED ON ATMEL'S WEB SITE, ATMEL ASSUMES NO LIABILITY WHATSOEVER AND DISCLAIMS ANY EXPRESS, IMPLIED OR STATUTORY WARRANTY RELATING TO ITS PRODUCTS INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTY OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE, OR NON-INFRINGEMENT. IN NO EVENT SHALL ATMEL BE LIABLE FOR ANY DIRECT, INDIRECT, CONSEQUENTIAL, PUNITIVE, SPECIAL OR INCIDENTAL DAMAGES (INCLUDING, WITHOUT LIMITATION, DAMAGES FOR LOSS OF PROFITS, BUSINESS INTERRUPTION, OR LOSS OF INFORMATION) ARISING OUT OF THE USE OR INABILITY TO USE THIS DOCUMENT, EVEN IF ATMEL HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES.** Atmel makes no representations or warranties with respect to the accuracy or completeness of the contents of this document and reserves the right to make changes to specifications and product descriptions at any time without notice. Atmel does not make any commitment to update the information contained herein. Unless specifically provided otherwise, Atmel products are not suitable for, and shall not be used in, automotive applications. Atmel's products are not intended, authorized, or warranted for use as components in applications intended to support or sustain life.

© 2012 Atmel Corporation. All rights reserved.

Atmel®, logo and combinations thereof, and others are registered trademarks or trademarks of Atmel Corporation or its subsidiaries. Other terms and product names may be trademarks of others.