


## Silicon NPN Planar RF Transistor

### Applications

RF-amplifier up to GHz range specially for wide band antenna amplifier.

### Features

- High power gain
- Low noise figure
- High transition frequency



BFR90 Marking

Plastic case (~TO 50)

1= Collector; 2= Base; 3= Emitter

### Absolute Maximum Ratings

Parameters	Symbol	Value	Unit
Collector-base voltage	V <sub>CBO</sub>	20	V
Collector-emitter voltage	V <sub>CEO</sub>	15	V
Emitter-base voltage	V <sub>EBO</sub>	2	V
Collector current	I <sub>C</sub>	30	mA
Total power dissipation    T <sub>amb</sub> ≤ 60°C	P <sub>tot</sub>	300	mW
Junction temperature	T <sub>j</sub>	150	°C
Storage temperature range	T <sub>stg</sub>	-65 to +150	°C

### Maximum Thermal Resistance

Parameters	Symbol	Value	Unit
Junction ambient	R <sub>thJA</sub>	300	K/W

**Electrical DC Characteristics** $T_j = 25^\circ\text{C}$ , unless otherwise specified

Parameters / Test Conditions	Symbol	Min.	Typ.	Max.	Unit
Collector cut-off current $V_{CB} = 20 \text{ V}, I_E = 0 \text{ A}$	$I_{CBO}$			50	nA
Collector-base breakdown voltage $I_C = 10 \mu\text{A}$	$V_{(\text{BR})\text{CBO}}$	20			V
Collector-emitter breakdown voltage $I_C = 2 \text{ mA}$	$V_{(\text{BR})\text{CEO}}$	15			V
Emitter-base breakdown voltage $I_E = 10 \mu\text{A}$	$V_{(\text{BR})\text{EBO}}$	2			V
DC forward current transfer ratio $I_C = 14 \text{ mA}, V_{CE} = 10 \text{ V}$	$h_{FE}$	25	50		mA

**Electrical AC Characteristics** $T_{\text{amb}} = 25^\circ\text{C}$ 

Parameters / Test Conditions	Symbol	Min.	Typ.	Max.	Unit
Transition frequency $I_C = 14 \text{ mA}, V_{CE} = 10 \text{ V}, f = 500 \text{ MHz}$	$f_T$		5		GHz
Collector-emitter capacitance $V_{CE} = 10 \text{ V}, f = 1 \text{ MHz}$	$C_{CE}$		0.27		pF
Collector-base capacitance $V_{CB} = 10 \text{ V}, f = 1 \text{ MHz}$	$C_{CB}$		0.36		pF
Emitter-base capacitance $V_{EB} = 0.5 \text{ V}, f = 1 \text{ MHz}$	$C_{EB}$		1.3		pF
Noise figure $I_C = 2 \text{ mA}, V_{CE} = 10 \text{ V}, f = 500 \text{ MHz}, Z_G = 50 \Omega$	$F_e$		2.2		dB
Power gain $I_C = 14 \text{ mA}, V_{CE} = 10 \text{ V}, Z_L = Z_{\text{Lopt}}, f = 500 \text{ MHz}$ $f = 800 \text{ MHz}$	$G_{pe}$ $G_{pe}$		19.5 14		dB dB
Linear output voltage – two tone intermodulation test $I_C = 14 \text{ mA}, V_{CE} = 10 \text{ V}, d_{IM} = 60 \text{ dB}, Z_G = Z_L = 50 \Omega, f_1 = 806 \text{ MHz}, f_2 = 810 \text{ MHz}$	$V_1 = V_2$		100		mV
Third order intercept point $I_C = 14 \text{ mA}, V_{CE} = 10 \text{ V}, f = 800 \text{ MHz}$	$IP_3$		23		dBm

## Common Source S-Parameters

V <sub>CE</sub> /V	I <sub>C</sub> /mA	f/MHz	S <sub>11</sub>		S <sub>21</sub>		S <sub>12</sub>		S <sub>22</sub>		
			LIN MAG	ANG	LIN MAG	ANG	LIN MAG	ANG	LIN MAG	ANG	
				deg		deg		deg		deg	
10	2	2	100	0.84	-25.7	6.21	157.1	0.02	74.8	0.96	-8.3
			300	0.61	-68.0	4.69	123.8	0.05	56.2	0.84	-18.4
			500	0.42	-101.2	3.57	102.1	0.07	49.3	0.75	-22.7
			800	0.28	-147.9	2.53	80.4	0.08	48.1	0.69	-27.8
			1000	0.26	-177.6	2.14	69.5	0.09	50.0	0.67	-31.6
			1200	0.27	156.2	1.84	59.0	0.11	51.9	0.65	-35.6
			1500	0.32	127.9	1.54	46.0	0.13	54.1	0.62	-41.9
			1800	0.39	109.1	1.34	34.2	0.15	55.0	0.59	-48.8
			2000	0.43	98.7	1.24	27.3	0.18	54.2	0.57	-53.8
			100	0.67	-36.6	12.62	146.6	0.02	71.9	0.91	-13.0
	5	5	300	0.36	-83.1	7.54	110.1	0.04	60.7	0.72	-20.7
			500	0.21	-116.9	5.07	91.8	0.06	60.6	0.65	-22.2
			800	0.13	-173.7	3.37	74.5	0.08	61.0	0.61	-26.3
			1000	0.14	153.1	2.78	65.5	0.10	60.5	0.59	-29.8
			1200	0.17	130.1	2.37	56.7	0.12	59.0	0.57	-33.6
			1500	0.23	110.4	1.97	45.3	0.15	56.1	0.54	-39.7
			1800	0.29	97.7	1.71	34.6	0.18	53.1	0.51	-45.7
			2000	0.33	91.2	1.58	28.0	0.20	50.3	0.49	-50.0
			100	0.49	-47.6	18.87	135.7	0.02	71.4	0.83	-16.8
			300	0.19	-93.8	9.12	101.1	0.04	68.0	0.63	-19.6
	10	10	500	0.09	-133.4	5.82	86.1	0.06	68.4	0.58	-20.2
			800	0.07	151.2	3.77	71.2	0.09	66.5	0.56	-24.4
			1000	0.10	124.5	3.09	63.3	0.11	64.3	0.54	-28.2
			1200	0.14	109.4	2.63	55.2	0.13	61.4	0.52	-32.2
			1500	0.19	98.6	2.17	44.7	0.16	56.9	0.49	-38.0
			1800	0.26	90.8	1.89	34.6	0.20	52.4	0.46	-44.1
			2000	0.29	86.0	1.75	28.3	0.22	48.9	0.44	-48.0
			100	0.39	-53.4	21.53	130.3	0.01	72.2	0.79	-17.8
			300	0.13	-98.6	9.58	97.8	0.04	71.0	0.60	-18.5
			500	0.06	-146.3	6.02	84.0	0.06	70.7	0.57	-19.2
	14	14	800	0.07	131.1	3.89	70.0	0.09	67.8	0.55	-23.7
			1000	0.10	113.4	3.18	62.4	0.11	65.3	0.53	-27.4
			1200	0.13	103.2	2.70	54.7	0.14	62.0	0.51	-31.5
			1500	0.19	94.2	2.23	44.3	0.17	57.0	0.48	-37.4
			1800	0.24	89.1	1.93	34.2	0.20	52.3	0.45	-43.3
			2000	0.29	85.3	1.79	28.13	0.22	48.6	0.43	-47.3
5	5	5	100	0.65	-39.9	12.44	145.23	0.02	70.3	0.88	-16.2
			300	0.35	-91.8	7.26	108.30	0.05	58.7	0.65	-25.4
			500	0.22	-130.4	4.85	90.23	0.07	58.5	0.57	-26.9
			800	0.16	177.4	3.22	72.60	0.10	58.2	0.52	-30.6
			1000	0.18	150.9	2.66	63.49	0.12	57.3	0.50	-34.5
			1200	0.21	131.6	2.28	54.46	0.14	55.5	0.47	-38.6
			1500	0.27	112.7	1.89	42.86	0.18	51.9	0.44	-45.2
			1800	0.33	100.1	1.65	31.82	0.21	48.2	0.40	-52.1
			2000	0.37	92.8	1.53	25.204	0.24	45.0	0.38	-56.9

**Common Source S-Parameters**

V <sub>CE</sub> /V	I <sub>C</sub> /mA	f/MHz	S <sub>11</sub>		S <sub>21</sub>		S <sub>12</sub>		S <sub>22</sub>		
			LIN MAG	ANG	LIN MAG	ANG	LIN MAG	ANG	LIN MAG	ANG	
				deg		deg		deg		deg	
5	2	2	100	0.82	-27.87	6.31	155.8	0.03	73.8	0.95	-10.2
			300	0.59	-72.7	4.66	121.6	0.06	54.0	0.80	-22.1
			500	0.41	-107.7	3.49	99.9	0.08	46.7	0.70	-27.0
			800	0.30	-154.9	2.474	78.0	0.10	44.9	0.63	-32.3
			1000	0.29	176.7	2.08	66.9	0.11	46.2	0.60	-36.3
			1200	0.30	153.2	1.80	56.4	0.12	47.6	0.57	-40.6
			1500	0.35	126.8	1.50	43.1	0.15	48.9	0.54	-47.6
			1800	0.41	108.7	1.32	31.2	0.18	49.2	0.50	-55.5
			2000	0.45	99.1	1.22	24.4	0.20	48.0	0.48	-61.1
			100	0.18	-87.0	24.23	118.5	0.01	76.0	0.64	-23.6
	30	30	300	0.10	-163.4	9.42	91.4	0.04	75.5	0.48	-19.7
			500	0.11	157.7	5.83	79.4	0.07	73.0	0.45	-20.4
			800	0.14	127.7	3.73	65.9	0.11	67.9	0.43	-25.3
			1000	0.17	117.0	3.05	58.5	0.14	64.1	0.42	-29.8
			1200	0.20	108.4	2.59	50.7	0.16	59.9	0.40	-34.4
			1500	0.25	100.0	2.14	40.2	0.20	53.9	0.36	-40.8
			1800	0.31	93.2	1.86	29.9	0.23	48.1	0.33	-47.1
			2000	0.35	88.4	1.71	23.8	0.26	43.9	0.30	-51.6
			100	0.26	-71.1	22.95	123.4	0.01	72.4	0.68	-23.9
			300	0.11	-140.3	9.39	93.8	0.04	73.2	0.49	-22.0
	20	20	500	0.09	169.9	5.84	81.1	0.07	71.5	0.46	-22.0
			800	0.13	131.1	3.75	67.3	0.11	66.9	0.43	-26.7
			1000	0.15	117.8	3.07	59.7	0.14	63.3	0.42	-31.0
			1200	0.18	109.5	2.62	51.7	0.16	59.3	0.39	-35.4
			1500	0.24	99.5	2.16	41.1	0.20	53.3	0.36	-41.8
			1800	0.30	93.1	1.87	30.9	0.24	47.7	0.32	-48.1
			2000	0.33	87.9	1.73	24.8	0.26	43.4	0.30	-52.4
			100	0.45	-54.6	18.55	133.7	0.02	70.4	0.79	-21.5
			300	0.19	-112.5	8.73	99.4	0.04	66.6	0.55	-24.7
			500	0.12	-156.4	5.54	84.5	0.07	66.8	0.49	-24.9
	10	10	800	0.12	148.7	3.60	69.5	0.11	64.0	0.46	-28.7
			1000	0.15	129.3	2.96	61.3	0.13	61.4	0.44	-32.8
			1200	0.18	117.0	2.51	53.0	0.16	58.0	0.42	-37.1
			1500	0.24	104.4	2.08	42.1	0.19	52.8	0.38	-43.5
			1800	0.30	94.9	1.82	31.8	0.23	47.7	0.35	-49.9
			2000	0.34	89.5	1.67	25.44	0.25	43.7	0.32	-54.5
			100	0.35	-62.6	20.95	128.4	0.02	71.4	0.73	-23.2
			300	0.14	-124.4	9.11	96.3	0.04	70.1	0.51	-23.7
			500	0.10	-173.0	5.71	82.7	0.07	69.3	0.47	-23.7
			800	0.12	138.3	3.70	68.2	0.11	65.5	0.44	-27.7

**We reserve the right to make changes to improve technical design without further notice.**

Parameters can vary in different applications. All operating parameters must be validated for each customer application by the customer. Should the buyer use TEMIC products for any unintended or unauthorized application, the buyer shall indemnify TEMIC against all claims, costs, damages, and expenses, arising out of, directly or indirectly, any claim of personal damage, injury or death associated with such unintended or unauthorized use.

TEMIC TELEFUNKEN microelectronic GmbH, P.O.B. 3535, D-74025 Heilbronn, Germany  
Telephone: 49 (0)7131 67 2831, Fax Number: 49 (0)7131 67 2423