

124NQ... SERIES

SCHOTTKY RECTIFIER

120 Amp

Major Ratings and Characteristics



Characteristics	124NQ...	Units
$I_{F(AV)}$ Rectangular waveform	120	A
V_{RRM} range	35 to 45	V
I_{FSM} @ $t_p = 5 \mu s$ sine	27,000	A
V_F @ 120Apk, $T_J = 100^\circ C$	0.52	V
T_J range	-55 to 125	$^\circ C$

Description/Features

The 124NQ high current Schottky rectifier modules have been optimized for extremely low forward voltage drop, with higher leakage. The proprietary barrier technology allows for reliable operation up to $125^\circ C$ junction temperature. Typical applications are in switching power supplies, converters, free-wheeling diodes, welding, and reverse battery protection.

- $125^\circ C$ T_J operation
- Unique high power Half Pak module
- High purity, high temperature epoxy encapsulation for enhanced mechanical strength and moisture resistance
- Extremely low forward voltage drop
- High frequency operation
- Guard ring enhanced ruggedness and long term reliability

CASE STYLE AND DIMENSIONS



Outline HALF PAK Module

Dimensions in millimeters and inches

Voltage Ratings

Part number	124NQ035	124NQ040	124NQ045
V_R Max. DC Reverse Voltage (V)	35	40	45
V_{RWM} Max. Working Peak Reverse Voltage (V)			

Absolute Maximum Ratings

Parameters	124NQ	Units	Conditions
$I_{F(AV)}$ Max. Average Forward Current * See Fig. 5	120	A	50% duty cycle @ $T_C = 76^\circ\text{C}$, rectangular wave form
I_{FSM} Max. Peak One Cycle Non-Repetitive Surge Current * See Fig. 7	27,000	A	5 μs Sine or 3 μs Rect. pulse
	2400		10ms Sine or 6ms Rect. pulse
E_{AS} Non-Repetitive Avalanche Energy	135	mJ	$T_J = 25^\circ\text{C}$, $I_{AS} = 20$ Amps, $L = 0.67$ mH
I_{AR} Repetitive Avalanche Current	20	A	Current decaying linearly to zero in 1 μsec Frequency limited by T_J max. $V_A = 1.5 \times V_R$ typical

Electrical Specifications

Parameters	124NQ	Units	Conditions
V_{FM} Max. Forward Voltage Drop (1) * See Fig. 1	0.54	V	@ 120A
	0.71	V	@ 240A
	0.52	V	@ 120A
	0.71	V	@ 240A
I_{RM} Max. Reverse Leakage Current (1) * See Fig. 2	10	mA	$T_J = 25^\circ\text{C}$
	1200	mA	$T_J = 125^\circ\text{C}$
C_T Max. Junction Capacitance	5200	pF	$V_R = 5V_{DC}$, (test signal range 100Khz to 1Mhz) 25°C
L_S Typical Series Inductance	7.0	nH	From top of terminal hole to mounting plane
dv/dt Max. Voltage Rate of Change (Rated V_R)	10,000	V/ μs	

(1) Pulse Width < 300 μs , Duty Cycle < 2%

Thermal-Mechanical Specifications

Parameters			124NQ	Units	Conditions
T _j	Max. Junction Temperature Range		-55 to 125	°C	
T _{stg}	Max. Storage Temperature Range		-55 to 125	°C	
R _{thJC}	Max. Thermal Resistance Junction to Case		0.40	°C/W	DC operation * See Fig. 4
R _{thCS}	Typical Thermal Resistance, Case to Heatsink		0.15	°C/W	Mounting surface, smooth and greased
wt	Approximate Weight		25.6 (0.9)	g (oz.)	
T	Mounting Torque	Min.	40 (35)	Kg-cm (lbf-in)	Non-lubricated threads
		Max.	58 (50)		
	Terminal Torque	Min.	58 (50)		
		Max.	86 (75)		
Case Style			HALF PAK Module		




Fig. 1 - Maximum Forward Voltage Drop Characteristics




Fig. 2 - Typical Values of Reverse Current Vs. Reverse Voltage




Fig. 3 - Typical Junction Capacitance Vs. Reverse Voltage




Fig. 4 - Maximum Thermal Impedance Z_{thJC} Characteristics




Fig. 5 - Maximum Allowable Case Temperature Vs. Average Forward Current




Fig. 6 - Forward Power Loss Characteristics




Fig. 7 - Maximum Non-Repetitive Surge Current




Fig. 8 - Unclamped Inductive Test Circuit