

International **IR** Rectifier

85HQ... SERIES

SCHOTTKY RECTIFIER

Amp


Major Ratings and Characteristics

Characteristics	85HQ...	Units
$I_{F(AV)}$ Rectangular waveform	85	A
V_{RRM} range	35 to 45	V
I_{FSM} @ $t_p=5\ \mu s$ sine	9000	A
V_F @ 85 Apk, $T_J=125^\circ C$	0.62	V
T_J range	-65 to 175	°C

Description/Features

The 85HQ Schottky rectifier series has been optimized for low reverse leakage at high temperature. The proprietary barrier technology allows for reliable operation up to $175^\circ C$ junction temperature. Typical applications are in switching power supplies, converters, free-wheeling diodes, and reverse battery protection.

- $175^\circ C T_J$ operation
- Low forward voltage drop
- High frequency operation
- Guard ring for enhanced ruggedness and long term reliability
- Hermetic packaging



Voltage Ratings

Part number	85HQ035	85HQ040	85HQ045
V_R Max. DC Reverse Voltage (V)	35	40	45
V_{RWM} Max. Working Peak Reverse Voltage (V)			

Absolute Maximum Ratings

Parameters	85HQ	Units	Conditions
$I_{F(AV)}$ Max. Average Forward Current * See Fig. 5	85	A	50% duty cycle @ $T_c = 112^\circ\text{C}$, rectangular waveform
I_{FSM} Max. Peak One Cycle Non-Repetitive Surge Current * See Fig. 7	9000	A	5μs Sine or 3μs Rect. pulse
	1130		10ms Sine or 6ms Rect. pulse
E_{AS} Non-Repetitive Avalanche Energy	114	mJ	$T_j = 25^\circ\text{C}$, $I_{AS} = 17$ Amps, $L = 0.79$ mH
I_{AR} Repetitive Avalanche Current	17	A	Current decaying linearly to zero in 1 μsec Frequency limited by T_j max. $V_A = 1.5 \times V_R$ typical

Electrical Specifications

Parameters	85HQ	Units	Conditions
V_{FM} Max. Forward Voltage Drop (1) * See Fig. 1	0.72	V	$T_j = 25^\circ\text{C}$
	0.89	V	$T_j = 125^\circ\text{C}$
	0.62	V	$T_j = 25^\circ\text{C}$
	0.77	V	$T_j = 125^\circ\text{C}$
I_{RM} Max. Reverse Leakage Current (1) * See Fig. 2	5	mA	$V_R = \text{rated } V_R$
	45	mA	$T_j = 125^\circ\text{C}$
C_T Max. Junction Capacitance	2600	pF	$V_R = 5V_{DC}$, (test signal range 100Khz to 1Mhz) 25°C
L_S Typical Series Inductance	7.5	nH	Measured from top of terminal to mounting plane
dv/dt Max. Voltage Rate of Change (Rated V_R)	10,000	V/ μs	

(1) Pulse Width < 300μs, Duty Cycle < 2%

Thermal-Mechanical Specifications

Parameters	85HQ	Units	Conditions
T_j Max. Junction Temperature Range	-65 to 175	°C	
T_{stg} Max. Storage Temperature Range	-65 to 175	°C	
R_{thJC} Max. Thermal Resistance Junction to Case	0.83	°C/W	DC operation * See Fig. 4
R_{thCS} Typical Thermal Resistance, Case to Heatsink	0.25	°C/W	Mounting surface, smooth and greased
wt Approximate Weight	15(0.53)	g(oz.)	
T Mounting Torque	Min.	23(20)	Kg-cm (lbf-in)
	Max.	46(40)	
Case Style	DO-203AB(DO-5)	JEDEC	




Fig. 1-Maximum Forward Voltage Drop Characteristics




Fig. 2-Typical Values Of Reverse Current
Vs. Reverse Voltage




Fig. 3-Typical Junction Capacitance
Vs. Reverse Voltage




Fig. 4-Maximum Thermal Impedance Z_{thJC} Characteristics




Fig.5-Maximum Allowable Case Temperature Vs. Average Forward Current




Fig.6-Forward Power Loss Characteristics




Fig.7-Maximum Non-Repetitive Surge Current




Fig.8-Unclamped Inductive Test Circuit