

HEXFRED™ ULTRA FAST, SOFT RECOVERY DIODE 1200V, 15A

Major Ratings and Characteristics

Characteristics		Units
V_{br} (per leg)	1200	V
$I_F(AV)$	15	A
t_{rr} (per leg)	95	ns
Q_{rr} (per leg)	180	nC
I_{RRM} (per leg)	8.0	A
V_F (per leg)	3.3	V

Description

International Rectifier's HFA35HA120C is a state of the art ultra fast recovery diode. Employing the latest in epitaxial construction and advanced processing techniques it features a superb combination of characteristics which result in performance which is unsurpassed by any rectifier previously available.

With basic ratings of 1200 volts and 15 amps continuous current, the HFA35HA120C is especially well suited for use as the companion diode for IGBTs and MOSFETs. In addition to ultra fast recovery time, the HEXFRED product line features extremely low values of peak recovery current (I_{RRM}) and does not exhibit any tendency to "snap-off" during the t_p portion of recovery.

Features:

- Ultrafast Recovery
- Ultra Soft Recovery
- Very Low I_{RRM}
- Very Low Q_{rr}
- Guaranteed Avalanche
- Specified at Operating Conditions
- Hermetic
- Center Tap



Benefits:

- Reduced RFI and EMI
- Reduced Power Loss in Diode and Switching Transistor
- Higher Frequency Operation
- Reduced Snubbing
- Reduced Parts Count

The HEXFRED features combine to offer designers a rectifier with lower noise and significantly lower switching losses in both the diode and the switching transistor. These HEXFRED advantages can help to significantly reduce snubbing, component count and heatsink sizes.

The HEXFRED HFA35HA120C is ideally suited for applications in power supplies and power conversion systems (such as inverters, converters, UPS systems, and power factor correction circuits), motor drives, and many other similar applications where high speed, high efficiency rectification is needed.

CASE STYLE AND DIMENSIONS



Conforms to JEDEC Outline TO-204AE (Modified TO-3)
Dimensions in Millimeters and (Inches)

Voltage Ratings: $T_J = 25 - 150^{\circ}\text{C}$

Parameter			Units	
V_{br} (per leg)	Max D.C. Reverse Voltage (V)	1200	V	70K ft, $I_R < 25\mu\text{A}$
V_{ISO} (per leg)	Max PK Repetitive Reverse Voltage (V)	600		

Absolute Maximum Ratings

Parameter		Min	Typ	Max	Units	Conditions
I_F (AV)	Max Average Forward Current	—	—	15	A	$T_C = 100^{\circ}\text{C}$, d.c. = 50%, rect. wave $V_R = 0.8 V_{RRM}$
I_{FSM} (per leg)	Max Single Pulse Forward Current	—	—	130		$T_C = 25^{\circ}\text{C}$, 1/2 Sine Wave, 60 Hz P.W. = 833 ms
I_{AS}	Max Single Pulse Avalanche Current	—	—	2		$L = 100 \mu\text{H}$

Electrical Specifications: $T_J = 25^{\circ}\text{C}$ unless otherwise specified

Parameter		Min	Typ	Max	Units	Conditions
V_{FM} (per leg)	Max Forward Voltage	—	—	3.3	V	$I_F = 7\text{A}$
		—	—	4.3		$I_F = 15\text{A}$
		—	—	3.1		$I_F = 15\text{A}$, $T_J = 125^{\circ}\text{C}$
I_{RM} (per leg)	Max Reverse Leakage Current	—	—	20	μA	$V_R = V_R$ Rated
		—	—	1.0	mA	$T_J = 125^{\circ}\text{C}$, $V_R = 0.8 \times V_R$ Rated
C_T (per leg)	Junction Capacitance	—	—	20	pF	$V_R = 200\text{V}$
L_S	Internal Source Inductance	—	13	—	nH	Measured lead to lead 5mm from package body

Dynamic Recovery Specifications: $T_J = 25^{\circ}\text{C}$ unless otherwise specified

Parameter		Min	Typ	Max	Units	Conditions
t_{rr} (per leg)	Reverse Recovery Time	—	—	95	ns	$I_F = 7.0\text{A}$, $di/dt \leq 200\text{A}/\mu\text{s}$, $V_R = 200\text{V}$
I_{RRM} (per leg)	Max Reverse Recovery Current	—	—	8.0	A	$I_F = 7.0\text{A}$, $di/dt \leq 200\text{A}/\mu\text{s}$, $V_R = 200\text{V}$
Q_{RR} (per leg)	Reverse Recovered Charge	—	—	380	nC	$I_F = 7.0\text{A}$, $di/dt \leq 200\text{A}/\mu\text{s}$, $V_R = 200\text{V}$

Thermal-Mechanical Specifications

Parameter		Min	Typ	Max	Units	Conditions
T_J, T_{STG}	Junction and Storage Temp Range	-55	—	150	$^{\circ}\text{C}$	
$R_{\theta JC}$	Thermal Resistance; Junction to Case	—	—	2.00	K/W	
W_T	Weight	—	11.5	—	g	
Case	TO-204AA	—	JEDEC	—		