


## HEXFET® Power MOSFET

- Isolated Package
- High Voltage Isolation = 2.5KVRMS ⑥
- Sink to Lead Creepage Dist.= 4.8mm
- Dynamic dv/dt Rating
- Low Thermal Resistance




$V_{DSS} = 600V$   
 $R_{DS(on)} = 1.2\Omega$   
 $I_D = 3.5A$

### Description

Third Generation HEXFETs from International Rectifier provide the designer with the best combination of fast switching, ruggedized device design, low on-resistance and cost-effectiveness.

The TO-220 Fullpak eliminates the need for additional insulating hardware in commercial-industrial applications. The moulding compound used provides a high isolation capability and a low thermal resistance between the tab and external heatsink. This isolation is equivalent to using a 100 micron mica barrier with standard TO-220 product. The Fullpak is mounted to a heatsink using a single clip or by a single screw fixing.



DATA SHEETS

### Absolute Maximum Ratings

|                           | Parameter  | Max.                  | Units             |
|---------------------------|--|-----------------------|-------------------|
| $I_D @ T_C = 25^\circ C$  | Continuous Drain Current, $V_{GS} @ 10 V$        | 3.5                   |                   |
| $I_D @ T_C = 100^\circ C$ | Continuous Drain Current, $V_{GS} @ 10 V$        | 2.2                   | A                 |
| $I_{DM}$                  | Pulsed Drain Current ①                           | 14                    |                   |
| $P_D @ T_C = 25^\circ C$  | Power Dissipation                                | 40                    | W                 |
|                           | Linear Derating Factor                           | 0.32                  | W/ <sup>o</sup> C |
| $V_{GS}$                  | Gate-to-Source Voltage                           | $\pm 20$              | V                 |
| $E_{AS}$                  | Single Pulse Avalanche Energy ②                  | 500                   | mJ                |
| $I_{AR}$                  | Avalanche Current ①                              | 3.5                   | A                 |
| $E_{AR}$                  | Repetitive Avalanche Energy ①                    | 4.0                   | mJ                |
| $dv/dt$                   | Peak Diode Recovery $dv/dt$ ③                    | 3.0                   | V/ns              |
| $T_J$<br>$T_{STG}$        | Operating Junction and Storage Temperature Range | -55 to +150           | $^\circ C$        |
|                           | Soldering Temperature, for 10 seconds            | 300 (1.6mm from case) |                   |
|                           | Mounting Torque, 6-32 or M3 screw                | 10 lbf-in (1.1 N·m)   |                   |

### Thermal Resistance

|           | Parameter           | Min. | Typ. | Max. | Units        |
|-----------|---------------------|------|------|------|--------------|
| $R_{J/C}$ | Junction-to-Case    | —    | —    | 3.1  | $^\circ C/W$ |
| $R_{J/A}$ | Junction-to-Ambient | —    | —    | 65   |              |

Electrical Characteristics @  $T_J = 25^\circ\text{C}$  (unless otherwise specified)

|                                 | Parameter                            | Min. | Typ. | Max. | Units               | Test Conditions   |
|---------------------------------|--------------------------------------|------|------|------|---------------------|---|
| $V_{(BR)DSS}$                   | Drain-to-Source Breakdown Voltage    | 600  | —    | —    | V                   | $V_{GS}=0\text{V}$ , $I_D = 250\mu\text{A}$                                     |
| $\Delta V_{(BR)DSS}/\Delta T_J$ | Breakdown Voltage Temp. Coefficient  | —    | 0.70 | —    | V/ $^\circ\text{C}$ | Reference to $25^\circ\text{C}$ , $I_D = 1\text{mA}$                            |
| $R_{DS(on)}$                    | Static Drain-to-Source On-Resistance | —    | —    | 1.2  | $\Omega$            | $V_{GS}=0\text{V}$ , $I_D=2.1\text{A}$ ④  |
| $V_{GS(th)}$                    | Gate Threshold Voltage               | 2.0  | —    | 4.0  | V                   | $V_{DS}=V_{GS}$ , $I_D = 250\mu\text{A}$  |
| $g_{fs}$                        | Forward Transconductance             | 4.9  | —    | —    | S                   | $V_{DS}=50\text{V}$ , $I_D=2.1\text{A}$ ④                                       |
| $I_{loss}$                      | Drain-to-Source Leakage Current      | —    | —    | 100  | $\mu\text{A}$       | $V_{DS}=600\text{V}$ , $V_{GS}=0\text{V}$                                       |
|                                 |                                      | —    | —    | 500  | $\mu\text{A}$       | $V_{DS}=480\text{V}$ , $V_{GS}=0\text{V}$ , $T_J=125^\circ\text{C}$             |
| $I_{GSS}$                       | Gate-to-Source Forward Leakage       | —    | —    | 100  | nA                  | $V_{GS}=20\text{V}$   |
|                                 | Gate-to-Source Reverse Leakage       | —    | —    | 100  | nA                  | $V_{GS}=-20\text{V}$  |
| $Q_g$                           | Total Gate Charge                    | —    | —    | 60   | nC                  | $I_D=6.2\text{A}$   |
| $Q_{gs}$                        | Gate-to-Source Charge                | —    | —    | 8.3  |                     | $V_{DS}=360\text{V}$  |
| $Q_{gd}$                        | Gate-to-Drain ("Miller") Charge      | —    | —    | 30   |                     | $V_{GS}=10\text{V}$ See Fig. 6 and 13 ④   |
| $t_{d(on)}$                     | Turn-On Delay Time                   | —    | 13   | —    | ns                  | $V_{DD}=300\text{V}$  |
| $t_r$                           | Rise Time                            | —    | 18   | —    |                     | $I_D=6.2\text{A}$   |
| $t_{d(off)}$                    | Turn-Off Delay Time                  | —    | 55   | —    |                     | $R_G=9.1\Omega$   |
| $t_f$                           | Fall Time                            | —    | 20   | —    |                     | $R_D=47\Omega$ See Figure 10 ④  |
| $L_D$                           | Internal Drain Inductance            | —    | 4.5  | —    | nH                  | Between lead,<br>6 mm (0.25in.)<br>from package<br>and center of<br>die contact |
| $L_s$                           | Internal Source Inductance           | —    | 7.5  | —    |                     |   |
| $C_{iss}$                       | Input Capacitance                    | —    | 1300 | —    | pF                  | $V_{GS}=0\text{V}$  |
| $C_{oss}$                       | Output Capacitance                   | —    | 160  | —    |                     | $V_{DS}=25\text{V}$   |
| $C_{rss}$                       | Reverse Transfer Capacitance         | —    | 30   | —    |                     | $f=1.0\text{MHz}$ See Figure 5  |
| $C$                             | Drain to Sink Capacitance            | —    | 12   | —    | pF                  | $f=1.0\text{MHz}$   |



## Source-Drain Ratings and Characteristics

|          | Parameter                                 | Min.  | Typ. | Max. | Units         | Test Conditions   |
|----------|---|---|------|------|---------------|---|
| $I_S$    | Continuous Source Current<br>(Body Diode) | —   | —    | 3.5  | A             | MOSFET symbol<br>showing the<br>integral reverse<br>p-n junction diode. |
| $I_{SM}$ | Pulsed Source Current<br>(Body Diode) ①   | —   | —    | 14   |               |   |
| $V_{SD}$ | Diode Forward Voltage                     | —   | —    | 1.5  |               |   |
| $t_{rr}$ | Reverse Recovery Time                     | —   | 470  | 940  | ns            | $T_J=25^\circ\text{C}$ , $I_F=6.2\text{A}$                              |
| $Q_{rr}$ | Reverse Recovery Charge                   | —   | 4.0  | 7.9  | $\mu\text{C}$ | $di/dt=100\text{A}/\mu\text{s}$ ④                                       |
| $t_{on}$ | Forward Turn-On Time                      | Intrinsic turn-on time is negligible (turn-on is dominated by $L_s+L_D$ ) |      |      |               |   |



## Notes:


① Repetitive rating; pulse width limited by max. junction temperature (See Figure 11)

③  $I_{SD}\leq 6.2\text{A}$ ,  $di/dt\leq 80\text{A}/\mu\text{s}$ ,  $V_{DD}\leq V_{(BR)DSS}$ ,  $T_J\leq 150^\circ\text{C}$


⑤  $t=60\text{s}$ ,  $f=60\text{Hz}$

②  $V_{DD}=50\text{V}$ , starting  $T_J=25^\circ\text{C}$ ,  $L=74\text{mH}$   
 $R_G=25\Omega$ ,  $I_{AS}=3.5\text{A}$  (See Figure 12)


④ Pulse width  $\leq 300\ \mu\text{s}$ ; duty cycle  $\leq 2\%$ .




**Fig 1.** Typical Output Characteristics,  
 $T_C = 25^\circ\text{C}$




**Fig 2.** Typical Output Characteristics,  
 $T_C = 150^\circ\text{C}$




**Fig 3.** Typical Transfer Characteristics




**Fig 4.** Normalized On-Resistance  
Vs. Temperature




**Fig 5.** Typical Capacitance Vs.  
Drain-to-Source Voltage



**Fig 6.** Typical Gate Charge Vs.  
Gate-to-Source Voltage



**Fig 7.** Typical Source-Drain Diode  
Forward Voltage



**Fig 8.** Maximum Safe Operating Area




Fig 9. Maximum Drain Current Vs. Case Temperature




Fig 10a. Switching Time Test Circuit




Fig 10b. Switching Time Waveforms







Fig 11. Maximum Effective Transient Thermal Impedance, Junction-to-Case




**Fig 12a.** Unclamped Inductive Test Circuit




**Fig 12b.** Unclamped Inductive Waveforms



**Fig 12c.** Maximum Avalanche Energy Vs. Drain Current



**Fig 13a.** Basic Gate Charge Waveform



**Fig 13b.** Gate Charge Test Circuit

**Appendix A:** Figure 14, Peak Diode Recovery dv/dt Test Circuit – See page 1505

**Appendix B:** Package Outline Mechanical Drawing – See page 1510

**Appendix C:** Part Marking Information – See page 1517

**International**  
**IR** Rectifier