

International  
**IR** Rectifier

**Ultrafast Rectifier**

**MUR1620CT**  
**MURB1620CT**  
**MURB1620CT-1**

**Features**

- Ultrafast Recovery Time
- Low Forward Voltage Drop
- Low Leakage Current
- 175°C Operating Junction Temperature

$$\begin{aligned} t_{rr} &= 25\text{ns} \\ I_{F(AV)} &= 16\text{Amp} \\ V_R &= 200\text{V} \end{aligned}$$

**Description/Applications**

International Rectifier's MUR.. series are the state of the art Ultra fast recovery rectifiers specifically designed with optimized performance of forward voltage drop and ultra fast recovery time.

The planar structure and the platinum doped life time control, guarantee the best overall performance, ruggedness and reliability characteristics.


These devices are intended for use in the output rectification stage of SMPS, UPS, DC-DC converters as well as free-wheeling diode in low voltage inverters and chopper motor drives.

Their extremely optimized stored charge and low recovery current minimize the switching losses and reduce over dissipation in the switching element and snubbers.


**Absolute Maximum Ratings**

Parameters		Max	Units
$V_{RRM}$	Peak Repetitive Peak Reverse Voltage	200	V
$I_{F(AV)}$	Average Rectified Forward Current Per Leg Total Device, (Rated $V_R$ ), $T_C = 150^\circ\text{C}$	8.0 16	A
$I_{FSM}$	Non Repetitive Peak Surge Current Per Leg	100	
$I_{FM}$	Peak Repetitive Forward Current (Rated $V_R$ , Square wave, 20 KHz), $T_C = 150^\circ\text{C}$	16	
$T_J, T_{STG}$	Operating Junction and Storage Temperatures	-65 to 175	°C

**Case Styles**



TO-220AB



D<sup>2</sup>PAK



TO-262

MUR1620CT, MURB1620CT, MURB1620CT-1

Bulletin PD-20718 rev. B 01/01

 International  
 Rectifier

**Electrical Characteristics @  $T_J = 25^\circ\text{C}$  (unless otherwise specified)**

Parameters		Min	Typ	Max	Units	Test Conditions
V <sub>BR</sub> , V <sub>r</sub>	Breakdown Voltage, Blocking Voltage	200	-	-	V	I <sub>R</sub> = 100µA
V <sub>F</sub>	Forward Voltage	-	-	0.975	V	I <sub>F</sub> = 8A
		-	-	0.895	V	I <sub>F</sub> = 8A, T <sub>J</sub> = 150°C
I <sub>R</sub>	Reverse Leakage Current	-	-	5	µA	V <sub>R</sub> = V <sub>R</sub> Rated
		-	-	250	µA	T <sub>J</sub> = 150°C, V <sub>R</sub> = V <sub>R</sub> Rated
C <sub>T</sub>	Junction Capacitance	-	25	-	pF	V <sub>R</sub> = 200V
L <sub>S</sub>	Series Inductance	-	8.0	-	nH	Measured lead to lead 5mm from package body


**Dynamic Recovery Characteristics @  $T_J = 25^\circ\text{C}$  (unless otherwise specified)**

Parameters		Min	Typ	Max	Units	Test Conditions
t <sub>rr</sub>	Reverse Recovery Time	-	-	35	ns	I <sub>F</sub> = 1.0A, dI <sub>F</sub> /dt = 50A/µs, V <sub>R</sub> = 30V
		-	-	25		I <sub>F</sub> = 0.5A, I <sub>R</sub> = 1.0A, I <sub>REC</sub> = 0.25A
		-	20	-		T <sub>J</sub> = 25°C
		-	34	-		T <sub>J</sub> = 125°C
I <sub>RRM</sub>	Peak Recovery Current	-	1.7	-	A	T <sub>J</sub> = 25°C
		-	4.2	-		T <sub>J</sub> = 125°C
Q <sub>rr</sub>	Reverse Recovery Charge	-	23	-	nC	T <sub>J</sub> = 25°C
		-	75	-		T <sub>J</sub> = 125°C


**Thermal - Mechanical Characteristics**

Parameters				Min	Typ	Max	Units	
T <sub>J</sub>	Max. Junction Temperature Range			-	-	-65 to 175	°C	
T <sub>Stg</sub>	Max. Storage Temperature Range			-	-	-65 to 175		
R <sub>thJC</sub>	Thermal Resistance, Junction to Case	Per Leg		-	-	3.0	°C/W	
R <sub>thJA</sub> <sup>①</sup>	Thermal Resistance, Junction to Ambient	Per Leg		-	-	50		
R <sub>thCS</sub> <sup>②</sup>	Thermal Resistance, Case to Heatsink			-	0.5	-		
Wt	Weight			-	2.0	-	g	
				-	0.07	-	(oz)	
Mounting Torque				6.0	-	12	Kg-cm	
				5.0	-	10	lbf.in	


<sup>①</sup> Typical Socket Mount<sup>②</sup> Mounting Surface, Flat, Smooth and Greased




**Fig.1-Typical Forward Voltage Drop Characteristics**




**Fig.2-Typical Values Of Reverse Current Vs. Reverse Voltage**




**Fig.3-Typical Junction Capacitance Vs. Reverse Voltage**




**Fig.4-Max. Thermal Impedance  $Z_{thJC}$  Characteristics**




**Fig. 5 - Max. Allowable Case Temperature Vs. Average Forward Current**



**Fig. 6 -Forward Power Loss Characteristics**




**Fig. 7 -Typical Reverse Recovery vs. di<sub>F</sub>/dt**




**Fig. 8 -Typical Stored Charge vs. di<sub>F</sub>/dt**

(3) Formula used:  $T_C = T_J - (P_d + P_{d_{REV}}) \times R_{thJC}$ ;  
 $P_d = \text{Forward Power Loss} = I_{F(AV)} \times V_{FM} @ (I_{F(AV)} / D)$  (see Fig. 6);  
 $P_{d_{REV}} = \text{Inverse Power Loss} = V_{R1} \times I_R (1 - D)$ ;  $I_R @ V_{R1} = \text{rated } V_R$





**Fig. 9- Reverse Recovery Parameter Test Circuit**




**Fig. 10 - Reverse Recovery Waveform and Definitions**

### Outline Table



### Outline Table



### Ordering Information Table

Device Code					
MUR	B	16	20	CT	-1
(1)	(2)	(3)	(4)	(5)	(6)
<b>1</b>	- Ultrafast MUR Series				
<b>2</b>	- B = D <sup>2</sup> Pak / TO-262				
	None = TO-220AB				
<b>3</b>	- Current Rating (16 = 16A)				
<b>4</b>	- Voltage Rating (20 = 200V)				
<b>5</b>	- CT = Center Tap (Dual) TO-220/D <sup>2</sup> PAK/TO-262				
<b>6</b>	- "-1" = TO-262 Option				

MUR1620CT, MURB1620CT, MURB1620CT-1

Bulletin PD-20718 rev. B 01/01

---

International  
**IR** Rectifier

International  
**IR** Rectifier

**IR WORLD HEADQUARTERS:** 233 Kansas St., El Segundo, California 90245, USA Tel: (310) 252-7105  
TAC Fax: (310) 252-7309  
Visit us at [www.irf.com](http://www.irf.com) for sales contact information. 01/01