

**CERAMIC HOUSING**

16.5 (0.65) MAX.

8.5 (0.33) DIA.

4.3 (0.17) DIA.

157 (6.18)

170 (6.69)

55 (2.16) MIN.

24 (0.94) MAX.

10 (0.39) MAX.

21 (0.83) MAX.

29.5 (1.16) MAX.

1/2"-20UNF-2A

SW 27

RED SILICON RUBBER

RED CATHODE

RED SHRINK

WHITE GATE

WHITE SHRINK

C.S. 0.4 mm<sup>2</sup> (0.0006 s.i.)

215 (8.46) ± 10 (0.39)

22.5 (0.88) MAX. DIA.

2.6 (0.10) MAX.

9.5 (0.37) MIN.

20 (0.79) MIN.

FLEXIBLE LEAD

C.S. 16mm<sup>2</sup> (.025 s.i.)

Fast-on Terminals

AMP. 280000-1

REF-250

Case Style TO-209AC (TO-94)

All dimensions in millimeters (inches)

**CERAMIC HOUSING**

16.5 (0.65) MAX.

8.5 (0.33) DIA.

4.3 (0.17) DIA.

157 (6.18)

170 (6.69)

55 (2.16) MIN.

24 (0.94) MAX.

10 (0.39) MAX.

21 (0.83) MAX.

29.5 (1.16) MAX.

1/2"-20UNF-2A

SW 27

RED SILICON RUBBER

RED CATHODE

RED SHRINK

WHITE GATE

WHITE SHRINK

C.S. 0.4 mm<sup>2</sup> (0.0006 s.i.)

215 (8.46) ± 10 (0.39)

22.5 (0.88) MAX. DIA.

2.6 (0.10) MAX.

9.5 (0.37) MIN.

20 (0.79) MIN.

FLEXIBLE LEAD

C.S. 16mm<sup>2</sup> (.025 s.i.)

Fast-on Terminals

AMP. 280000-1

REF-250

Case Style TO-209AC (TO-94)

All dimensions in millimeters (inches)

