

Description/Features

The SD51 Schottky rectifier has been optimized for very low forward voltage drop, with moderate leakage. The proprietary barrier technology allows for reliable operation up to 150° C junction temperature. Typical applications are in switching power supplies, converters, free-wheeling diodes, and reverse battery protection.

- 150° C T_J operation
- Very low forward voltage drop
- High frequency operation
- Guard ring for enhanced ruggedness and long term reliability
- Hermetic packaging



SD51

PD-2.327 rev. A 12/97

International
IR Rectifier

Voltage Ratings

Part number	SD51
V_R Max. DC Reverse Voltage (V)	35/45 (1)
V_{RWM} Max. Working Peak Reverse Voltage (V)	

(1) For SD51 V_{RWM} and V_{RRM} = 45V @ T_J = 25°C, =35V @ T_J = 150°C

Absolute Maximum Ratings

Parameters	SD51	Units	Conditions
$I_{F(AV)}$ Max. Average Forward Current * See Fig. 5	60	A	50% duty cycle @ T_C = 90°C, rectangular wave form
I_{FSM} Max. Peak One Cycle Non-Repetitive Surge Current * See Fig. 7	800	A	60Hz half cycle sine wave or 5ms rectangular pulse Following any rated load condition and with rated V_{RRM} applied

Electrical Specifications

Parameters	SD51	Units	Conditions
V_{FM} Max. Forward Voltage Drop (2) * See Fig. 1	0.58	V	@ 35A T_J = 25 °C
	0.66	V	@ 60A
	0.86	V	@ 120A
	0.75	V	@ 120A T_J = 150 °C
I_{RM} Max. Reverse Leakage Current (2) * See Fig. 2	50	mA	T_J = 25 °C
	200	mA	T_J = 125 °C V_R = rated V_R
C_T Max. Junction Capacitance	2900	pF	V_R = 5V _{DC} , (test signal range 100Khz to 1Mhz) 25 °C
L_S Typical Series Inductance	7.5	nH	Measured from top of terminal to mounting plane
dv/dt Max. Voltage Rate of Change (Rated V_R)	1000	V/ μ s	

(2) Pulse Width < 300 μ s, Duty Cycle < 2%

Thermal-Mechanical Specifications

Parameters	SD51	Units	Conditions
T_J Max. Junction Temperature Range	-65 to 150	°C	
T_{stg} Max. Storage Temperature Range	-65 to 150	°C	
R_{thJC} Max. Thermal Resistance Junction to Case	1.0	°C/W	DC operation * See Fig. 4
R_{thCS} Typical Thermal Resistance, Case to Heatsink	0.25	°C/W	Mounting surface, smooth and greased
wt Approximate Weight	15(0.53)	g(oz.)	
T Mounting Torque	Min. 23(20)	Kg-cm (lbf-in)	Non-lubricated threads
	Max. 46(40)		
Case Style	DO-203AB(DO-5)		JEDEC

* For Additional Informations and Graphs, Please See the 50HQ Series




Fig. 1 - Maximum Forward Voltage Drop Characteristics




Fig. 2 - Typical Values of Reverse Current Vs. Reverse Voltage




Fig. 3 - Typical Junction Capacitance Vs. Reverse Voltage




Fig. 4 - Maximum Thermal Impedance Z_{thJC} Characteristics




Fig. 5 - Maximum Allowable Case Temperature Vs. Average Forward Current




Fig. 6 - Forward Power Loss Characteristics




Fig. 7 - Max. Non-Repetitive Surge Current