




Telecom IC Navigator

International Rectifier

										
Topology	Operating Voltage Range V(Pk)	Dielectric Strength Input/Output V(rms)	Max On-State Resistance @25°C Ω (AC/DC)	Max Load Current @ 40°C AC/DC (mA)	Nominal Control Current (DC) (mA)	6 pin DIP	SM 6 pin DIP	8 pin DIP	SM 8 pin DIP	8 pin SM Thin Pak
Photovoltaic Relay Single Pole	+250	4000	10/3	190/320	2	PVT312(T)	PVT312S(T)			
			15/4.25	170/300	2	PVT312L(T)	PVT312LS(T)			
	+400	4000	27/7	140/210	3	PVT412(T)	PVT412S(T)			
			35/9	120/200	3	PVT412L(T)	PVT412LS(T)			
			16/7	170/300	3	PVT442(T)	PVT442S(T)			
Double Pole	+250	4000	10/10	170/170	2			PVT322(T)	PVT322S(T)	
			8/8	170/170	2			PVT322A(T)	PVT322AS(T)	
	+400	4000	35/35	120/120	2			PVT422(T)	PVT422S(T)	
			3750	120/120	2					PVT422P(T)
Single Pole & Ring Detect	+400	3750	35/35	120/120	3					PVO402P(T)
			22/22	150/150	5					PVO402AP(T)
Application Selection Codes		Telecom 								
		T								