



## Contents



## High Voltage IGBT

| $V_{CES}$<br>max | $I_c$<br>$T_c = 25^\circ\text{C}$ | $V_{CE(sat)}$<br>typ.<br>$T_c = 25^\circ\text{C}$ | ISOPLUS i4-PAC™<br> | Page   |
|------------------|-----------------------------------|---------------------------------------------------|------------------------------------------------------------------------------------------------------|--------|
| V                | A                                 | V                                                 |                                                                                                      |        |
| 2200             | 32                                | 3.2                                               | ➤ IXL <i>F</i> 19N220A                                                                               | B6 - 2 |
| 2500             | 32                                | 3.2                                               | ➤ IXL <i>F</i> 19N250A                                                                               |        |



➤ New product

# High Voltage IGBT

in High Voltage  
ISOPLUS i4-PAC™

**IXLF 19N220A**  
**IXLF 19N250A**

**$I_{C25}$  = 32 A**  
 **$V_{CES}$  = 2200/2500 V**  
 **$V_{CE(sat)}$  = 3.2 V**  
 **$t_f$  = 50 ns**



| IGBT      |                                                                            |                              |              |        |
|-----------|----------------------------------------------------------------------------|------------------------------|--------------|--------|
| Symbol    | Conditions                                                                 | Maximum Ratings              |              |        |
| $V_{CES}$ | $T_{VJ} = 25^{\circ}\text{C to } 150^{\circ}\text{C}$                      | IXLF 19N220A<br>IXLF 19N250A | 2200<br>2500 | V<br>V |
| $V_{GES}$ |                                                                            |                              | $\pm 20$     | V      |
| $I_{C25}$ | $T_C = 25^{\circ}\text{C}$                                                 |                              | 32           | A      |
| $I_{C90}$ | $T_C = 90^{\circ}\text{C}$                                                 |                              | 19           | A      |
| $I_{CM}$  | $V_{GE} = \pm 15 \text{ V}; R_G = 47 \Omega; T_{VJ} = 125^{\circ}\text{C}$ |                              | 70           | A      |
| $V_{CEK}$ | RBSOA, Clamped inductive load; $L = 100 \mu\text{H}$                       |                              | 1200         | V      |
| $P_{tot}$ | $T_C = 25^{\circ}\text{C}$                                                 |                              | 250          | W      |

| Symbol                                                                 | Conditions                                                                                                                                      | Characteristic Values<br>( $T_{VJ} = 25^{\circ}\text{C}$ , unless otherwise specified) |                                      |                                  |
|------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------|--------------------------------------|----------------------------------|
|                                                                        |                                                                                                                                                 | min.                                                                                   | typ.                                 | max.                             |
| $V_{CE(sat)}$                                                          | $I_C = 19 \text{ A}; V_{GE} = 15 \text{ V}; T_{VJ} = 25^{\circ}\text{C}$<br>$T_{VJ} = 125^{\circ}\text{C}$                                      |                                                                                        | 3.2<br>4.7                           | 3.9<br>V<br>V                    |
| $V_{GE(th)}$                                                           | $I_C = 1 \text{ mA}; V_{GE} = V_{CE}$                                                                                                           | 5                                                                                      |                                      | 8 V                              |
| $I_{CES}$                                                              | $V_{CE} = V_{CES}; V_{GE} = 0 \text{ V}; T_{VJ} = 25^{\circ}\text{C}$<br>$T_{VJ} = 125^{\circ}\text{C}$                                         |                                                                                        | 0.2                                  | 0.15 mA<br>mA                    |
| $I_{GES}$                                                              | $V_{CE} = 0 \text{ V}; V_{GE} = \pm 20 \text{ V}$                                                                                               |                                                                                        |                                      | 500 nA                           |
| $t_{d(on)}$<br>$t_r$<br>$t_{d(off)}$<br>$t_f$<br>$E_{on}$<br>$E_{off}$ | Inductive load, $T_{VJ} = 125^{\circ}\text{C}$<br>$V_{CE} = 1500 \text{ V}; I_C = 19 \text{ A}$<br>$V_{GE} = \pm 15 \text{ V}; R_G = 47 \Omega$ |                                                                                        | 200<br>100<br>600<br>50<br>11<br>3.6 | ns<br>ns<br>ns<br>ns<br>mJ<br>mJ |
| $C_{ies}$                                                              |                                                                                                                                                 |                                                                                        | 2.2                                  | nF                               |
| $Q_{Gon}$                                                              |                                                                                                                                                 |                                                                                        | 130                                  | nC                               |
| $R_{thJC}$                                                             |                                                                                                                                                 |                                                                                        |                                      | 0.5 K/W                          |

## Features

- High Voltage IGBT
  - substitute for high voltage MOSFETs with significantly lower voltage drop and comparable switching speed
  - substitute for high voltage thyristors with voltage control of turn on and turn off
  - substitute for electromechanical trigger and discharge relays
- ISOPLUS i4-PAC™ high voltage package
  - isolated back surface
  - enlarged creepage towards heatsink
  - enlarged creepage between high voltage pins
  - application friendly pinout
  - high reliability
  - industry standard outline

## Applications

- switched mode power supplies
- DC-DC converters
- resonant converters
- laser generators, x ray generators
- discharge circuits

**Component**

| Symbol     | Conditions                                     | Maximum Ratings |    |
|------------|------------------------------------------------|-----------------|----|
| $T_{VJ}$   |                                                | -55...+150      | °C |
| $T_{stg}$  |                                                | -55...+125      | °C |
| $V_{ISOL}$ | $I_{ISOL} \leq 1 \text{ mA}; 50/60 \text{ Hz}$ | 2500            | V~ |
| $F_c$      | mounting force with clip                       | 20...120        | N  |

| Symbol     | Conditions             | Characteristic Values |      |      |
|------------|------------------------|-----------------------|------|------|
|            |                        | min.                  | typ. | max. |
| $d_s, d_A$ | C pin - E pin          | 7.0                   |      | mm   |
| $d_s, d_A$ | pin - backside metal   | 5.5                   |      | mm   |
| $R_{thCH}$ | with heatsink compound |                       | 0.15 | K/W  |
| Weight     |                        |                       | 9    | g    |

**Dimensions in mm (1 mm = 0.0394")**
