



μ -POWER OPERATIONAL AMPLIFIER


■ GENERAL DESCRIPTION

The NJM4250 is extremely versatile programmable monolithic operational amplifiers. A single external master bias current setting resistor programs the input bias current, input offset current, quiescent power consumption, slew rate, input noise, and the gain-bandwidth product. The device is a truly general purpose operational amplifier.

■ FEATURES

- Operating Voltage $(\pm 1V \sim \pm 18V)$
- Low Operating Current $(0.1mA \text{ max.})$
- Programmable monolithic OP-Amp
- Very Low Power Consumption
- Package Outline DIP8, DMP8, SSOP8
- Bipolar Technology

■ PACKAGE OUTLINE



NJM4250D




NJM4250M



NJM4250V

■ PIN CONFIGURATION




NJM4250D

NJM4250M

NJM4250V

■ EQUIVALENT CIRCUIT (1/2 shown)





■ ABSOLUTE MAXIMUM RATINGS

(Ta=25°C)

PARAMETER	SYMBOL	RATINGS	UNIT
Supply Voltage	V ⁺ /V ⁻	±18	V
Differential Input Voltage	V _{ID}	±30	V
Input Voltage	V _{IC}	±15 (note)	V
	P _D	(DIP8) 500 (DMP8) 300 (SSOP8) 250	mW mW mW
Operating Temperature Range	I _{SET}	150	μA
Storage Temperature Range	T _{opr}	-20 ~ +75	°C
	T _{stg}	-40 ~ +125	°C


(note) For supply voltage less than ±15V, the absolute maximum input voltage is equal to the supply voltage.

■ ELECTRICAL CHARACTERISTICS


(Ta=25°C, V⁺/V⁻=±15V)

PARAMETER	SYMBOL	TEST CONDITION	I _{SET} =1 μA		I _{SET} =10 μA		UNIT
			MIN.	MAX.	MIN.	MAX.	
Input Offset Voltage 1	V _{IO} 1	R _S ≤100kΩ	—	5	—	6	mV
Input Offset Voltage 2	V _{IO} 2	V ⁺ /V ⁻ =±1.5V, R _S ≤100kΩ	—	5	—	6	mV
Input Offset Current	I _{IO}	—	6	—	—	20	nA
Input Bias Current 1	I _B 1	—	10	—	—	75	nA
Input Bias Current 2	I _B 2	V ⁺ /V ⁻ =±1.5V	—	10	—	75	nA
Large Signal Voltage Gain 1	A _V 1	V _o =±10V, R _L ≥100kΩ	96	—	—	—	dB
Large Signal Voltage Gain 2	A _V 2	V _o =±10V, R _L ≥10kΩ	—	—	96	—	dB
Operating Current 1	I _{CC} 1	—	11	—	—	100	μA
Operating Current 2	I _{CC} 2	V ⁺ /V ⁻ =±1.5V	—	8	—	90	μA
Input Common Mode Voltage Range 1	V _{ICM} 1	—	±13.5	—	±13.5	—	V
Input Common Mode Voltage Range 2	V _{ICM} 2	V ⁺ /V ⁻ =±1.5V	±0.6	—	±0.6	—	V
Maximum Output Voltage Swing 1	V _{OM} 1	R _L ≥100kΩ	±12	—	—	—	V
Maximum Output Voltage Swing 2	V _{OM} 2	V ⁺ /V ⁻ =±1.5V, R _L ≥100kΩ	±0.6	—	—	—	V
Maximum Output Voltage Swing 3	V _{OM} 3	R _L ≥10kΩ	—	—	±12	—	V
Maximum Output Voltage Swing 4	V _{OM} 4	V ⁺ /V ⁻ =±1.5V, R _L ≥10kΩ	—	—	±0.6	—	V
Common Mode Rejection Ratio	CMR	R _S ≤10kΩ	70	—	70	—	dB
Supply Voltage Rejection Ratio	SVR	R _S ≤10kΩ	74	—	74	—	dB


■ TYPICAL APPLICATION (I_{SET}, V_{IO} Adjustment)



$$I_{SET} = \frac{V^+ + |V^-| - 0.5}{R_{SET}}$$









$$I_{SET} = \frac{V^+ - 0.5}{R_{SET}}$$



Offset Adjustment



■ TYPICAL CHARACTERISTICS






■ TYPICAL CHARACTERISTICS


**Maximum Output Voltage Swing
vs.
Operating Voltage**

($1 \mu\text{A} \leq I_{\text{SET}} \leq 10 \mu\text{A}$, $R_L = 10\text{k}\Omega$, $T_a = 25^\circ\text{C}$)




**Operating Current
vs.
Set Current**

($T_a = 25^\circ\text{C}$)




**Operating Current
vs.
Ambient Temperature**






**Open Loop Voltage Gain
vs.
Set Current**

($R_L = 10\text{k}\Omega$, $T_a = 25^\circ\text{C}$)





■ TYPICAL CHARACTERISTICS



■ TYPICAL APPLICATIONS

500nW 10times Inverting Amplifier

