



3-Terminal Positive Voltage Regulator

■ GENERAL DESCRIPTION

The NJM7800 series of monolithic 3-Terminal Positive Voltage Regulators is constructed using the New JRC Planar epitaxial process. These regulators employ internal current-limiting, thermal-shutdown and safe-area compensation making them essentially indestructible. If adequate heat sinking is provided, they can deliver over 1A output current. They are intended as fixed voltage regulators in a wide range of applications including local (on card) regulation for elimination of distribution problems associated with single point regulation. In addition to use as fixed voltage regulators, these devices can be used with external components to obtain adjustable output voltages and currents.


■ FEATURES

- Operating Voltage
- Internal Short Circuit Current Limit
- Internal Thermal Overload Protection
- Excellent Ripple Rejection
- Guarantee'd 1.5A Output Current
- Package Outline
- Bipolar Technology


TO-220F, TO-252

■ PACKAGE OUTLINE

(TO-220F)



(TO-252)




NJM7800FA

NJM7800DA

- | | |
|--------|--------|
| 1. IN | 1. IN |
| 2. GND | 2. GND |
| 3. OUT | 3. OUT |

(note) The radiation fin is connected pin2.

■ EQUIVALENT CIRCUIT





■ ABSOLUTE MAXIMUM RATINGS

(Ta=25°C)

PARAMETER	SYMBOL	MAXIMUM RATINGS			UNIT	
Input Voltage	V _{IN}	7805~7809	35		V	
		7812~7815	35			
		7818~7824	40			
Storage Temperature Range	T _{stg}	-40 ~ +150			°C	
Operating Temperature Range	Operating Junction Temperature		T _j	-30~+150	°C	
	Operating Junction Temperature		T _{opr}	-30~+75		
Power Dissipation	P _D	TO220F	16 (T _c ≤70°C)		W	
		TO252	10 (T _c =25°C) 1 (T _a ≤25°C)			

■ THERMAL CHARACTERISTICS

Thermal Resistance		Junction-to-Ambient Temperature	θ _{ja}	60	125	°C/W
		Junction-to-Case	θ _{jc}	5	12.5	

■ ELECTRICAL CHARACTERISTICS (C₁=0.33 μF, C₀=0.1 μF, T_j=25°C) Measurement is to be conducted in pulse testing.

PARAMETER	SYMBOL	TEST CONDITIONS	F TYP.			DL TYP.			UNIT
			MIN.	_TYP.	MAX.	MIN.	_TYP.	MAX.	
NJM7805A									
Output Voltage	V _O	V _{IN} =10V, I _O =0.5A	4.8	5.0	5.2	4.8	5.0	5.2	V
Quiescent Current	I _Q	V _{IN} =10V, I _O =0mA	—	4.2	6.0	—	4.2	6.0	mA
Load Regulation	ΔV _O -I _O	V _{IN} =10V, I _O =0.005~1.5A	—	15	50	—	15	100	mV
Line Regulation	ΔV _O -V _{IN}	V _{IN} =7~25V, I _O =0.5A	—	3	50	—	3	100	mV
Ripple Rejection	RR	V _{IN} =10V, I _O =0.5A, e _{in} =2V p.p., f=120Hz	68	78	—	68	78	—	dB
Output Noise Voltage	V _{NO}	V _{IN} =10V, BW=10Hz~100kHz, I _O =0.5A	—	45	—	—	45	—	μV
Average Temperature Coefficient of Output Voltage	ΔV _O /ΔT	V _{IN} =10V, I _O 5mA	—	-0.5	—	—	-0.5	—	mV/°C



■ ELECTRICAL CHARACTERISTICS ($C_1=0.33\ \mu F$, $C_0=0.1\ \mu F$, $T_j=25^\circ C$) Measurement is to be conducted in pulse testing.



PARAMETER	SYMBOL	TEST CONDITIONS	F TYP.			DL TYP.			UNIT
			MIN.	TYP.	MAX.	MIN.	TYP.	MAX.	
NJM7806A									
Output Voltage	V_o	$V_{IN}=11V$, $I_o=0.5A$	5.75	6.0	6.25	5.75	6.0	6.25	V
Quiescent Current	I_Q	$V_{IN}=11V$, $I_o=0mA$	—	4.3	6.0	—	4.3	6.0	mA
Load Regulation	$\Delta V_o/I_o$	$V_{IN}=11V$, $I_o=0.005\sim 1.5A$	—	15	60	—	15	120	mV
Line Regulation	$\Delta V_o/V_{IN}$	$V_{IN}=8\sim 25V$, $I_o=0.5A$	—	5	60	—	5	120	mV
Ripple Rejection	RR	$V_{IN}=11V$, $I_o=0.5A$, $e_{in}=2V_{P-P}$, $f=120Hz$	65	75	—	65	75	—	dB
Output Noise Voltage	V_{NO}	$V_{IN}=11V$, $BW=10Hz\sim 100kHz$, $I_o=0.5A$	—	45	—	—	45	—	μV
Average Temperature Coefficient of Output Voltage	$\Delta V_o/\Delta T$	$V_{IN}=11V$, $I_o 5mA$	—	-0.6	—	—	-0.6	—	mV/°C
NJM7808A									
Output Voltage	V_o	$V_{IN}=14V$, $I_o=0.5A$	7.7	8.0	8.3	7.7	8.0	8.3	V
Quiescent Current	I_Q	$V_{IN}=14V$, $I_o=0mA$	—	4.3	6.0	—	4.3	6.0	mA
Load Regulation	$\Delta V_o/I_o$	$V_{IN}=14V$, $I_o=0.005\sim 1.5A$	—	15	80	—	15	160	mV
Line Regulation	$\Delta V_o/V_{IN}$	$V_{IN}=10.5\sim 25V$, $I_o=0.5A$	—	6	80	—	6	160	mV
Ripple Rejection	RR	$V_{IN}=14V$, $I_o=0.5A$, $e_{in}=2V_{P-P}$, $f=120Hz$	62	72	—	62	72	—	dB
Output Noise Voltage	V_{NO}	$V_{IN}=14V$, $BW=10Hz\sim 100kHz$, $I_o=0.5A$	—	55	—	—	55	—	μV
Average Temperature Coefficient of Output Voltage	$\Delta V_o/\Delta T$	$V_{IN}=14V$, $I_o 5mA$	—	-0.8	—	—	-0.8	—	mV/°C
NJM7809A									
Output Voltage	V_o	$V_{IN}=15V$, $I_o=0.5A$	8.65	9.0	9.35	8.65	9.0	9.35	V
Quiescent Current	I_Q	$V_{IN}=15V$, $I_o=0mA$	—	4.3	6.0	—	4.3	6.0	mA
Load Regulation	$\Delta V_o/I_o$	$V_{IN}=15V$, $I_o=0.005\sim 1.5A$	—	15	90	—	15	180	mV
Line Regulation	$\Delta V_o/V_{IN}$	$V_{IN}=11.5\sim 25V$, $I_o=0.5A$	—	7	90	—	7	180	mV
Ripple Rejection	RR	$V_{IN}=15V$, $I_o=0.5A$, $e_{in}=2V_{P-P}$, $f=120Hz$	62	72	—	62	72	—	dB
Output Noise Voltage	V_{NO}	$V_{IN}=15V$, $BW=10Hz\sim 100kHz$, $I_o=0.5A$	—	60	—	—	60	—	μV
Average Temperature Coefficient of Output Voltage	$\Delta V_o/\Delta T$	$V_{IN}=15V$, $I_o 5mA$	—	-0.9	—	—	-0.9	—	mV/°C
NJM7812A									
Output Voltage	V_o	$V_{IN}=19V$, $I_o=0.5A$	11.5	12.0	12.5	11.5	12.0	12.5	V
Quiescent Current	I_Q	$V_{IN}=19V$, $I_o=0mA$	—	4.3	6.0	—	4.3	6.0	mA
Load Regulation	$\Delta V_o/I_o$	$V_{IN}=19V$, $I_o=0.005\sim 1.5A$	—	25	120	—	25	240	mV
Line Regulation	$\Delta V_o/V_{IN}$	$V_{IN}=14.5\sim 30V$, $I_o=0.5A$	—	10	120	—	10	240	mV
Ripple Rejection	RR	$V_{IN}=19V$, $I_o=0.5A$, $e_{in}=2V_{P-P}$, $f=120Hz$	61	71	—	61	71	—	dB
Output Noise Voltage	V_{NO}	$V_{IN}=19V$, $BW=10Hz\sim 100kHz$, $I_o=0.5A$	—	75	—	—	75	—	μV
Average Temperature Coefficient of Output Voltage	$\Delta V_o/\Delta T$	$V_{IN}=19V$, $I_o 5mA$	—	-1.2	—	—	-1.2	—	mV/°C


ELECTRICAL CHARACTERISTICS ($C_1=0.33\ \mu F$, $C_0=0.1\ \mu F$, $T_j=25^\circ C$) Measurement is to be conducted in pulse testing.

PARAMETER	SYMBOL	TEST CONDITIONS	F TYP.			DL TYP.			UNIT
			MIN.	TYP.	MAX.	MIN.	TYP.	MAX.	
NJM7815A									
Output Voltage	V_O	$V_{IN}=23V$, $I_O=0.5A$	14.4	15.0	15.6	14.4	15.0	15.6	V
Quiescent Current	I_Q	$V_{IN}=23V$, $I_O=0mA$	—	4.4	6.0	—	4.4	6.0	mA
Load Regulation	ΔV_O-I_O	$V_{IN}=23V$, $I_O=0.005\sim 1.5A$	—	35	150	—	35	300	mV
Line Regulation	ΔV_O-V_{IN}	$V_{IN}=17.5\sim 30V$, $I_O=0.5A$	—	11	150	—	11	300	mV
Ripple Rejection	RR	$V_{IN}=23V$, $I_O=0.5A$, $e_{in}=2V_{p-p}$, $f=120Hz$	60	70	—	60	70	—	dB
Output Noise Voltage	V_{NO}	$V_{IN}=23V$, $BW=10Hz\sim 100kHz$, $I_O=0.5A$	—	90	—	—	90	—	μV
Average Temperature Coefficient of Output Voltage	$\Delta V_O/\Delta T$	$V_{IN}=23V$, $I_O 5mA$	—	-1.5	—	—	-1.5	—	$mV/^\circ C$
NJM7818A									
Output Voltage	V_O	$V_{IN}=27V$, $I_O=0.5A$	17.3	18.0	18.7	17.3	18.0	18.7	V
Quiescent Current	I_Q	$V_{IN}=27V$, $I_O=0mA$	—	4.5	6.0	—	4.5	6.0	mA
Load Regulation	ΔV_O-I_O	$V_{IN}=27V$, $I_O=0.005\sim 1.5A$	—	55	180	—	55	360	mV
Line Regulation	ΔV_O-V_{IN}	$V_{IN}=21\sim 33V$, $I_O=0.5A$	—	15	180	—	15	360	mV
Ripple Rejection	RR	$V_{IN}=27V$, $I_O=0.5A$, $e_{in}=2V_{p-p}$, $f=120Hz$	59	69	—	59	69	—	dB
Output Noise Voltage	V_{NO}	$V_{IN}=27V$, $BW=10Hz\sim 100kHz$, $I_O=0.5A$	—	100	—	—	100	—	μV
Average Temperature Coefficient of Output Voltage	$\Delta V_O/\Delta T$	$V_{IN}=27V$, $I_O 5mA$	—	-1.8	—	—	-1.8	—	$mV/^\circ C$
NJM7820A									
Output Voltage	V_O	$V_{IN}=29V$, $I_O=0.5A$	19.2	20.0	20.8	19.2	20.0	20.8	V
Quiescent Current	I_Q	$V_{IN}=29V$, $I_O=0mA$	—	4.5	6.0	—	4.5	6.0	mA
Load Regulation	ΔV_O-I_O	$V_{IN}=29V$, $I_O=0.005\sim 1.5A$	—	61	200	—	61	400	mV
Line Regulation	ΔV_O-V_{IN}	$V_{IN}=23\sim 35V$, $I_O=0.5A$	—	16	200	—	16	400	mV
Ripple Rejection	RR	$V_{IN}=29V$, $I_O=0.5A$, $e_{in}=2V_{p-p}$, $f=120Hz$	58	68	—	58	68	—	dB
Output Noise Voltage	V_{NO}	$V_{IN}=29V$, $BW=10Hz\sim 100kHz$, $I_O=0.5A$	—	120	—	—	120	—	μV
Average Temperature Coefficient of Output Voltage	$\Delta V_O/\Delta T$	$V_{IN}=29V$, $I_O 5mA$	—	-2.0	—	—	-2.0	—	$mV/^\circ C$
NJM7824A									
Output Voltage	V_O	$V_{IN}=33V$, $I_O=0.5A$	23.0	24.0	25.0	23.0	24.0	25.0	V
Quiescent Current	I_Q	$V_{IN}=33V$, $I_O=0mA$	—	4.6	6.0	—	4.6	6.0	mA
Load Regulation	ΔV_O-I_O	$V_{IN}=33V$, $I_O=0.005\sim 1.5A$	—	65	240	—	65	480	mV
Line Regulation	ΔV_O-V_{IN}	$V_{IN}=27\sim 38V$, $I_O=0.5A$	—	18	240	—	18	480	mV
Ripple Rejection	RR	$V_{IN}=33V$, $I_O=0.5A$, $e_{in}=2V_{p-p}$, $f=120Hz$	56	66	—	56	66	—	dB
Output Noise Voltage	V_{NO}	$V_{IN}=33V$, $BW=10Hz\sim 100kHz$, $I_O=0.5A$	—	120	—	—	120	—	μV
Average Temperature Coefficient of Output Voltage	$\Delta V_O/\Delta T$	$V_{IN}=33V$, $I_O 5mA$	—	-2.4	—	—	-2.4	—	$mV/^\circ C$





■ POWER DISSIPATION VS. AMBIENT TEMPERATURE



■ TEST CIRCUIT


1. Output Voltage, Line Regulation, Load Regulation, Quiescent Current, Average Temperature Coefficient of Output Voltage, Output Noise Voltage






■ TYPICAL CHARACTERISTICS


NJM7805/15/24 Output Characteristics



NJM7805 Dropout Characteristics




NJM7812 Dropout Characteristics



NJM7805/15/24 Load Characteristics


($T_j = 25^\circ C$)






■ TYPICAL CHARACTERISTICS


NJM7800 Series Short Circuit Output Current
($T_j = 25^\circ\text{C}$, ∞ Heat Sink)




NJM7805/24 Quiescent Current vs. Input Voltage
($T_j = 25^\circ\text{C}$)




NJM7805/15/24 Output Voltage vs. Junction Temperature



NJM7805/12/24 Ripple Rejection vs. Frequency



**■ TYPICAL CHARACTERISTICS****NJM7805 Output Voltage vs. Temperature****NJM7808 Output Voltage vs. Temperature**