


QUARTZ CRYSTAL OSCILLATOR
PRELIMINARY
■ GENERAL DESCRIPTION

The NJU6329 series is a C-MOS quartz crystal oscillator which consists of an oscillation amplifier, 3-stage divider and 3-state output buffer.

The oscillation frequency is as wide as up to 50MHz and the symmetry of 45-55% is realized over full oscillation frequency range.

The oscillation amplifier incorporates feed-back resistance and oscillation capacitors(Cg, Cd), therefore, it requires no external component except quartz crystal.


The 3-stage divider generates f_0 , $f_0/2$, $f_0/4$ and $f_0/8$ and only one frequency selected by internal circuits is output.

The 3-state output buffer is TTL compatible and capable of 10 TTL driving.

The difference between NJU6329 and NJU6322 series is pin configuration only.

■ PACKAGE OUTLINE

NJU6329XC

NJU6329XE
4
■ PIN CONFIGURATION/PAD LOCATION

■ FEATURES

- Operating Voltage — 3.0~6.0V
- Maximum Oscillation Frequency — 50MHz
- Low Operating Current
- High Fan-out — TTL 10
- 3-state Output Buffer
- Selected Frequency OutPut (mask option)
Only one frequency of f_0 , $f_0/2$, $f_0/4$ and $f_0/8$ output
- Oscillation Capacitor Cg and Cd on-chip
- Oscillation and/or Output Stand-by Function
- Package Outline — CHIP/EMP8
- C-MOS Technology

■ COORDINATES

 Unit: μm


No.	PAD	X	Y
1	V _{DD}	-450	257
2	XT	-450	84
3	XT	-450	-83
4	CONT	-450	-249
5	V _{SS}	475	-249
8	F _{OUT}	475	257

Chip Size : 1.24 X 0.8mm
 Chip Center : X=0 μm , Y=0 μm
 Chip Thickness : 400 μm ±30 μm

(Note) No. 6 and 7 terminals are only for package type information. There are no PAD on the chip.

■ LINE-UP TABLE

Type No.	Output Freq.	Cg	Cd	Osc.Stop Function
NJU6329A	f_0	23pF	23pF	No
NJU6329B	$f_0/2$	23pF	23pF	No
NJU6329C	$f_0/4$	23pF	23pF	No
NJU6329D	$f_0/8$	23pF	23pF	No


■ BLOCK DIAGRAM

■ TERMINAL DESCRIPTION

NO.	SYMBOL	F U N C T I O N	
1	V _{DD}	+ 5V	
2	$\overline{XT}$	Quartz Crystal Connecting Terminals	
3	XT		
4	$\overline{CONT}$	3-State Output Control and Divider Reset	
		$\overline{CONT}$	F _{OUT}
		H	Output either one frequency from f _o , f _o /2, f _o /4, and f _o /8
		L	Output High Impedance and Divider Reset
5	V _{SS}	GND	
8	F _{OUT}	Output either one frequency from f _o , f _o /2, f _o /4, and f _o /8 (Note)	

(Note) Reference the Line-Up Table

■ ABSOLUTE MAXIMUM RATINGS

($T_a=25^{\circ}\text{C}$)

P A R A M E T E R	SYMBOL	R A T I N G S	UNIT
Supply Voltage	V_{DD}	-0.5 ~ +7.0	V
Input Voltage	V_{IN}	$V_{SS}-0.5 \sim V_{DD}+0.5$	V
Output Voltage	V_O	-0.5 ~ $V_{DD}+0.5$	V
Input Current	I_{IN}	± 10	mA
Output Current	I_O	± 25	mA
Power Dissipation	P_D	200 (EMP)	mW
Operating Temperature Range	T_{OPR}	-40 ~ + 85	$^{\circ}\text{C}$
Storage Temperature Range	T_{STG}	-55 ~ +125	$^{\circ}\text{C}$



■ ELECTRICAL CHARACTERISTICS

 ($T_a=25^{\circ}\text{C}$, $V_{DD}=5\text{V}$)

PARAMETER	SYMBOL	CONDITIONS	MIN	TYP	MAX	UNIT
Operating Voltage	V_{DD}		3		6	V
Operating Current	I_{DD}	$f_{osc}=16\text{MHz}$, No Load			15	mA
Stand-by Current	I_{st}	$\overline{\text{CONT}}, \text{XT}=V_{SS}$, No Load (Note)			1	μA
Input Voltage	V_{IH}		3.5		5.0	V
	V_{IL}		0		1.5	
Output Current	I_{OH}	$V_{DD}=5\text{V}$, $V_{OH}=4.5\text{V}$	4			mA
	I_{OL}	$V_{DD}=5\text{V}$, $V_{OL}=0.5\text{V}$	16			
Input Current	I_{IN}	$\overline{\text{CONT}}$ Terminal, $\overline{\text{CONT}}=V_{SS}$			400	μA
3-St Off-leakage Current	I_{OZ}	$\overline{\text{CONT}}=V_{SS}$, $F_{OUT}=V_{SS}$ or V_{DD}			± 0.1	μA
Internal Capacitor	C_g, C_d	$f_{osc}=16\text{MHz}$		23		pF
Max. Oscillation Freq.	f_{MAX}		50			MHz
Output Signal Symmetry	SYM	$C_L=15\text{pF}$ at 1.4V	45	50	55	%
Output Signal Rise Time	t_{r1}	$C_L=15\text{pF}$, 20~80%			8	ns
	t_{r2}	$C_L=15\text{pF}$, $R_L=390\Omega$, 0.4~2.4V			6	
Output Signal Fall Time	t_{f1}	$C_L=15\text{pF}$, 80~20%			6	ns
	t_{f2}	$C_L=15\text{pF}$, $R_L=390\Omega$, 2.4~0.4V			4	

 Note) Excluding input current on $\overline{\text{CONT}}$ terminal.

■ MEASUREMENT CIRCUITS

 (1) Output Signal Symmetry ($C_L=15\text{pF}$)




(2) Output Signal Rise/Fall Time ($C_L=15\text{pF}$)

