

S Y M B O L	COMMON DIMENSIONS			
M	COMMON DIMENSIONS			N <sub>O</sub> T <sub>E</sub>
_ ĭ_	MIN.	NOM.	MAX.	΄Ε
Α	_	0.90	1.00	
A1	0.00	0.01	0.05	11
b	0.18	0.23	0.30	4
D	10.00 BSC			
D1	9.75 BSC			
е	0.50 BSC			
Ε	10.00 BSC			
E1	9.75 BSC			
L	0.50	0.60	0.75	
N	68			3
Nd	17			3
Ne	17			3
θ	0		12°	
Р	0	0.42	0.60	
D2	4.40	4.55	4.70	
E2	4.40	4.55	4.70	

- 1. DIE THICKNESS ALLOWABLE IS .012 INCHES MAXIMUM.
- 2. DIMENSIONING & TOLERANCES CONFORM TO ASME Y14.5M. 1994.
- N IS THE NUMBER OF TERMINALS.

  Nd IS THE NUMBER OF TERMINALS IN X-DIRECTION &

  Ne IS THE NUMBER OF TERMINALS IN Y-DIRECTION.
- 4. DIMENSION b APPLIES TO PLATED TERMINAL AND IS MEASURED BETWEEN 0.20 AND 0.25mm FROM TERMINAL TIP.
- THE PIN #1 IDENTIFIER MUST BE LOCATED ON THE TOP SURFACE OF THE PACKAGE BY USING INDENTATION MARK OR OTHER FEATURE OF PACKAGE BODY.
- 6. EXACT SHAPE AND SIZE OF THIS FEATURE IS OPTIONAL.
- 7. ALL DIMENSIONS ARE IN MILLIMETERS.
- 8. PACKAGE WARPAGE MAX 0.10mm.
- APPLIES TO EXPOSED SURFACE OF PADS AND TERMINALS.
- APPLIES ONLY TO TERMINALS.



