



BTW67 and BTW69 Series

STANDARD

50A SCRs

MAIN FEATURES:


Symbol	Value	Unit
$I_T(\text{RMS})$	50	A
$V_{\text{DRM}}/V_{\text{RRM}}$	600 to 1200	V
I_{GT}	80	mA

DESCRIPTION

Available in high power packages, the BTW67 / BTW69 Series is suitable in applications where power handling and power dissipation are critical, such as solid state relays, welding equipment, high power motor control.

Based on a clip assembly technology, they offer a superior performance in surge current handling capabilities.

Thanks to their internal ceramic pad, they provide high voltage insulation (2500V RMS), complying with UL standards (file ref: E81734).



ABSOLUTE RATINGS (limiting values)

Symbol	Parameter		Value	Unit
$I_T(\text{RMS})$	RMS on-state current (180° conduction angle)		RD91 TOP3 Ins.	$T_c = 70^\circ\text{C}$ $T_c = 75^\circ\text{C}$
$I_T(\text{AV})$	Average on-state current (180° conduction angle)		RD91 TOP3 Ins.	$T_c = 70^\circ\text{C}$ $T_c = 75^\circ\text{C}$
I_{TSM}	Non repetitive surge peak on-state current		tp = 8.3 ms tp = 10 ms	$T_j = 25^\circ\text{C}$
I_t	I_t Value for fusing		$T_j = 25^\circ\text{C}$	$1680 \text{ A}^2\text{s}$
dl/dt	Critical rate of rise of on-state current $I_G = 2 \times I_{\text{GT}}$, $t_r \leq 100 \text{ ns}$		$F = 60 \text{ Hz}$	$T_j = 125^\circ\text{C}$
I_{GM}	Peak gate current		$T_j = 125^\circ\text{C}$	8 A
$P_{G(\text{AV})}$	Average gate power dissipation		$T_j = 125^\circ\text{C}$	1 W
T_{stg} T_j	Storage junction temperature range Operating junction temperature range			- 40 to + 150 - 40 to + 125 °C
V_{RGM}	Maximum peak reverse gate voltage			5 V

BTW67 and BTW69 Series

ELECTRICAL CHARACTERISTICS ($T_j = 25^\circ\text{C}$, unless otherwise specified)

Symbol	Test Conditions		Value	Unit
I_{GT}	$V_D = 12 \text{ V}$	$R_L = 33 \Omega$	MIN.	8
			MAX.	80
			MAX.	1
V_{GT}				V
V_{GD}	$V_D = V_{DRM}$	$R_L = 3.3 \text{ k}\Omega$	$T_j = 125^\circ\text{C}$	MIN.
				0.2
I_H	$I_T = 500 \text{ mA}$ Gate open		MAX.	150
I_L	$I_G = 1.2 I_{GT}$		MAX.	200
dV/dt	$V_D = 67\% V_{DRM}$ Gate open		$T_j = 125^\circ\text{C}$	MIN.
				1000
V_{TM}	$I_{TM} = 100 \text{ A}$ $t_p = 380 \mu\text{s}$		$T_j = 25^\circ\text{C}$	MAX.
				1.9
V_{t0}	Threshold voltage		$T_j = 125^\circ\text{C}$	MAX.
				1.0
R_d	Dynamic resistance		$T_j = 125^\circ\text{C}$	MAX.
				8.5
I_{DRM}	$V_{DRM} = V_{RRM}$		$T_j = 25^\circ\text{C}$	MAX.
			$T_j = 125^\circ\text{C}$	5
I_{RRM}				mA


THERMAL RESISTANCES

Symbol	Parameter	Value	Unit
$R_{th(j-c)}$	Junction to case (DC)	RD91 (Insulated)	°C/W
		TOP3 Insulated	0.9
$R_{th(j-a)}$	Junction to ambient	TOP3 Insulated	50

PRODUCT SELECTOR

Part Number	Voltage (xxx)			Sensitivity	Package
	600 V	800 V	1200 V		
BTW67-xxx	X	X	X	80 mA	RD91
BTW69-xxx	X	X	X	80 mA	TOP3 Ins.

ORDERING INFORMATION



OTHER INFORMATION

Part Number	Marking	Weight	Base Quantity	Packing mode
BTW67-xxx	BTW67xxx	20.0 g	25	Bulk
BTW69-xxx	BTW69xxx	4.5 g	120	Bulk

Note: xxx = voltage

Fig. 1: Maximum average power dissipation versus average on-state current.




Fig. 3: Relative variation of thermal impedance versus pulse duration.




Fig. 5: Surge peak on-state current versus number of cycles.




Fig. 2: Average and D.C. on-state current versus case temperature.




Fig. 4: Relative variation of gate trigger current, holding current and latching current versus junction temperature.






Fig. 6: Non-repetitive surge peak on-state current for a sinusoidal pulse with width $tp < 10\text{ms}$, and corresponding value of I_t .



BTW67 and BTW69 Series

Fig. 7: On-state characteristics (maximum values).



PACKAGE MECHANICAL DATA

RD91 (Plastic)

The mechanical drawing shows two views of the package. The top view illustrates the lead configuration with dimensions A1, A2, L1, L2, B1, B2, C, C1, C2, E3, F, I, N1, and N2. The bottom view shows the outline with dimensions A, B, E3, and I.

REF.	DIMENSIONS			
	Millimeters		Inches	
	Min.	Max.	Min.	Max.
A		40.00		1.575
A1	29.90	30.30	1.177	1.193
A2		22.00		0.867
B		27.00		1.063
B1	13.50	16.50	0.531	0.650
B2		24.00		0.945
C		14.00		0.551
C1		3.50		0.138
C2	1.95	3.00	0.077	0.118
E3	0.70	0.90	0.027	0.035
F	4.00	4.50	0.157	0.177
I	11.20	13.60	0.441	0.535
L1	3.10	3.50	0.122	0.138
L2	1.70	1.90	0.067	0.075
N1	33°	43°	33°	43°
N2	28°	38°	28°	38°

4/5

PACKAGE MECHANICAL DATA

TOP3 Ins.(Plastic)

REF.	DIMENSIONS					
	Millimeters			Inches		
	Min.	Typ.	Max.	Min.	Typ.	Max.
A	4.4		4.6	0.173		0.181
B	1.45		1.55	0.057		0.061
C	14.35		15.60	0.565		0.614
D	0.5		0.7	0.020		0.028
E	2.7		2.9	0.106		0.114
F	15.8		16.5	0.622		0.650
G	20.4		21.1	0.815		0.831
H	15.1		15.5	0.594		0.610
J	5.4		5.65	0.213		0.222
K	3.4		3.65	0.134		0.144
L	4.08		4.17	0.161		0.164
P	1.20		1.40	0.047		0.055
R		4.60			0.181	

Information furnished is believed to be accurate and reliable. However, STMicroelectronics assumes no responsibility for the consequences of use of such information nor for any infringement of patents or other rights of third parties which may result from its use. No license is granted by implication or otherwise under any patent or patent rights of STMicroelectronics. Specifications mentioned in this publication are subject to change without notice. This publication supersedes and replaces all information previously supplied. STMicroelectronics products are not authorized for use as critical components in life support devices or systems without express written approval of STMicroelectronics.

© The ST logo is a registered trademark of STMicroelectronics

© 2000 STMicroelectronics - Printed in Italy - All Rights Reserved

STMicroelectronics GROUP OF COMPANIES

Australia - Brazil - China - Finland - France - Germany - Hong Kong - India - Italy - Japan - Malaysia - Malta - Morocco
Singapore - Spain - Sweden - Switzerland - United Kingdom

<http://www.st.com>

