



## HIGH EFFICIENCY FAST RECOVERY RECTIFIER DIODES

### FEATURES

- SUITED FOR SMPS
- VERY LOW FORWARD LOSSES
- NEGLIGIBLE SWITCHING LOSSES
- HIGH SURGE CURRENT CAPABILITY
- HIGH AVALANCHE ENERGY CAPABILITY
- INSULATED :  
Insulating voltage = 2500 V<sub>RMS</sub>  
Capacitance = 55 pF



**ISOTOP**  
(Plastic)

### DESCRIPTION

Dual rectifier suited for switchmode power supply and high frequency DC to DC converters.  
Packaged in ISOTOP™ this device is intended for use in low voltage, high frequency inverters, free wheeling and polarity protection applications.

### ABSOLUTE MAXIMUM RATINGS

Symbol	Parameter			Value	Unit
I <sub>F(RMS)</sub>	RMS forward current		Per diode	150	A
I <sub>F(AV)</sub>	Average forward current $\delta = 0.5$	T <sub>c</sub> =110°C	Per diode	100	A
I <sub>FSM</sub>	Surge non repetitive forward current	tp=10ms sinusoidal	Per diode	1600	A
T <sub>stg</sub> T <sub>j</sub>	Storage and junction temperature range			- 40 to + 150 - 40 to + 150	°C °C

Symbol	Parameter	Value	Unit
V <sub>RRM</sub>	Repetitive peak reverse voltage	200	V

ISOTOP is a trademark of STMicroelectronics.

## BYV255V

### THERMAL RESISTANCE

Symbol	Parameter	Value	Unit
R <sub>th</sub> (j-c)	Junction to case	Per diode	0.4
		Total	0.25
R <sub>th</sub> (c)	Coupling	0.1	°C/W

When the diodes 1 and 2 are used simultaneously :

$$T_j - T_c \text{ (diode 1)} = P(\text{diode 1}) \times R_{th(j-c)}(\text{Per diode}) + P(\text{diode 2}) \times R_{th(c)}$$

### ELECTRICAL CHARACTERISTICS (Per diode)

#### STATIC CHARACTERISTICS

Symbol	Test Conditions		Min.	Typ.	Max.	Unit
I <sub>R</sub> *	T <sub>j</sub> = 25°C	V <sub>R</sub> = V <sub>RRM</sub>			100	µA
	T <sub>j</sub> = 100°C				10	mA
V <sub>F</sub> **	T <sub>j</sub> = 125°C	I <sub>F</sub> = 100 A			0.85	V
	T <sub>j</sub> = 125°C	I <sub>F</sub> = 200 A			1.00	
	T <sub>j</sub> = 25°C	I <sub>F</sub> = 200 A			1.15	

Pulse test : \* tp = 5 ms, duty cycle < 2 %

\*\* tp = 380 µs, duty cycle < 2 %


### RECOVERY CHARACTERISTICS

Symbol	Test Conditions			Min.	Typ.	Max.	Unit
trr	T <sub>j</sub> = 25°C	I <sub>F</sub> = 0.5A	I <sub>rr</sub> = 0.25A			55	ns
		I <sub>F</sub> = 1A V <sub>R</sub> = 30V	dI <sub>F</sub> /dt = -50A/µs			80	
tfr	T <sub>j</sub> = 25°C	I <sub>F</sub> = 1A V <sub>FR</sub> = 1.1 x V <sub>F</sub>	tr = 5 ns		10		ns
V <sub>FP</sub>	T <sub>j</sub> = 25°C	I <sub>F</sub> = 1A	tr = 5 ns		1.5		V


### TURN-OFF SWITCHING CHARACTERISTICS

Symbol	Test Conditions			Min.	Typ.	Max.	Unit
I <sub>RM</sub>	T <sub>j</sub> = 100°C	I <sub>F</sub> = 100A L <sub>p</sub> ® 0.05µH V <sub>cc</sub> ® 0.6 V <sub>RRM</sub>	dI <sub>F</sub> /dt = -200A/µs			16	A
			dI <sub>F</sub> /dt = -400A/µs		24		


**Fig.1 :** Average forward power dissipation versus average forward current.




**Fig.3 :** Forward voltage drop versus forward current (maximum values).




**Fig.5 :** Non repetitive surge peak forward current versus overload duration.




**Fig.2 :** Peak current versus form factor.



**Fig.4 :** Relative variation of thermal impedance junction to case versus pulse duration.




**Fig.6 :** Average current versus ambient temperature. (duty cycle : 0.5)




## BYV255V

---


**Fig.7** : Junction capacitance versus reverse voltage applied (Typical values).




**Fig.9** : Peak reverse current versus dIF/dt.




**Fig.8** : Recovery charges versus dIF/dt.



**Fig.10** : Dynamic parameters versus junction temperature.



**PACKAGE MECHANICAL DATA**  
**ISOTOP**


REF.	DIMENSIONS			
	Millimeters		Inches	
	Min.	Max.	Min.	Max.
A	11.80	12.20	0.465	0.480
A1	8.90	9.10	0.350	0.358
B	7.8	8.20	0.307	0.323
C	0.75	0.85	0.030	0.033
C2	1.95	2.05	0.077	0.081
D	37.80	38.20	1.488	1.504
D1	31.50	31.70	1.240	1.248
E	25.15	25.50	0.990	1.004
E1	23.85	24.15	0.939	0.951
E2	24.80 typ.		0.976 typ.	
G	14.90	15.10	0.587	0.594
G1	12.60	12.80	0.496	0.504
G2	3.50	4.30	0.138	0.169
F	4.10	4.30	0.161	0.169
F1	4.60	5.00	0.181	0.197
P	4.00	4.30	0.157	0.69
P1	4.00	4.40	0.157	0.173
S	30.10	30.30	1.185	1.193

- **Marking :** Type number
- **Cooling method :** C
- **Weight :** 27 g
- **Epoxy meets UL94, V0**

Information furnished is believed to be accurate and reliable. However, STMicroelectronics assumes no responsibility for the consequences of use of such information nor for any infringement of patents or other rights of third parties which may result from its use. No license is granted by implication or otherwise under any patent or patent rights of STMicroelectronics. Specifications mentioned in this publication are subject to change without notice. This publication supersedes and replaces all information previously supplied.

STMicroelectronics products are not authorized for use as critical components in life support devices or systems without express written approval of STMicroelectronics.

The ST logo is a registered trademark of STMicroelectronics

© 2000 STMicroelectronics - Printed in Italy - All rights reserved.

STMicroelectronics GROUP OF COMPANIES

Australia - Brazil - China - Finland - France - Germany - Hong Kong - India - Italy - Japan - Malaysia  
Malta - Morocco - Singapore - Spain - Sweden - Switzerland - United Kingdom - U.S.A.

<http://www.st.com>