

## HIGH SIDE SMART POWER SOLID STATE RELAY

| TYPE  | V <sub>DSS</sub> | R <sub>DS(on)</sub> | I <sub>OUT</sub> | V <sub>CC</sub> |
|-------|------------------|---------------------|------------------|-----------------|
| VN05N | 60 V             | 0.18 $\Omega$       | 13 A             | 26 V            |

- OUTPUT CURRENT (CONTINUOUS): 13A @ T<sub>c</sub>=25°C
- 5V LOGIC LEVEL COMPATIBLE INPUT
- THERMAL SHUT-DOWN
- UNDER VOLTAGE SHUT-DOWN
- OPEN DRAIN DIAGNOSTIC OUTPUT
- VERY LOW STAND-BY POWER DISSIPATION


### DESCRIPTION

The VN05N is a monolithic device made using SGS-THOMSON Vertical Intelligent Power Technology, intended for driving resistive or inductive loads with one side grounded.

Built-in thermal shut-down protects the chip from over temperature and short circuit.

The input control is 5V logic level compatible.


The open drain diagnostic output indicates open circuit (no load) and over temperature status.



### ORDER CODES:

|                      |              |
|----------------------|--------------|
| PENTAWATT vertical   | VN05N        |
| PENTAWATT horizontal | VN05N (011Y) |
| PENTAWATT in-line    | VN05N (012Y) |


### BLOCK DIAGRAM




## ABSOLUTE MAXIMUM RATING

| Symbol        | Parameter                                         | Value      | Unit             |
|---------------|---------------------------------------------------|------------|------------------|
| $V_{(BR)DSS}$ | Drain-Source Breakdown Voltage                    | 60         | V                |
| $I_{OUT}$     | Output Current (cont.)                            | 13         | A                |
| $I_R$         | Reverse Output Current                            | -13        | A                |
| $I_{IN}$      | Input Current                                     | $\pm 10$   | mA               |
| $-V_{CC}$     | Reverse Supply Voltage                            | -4         | V                |
| $I_{STAT}$    | Status Current                                    | $\pm 10$   | mA               |
| $V_{ESD}$     | Electrostatic Discharge (1.5 k $\Omega$ , 100 pF) | 2000       | V                |
| $P_{tot}$     | Power Dissipation at $T_c \leq 25^\circ\text{C}$  | 56         | W                |
| $T_j$         | Junction Operating Temperature                    | -40 to 150 | $^\circ\text{C}$ |
| $T_{stg}$     | Storage Temperature                               | -55 to 150 | $^\circ\text{C}$ |

## CONNECTION DIAGRAM



## CURRENT AND VOLTAGE CONVENTIONS



## THERMAL DATA

|                |                                     |     |     |               |
|----------------|-------------------------------------|-----|-----|---------------|
| $R_{thj-case}$ | Thermal Resistance Junction-case    | Max | 2.2 | $^{\circ}C/W$ |
| $R_{thj-amb}$  | Thermal Resistance Junction-ambient | Max | 60  | $^{\circ}C/W$ |

ELECTRICAL CHARACTERISTICS ( $V_{CC} = 13 V$ ;  $-40 \leq T_j \leq 125^{\circ}C$  unless otherwise specified)

## POWER

| Symbol   | Parameter           | Test Conditions                                            | Min. | Typ. | Max.         | Unit                 |
|----------|---------------------|------------------------------------------------------------|------|------|--------------|----------------------|
| $V_{CC}$ | Supply Voltage      |                                                            | 7    |      | 26           | V                    |
| $R_{on}$ | On State Resistance | $I_{OUT} = 6 A$<br>$I_{OUT} = 6 A \quad T_j = 25^{\circ}C$ |      |      | 0.36<br>0.18 | $\Omega$<br>$\Omega$ |
| $I_S$    | Supply Current      | Off State<br>On State $T_j \geq 25^{\circ}C$               |      |      | 50<br>15     | $\mu A$<br>mA        |

## SWITCHING

| Symbol          | Parameter                             | Test Conditions                                                                     | Min. | Typ. | Max.     | Unit                     |
|-----------------|---------------------------------------|-------------------------------------------------------------------------------------|------|------|----------|--------------------------|
| $t_{d(on)}$     | Turn-on Delay Time Of Output Current  | $I_{OUT} = 6 A$ Resistive Load<br>Input Rise Time $< 0.1 \mu s$ $T_j = 25^{\circ}C$ |      | 15   |          | $\mu s$                  |
| $t_r$           | Rise Time Of Output Current           | $I_{OUT} = 6 A$ Resistive Load<br>Input Rise Time $< 0.1 \mu s$ $T_j = 25^{\circ}C$ |      | 30   |          | $\mu s$                  |
| $t_{d(off)}$    | Turn-off Delay Time Of Output Current | $I_{OUT} = 6 A$ Resistive Load<br>Input Rise Time $< 0.1 \mu s$ $T_j = 25^{\circ}C$ |      | 20   |          | $\mu s$                  |
| $t_f$           | Fall Time Of Output Current           | $I_{OUT} = 6 A$ Resistive Load<br>Input Rise Time $< 0.1 \mu s$ $T_j = 25^{\circ}C$ |      | 10   |          | $\mu s$                  |
| $(di/dt)_{on}$  | Turn-on Current Slope                 | $I_{OUT} = 6 A$<br>$I_{OUT} = I_{OV}$                                               |      |      | 0.5<br>2 | A/ $\mu s$<br>A/ $\mu s$ |
| $(di/dt)_{off}$ | Turn-off Current Slope                | $I_{OUT} = 6 A$<br>$I_{OUT} = I_{OV}$                                               |      |      | 2<br>4   | A/ $\mu s$<br>A/ $\mu s$ |

## LOGIC INPUT

| Symbol         | Parameter                | Test Conditions                       | Min. | Typ.      | Max. | Unit    |
|----------------|--------------------------|---------------------------------------|------|-----------|------|---------|
| $V_{IL}$       | Input Low Level Voltage  |                                       |      |           | 0.8  | V       |
| $V_{IH}$       | Input High Level Voltage |                                       | 2    |           | (*)  | V       |
| $V_{I(hyst.)}$ | Input Hysteresis Voltage |                                       |      | 0.5       |      | V       |
| $I_{IN}$       | Input Current            | $V_{IN} = 5 V$                        |      | 250       | 500  | $\mu A$ |
| $V_{ICL}$      | Input Clamp Voltage      | $I_{IN} = 10 mA$<br>$I_{IN} = -10 mA$ |      | 6<br>-0.7 |      | V<br>V  |

## PROTECTIONS AND DIAGNOSTICS

| Symbol               | Parameter                 | Test Conditions     | Min. | Typ. | Max. | Unit |
|----------------------|---------------------------|---------------------|------|------|------|------|
| $V_{STAT} (\bullet)$ | Status Voltage Output Low | $I_{STAT} = 1.6 mA$ |      |      | 0.4  | V    |
| $V_{USD}$            | Under Voltage Shut Down   |                     |      | 6.5  |      | V    |

**ELECTRICAL CHARACTERISTICS** (continued)**PROTECTION AND DIAGNOSTICS** (continued)

| Symbol        | Parameter                                              | Test Conditions                                                                | Min. | Typ.      | Max. | Unit             |
|---------------|--------------------------------------------------------|--------------------------------------------------------------------------------|------|-----------|------|------------------|
| $V_{SCL}$ (•) | Status Clamp Voltage                                   | $I_{STAT} = 10 \text{ mA}$<br>$I_{STAT} = -10 \text{ mA}$                      |      | 6<br>-0.7 |      | V<br>V           |
| $t_{SC}$      | Switch-off Time in Short Circuit Condition at Start-Up | $R_{LOAD} < 10 \text{ m}\Omega$ $T_c = 25 \text{ }^\circ\text{C}$              |      | 1.5       | 5    | ms               |
| $I_{OV}$      | Over Current                                           | $R_{LOAD} < 10 \text{ m}\Omega$ $-40 \leq T_c \leq 125 \text{ }^\circ\text{C}$ |      |           | 60   | A                |
| $I_{AV}$      | Average Current in Short Circuit                       | $R_{LOAD} < 10 \text{ m}\Omega$ $T_c = 85 \text{ }^\circ\text{C}$              |      | 1.4       |      | A                |
| $I_{OL}$      | Open Load Current Level                                |                                                                                | 5    |           | 180  | mA               |
| $T_{TSD}$     | Thermal Shut-down Temperature                          |                                                                                | 140  |           |      | $^\circ\text{C}$ |
| $T_R$         | Reset Temperature                                      |                                                                                | 125  |           |      | $^\circ\text{C}$ |

(\*) The  $V_{IH}$  is internally clamped at 6V about. It is possible to connect this pin to an higher voltage via an external resistor calculated to not exceed 10 mA at the input pin.

(•) Status determination > 100  $\mu\text{s}$  after the switching edge.

**FUNCTIONAL DESCRIPTION**

The device has a diagnostic output which indicates open circuit (no load) and over temperature conditions. The output signals are processed by internal logic.

To protect the device against short circuit and over-current condition, the thermal protection turns the integrated Power MOS off at a minimum junction temperature of  $140 \text{ }^\circ\text{C}$ . When the temperature returns to about  $125 \text{ }^\circ\text{C}$  the switch is automatically turned on again.

In short circuit conditions the protection reacts with virtually no delay, the sensor being located in the region of the die where the heat is generated.

**PROTECTING THE DEVICE AGAINST REVERSE BATTERY**

The simplest way to protect the device against a continuous reverse battery voltage (-26V) is to insert a Schottky diode between pin 1 (GND) and ground, as shown in the typical application circuit (fig. 3).

The consequences of the voltage drop across this diode are as follows:

- If the input is pulled to power GND, a negative voltage of  $-V_F$  is seen by the device. ( $V_{IL}$ ,  $V_{IH}$  thresholds and  $V_{STAT}$  are increased by  $V_F$  with respect to power GND).
- The undervoltage shutdown level is increased by  $V_F$ .

If there is no need for the control unit to handle external analog signals referred to the power GND, the best approach is to connect the reference potential of the control unit to node [1] (see application circuit in fig. 4), which becomes the common signal GND for the whole control board.

In this way no shift of  $V_{IH}$ ,  $V_{IL}$  and  $V_{STAT}$  takes place and no negative voltage appears on the INPUT pin; this solution allows the use of a standard diode, with a breakdown voltage able to handle any ISO normalized negative pulses that occurs in the automotive environment.

## TRUTH TABLE

|                        | INPUT  | OUTPUT | DIAGNOSTIC |
|------------------------|--------|--------|------------|
| Normal Operation       | L<br>H | L<br>H | H<br>H     |
| Open Circuit (No Load) | H      | H      | L          |
| Over-temperature       | H      | L      | L          |
| Under-voltage          | X      | L      | H          |

Figure 1: Waveforms











Figure 2: Over Current Test Circuit




**Figure 3:** Typical Application Circuit With A Schottky Diode For Reverse Supply Protection**Figure 4:** Typical Application Circuit With Separate Signal Ground

$R_{DS(on)}$  vs Junction Temperature $R_{DS(on)}$  vs Supply Voltage $R_{DS(on)}$  vs Output Current


Input voltages vs Junction Temperature



Output Current Derating




Open Load vs Junction Temperature



# Pentawatt (vertical) MECHANICAL DATA


| DIM. | mm    |       |      | inch  |       |       |
|------|-------|-------|------|-------|-------|-------|
|      | MIN.  | TYP.  | MAX. | MIN.  | TYP.  | MAX.  |
| A    |       |       | 4.8  |       |       | 0.189 |
| C    |       |       | 1.37 |       |       | 0.054 |
| D    | 2.4   |       | 2.8  | 0.094 |       | 0.110 |
| D1   | 1.2   |       | 1.35 | 0.047 |       | 0.053 |
| E    | 0.35  |       | 0.55 | 0.014 |       | 0.022 |
| F    | 0.8   |       | 1.05 | 0.031 |       | 0.041 |
| F1   | 1     |       | 1.4  | 0.039 |       | 0.055 |
| G    | 3.2   | 3.4   | 3.6  | 0.126 | 0.134 | 0.142 |
| G1   | 6.6   | 6.8   | 7    | 0.260 | 0.268 | 0.276 |
| H2   |       |       | 10.4 |       |       | 0.409 |
| H3   | 10.05 |       | 10.4 | 0.396 |       | 0.409 |
| L    |       | 17.85 |      |       | 0.703 |       |
| L1   |       | 15.75 |      |       | 0.620 |       |
| L2   |       | 21.4  |      |       | 0.843 |       |
| L3   |       | 22.5  |      |       | 0.886 |       |
| L5   | 2.6   |       | 3    | 0.102 |       | 0.118 |
| L6   | 15.1  |       | 15.8 | 0.594 |       | 0.622 |
| L7   | 6     |       | 6.6  | 0.236 |       | 0.260 |
| M    |       | 4.5   |      |       | 0.177 |       |
| M1   |       | 4     |      |       | 0.157 |       |
| Dia  | 3.65  |       | 3.85 | 0.144 |       | 0.152 |



P010E


### Pentawatt (horizontal) MECHANICAL DATA

| DIM. | mm    |      |      | inch  |       |       |
|------|-------|------|------|-------|-------|-------|
|      | MIN.  | TYP. | MAX. | MIN.  | TYP.  | MAX.  |
| A    |       |      | 4.8  |       |       | 0.189 |
| C    |       |      | 1.37 |       |       | 0.054 |
| D    | 2.4   |      | 2.8  | 0.094 |       | 0.110 |
| D1   | 1.2   |      | 1.35 | 0.047 |       | 0.053 |
| E    | 0.35  |      | 0.55 | 0.014 |       | 0.022 |
| F    | 0.8   |      | 1.05 | 0.031 |       | 0.041 |
| F1   | 1     |      | 1.4  | 0.039 |       | 0.055 |
| G    | 3.2   | 3.4  | 3.6  | 0.126 | 0.134 | 0.142 |
| G1   | 6.6   | 6.8  | 7    | 0.260 | 0.268 | 0.276 |
| H2   |       |      | 10.4 |       |       | 0.409 |
| H3   | 10.05 |      | 10.4 | 0.396 |       | 0.409 |
| L    | 14.2  |      | 15   | 0.559 |       | 0.590 |
| L1   | 5.7   |      | 6.2  |       |       | 0.244 |
| L2   | 14.6  |      | 15.2 |       |       | 0.598 |
| L3   | 3.5   |      | 4.1  | 0.137 |       | 0.161 |
| L5   | 2.6   |      | 3    | 0.102 |       | 0.118 |
| L6   | 15.1  |      | 15.8 | 0.594 |       | 0.622 |
| L7   | 6     |      | 6.6  | 0.236 |       | 0.260 |
| Dia  | 3.65  |      | 3.85 | 0.144 |       | 0.152 |



### Pentawatt (In- Line) MECHANICAL DATA

| DIM. | mm    |       |      | inch  |       |       |
|------|-------|-------|------|-------|-------|-------|
|      | MIN.  | TYP.  | MAX. | MIN.  | TYP.  | MAX.  |
| A    |       |       | 4.8  |       |       | 0.189 |
| C    |       |       | 1.37 |       |       | 0.054 |
| D    | 2.4   |       | 2.8  | 0.094 |       | 0.110 |
| D1   | 1.2   |       | 1.35 | 0.047 |       | 0.053 |
| E    | 0.35  |       | 0.55 | 0.014 |       | 0.022 |
| F    | 0.8   |       | 1.05 | 0.031 |       | 0.041 |
| F1   | 1     |       | 1.4  | 0.039 |       | 0.055 |
| G    | 3.2   | 3.4   | 3.6  | 0.126 | 0.134 | 0.142 |
| G1   | 6.6   | 6.8   | 7    | 0.260 | 0.268 | 0.276 |
| H2   |       |       | 10.4 |       |       | 0.409 |
| H3   | 10.05 |       | 10.4 | 0.396 |       | 0.409 |
| L2   | 23.05 | 23.4  | 23.8 | 0.907 | 0.921 | 0.937 |
| L3   | 25.3  | 25.65 | 26.1 | 0.996 | 1.010 | 1.028 |
| L5   | 2.6   |       | 3    | 0.102 |       | 0.118 |
| L6   | 15.1  |       | 15.8 | 0.594 |       | 0.622 |
| L7   | 6     |       | 6.6  | 0.236 |       | 0.260 |
| Dia  | 3.65  |       | 3.85 | 0.144 |       | 0.152 |



Information furnished is believed to be accurate and reliable. However, SGS-THOMSON Microelectronics assumes no responsibility for the consequences of use of such information nor for any infringement of patents or other rights of third parties which may result from its use. No license is granted by implication or otherwise under any patent or patent rights of SGS-THOMSON Microelectronics. Specifications mentioned in this publication are subject to change without notice. This publication supersedes and replaces all information previously supplied. SGS-THOMSON Microelectronics products are not authorized for use as critical components in life support devices or systems without express written approval of SGS-THOMSON Microelectronics.

© 1994 SGS-THOMSON Microelectronics - All Rights Reserved

SGS-THOMSON Microelectronics GROUP OF COMPANIES

Australia - Brazil - France - Germany - Hong Kong - Italy - Japan - Korea - Malaysia - Malta - Morocco - The Netherlands -  
Singapore - Spain - Sweden - Switzerland - Taiwan - Thailand - United Kingdom - U.S.A