

V _{RSM}	V _{RRM} V _{DRM}	(dv/dt) _{cr}	I _T RMS (maximum values for continuous operation)	
			450 A	550 A
V	V	V/μs	I _{TAV} (sin. 180; T _{case} = . . . °C)	
			285 A (77 °C)	350 A (85 °C)
500	400	500	SKT 250/04 D	SKT 300/04 D
900	800	500	SKT 250/08 D	SKT 300/08 D*
1300	1200	1000	SKT 250/12 E	SKT 300/12 E*
1500	1400	1000	SKT 250/14 E	SKT 300/14 E*
1700	1600	1000	SKT 250/16 E	SKT 300/16 E*

Thyristors

SKT 250 SKT 300



Features

- Hermetic metal cases with ceramic insulators
- Threaded studs ISO M24 x 1,5 or UNF 3/4-16
- High i²t and I_{TSM} values for easy fusing
- International standard cases

Typical Applications

- DC motor control (e. g. for machine tools)
- Controlled rectifiers (e. g. for battery charging)
- AC controllers (e. g. for temperature control)

Symbol	Conditions	SKT 250	SKT 300	Units
I _{TAV}	sin. 180; (T _{case} = . . .)	250 (85 °C)	300 (93 °C)	A
I _{TSM}	T _{vj} = 25 °C; 10 ms T _{vj} = 130 °C; 10 ms	7000 6000	11 000 10 000	A A
i ² t	T _{vj} = 25 °C; 8,35 ... 10 ms T _{vj} = 130 °C; 8,35 ... 10 ms	245 000 180 000	600 000 500 000	A ² s A ² s
t _{gd}	T _{vj} = 25 °C; I _G = 1 A; di _G /dt = 1 A/μs	typ. 1		μs
t _{gr}	V _D = 0,67 · V _{DRM}	typ. 2		μs
(di/dt) _{cr}	f = 50 ... 60 Hz	100		A/μs
I _H	T _{vj} = 25 °C;	typ. 150; max. 250		mA
I _L	T _{vj} = 25 °C; R _G = 33 Ω	typ. 300; max. 600		mA
t _q	T _{vj} = 130 °C; typ.	50 ... 150		μs
V _T	T _{vj} = 25 °C; I _T = 800 A; max.	1,65	1,45	V
V _{T(TO)}	T _{vj} = 130 °C	1,0	0,9	V
r _T	T _{vj} = 130 °C	0,7	0,5	mΩ
I _{DD} , I _{RD}	T _{vj} = 130 °C; V _{DD} = V _{DRM} V _{RD} = V _{RRM}	50	50	mA
V _{GT}	T _{vj} = 25 °C	3		V
I _{GT}	T _{vj} = 25 °C	200		mA
V _{GD}	T _{vj} = 130 °C	0,25		V
I _{GD}	T _{vj} = 130 °C	10		mA
R _{thjc}	cont.	0,110	0,090	°C/W
	sin. 180	0,123	0,096	°C/W
	rec. 120	0,137	0,101	°C/W
R _{thch}		0,015		°C/W
T _{vj}		- 40 ... +130		°C
T _{stg}		- 55 ... +150		°C
M	SI units	60 (UNF: 30)		Nm
a	US units	530 (UNF: 265)		lb. in.
w		5 · 9,81		m/s ²
		450		g
Case		B 7		

* available with UNF thread 3/4-16 UNF2A, e.g. SKT 300/08 D UNF




Fig. 1 a Power dissipation vs. on-state current and ambient temperature




Fig. 1 b Power dissipation vs. on-state current and ambient temperature




Fig. 2 a Rated on-state current vs. case temperature




Fig. 2 b Rated on-state current vs. case temperature




Fig. 3 Recovered charge vs. current decrease




Fig. 4 a Transient thermal impedance vs. time




Fig. 4 b Transient thermal impedance vs. time




Fig. 5 a Thermal resistance vs. conduction angle




Fig. 5 b Thermal resistance vs. conduction angle




Fig. 6 a On-state characteristics




Fig. 6 b On-state characteristics




Fig. 7 a Power dissipation vs. on-state current




Fig. 7 b Power dissipation vs. on-state current




Fig. 8 Surge overload current vs. time




Fig. 9 Gate trigger characteristics


SKT 250
SKT 300

Case B 7

IEC-Publ. 191-2: A 29 MA

DIN 41893: (207 B 4)

JEDEC: TO-209 AD (TO-118)



C:	Cathode terminal (red sleeve)	Dimensions in mm
1		
2		
3		
4		
5		
6		
7		
8		
9		
10		
11		
12		
13		
14		
15		
16		
17		
18		
19		
20		
21		
22		
23		
24		
25		
26		
27		
28		
29		
30		
31		
32		
33		
34		
35		
36		
37		
38		
39		
40		
41		
42		
43		
44		
45		
46		
47		
48		
49		
50		
51		
52		
53		
54		
55		
56		
57		
58		
59		
60		
61		
62		
63		
64		
65		
66		
67		
68		
69		
70		
71		
72		
73		
74		
75		
76		
77		
78		
79		
80		
81		
82		
83		
84		
85		
86		
87		
88		
89		
90		
91		
92		
93		
94		
95		
96		
97		
98		
99		
100		

A: Anode terminal

G: Gate terminal (yellow sleeve)

HK: Auxiliary cathode terminal (red sleeve)