



www.xicor.com

1511 Buckeye Drive • Milpitas, CA 95035 • Tel: (408) 432-8888 • Fax: (408) 432-0640

Mixed Signal Products

Product	Description	Pkg Code	Temp Range	SFX	VCC (V)	ICC (MA)	ISB (UA)	Freq (MHZ)	TAA (NS)
X9316Z/W	SINGLE XDCCP, LOW POWER 32 TAP +/- 5 VOLTS	P14 S(14)	C,I	*	4.5-5.5	3	1	-	-
			C,I	-3	3.0-5.5	3	1	-	-
X9317 Z/W/U/T/ N/L	SINGLE XDCCP, LOW POWER 100 TAP +/- 5 VOLTS	S8, V8 P	C,I	*	4.5-5.5	0.4	1	-	-
			C,I	-2.7	2.7-5.5	0.4	1	-	-
X9420 Y/W	SINGLE XDCCP, 64 TAP +/- 5 VOLTS	S16 V14	C,I,M	*	4.5-5.5	0.4	1	-	-
			C,I	-2.7	2.7-5.5	0.4	1		
X9410/18 Y/W	DUAL XDCCP, 64 TAP +/- 5 VOLTS	S24 V24	C,I,M	*	4.5-5.5	0.4	1	-	-
			C,I	-2.7	2.7-5.5	0.4	1		
X9400/08 Y/W	QUAD XDCCP, 64 TAP +/- 5 VOLTS	S24 V24	C,I,M	*	4.5-5.5	0.4	1	-	-
			C,I	-2.7	2.7-5.5	0.4	1		
X9430/38 Y/W	SMART OP AMP	S24 V24	C,I,M	*	4.5-5.5	0.4	1	-	-
			C,I	-2.7	2.7-5.5	0.4	1		
X9440/48 Y/W	SMART COMPARATOR	S24 V24	C,I,M	*	4.5-5.5	0.4	1	-	-
			C,I	-2.7	2.7-5.5	0.4	1		
X9511Z/W	PUSHPOT 32 TAP +/- 5 VOLTS	P,S	C,I,M	*	4.5-5.5	3	500	-	-
X9514W	PUSHPOT, LOG TAPER 32 TAP +/- 5 VOLTS	P,S	C,I,M	*	4.5-5.5	3	500	-	-
X9C102	SINGLE XDCCP 100 TAP +/- 5 VOLTS	P,S D	C,I,M	*	4.5-5.5	3	500	-	-
X9C103	SINGLE XDCCP 100 TAP +/- 5 VOLTS	P,S D	C,I,M	*	4.5-5.5	3	500	-	-
X9C104	SINGLE XDCCP 100 TAP +/- 5 VOLTS	P,S D	C,I,M	*	4.5-5.5	3	500	-	-
X9C303	SINGLE XDCCP LOG TAPER 100 TAP +/- 5 VOLTS	P,S V8	C,I,M	*	4.5-5.5	3	500	-	-
X9C503	SINGLE XDCCP 100 TAP +/- 5 VOLTS	P,S D	C,I,M	*	4.5-5.5	3	500	-	-

Security Products

Product	Description	Density	Pkg Code	Temp Range	SFX	VCC (V)	ICC (MA)	ISB (UA)	Freq (MHZ)	TAA (NS)
X76F100	SECURE SERIAL FLASH WITH PASSWORD PROTECT AND 2-WIRE SERIAL INTERFACE	896 BITS	P,S,X, M	C,E	*	4.5-5.5	3	100	1	-
					-3	3.0-3.6	3	50	1	-
X76F102	SECURE SECURE SERIAL FLASH	896 BITS	V,X	C,E	*	4.5-5.5	3	50	1	-
					-2	2.0-5.5	3	50	1	-

PKG Codes: P=PDIP, D=CERDIP, S=SOIC, M=MSOP, J=PLCC, E=LCC, L=TQFP, V=TSSOP, X=COB, Y=ISO CARD
Resistor Values (Ohms): Z=1K, Y=2K, W=10K, U=50K, T=100K, M=2K, 10K, 10K, 50K, SFX ***="Blank"

Xicor