

## LM193A/LM193QML

# Low Power Low Offset Voltage Dual Comparators

### General Description

The LM193 series consists of two independent precision voltage comparators with an offset voltage specification as low as 2.0 mV max for two comparators which were designed specifically to operate from a single power supply over a wide range of voltages. Operation from split power supplies is also possible and the low power supply current drain is independent of the magnitude of the power supply voltage. These comparators also have a unique characteristic in that the input common-mode voltage range includes ground, even though operated from a single power supply voltage.

Application areas include limit comparators, simple analog to digital converters; pulse, squarewave and time delay generators; wide range VCO; MOS clock timers; multivibrators and high voltage digital logic gates. The LM193 series was designed to directly interface with TTL and CMOS. When operated from both plus and minus power supplies, the LM193 series will directly interface with MOS logic where their low power drain is a distinct advantage over standard comparators.

### Advantages

- High precision comparators
- Reduced  $V_{OS}$  drift over temperature
- Eliminates need for dual supplies
- Allows sensing near ground
- Compatible with all forms of logic
- Power drain suitable for battery operation


### Features

- Wide supply
  - Voltage range:  $2.0V_{DC}$  to  $36V_{DC}$
  - Single or dual supplies:  $\pm 1.0V$  to  $\pm 18V$
- Very low supply current drain (0.4 mA) — independent of supply voltage
- Low input biasing current: 25 nA typ
- Low input offset current:  $\pm 5$  nA typ
- Input common-mode voltage range includes ground
- Differential input voltage range equal to the power supply voltage
- Low output saturation voltage, : 250 mV at 4 mA typ
- Output voltage compatible with TTL, DTL, ECL, MOS and CMOS logic systems

### Ordering Information


NS Part Number	JAN Part Number	NS Package Number	Package Description
LM193H/883		H08C	8LD T0-99 Metal Can
LM193J/883		J08A	8LD Cerdip
LM193AH/883	5962-9452602MGA	H08C	8LD T0-99 Metal Can
LM193AJ/883	5962-9452602MPA	J08A	8LD Cerdip
LM193AH-QMLV	5962-9452602VGA	H08C	8LD T0-99 Metal Can
LM193AJ-QMLV	5962-9452602VPA	J08A	8LD Cerdip

Squarewave Oscillator




20139638

Non-Inverting Comparator with Hysteresis




20139609

## Schematic and Connection Diagrams




20139602

### Metal Can Package



20139603

### Dual-In-Line Package



20139601

## Absolute Maximum Ratings (Note 1)

Supply Voltage, $V^+$	$36V_{DC}$ or $\pm 18V_{DC}$
Differential Input Voltage (Note 6)	36V
Input Voltage	$-0.3V_{DC}$ to $+36V_{DC}$
Input Current ( $V_{IN} < -0.3V_{DC}$ ) (Note 5)	50 mA
Maximum Junction Temperature	150°C
Power Dissipation (Note 2), (Note 3)	
Metal Can	660 mW
CERDIP	780 mW
Output Short-Circuit to Ground (Note 4)	Continuous
Operating Temperature Range	$-55^{\circ}\text{C} \leq T_A \leq +125^{\circ}\text{C}$
Storage Temperature Range	$-65^{\circ}\text{C} \leq T_A \leq +150^{\circ}\text{C}$
Thermal Resistance	
$\theta_{JA}$	
Metal Can (Still Air)	174°C/W
Metal Can (500LF/Min Air flow)	99°C/W
CERDIP (Still Air)	146°C/W
CERDIP (500LF/Min Air flow)	85°C/W
$\theta_{JC}$	
Metal Can	44°C/W
CERDIP	33°C/W
Lead Temperature (Soldering, 10 seconds)	260°C
ESD Tolerance (Note 7)	500V

## Quality Conformance Inspection

Mil-Std-883, Method 5005 - Group A

Subgroup	Description	Temp°C
1	Static tests at	25
2	Static tests at	125
3	Static tests at	-55
4	Dynamic tests at	25
5	Dynamic tests at	125
6	Dynamic tests at	-55
7	Functional tests at	25
8A	Functional tests at	125
8B	Functional tests at	-55
9	Switching tests at	25
10	Switching tests at	125
11	Switching tests at	-55
12	Settling time at	25
13	Settling time at	125
14	Settling time at	-55

## LM193 Electrical Characteristics

### DC Parameters

The following conditions apply, unless otherwise specified.  $+V = 5V$ ,  $V_{CM} = 0V$

Symbol	Parameter	Conditions	Notes	Min	Max	Unit	Sub-groups
$I_{CC}$	Supply Current				1.0	mA	1, 2, 3
		$+V = 36V$			2.5	mA	1, 2, 3
$I_{CEX}$	Output Leakage Current	$+V = 30V$ , $+V_I = 1V$ , $V_O = 30V$ , $-V_I = 0V$		-0.65	0.65	$\mu A$	1
				-1.0	1.0	$\mu A$	2, 3
$I_{Sink}$	Output Sink Current	$V_O = 1.5V$ , $-V_I = 1V$ , $+V_I = 0V$		6.0		mA	1
$V_{Sat}$	Output Saturation Voltage	$I_{Sink} = 4mA$ , $-V_I = 1V$ , $+V_I = 0V$			0.4	V	1
					0.7	V	2, 3
$V_{IO}$	Input Offset Voltage			-5.0	5.0	mV	1
				-9.0	9.0	mV	2, 3
		$+V = 30V$		-5.0	5.0	mV	1
				-9.0	9.0	mV	2, 3
		$+V = 30V$ , $V_{CM} = 28.5V$		-5.0	5.0	mV	1
		$+V = 30V$ , $V_{CM} = 28.0V$		-9.0	9.0	mV	2, 3
$\pm I_{IB}$	Input Bias Current			-100	-1.0	nA	1
				-300	-1.0	nA	2, 3
$I_{IO}$	Input offset Current	$R_S = 50\Omega$		-25	25	nA	1
				-100	100	nA	2, 3
$V_{CM}$	Common Mode Voltage	$+V = 30V$	(Note 8)		28.5	V	1
			(Note 8)		28	V	2, 3
PSRR	Power Supply Rejection Ratio	$+V = 5V$ to $30V$ , $R_S = 50\Omega$		60		dB	1
CMRR	Common Mode Rejection Ratio	$+V = 30V$ , $R_S = 50\Omega$ $V_{CM} = 0V$ to $28.5V$ ,		60		dB	1
$V_{Diff}$	Differential Input Voltage	$+V = 30V$ , $+V_I = 36V$ , $-V_I = 0V$	(Note 10)		500	nA	1, 2, 3
		$+V = 30V$ , $+V_I = 0V$ , $-V_I = +36V$	(Note 10)		500	nA	1, 2, 3
$A_{VS}$	Voltage Gain	$+V = 15V$ , $R_{PullUp} = 15K\Omega$ $1V \leq V_O \leq 11V$ ,	(Note 9)	50		V/mV	4

### AC Parameters

The following conditions apply, unless otherwise specified.  $+V = 5V$

Symbol	Parameter	Conditions	Notes	Min	Max	Unit	Sub-groups
$t_{RLH}$	Response Time	$V_{OD} = 5mV$			5.0	$\mu S$	9
		$V_{OD} = 50mV$			0.8	$\mu S$	9
$t_{RHL}$	Response Time	$V_{OD} = 5mV$			2.5	$\mu S$	9
		$V_{OD} = 50mV$			0.8	$\mu S$	9

## LM193A Electrical Characteristics

### DC Parameters

The following conditions apply, unless otherwise specified.  $+V = 5V$ ,  $V_{CM} = 0V$

Symbol	Parameter	Conditions	Notes	Min	Max	Unit	Sub-groups
$I_{CC}$	Supply Current	$R_L = \text{Infinity}$			1.0	mA	1, 2, 3
		$+V = 36V$ , $R_L = \text{Infinity}$			2.5	mA	1, 2, 3
$I_{CEX}$	Output Leakage Current	$+V = 30V$ , $+V_I = 1V$ , $V_O = 30$ , $-V_I = 0$		-0.65	0.65	$\mu A$	1
				-1.0	1.0	$\mu A$	2, 3
$I_{Sink}$	Output Sink Current	$V_O = 1.5V$ , $-V_I = 1V$ , $+V_I = 0V$		6.0		mA	1
				4.0		mA	2, 3
$V_{Sat}$	Output Saturation Voltage	$I_{Sink} = 4mA$ , $-V_I = 1V$ , $+V_I = 0V$			0.4	V	1
					0.7	V	2, 3
$V_{IO}$	Input Offset Voltage			-2.0	2.0	mV	1
				-4.0	4.0	mV	2, 3
		$+V = 30V$		-2.0	2.0	mV	1
				-4.0	4.0	mV	2, 3
		$+V = 30V$ , $V_{CM} = 28.5V$		-2.0	2.0	mV	1
		$+V = 30V$ , $V_{CM} = 28.0V$		-4.0	4.0	mV	2, 3
$\pm I_{IB}$	Input Bias Current	$V_O = 1.5V$		-100	-1.0	nA	1
				-300	-1.0	nA	2, 3
$I_{IO}$	Input offset Current	$R_S = 50\Omega$ , $V_O = 1.5V$		-25	25	nA	1
				-100	100	nA	2, 3
$V_{CM}$	Common Mode Voltage	$+V = 30V$	(Note 8)		28.5	V	1
			(Note 8)		28	V	2, 3
PSRR	Power Supply Rejection Ratio	$+V = 5V$ to $30V$ , $R_S = 50\Omega$		60		dB	1
CMRR	Common Mode Rejection Ratio	$+V = 30V$ , $R_S = 50\Omega$ $V_{CM} = 0V$ to $28.5V$ ,		60		dB	1
$V_{Diff}$	Differential Input Voltage	$+V = 30V$ , $+V_I = 36V$ , $-V_I = 0V$	(Note 10)		500	nA	1, 2, 3
		$+V = 30V$ , $+V_I = 0V$ , $-V_I = +36V$	(Note 10)		500	nA	1, 2, 3
$A_{VS}$	Voltage Gain	$+V = 15V$ , $R_{PullUp} = 15K\Omega$ $1V \leq V_O \leq 11V$ ,	(Note 9)	50		V/mV	4
			(Note 9)	25		V/mV	5, 6

### AC Parameters

The following conditions apply, unless otherwise specified.  $+V = 5V$ ,  $V_{CM} = 0V$

Symbol	Parameter	Conditions	Notes	Min	Max	Unit	Sub-groups
$t_{RLH}$	Response Time	$V_{OD} = 5mV$			5.0	$\mu S$	9
		$V_{OD} = 50mV$			0.8	$\mu S$	9
$t_{RHL}$	Response Time	$V_{OD} = 5mV$			2.5	$\mu S$	9
		$V_{OD} = 50mV$			0.8	$\mu S$	9

## LM193A Electrical Characteristics (Continued)

### DC Drift Parameters

The following conditions apply, unless otherwise specified.  $+V = 5V$ ,  $V_{CM} = 0V$

Delta calculations performed on QMLV devices at Group B, Subgroup 5 only

Symbol	Parameter	Conditions	Notes	Min	Max	Unit	Sub-groups
$V_{IO}$	Input Offset Voltage	$+V = 30V$		-1.0	1.0	mV	1
$\pm I_{IB}$	Input Bias Current			-15	15	nA	1

**Note 1:** Absolute Maximum Ratings indicate limits beyond which damage to the device may occur. Operating Ratings indicate conditions for which the device is functional, but do not guarantee specific performance limits. For guaranteed specifications and test conditions, see the Electrical Characteristics. The guaranteed specifications apply only for the test conditions listed. Some performance characteristics may degrade when the device is not operated under the listed test conditions.

**Note 2:** The maximum power dissipation must be derated at elevated temperatures and is dictated by  $T_{Jmax}$  (maximum junction temperature),  $\theta_{JA}$  (package junction to ambient thermal resistance), and  $T_A$  (ambient temperature). The maximum allowable power dissipation at any temperature is  $P_{Dmax} = (T_{Jmax} - T_A)/\theta_{JA}$  or the number given in the Absolute Maximum Ratings, whichever is lower.

**Note 3:** The LM193A must be derated based on a  $150^\circ C$ ,  $T_{Jmax}$ . The low bias dissipation and the ON-OFF characteristic of the outputs keep the chip dissipation very small ( $P_D \leq 100mW$ ), provided the output transistors are allowed to saturate.

**Note 4:** Short circuits from the output to  $V^+$  can cause excessive heating and eventual destruction. When considering short circuits to ground, the maximum output current is approximately 20 mA independent of the magnitude of  $V^+$ .

**Note 5:** This input current will only exist when the voltage at any of the input leads is driven negative. It is due to the collector-base junction of the input PNP transistors becoming forward biased and thereby acting as input diode clamps. In addition to this diode action, there is also lateral NPN parasitic transistor action on the IC chip. This transistor action can cause the output voltages of the comparators to go to the  $V^+$  voltage level (or to ground for a large overdrive) for the time duration that an input is driven negative. This is not destructive and normal output states will re-establish when the input voltage, which was negative, again returns to a value greater than  $-0.3V_{DC}$ .

**Note 6:** Positive excursions of input voltage may exceed the power supply level. As long as the other voltage remains within the common-mode range, the comparator will provide a proper output state. The low input voltage state must not be less than  $-0.3V$  (or  $0.3V$  below the magnitude of the negative power supply, if used).

**Note 7:** Human body model,  $1.5K\Omega$  in series with  $100pF$ .


**Note 8:** Parameter guaranteed by the  $V_{IO}$  tests.

**Note 9:** Datalog reading in  $K = V/mV$ .

**Note 10:** The value for  $V_{Dff}$  is not datalogged during Read and Record.


## Typical Performance Characteristics

Supply Current




20139625

Input Current




20139626

Output Saturation Voltage




20139627

Response Time for Various Input Overdrives — Negative Transition



20139628

Response Time for Various Input Overdrives — Positive Transition



20139629

## Application Hints

The LM193 series are high gain, wide bandwidth devices which, like most comparators, can easily oscillate if the output lead is inadvertently allowed to capacitively couple to the inputs via stray capacitance. This shows up only during the output voltage transition intervals as the comparator change states. Power supply bypassing is not required to solve this problem. Standard PC board layout is helpful as it reduces stray input-output coupling. Reducing the input resistors to  $< 10\text{ K}\Omega$  reduces the feedback signal levels and finally, adding even a small amount (1.0 to 10 mV) of positive feedback (hysteresis) causes such a rapid transition that oscillations due to stray feedback are not possible. Simply socketing the IC and attaching resistors to the pins will cause input-output oscillations during the small transition intervals unless hysteresis is used. If the input signal is a pulse waveform, with relatively fast rise and fall times, hysteresis is not required.

All input pins of any unused comparators should be tied to the negative supply.

The bias network of the LM193 series establishes a drain current which is independent of the magnitude of the power supply voltage over the range of from  $2.0\text{ V}_{\text{DC}}$  to  $30\text{ V}_{\text{DC}}$ .


It is usually unnecessary to use a bypass capacitor across the power supply line.

The differential input voltage may be larger than  $V^+$  without damaging the device (Note 6). Protection should be provided to prevent the input voltages from going negative more than  $-0.3\text{ V}_{\text{DC}}$  (at  $25^\circ\text{C}$ ). An input clamp diode can be used as shown in the applications section.


The output of the LM193 series is the uncommitted collector of a grounded-emitter NPN output transistor. Many collectors can be tied together to provide an output OR'ing function. An output pull-up resistor can be connected to any available power supply voltage within the permitted supply voltage range and there is no restriction on this voltage due to the magnitude of the voltage which is applied to the  $V^+$  terminal of the LM193 package. The output can also be used as a simple SPST switch to ground (when a pull-up resistor is not used). The amount of current which the output device can sink is limited by the drive available (which is independent of  $V^+$ ) and the  $\beta$  of this device. When the maximum current limit is reached (approximately 16mA), the output transistor will come out of saturation and the output voltage will rise very rapidly. The output saturation voltage is limited by the approximately  $60\Omega\text{ }r_{\text{SAT}}$  of the output transistor. The low offset voltage of the output transistor (1.0mV) allows the output to clamp essentially to ground level for small load currents.

## Typical Applications $(V^+=5.0\text{ V}_{\text{DC}})$


Basic Comparator




Driving CMOS




Driving TTL



Squarewave Oscillator




Pulse Generator



\* For large ratios of  $R1/R2$ ,  $D1$  can be omitted.


Crystal Controlled Oscillator





## Typical Applications ( $V^+ = 5.0\text{ V}_{\text{DC}}$ ) (Continued)


### Two-Decade High Frequency VCO



20139641


 $V^+ = +30\text{ V}_{\text{DC}}$ 
 $+250\text{ mV}_{\text{DC}} \leq V_C \leq +50\text{ V}_{\text{DC}}$ 
 $700\text{Hz} \leq f_o \leq 100\text{kHz}$ 

### Basic Comparator




20139606

### Non-Inverting Comparator with Hysteresis




20139609

### Inverting Comparator with Hysteresis



20139610

### Output Strobing




\* OR LOGIC GATE  
WITHOUT PULL-UP RESISTOR

20139611


# Typical Applications ( $V^+=5.0\text{ V}_{\text{DC}}$ ) (Continued)

AND Gate




20139612

OR Gate




20139613

Large Fan-in AND Gate




20139614

Limit Comparator




20139615

Comparing Input Voltages of Opposite Polarity



20139616


ORing the Outputs



20139617


## Typical Applications ( $V^+=5.0\text{ V}_{\text{DC}}$ ) (Continued)

### Zero Crossing Detector (Single Power Supply)




20139621

### One-Shot Multivibrator




20139622

### Bi-Stable Multivibrator




20139624

### One-Shot Multivibrator with Input Lock Out




20139623

### Zero Crossing Detector



20139643


### Comparator With a Negative Reference



20139644

## Typical Applications ( $V^+=5.0\text{ V}_{\text{DC}}$ ) (Continued)


### Time Delay Generator



20139607

## Split-Supply Applications ( $V^+=+15\text{ V}_{\text{DC}}$ and $V^-=-15\text{ V}_{\text{DC}}$ )

### MOS Clock Driver




20139642



## Revision History Section

Date Released	Revision	Section	Originator	Changes
05/09/05	A	New Release. Corporate format	L. Lytle	2 MDS datasheets converted into one Corp. datasheet format. MNLM193A-X Rev 1B3 & MNLM193-X Rev 0E1. The Iout Vsat condition for LM193 was changed to Isink for consistency with the LM193A and JAN electrical conditions. Also, redundant parameters were removed from conditions that were defined at beginning of the table. MDS data sheets will be archived.


# Physical Dimensions inches (millimeters) unless otherwise noted



**Metal Can Package (H)**  
**NS Package Number H08C**



**Ceramic Dual-In-Line Package**  
**NS Package Number J08A**



J08A (Rev M)

## Notes

National does not assume any responsibility for use of any circuitry described, no circuit patent licenses are implied and National reserves the right at any time without notice to change said circuitry and specifications.

For the most current product information visit us at [www.national.com](http://www.national.com).

### LIFE SUPPORT POLICY

NATIONAL'S PRODUCTS ARE NOT AUTHORIZED FOR USE AS CRITICAL COMPONENTS IN LIFE SUPPORT DEVICES OR SYSTEMS WITHOUT THE EXPRESS WRITTEN APPROVAL OF THE PRESIDENT AND GENERAL COUNSEL OF NATIONAL SEMICONDUCTOR CORPORATION. As used herein:

1. Life support devices or systems are devices or systems which, (a) are intended for surgical implant into the body, or (b) support or sustain life, and whose failure to perform when properly used in accordance with instructions for use provided in the labeling, can be reasonably expected to result in a significant injury to the user.
2. A critical component is any component of a life support device or system whose failure to perform can be reasonably expected to cause the failure of the life support device or system, or to affect its safety or effectiveness.

### BANNED SUBSTANCE COMPLIANCE

National Semiconductor manufactures products and uses packing materials that meet the provisions of the Customer Products Stewardship Specification (CSP-9-111C2) and the Banned Substances and Materials of Interest Specification (CSP-9-111S2) and contain no "Banned Substances" as defined in CSP-9-111S2.



**National Semiconductor**  
Americas Customer  
Support Center  
Email: [new.feedback@nsc.com](mailto:new.feedback@nsc.com)  
Tel: 1-800-272-9959

[www.national.com](http://www.national.com)

**National Semiconductor**  
Europe Customer Support Center  
Fax: +49 (0) 180-530 85 86  
Email: [europe.support@nsc.com](mailto:europe.support@nsc.com)  
Deutsch Tel: +49 (0) 69 9508 6208  
English Tel: +44 (0) 870 24 0 2171  
Français Tel: +33 (0) 1 41 91 8790

**National Semiconductor**  
Asia Pacific Customer  
Support Center  
Email: [ap.support@nsc.com](mailto:ap.support@nsc.com)

**National Semiconductor**  
Japan Customer Support Center  
Fax: 81-3-5639-7507  
Email: [jpn.feedback@nsc.com](mailto:jpn.feedback@nsc.com)  
Tel: 81-3-5639-7560