

International
IR Rectifier

15TQ060
15TQ060S

SCHOTTKY RECTIFIER

15 Amp

Major Ratings and Characteristics



Characteristics	15TQ060	Units
$I_{F(AV)}$ Rectangular waveform	15	A
V_{RRM}	60	V
I_{FSM} @ $t_p = 5\mu s$ sine	1000	A
V_F @ $15\text{A}_{pk}, T_J = 125^\circ\text{C}$	0.56	V
T_J range	-55 to 150	°C

Description/Features

The 15TQ060 Schottky rectifier has been optimized for very low forward voltage drop, with moderate leakage. The proprietary barrier technology allows for reliable operation up to 150°C junction temperature. Typical applications are in switching power supplies, converters, free-wheeling diodes, and reverse battery protection.

- $150^\circ\text{C} T_J$ operation
- High purity, high temperature epoxy encapsulation for enhanced mechanical strength and moisture resistance
- Very low forward voltage drop
- High frequency operation
- Guard ring for enhanced ruggedness and long term reliability

Case Styles



15TQ060, 15TQ060S

Bulletin PD-20563 rev. A 09/01

International
 Rectifier

Voltage Ratings

Part number	15TQ060	
V_R Max. DC Reverse Voltage (V)		
V_{RRM} Max. Working Peak Reverse Voltage (V)		60

Absolute Maximum Ratings

Parameters	15TQ	Units	Conditions
$I_{F(AV)}$ Max. Average Forward Current * See Fig. 5	15	A	50% duty cycle @ $T_C = 104^\circ\text{C}$, rectangular waveform
I_{FSM} Max. Peak One Cycle Non-Repetitive Surge Current * See Fig. 7	1000	A	5μs Sine or 3μs Rect. pulse
	260		10ms Sine or 6ms Rect. pulse
E_{AS} Non-Repetitive Avalanche Energy	6	mJ	$T_J = 25^\circ\text{C}$, $I_{AS} = 1.50$ Amps, $L = 11.5$ mH
I_{AR} Repetitive Avalanche Current	1.50	A	Current decaying linearly to zero in 1 μsec Frequency limited by T_J max. $V_A = 1.5 \times V_R$ typical

Electrical Specifications

Parameters	15TQ	Units	Conditions
V_{FM} Max. Forward Voltage Drop (1) * See Fig. 1	0.62	V	$T_J = 25^\circ\text{C}$
	0.82	V	$T_J = 125^\circ\text{C}$
	0.56	V	
	0.71	V	
I_{RM} Max. Reverse Leakage Current (1) * See Fig. 2	0.80	mA	$V_R = \text{rated } V_R$
	45	mA	
C_T Max. Junction Capacitance	720	pF	$V_R = 5V_{DC}$, (test signal range 100Khz to 1Mhz) 25°C
L_S Typical Series Inductance	8.0	nH	Measured lead to lead 5mm from package body
dv/dt Max. Voltage Rate of Change (Rated V_R)	10000	V/ μs	

(1) Pulse Width < 300μs, Duty Cycle < 2%

Thermal-Mechanical Specifications

Parameters	15TQ	Units	Conditions
T_J Max. Junction Temperature Range	-55 to 150	°C	
T_{stg} Max. Storage Temperature Range	-55 to 150	°C	
R_{thJC} Max. Thermal Resistance Junction to Case	3.25	°C/W	DC operation * See Fig. 4
R_{thCS} Typical Thermal Resistance, Case to Heatsink	0.50	°C/W	Mounting surface, smooth and greased
wt Approximate Weight	2(0.07)	g(oz.)	
T Mounting Torque	Min.	6(5)	Kg-cm (lbf-in)
	Max.	12(10)	
Case Style	TO-220AC		JEDEC




Fig.1-Maximum Forward Voltage Drop Characteristics




Fig.2-Typical Values of Reverse Current Vs. Reverse Voltage




Fig.3-Typical Junction Capacitance Vs. Reverse Voltage




Fig.4-Maximum Thermal Impedance Z_{thJC} Characteristics

15TQ060, 15TQ060S

Bulletin PD-20563 rev. A 09/01

International
IR Rectifier




Fig. 5-Maximum Allowable Case Temperature
Vs. Average Forward Current




Fig. 6-Forward Power Loss Characteristics




Fig. 7-Maximum Non-Repetitive Surge Current






Fig. 8-Unclamped Inductive Test Circuit

(2) Formula used: $T_c = T_j - (P_d + P_{d,REV}) \times R_{th,JC}$;

$P_d = \text{Forward Power Loss} = I_{F(AV)} \times V_{FM} @ (I_{F(AV)} / D)$ (see Fig. 6);

$P_{d,REV} = \text{Inverse Power Loss} = V_{R1} \times I_R (1 - D)$; $I_R @ V_{R1} = 80\%$ rated V_R

Outline Table



15TQ060, 15TQ060S
Bulletin PD-20563 rev. A 09/01

International
IR Rectifier

Data and specifications subject to change without notice.
This product has been designed and qualified for Industrial Level.
Qualification Standards can be found on IR's Web site.

International
IR Rectifier

IR WORLD HEADQUARTERS: 233 Kansas St., El Segundo, California 90245, USA Tel: (310) 252-7105
TAC Fax: (310) 252-7309
Visit us at www.irf.com for sales contact information. 09/01