


1 Kbit (128 × 8 bit) Serial CMOS EEPROMs, Serial Peripheral Interface (SPI) Synchronous Bus

SLx 25C010

Preliminary

Features

- **Serial peripheral interface (SPI) compatible, supports SPI Modes 0,0 and 1,1**
- **Page Protection Mode™ for protecting the EEPROM against unintended data changes (SLx 25C010.../P types only)**
- **Low power CMOS**
- **Clock frequency up to 2.1 MHz**
- **$V_{CC} = 2.7$ to 5.5 V operation**
- **8-byte page mode**
- **Write protect (\overline{WP}) pin and write disable instruction for both hardware and software data protection**
- **Block write protection**
 - Protect 1/4, 1/2 or entire array
- **Filtered inputs for noise suppression with Schmitt trigger**
- **High programming flexibility**
 - Internal programming voltage
 - Self timed write cycle including erase (5 ms typical) for up to 8 bytes
 - Byte-write and page-write programming, between 1 and 8 bytes
- **High reliability**
 - Endurance 10^6 cycles¹⁾
 - Data retention 40 years¹⁾
 - ESD protection > 4000 V on all pins
- **8 pin DIP/DSO packages**
- **Available for extended temperature ranges**
 - Industrial: – 40 °C to + 85 °C
 - Automotive: – 40 °C to + 125 °C
 (– 40 °C to +150 °C on request)



P-DIP-8-4



P-DSO-8-3

¹⁾ Values are temperature dependent, for further information please refer to your Siemens sales office.