

Switching (300V, 16A)

2SK2739

●Features


- 1) Low on-resistance.
- 2) Fast switching speed.
- 3) Wide SOA (safe operating area).
- 4) Gate-source voltage (V_{GS}) guaranteed to be $\pm 30V$.
- 5) Easily designed drive circuits.
- 6) Easy to use in parallel.

●Structure

Silicon N-channel

MOSFET

●External dimensions (Units: mm)



●Absolute maximum ratings ($T_a = 25^\circ C$)

Parameter		Symbol	Limits	Unit
Drain-source voltage		V_{DS}	300	V
Gate-source voltage		V_{GS}	± 30	V
Drain current	Continuous	I_D	16	A
	Pulsed	I_{DP}^*	48	A
Reverse drain current	Continuous	I_{DR}	16	A
	Pulsed	I_{DRP}^*	48	A
Total power dissipation ($T_c=25^\circ C$)		P_D	30	W
Channel temperature		T_{ch}	150	$^\circ C$
Storage temperature		T_{stg}	$-55 \sim +150$	$^\circ C$

* $P_W \leq 10 \mu s$, Duty cycle $\leq 1\%$

●Packaging specifications

Type	Package	Bulk
	Code	—
	Basic ordering unit (pieces)	500
2SK2739		○

●Electrical characteristics (Ta = 25°C)

Parameter	Symbol	Min.	Typ.	Max.	Unit	Test Conditions
Gate-source leakage	I_{GSS}	—	—	± 100	nA	$V_{GS} = \pm 30V, V_{DS} = 0V$
Drain-source breakdown voltage	$V_{(BR)DSS}$	300	—	—	V	$I_D = 1mA, V_{GS} = 0V$
Zero gate voltage drain current	I_{DSS}	—	—	100	μA	$V_{DS} = 300V, V_{GS} = 0V$
Gate threshold voltage	$V_{GS(th)}$	2.0	—	4.0	V	$V_{DS} = 10V, I_D = 1mA$
Static drain-source on-state resistance	$R_{DS(on)}$	—	0.27	0.33	Ω	$I_D = 8A, V_{GS} = 10V$
Forward transfer admittance	$ Y_{fs} ^*$	5.0	10	—	S	$I_D = 8A, V_{DS} = 10V$
Input capacitance	C_{iss}	—	1240	—	pF	$V_{DS} = 10V$ $V_{GS} = 0V$ $f = 1MHz$
Output capacitance	C_{oss}	—	350	—	pF	
Reverse transfer capacitance	C_{rss}	—	73	—	pF	
Turn-on delay time	$t_{d(on)}$	—	19	—	ns	$I_D = 8A, V_{DD} = 100V$ $V_{GS} = 10V$ $R_L = 12.5\Omega$ $R_G = 10\Omega$
Rise time	t_r	—	24	—	ns	
Turn-off delay time	$t_{d(off)}$	—	66	—	ns	
Fall time	t_f	—	22	—	ns	
Reverse recovery time	t_{rr}	—	230	—	ns	$I_{DR} = 16A, V_{GS} = 0V$
Reverse recovery charge	Q_{rr}	—	1.8	—	μC	$di/dt = 100A/\mu s$

* $P_w \leq 300 \mu s$, Duty cycle $\leq 1\%$

●Electrical characteristic curves




Fig.1 Maximum safe operating area




Fig.2 Typical output characteristics




Fig.3 Typical transfer characteristics




Fig.4 Gate threshold voltage vs. channel temperature




Fig.5 Static drain-source on-state resistance vs. drain current




Fig.6 Static drain-source on-state resistance vs. gate-source voltage




Fig.7 Static drain-source on-state resistance vs. channel temperature




Fig.8 Forward transfer admittance vs. drain current




Fig.9 Reverse drain current vs. source-drain voltage (I)




Fig.10 Reverse drain current vs. source-drain voltage (II)




Fig.11 Typical capacitance vs. drain-source voltage




Fig.12 Switching characteristics (See Figures 16 and 17 for the measurement circuit and resultant waveforms)




Fig.13 Dynamic input characteristics
(See Figure 18 for measurement circuit)




Fig.14 Reverse recovery time
vs. reverse drain current




Fig.15 Normalized transient thermal
resistance vs. pulse width

● Switching characteristics measurement circuit




Fig.16 Switching time measurement circuit




Fig.17 Switching time waveforms




Fig.18 Gate charge measurement circuit