

DG408BP45

GATE TURN-OFF THYRISTOR

APPLICATIONS


- Variable speed A.C. motor drive inverters (VSD-AC).
- Uninterruptable Power Supplies
- High Voltage Converters.
- Choppers.
- Welding.
- Induction Heating.
- DC/DC Converters.

FEATURES

- Double Side Cooling.
- High Reliability In Service.
- High Voltage Capability.
- Fault Protection Without Fuses.
- High Surge Current Capability.
- Turn-off Capability Allows Reduction In Equipment Size And Weight. Low Noise Emission Reduces Acoustic Cladding Necessary For Environmental Requirements.

KEY PARAMETERS

I_{TCM}	1000A
V_{DRM}	4500V
$I_{T(AV)}$	320A
dV_D/dt	1000V/ μ s
di_T/dt	300A/ μ s



Outline type code: P. Turn to page 18 for further information.

VOLTAGE RATINGS

Type Number	Repetitive Peak Off-state Voltage V_{DRM} V	Repetitive Peak Reverse Voltage V_{RRM} V	Conditions
DG408BP45	4500	16	$T_{vj} = 125^{\circ}\text{C}$, $I_{DM} = 50\text{mA}$, $I_{RRM} = 50\text{mA}$

CURRENT RATINGS

Symbol	Parameter	Conditions	Max.	Units
I_{TCM}	Repetitive peak controllable on-state current	$V_D = V_{DRM}$, $T_j = 125^{\circ}\text{C}$, $di_{GQ}/dt = 30\text{A}/\mu\text{s}$, $C_s = 1.0\mu\text{F}$	1000	A
$I_{T(AV)}$	Mean on-state current	$T_{HS} = 80^{\circ}\text{C}$. Double side cooled. Half sine 50Hz.	320	A
$I_{T(RMS)}$	RMS on-state current	$T_{HS} = 80^{\circ}\text{C}$. Double side cooled. Half sine 50Hz.	500	A

SURGE RATINGS

Symbol	Parameter	Conditions	Max.	Units
I_{TSM}	Surge (non-repetitive) on-state current	10ms half sine. $T_j = 125^\circ\text{C}$	7.0	kA
I^2t	I^2t for fusing	10ms half sine. $T_j = 125^\circ\text{C}$	0.245×10^6	A^2s
di_T/dt	Critical rate of rise of on-state current	$V_D = 3000\text{V}$, $I_T = 1000\text{A}$, $T_j = 125^\circ\text{C}$, $I_{FG} > 30\text{A}$, Rise time $> 1.5\mu\text{s}$	300	$\text{A}/\mu\text{s}$
dV_D/dt	Rate of rise of off-state voltage	To 66% V_{DRM} ; $R_{GK} \leq 1.5\Omega$, $T_j = 125^\circ\text{C}$	225	$\text{V}/\mu\text{s}$
		To 66% V_{DRM} ; $V_{RG} = -2\text{V}$, $T_j = 125^\circ\text{C}$	1000	$\text{V}/\mu\text{s}$
L_S	Peak stray inductance in snubber circuit	-	200	nH

GATE RATINGS

Symbol	Parameter	Conditions	Min.	Max.	Units
V_{RGM}	Peak reverse gate voltage	This value maybe exceeded during turn-off	-	16	V
I_{FGM}	Peak forward gate current		20	70	A
$P_{FG(AV)}$	Average forward gate power		-	10	W
P_{RGM}	Peak reverse gate power		-	15	kW
di_{GQ}/dt	Rate of rise of reverse gate current		15	60	$\text{A}/\mu\text{s}$
$t_{ON(min)}$	Minimum permissible on time		20	-	μs
$t_{OFF(min)}$	Minimum permissible off time		100	-	μs




THERMAL RATINGS AND MECHANICAL DATA

Symbol	Parameter	Conditions		Min.	Max.	Units
$R_{th(j-hs)}$	DC thermal resistance - junction to heatsink surface	Double side cooled		-	0.041	$^\circ\text{C}/\text{W}$
		Anode side cooled		-	0.07	$^\circ\text{C}/\text{W}$
		Cathode side cooled		-	0.1	$^\circ\text{C}/\text{W}$
$R_{th(c-hs)}$	Contact thermal resistance	Clamping force 12.0kN With mounting compound	per contact	-	0.009	$^\circ\text{C}/\text{W}$
T_{vj}	Virtual junction temperature			-	125	$^\circ\text{C}$
T_{OP}/T_{stg}	Operating junction/storage temperature range			-40	125	$^\circ\text{C}$
-	Clamping force			11.0	15.0	kN

CHARACTERISTICS

$T_j = 125^\circ\text{C}$ unless stated otherwise					
Symbol	Parameter	Conditions	Min.	Max.	Units
V_{TM}	On-state voltage	At 1000A peak, $I_{G(ON)} = 4\text{A d.c.}$	-	3.5	V
I_{DM}	Peak off-state current	$V_{DRM} = 4500\text{V}$, $V_{RG} = 0\text{V}$	-	50	mA
I_{RRM}	Peak reverse current	At V_{RRM}	-	50	mA
V_{GT}	Gate trigger voltage	$V_D = 24\text{V}$, $I_T = 100\text{A}$, $T_j = 25^\circ\text{C}$	-	1.0	V
I_{GT}	Gate trigger current	$V_D = 24\text{V}$, $I_T = 100\text{A}$, $T_j = 25^\circ\text{C}$	-	1.5	A
I_{RGM}	Reverse gate cathode current	$V_{RGM} = 16\text{V}$, No gate/cathode resistor	-	50	mA
E_{ON}	Turn-on energy	$V_D = 3000\text{V}$	-	2300	mJ
t_d	Delay time	$I_T = 1000\text{A}$, $di_T/dt = 300\text{A}/\mu\text{s}$	-	1.5	μs
t_r	Rise time	$I_{FG} = 30\text{A}$, rise time $< 1.5\mu\text{s}$	-	5.0	μs
E_{OFF}	Turn-off energy	$I_T = 1000\text{A}$, $V_{DM} = V_{DRM}$ Snubber Cap $C_s = 1.0\mu\text{F}$, $di_{GQ}/dt = 30\text{A}/\mu\text{s}$	-	4120	mJ
t_{gs}	Storage time		-	14.0	μs
t_{gf}	Fall time		-	1.5	μs
t_{gq}	Gate controlled turn-off time		-	15.5	μs
Q_{GQ}	Turn-off gate charge		-	3000	μC
Q_{GQT}	Total turn-off gate charge		-	6000	μC
I_{GQM}	Peak reverse gate current		-	420	A

CURVES






FIG. 4 MAXIMUM (LIMIT) TRANSIENT THERMAL IMPEDANCE - DOUBLE SIDE COOLED




FIG. 5 SURGE (NON-REPETITIVE) ON-STATE CURRENT vs TIME




FIG. 6 STEADY STATE RECTANGULAR WAVE CONDUCTION LOSS - DOUBLE SIDE COOLED




FIG. 7 STEADY STATE SINUSOIDAL WAVE CONDUCTION LOSS - DOUBLE SIDE COOLED




FIG. 8 TURN-ON ENERGY vs ON-STATE CURRENT




FIG. 9 TURN-ON ENERGY vs PEAK FORWARD GATE CURRENT




FIG. 10 TURN-ON ENERGY vs ON-STATE CURRENT




FIG. 11 TURN-ON ENERGY vs PEAK FORWARD GATE CURRENT




FIG. 12 TURN-ON ENERGY vs RATE OF RISE OF ON-STATE CURRENT




FIG. 13 DELAY & RISE TIME vs TURN-ON CURRENT




FIG. 14 DELAY TIME & RISE TIME vs PEAK FORWARD GATE CURRENT




FIG. 15 TURN-OFF ENERGY vs ON-STATE CURRENT




FIG. 16 TURN-OFF ENERGY vs RATE OF RISE OF REVERSE GATE CURRENT




FIG. 17 TURN-OFF ENERGY vs ON-STATE CURRENT




FIG. 18 TURN-OFF ENERGY LOSS vs RATE OF RISE OF REVERSE GATE CURRENT




FIG. 19 TURN-OFF ENERGY vs ON-STATE CURRENT




FIG. 20 GATE STORAGE TIME vs ON-STATE CURRENT




FIG. 21 GATE STORAGE TIME vs RATE OF RISE OF REVERSE GATE CURRENT




FIG. 22 GATE FALL TIME vs ON-STATE CURRENT




FIG. 23 GATE FALL TIME vs RATE OF RISE OF REVERSE GATE CURRENT




FIG. 24 PEAK REVERSE GATE CURRENT vs TURN-OFF CURRENT




FIG. 25 PEAK REVERSE GATE CURRENT vs RATE OF RISE OF REVERSE GATE CURRENT




FIG. 26 TURN-OFF GATE CHARGE vs ON-STATE CURRENT




FIG. 27 TURN-OFF GATE CHARGE vs RATE OF RISE OF REVERSE GATE CURRENT





FIG. 28 RATE OF RISE OF OFF-STATE VOLTAGE vs GATE CATHODE RESISTANCE



Recommended gate conditions:


$I_{TCM} = 1000A$
 $I_{FG} = 30A$
 $I_{G(ON)} = 4A$ d.c.
 $t_{w1(min)} = 20\mu s$
 $I_{GQM} = 420A$
 $di_{GQ}/dt = 30A/\mu s$
 $Q_{GQ} = 3000\mu C$
 $V_{RG(min)} = 2V$
 $V_{RG(max)} = 16V$

These are recommended GEC Plessey Semiconductor conditions. Other conditions are permitted according to users gate drive specifications.

FIG. 29 GENERAL SWITCHING WAVEFORMS

PACKAGE DETAILS - P

For further package information, please contact your local Customer Service Centre. All dimensions in mm, unless stated otherwise. DO NOT SCALE.



GEC PLESSEY
SEMICONDUCTORS

HEADQUARTERS OPERATIONS

GEC PLESSEY SEMICONDUCTORS

Cheney Manor, Swindon,
Wiltshire, SN2 2QW, United Kingdom.
Tel: + 44 (0)1793 518000
Fax: + 44 (0)1793 518411

GEC PLESSEY SEMICONDUCTORS

P.O. Box 660017
1500 Green Hills Road,
Scotts Valley, California 95067-0017,
United States of America.
Tel: + 1 (408) 438 2900
Fax: + 1 (408) 438 5576

POWER PRODUCT CUSTOMER SERVICE CENTRES

- **FRANCE.** 2 rue Henri-Bergson, 92665 Asnieres Cedex.
Tel: + 33 1 40 80 54 00. Fax: + 33 1 40 80 55 87.
- **GERMANY.** Ungererstrasse 129, 80505 München.
Tel: + 49 (0)89 36 09 060. Fax: + 49 (0)89 36 09 06 55.
- **NORTH AMERICA.** Two Dedham Place, Suite 125, 3 Allied Drive, Dedham. MA 02026.
Tel: + 1 617 251 0126. Fax: + 1 617 251 0106.
- **UNITED KINGDOM.** Doddington Road, Lincoln. LN6 3LF.
Tel: + 44 (0)1522 500500. Fax: + 44 (0)1522 500550.

These are supported by Agents and Distributors in major countries world-wide.

© GEC Plessey Semiconductors 1995 Publication No. DS4091-2 Issue No. 2.2 November 1995

TECHNICAL DOCUMENTATION - NOT FOR RESALE. PRINTED IN UNITED KINGDOM.

This publication is issued to provide information only which (unless agreed by the Company in writing) may not be used, applied or reproduced for any purpose nor form part of any order or contract nor to be regarded as a representation relating to the products or services concerned. No warranty or guarantee express or implied is made regarding the capability, performance or suitability of any product or service. The Company reserves the right to alter without prior notice the specification, design or price of any product or service. Information concerning possible methods of use is provided as a guide only and does not constitute any guarantee that such methods of use will be satisfactory in a specific piece of equipment. It is the user's responsibility to fully determine the performance and suitability of any equipment using such information and to ensure that any publication or data used is up to date and has not been superseded. These products are not suitable for use in any medical products whose failure to perform may result in significant injury or death to the user. All products and materials are sold and services provided subject to the Company's conditions of sale, which are available on request.