

DPA05

Diffused Junction Type Silicon Diode

PIN Diode for

FM/AM Electronic Tuning AGC Drive Use

Use

· AGC output drive of FM/AM electronic tuning IC.


Features

- \cdot Especially suited for use in hybrid ICs. Contains two chips connected in series.
- · Small interterminal capacitance.
- · Reverse Voltage: 50V. · Forward Current: 50mA.

Package Dimensions

unit:mm

1147



Specifications

Absolute Maximum Ratings at Ta = 25°C


Parameter	Symbol	Conditions	Ratings	Unit
Reverse Voltage	٧ _R		50	V
Forward Current	ΙF	Ta=25°C	50	mA
Junction Temperature	Tj		125	°C
Storage Temperature	Tstg		-55 to +125	°C


Electrical Characteristics at Ta = 25°C

Parameter	Symbol	Conditions	Ratings			Unit
			min	typ	max	OTIIL
Forward Voltage	٧F	I _F =50mA		0.95		V
Reverse Current	I _R	V _R =50V			0.1	μΑ
Interterminal Capacitance	С	V _R =50V		0.25		pF
Series Resistance	r _s	I _F =10mA, f=100MHz		7		Ω

Marking: W9

Electrical Connection





- No products described or contained herein are intended for use in surgical implants, life-support systems, aerospace equipment, nuclear power control systems, vehicles, disaster/crime-prevention equipment and the like, the failure of which may directly or indirectly cause injury, death or property loss.
- Anyone purchasing any products described or contained herein for an above-mentioned use shall:
 - ① Accept full responsibility and indemnify and defend SANYO ELECTRIC CO., LTD., its affiliates, subsidiaries and distributors and all their officers and employees, jointly and severally, against any and all claims and litigation and all damages, cost and expenses associated with such use:
 - ② Not impose any responsibilty for any fault or negligence which may be cited in any such claim or litigation on SANYO ELECTRIC CO., LTD., its affiliates, subsidiaries and distributors or any of their officers and employees jointly or severally.
- Information (including circuit diagrams and circuit parameters) herein is for example only; it is not guaranteed for volume production. SANYO believes information herein is accurate and reliable, but no guarantees are made or implied regarding its use or any infringements of intellectual property rights or other rights of third parties.

This catalog provides information as of June, 1998. Specifications and information herein are subject to change without notice.