


Digital transistor (built-in resistors)

DTA144VUA / DTA144VKA / DTA144VSA

●Features

- 1) Built-in bias resistors enable the configuration of an inverter circuit without connecting external input resistors.
- 2) The bias resistors consist of thin-film resistors with complete isolation to allow positive biasing of the input, and parasitic effects are almost completely eliminated.
- 3) Only the on / off conditions need to be set for operation, making device design easy.
- 4) Higher mounting densities can be achieved.

●Circuit schematic



●Electrical characteristics (Ta=25°C)

Parameter	Symbol	Min.	Typ.	Max.	Unit	Conditions
Input voltage	$V_{I(off)}$	—	—	—1	V	$V_{CC} = -5V$, $I_o = -100 \mu A$
	$V_{I(on)}$	—5	—	—		$V_o = -0.3V$, $I_o = -2mA$
Output voltage	$V_{O(on)}$	—	—0.1	—0.3	V	$I_o = -10mA$, $I_i = -0.5mA$
Input current	I_i	—	—	—0.16	mA	$V_i = -5V$
Output current	$I_{O(off)}$	—	—	—0.5	μA	$V_{CC} = -50V$, $V_i = 0V$
DC current gain	G_i	33	—	—	—	$I_o = -5mA$, $V_o = -5V$
Input resistance	R_1	32.9	47	61.1	k Ω	—
Resistance ratio	R_2/R_1	0.17	0.21	0.26	—	—
Transition frequency	f_T	—	250	—	MHz	$V_{CE} = -10V$, $I_E = 5mA$, $f = 100MHz$ *

●Absolute maximum ratings (Ta=25°C)

Parameter		Symbol	Limits	Unit
Supply voltage		V_{CC}	—50	V
Input voltage		V_i	—40 ~ +15	V
Output current		I_o	—30	mA
		$I_{C(Max)}$	—10	
Power dissipation	DTA144VUA / DTA144VKA	P_d	200	mW
	DTA144VSA		300	
Junction temperature		T_j	150	°C
Storage temperature		T_{stg}	—55 ~ +150	°C

●Package, marking, and packaging specifications

Part No.	DTA144VUA	DTA144VKA	DTA144VSA
Package	UMT3	SMT3	SPT
Marking	E56	E56	—
Packaging code	T106	T146	TP
Basic ordering unit (pieces)	3000	3000	5000