


SANYO**FP108**TR:PNP Epitaxial Planar Silicon Transistor
SBD:Schottky Barrier Diode**DC-DC Converter Applications****Features**

- Composite type with a PNP transistor and a Schottky barrier diode contained in one package, facilitating high-density mounting.
- The FP108 is formed with 2 chips, one being equivalent to the 2SB1121 and the other the SB01-015CP, placed in one package.

Package Dimensions

unit:mm


2088A

**Specifications****Absolute Maximum Ratings at Ta = 25°C**

Parameter	Symbol	Conditions	Ratings	Unit
[TR]				
Collector-to-Base Voltage	V_{CBO}		-30	V
Collector-to-Emitter Voltage	V_{CEO}		-25	V
Emitter-to-Base Voltage	V_{EBO}		-6	V
Collector Current	I_C		-2	A
Collector Current (Pulse)	I_{CP}		-5	A
Base Current	I_B		-400	mA
Collector Dissipation	P_C	Mounted on ceramic board (250mm ² ×0.8mm)	1.3	W
Junction Temperature	T_J		150	°C
Storage Temperature	T_{stg}		-55 to +150	°C
[SBD]				
Repetitive Peak Reverse Voltage	V_{RRM}		15	V
Non-repetitive Peak Reverse Surge Voltage	V_{RSM}		17	V
Average Rectified Current	I_O		1	A
Surge Forward Current	I_{FSM}	50Hz sine wave, 1cycle	8	A
Junction Temperature	T_J		-55 to +125	°C
Storage Temperature	T_{stg}		-55 to +125	°C

Marking:108

Continued on next page.

Electrical Connection**SANYO Electric Co.,Ltd. Semiconductor Business Headquarters**

TOKYO OFFICE Tokyo Bldg., 1-10, 1 Chome, Ueno, Taito-ku, TOKYO, 110-8534 JAPAN

FP108


Continued from preceding page.

Electrical Characteristics at Ta=25°C


.Parameter	Symbol	Conditons	Ratings			Unit
			min	typ	max	
[TR]						
Collector Cutoff Current	I _{CBO}	V _{CB} =−20V, I _E =0			−0.1	μA
Emitter Cutoff Current	I _{EBO}	V _{EB} =−4V, I _C =0			−0.1	μA
DC Current Gain	h _{FE1}	V _{CE} =−2V, I _C =−100mA	140		400	
	h _{FE2}	V _{CE} =−2V, I _C =−1.5A	65			
Gain-Bandwidth Product	f _T	V _{CE} =−10V, I _C =−50mA		150		MHz
Output Capacitance	C _{ob}	V _{CE} =−10V, f=1MHz		32		pF
C-E Saturation Voltage	V _{CE(sat)}	I _C =−1.5A, I _B =−75mA		−0.35	−0.6	V
B-E Saturation Voltage	V _{BE(sat)}	I _C =−1.5A, I _B =−75mA		−0.85	−1.2	V
C-B Breakdown Voltage	V _{(BR)CBO}	I _C =−10μA, I _E =0	−30			V
C-E Breakdown Voltage	V _{(BR)CEO}	I _C =−1mA, R _{BE} =∞	−25			V
E-B Breakdown Voltage	V _{(BR)EBO}	I _E =−10μA, I _C =0	−6			V
Turn-ON Time	t _{on}	See specified Test Circuit		60		ns
Storage Time	t _{stg}	See specified Test Circuit		350		ns
Fall Time	t _f	See specified Test Circuit		25		ns
[SBD]						
Reverse Voltage	V _R	I _R =300μA	15			V
Forward Voltage	V _F	I _F =1A			0.55	V
Reverse Current	I _R	V _R =7.5V			50	μA
Interterminal Capacitance	C	V _R =10V, f=1MHz		30		pF
Reverse Recovery Time	t _{rr}	I _F =I _R =100mA, See specified Test Circuit			10	ns
Thermal Resistance	R _{thj-a}	Mounted on ceramic board (250mm²×0.8mm)		120		°C/W









Switching Time Test Circuit






(TR)



(SBD)







■ No products described or contained herein are intended for use in surgical implants, life-support systems, aerospace equipment, nuclear power control systems, vehicles, disaster/crime-prevention equipment and the like, the failure of which may directly or indirectly cause injury, death or property loss.

■ Anyone purchasing any products described or contained herein for an above-mentioned use shall:

- ① Accept full responsibility and indemnify and defend SANYO ELECTRIC CO., LTD., its affiliates, subsidiaries and distributors and all their officers and employees, jointly and severally, against any and all claims and litigation and all damages, cost and expenses associated with such use:
- ② Not impose any responsibility for any fault or negligence which may be cited in any such claim or litigation on SANYO ELECTRIC CO., LTD., its affiliates, subsidiaries and distributors or any of their officers and employees jointly or severally.

■ Information (including circuit diagrams and circuit parameters) herein is for example only; it is not guaranteed for volume production. SANYO believes information herein is accurate and reliable, but no guarantees are made or implied regarding its use or any infringements of intellectual property rights or other rights of third parties.

This catalog provides information as of May, 1998. Specifications and information herein are subject to change without notice.