

IL388DAA

High Performance Linear Optocoupler for Optical DAA in Telecommunications

Preliminary

FEATURES

- **2.3 mm High SMT Package**
- **High Sensitivity (K1) at Low Operating LED Current**
- **Couples AC and DC Signals**
- **Low Input-Output Capacitance**
- **Isolation Voltage, 2500 VDC**
- **Low Distortion, below -80 db (typical)**
- **0.4 mm Internal Insulation Thickness**


APPLICATIONS

- **Optical DAA for V.34 FAX/Modem PCMCIA Cards**
- **Digital Telephone Line Isolation**

DESCRIPTION

The IL388DAA family of Linear Optocoupler consist of an IRLED optically coupled to two photodiodes. The emitter is located such that both photodiodes receive approximately an equal amount of infrared light. The diodes produce a proportional amount of photocurrents. The ratio of the photocurrents stays constant with high accuracy when either the LED current changes or the ambient temperature changes. Thus one can control the output diode current optically by controlling the input photodiode current.

The IL388DAA optocouplers can be used with the aid of operational amplifiers in closed loop conditions to achieve highly linear and electrically isolated AC and or DC signal amplifiers.



Absolute Maximum Ratings

Emitter	Sym.	Min.	Max.	Units
Reverse Voltage	V_R	—	3	V
Forward Current	I_F	—	30	mA
Surge Current Pulse Width <10 μ s	I_{PK}	—	150	mA
Power Dissipation, $T_A=25^\circ\text{C}$	P_{LED}	—	150	mW
Derate Linearly from 25°C	—	—	2	mW/ $^\circ\text{C}$
Junction Temperature	T_J	—	100	$^\circ\text{C}$
Detector (each)				
Reverse Voltage	V_R	—	15	V
Power Dissipation	P	—	50	mW
Derate Linearly from 25°C	—	—	0.65	mW/ $^\circ\text{C}$
Junction Temperature	T_J		100	$^\circ\text{C}$
Coupler				
Isolation Test Voltage, t=1 sec	V_{ISOL}	1768		V_{RMS}
Total Package Power Dissipation	P_t	—	250	mW
Derate Linearly from 25°C	—	—	2.8	mW/ $^\circ\text{C}$
Storage Temperature	T_S	-40	150	$^\circ\text{C}$
Operating Temperature	T_{OP}	0	75	$^\circ\text{C}$
Lead Soldering Time at 260°C	—		10	sec.
Isolation Resistance $V_{IO}=500\text{ V}$, $T_A=25^\circ\text{C}$ $V_{IO}=500\text{ V}$, $T_A=100^\circ\text{C}$	—	$10^{12}\ \Omega$ $10^{11}\ \Omega$	—	—

Electrical Characteristics (T_A=25°C)

LED Emitter	Symbol	Min.	Typ.	Max.	Units	Test Conditions
Forward Voltage	V _F		1.8	2.1	V	I _F =10 mA
Reverse Current	I _R		.01	10	μA	V _R =3 V
V _F Temperature Coefficient	ΔV _F /Δ°C		-2.2		mV/°C	
Junction Capacitance	C _J		TBD		pF	V _F =0 V, f=1 MHz
Dynamic Resistance	ΔV _F /ΔI _F		6		Ω	
Detector						
Junction Capacitance	C _J		12		pF	V _F =0 V, f=1 MHz
AC Characteristics Photovoltaic Mode						
Frequency Response	BW(-3dB)		1.0		MHz	I _{P1} =25 μA Modulation current ΔI _{P1} =±6 μA
Phase Response			45		Deg.	
Rise Time			350		ns	
Package						
Input-Output Capacitance	C _{IO}		1		pF	V _F =0 V, f=1 MHz
Common Mode Capacitance	C _{cm}		0.5		pF	V _F =0 V, f=1 MHz
Coupled Characteristics			Min.	Typ.	Max.	Units
K ₁ at I _F =2 mA, V _D =0 V			0.007			
THD at f ₀ =316, I _{P1} =35 μA, V _D =0 V			-79			db
K ₃ =K ₂ /K ₁ , I _F =2 mA, V _D =0 V			0.7		1.3	

© Siemens Microelectronics, Inc., Optoelectronics Division, 1998

Printed in the United States of America.

All rights reserved.

Siemens and the Siemens logo are registered trademarks of Siemens AG, Inc.

The information provided is believed to be accurate and reliable.

Siemens reserves the right to make changes to the product described without notice.

No liability is assumed as a result of its use nor for any infringement of the rights of others.

This document may contain preliminary information and is subject to change by Siemens without notice. Siemens assumes no responsibility or liability for any use of the information contained herein. Nothing in this document shall operate as an express or implied license or indemnity under the intellectual property rights of Siemens or third parties.

The products described in this document are not intended for use in implantation or other direct life support applications where malfunction may result in the direct physical harm or injury to persons.

NO WARRANTIES OF ANY KIND, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY OF FITNESS FOR A PARTICULAR PURPOSE, ARE OFFERED IN THIS DOCUMENT.