



**FEATURES**

- Avalanche Rugged Technology
- Rugged Gate Oxide Technology
- Lower Input Capacitance
- Improved Gate Charge
- Extended Safe Operating Area
- 175°C Operating Temperature
- Lower Leakage Current : 10  $\mu$ A (Max.) @  $V_{DS} = 200V$
- Lower  $R_{DS(ON)}$  : 0.145  $\Omega$  (Typ.)

$$BV_{DSS} = 200 V$$

$$R_{DS(on)} = 0.18 \Omega$$

$$I_D = 18 A$$

**D<sup>2</sup>-PAK****I<sup>2</sup>-PAK**

1. Gate 2. Drain 3. Source

**Absolute Maximum Ratings**

| Symbol         | Characteristic                                                          | Value        | Units         |
|----------------|-------------------------------------------------------------------------|--------------|---------------|
| $V_{DSS}$      | Drain-to-Source Voltage                                                 | 200          | V             |
| $I_D$          | Continuous Drain Current ( $T_C=25^\circ C$ )                           | 18           | A             |
|                | Continuous Drain Current ( $T_C=100^\circ C$ )                          | 11.4         |               |
| $I_{DM}$       | Drain Current-Pulsed ①                                                  | 63           | A             |
| $V_{GS}$       | Gate-to-Source Voltage                                                  | $\pm 20$     | V             |
| $E_{AS}$       | Single Pulsed Avalanche Energy ②                                        | 64           | mJ            |
| $I_{AR}$       | Avalanche Current ①                                                     | 18           | A             |
| $E_{AR}$       | Repetitive Avalanche Energy ①                                           | 11           | mJ            |
| dv/dt          | Peak Diode Recovery dv/dt ③                                             | 5.0          | V/ns          |
| $P_D$          | Total Power Dissipation ( $T_A=25^\circ C$ ) *                          | 3.1          | W             |
|                | Total Power Dissipation ( $T_C=25^\circ C$ )                            | 110          | W             |
|                | Linear Derating Factor                                                  | 0.88         | W/ $^\circ C$ |
| $T_J, T_{STG}$ | Operating Junction and Storage Temperature Range                        | - 55 to +150 | $^\circ C$    |
| $T_L$          | Maximum Lead Temp. for Soldering Purposes, 1/8" from case for 5-seconds | 300          |               |

**Thermal Resistance**

| Symbol          | Characteristic        | Typ. | Max. | Units        |
|-----------------|-----------------------|------|------|--------------|
| $R_{\theta JC}$ | Junction-to-Case      | --   | 1.14 | $^\circ C/W$ |
| $R_{\theta JA}$ | Junction-to-Ambient * | --   | 40   |              |
| $R_{\theta JA}$ | Junction-to-Ambient   | --   | 62.5 |              |

\* When mounted on the minimum pad size recommended (PCB Mount).

### Electrical Characteristics ( $T_C=25^{\circ}\text{C}$ unless otherwise specified)

| Symbol                 | Characteristic                          | Min. | Typ. | Max. | Units                | Test Condition                                                              |
|------------------------|-----------------------------------------|------|------|------|----------------------|-----------------------------------------------------------------------------|
| $BV_{DSS}$             | Drain-Source Breakdown Voltage          | 200  | --   | --   | V                    | $V_{GS}=0V, I_D=250\mu A$                                                   |
| $\Delta BV/\Delta T_J$ | Breakdown Voltage Temp. Coeff.          | --   | 0.17 | --   | $V/^{\circ}\text{C}$ | $I_D=250\mu A$ <b>See Fig 7</b>                                             |
| $V_{GS(th)}$           | Gate Threshold Voltage                  | 1.0  | --   | 2.0  | V                    | $V_{DS}=5V, I_D=250\mu A$                                                   |
| $I_{GSS}$              | Gate-Source Leakage, Forward            | --   | --   | 100  | nA                   | $V_{GS}=20V$                                                                |
|                        | Gate-Source Leakage, Reverse            | --   | --   | -100 |                      | $V_{GS}=-20V$                                                               |
| $I_{DSS}$              | Drain-to-Source Leakage Current         | --   | --   | 10   | $\mu A$              | $V_{DS}=200V$                                                               |
|                        |                                         | --   | --   | 100  |                      | $V_{DS}=160V, T_C=125^{\circ}\text{C}$                                      |
| $R_{DS(on)}$           | Static Drain-Source On-State Resistance | --   | --   | 0.18 | $\Omega$             | $V_{GS}=5V, I_D=9A$ ④                                                       |
| $g_{fs}$               | Forward Transconductance                | --   | 13.3 | --   | $\bar{U}$            | $V_{DS}=40V, I_D=9A$ ④                                                      |
| $C_{iss}$              | Input Capacitance                       | --   | 1310 | 1705 | pF                   | $V_{GS}=0V, V_{DS}=25V, f=1\text{MHz}$<br><b>See Fig 5</b>                  |
| $C_{oss}$              | Output Capacitance                      | --   | 200  | 250  |                      |                                                                             |
| $C_{rss}$              | Reverse Transfer Capacitance            | --   | 95   | 120  |                      |                                                                             |
| $t_{d(on)}$            | Turn-On Delay Time                      | --   | 11   | 30   | ns                   | $V_{DD}=100V, I_D=18A,$<br>$R_G=4.6\Omega$<br><b>See Fig 13</b> ④ ⑤         |
| $t_r$                  | Rise Time                               | --   | 8    | 25   |                      |                                                                             |
| $t_{d(off)}$           | Turn-Off Delay Time                     | --   | 46   | 100  |                      |                                                                             |
| $t_f$                  | Fall Time                               | --   | 15   | 40   |                      |                                                                             |
| $Q_g$                  | Total Gate Charge                       | --   | 40   | 56   | nC                   | $V_{DS}=160V, V_{GS}=5V,$<br>$I_D=18A$<br><b>See Fig 6 &amp; Fig 12</b> ④ ⑤ |
| $Q_{gs}$               | Gate-Source Charge                      | --   | 6.8  | --   |                      |                                                                             |
| $Q_{gd}$               | Gate-Drain("Miller") Charge             | --   | 18.6 | --   |                      |                                                                             |


### Source-Drain Diode Ratings and Characteristics

| Symbol   | Characteristic            | Min. | Typ. | Max. | Units   | Test Condition                               |
|----------|---------------------------|------|------|------|---------|----------------------------------------------|
| $I_S$    | Continuous Source Current | --   | --   | 18   | A       | Integral reverse pn-diode in the MOSFET      |
| $I_{SM}$ | Pulsed-Source Current ①   | --   | --   | 63   |         |                                              |
| $V_{SD}$ | Diode Forward Voltage ④   | --   | --   | 1.5  | V       | $T_J=25^{\circ}\text{C}, I_S=18A, V_{GS}=0V$ |
| $t_{rr}$ | Reverse Recovery Time     | --   | 224  | --   | ns      | $T_J=25^{\circ}\text{C}, I_F=18A$            |
| $Q_{rr}$ | Reverse Recovery Charge   | --   | 1.55 | --   | $\mu C$ | $di_F/dt=100A/\mu s$ ④                       |


#### Notes ;

- ① Repetitive Rating : Pulse Width Limited by Maximum Junction Temperature
- ②  $L=0.3\text{mH}, I_{AS}=18A, V_{DD}=50V, R_G=27\Omega$ , Starting  $T_J=25^{\circ}\text{C}$
- ③  $I_{SD} \leq 18A, di/dt \leq 260A/\mu s, V_{DD} \leq BV_{DSS}$ , Starting  $T_J=25^{\circ}\text{C}$
- ④ Pulse Test : Pulse Width =  $250\mu s$ , Duty Cycle  $\leq 2\%$
- ⑤ Essentially Independent of Operating Temperature


**Fig 1. Output Characteristics**




**Fig 2. Transfer Characteristics**




**Fig 3. On-Resistance vs. Drain Current**



**Fig 4. Source-Drain Diode Forward Voltage**



**Fig 5. Capacitance vs. Drain-Source Voltage**



**Fig 6. Gate Charge vs. Gate-Source Voltage**




Fig 7. Breakdown Voltage vs. Temperature




Fig 8. On-Resistance vs. Temperature




Fig 9. Max. Safe Operating Area




Fig 10. Max. Drain Current vs. Case Temperature







Fig 11. Thermal Response



**Fig 12. Gate Charge Test Circuit & Waveform**



**Fig 13. Resistive Switching Test Circuit & Waveforms**



**Fig 14. Unclamped Inductive Switching Test Circuit & Waveforms**




Fig 15. Peak Diode Recovery dv/dt Test Circuit & Waveforms

