



KBPC1005 THRU KBPC110

SINGLE-PHASE SILICON BRIDGE


Reverse Voltage - 50 to 1000 Volts

Forward Current - 3.0 Amperes

Features

- Surge overload rating - 50 amperes peak
- Low forward voltage drop
- Small size; simple installation
- Tinned copper leads
- Mounting Position: Any
- Mounting: Thru hold for #6 screw

KBPC1



DIMENSIONS					
DIM	inches		mm		Note
	Min.	Max.	Min.	Max.	
A	0.580	0.620	14.96	15.71	
B	0.230	0.270	5.84	6.86	
C	0.405	0.445	10.29	11.31	
E	0.75	-	19	-	
F	0.028	0.032	0.71	0.81	φ
G	0.140	0.150	3.56	3.81	φ

Maximum Ratings and Electrical Characteristics

Ratings at 25°C ambient temperature unless otherwise specified.

Single phase, half wave, 60Hz, resistive or inductive load.

For capacitive load, derate current by 20%.

	Symbols	KBPC 1005	KBPC 101	KBPC 102	KBPC 104	KBPC 106	KBPC 108	KBPC 110	Units
Maximum repetitive peak reverse voltage	V_{RRM}	50	100	200	400	600	800	1000	Volts
Maximum RMS bridge input voltage	V_{RMS}	35	70	140	280	420	560	700	Volts
Maximum average forward rectified output current at $T_C=50^\circ\text{C}^*$ $T_C=100^\circ\text{C}^*$ $T_A=50^\circ\text{C}^{**}$	$I_{(AV)}$	3.0 2.0 2.0							Amps
Peak forward surge current, 8.3mS single half sine-wave superimposed on rated load	I_{FSM}	50.0							Amps
Maximum forward Voltage drop per bridge element at 1.5A peak	V_F	1.2							Volts
Maximum DC reverse current at rated DC blocking voltage per element $T_A=25^\circ\text{C}$ $T_A=100^\circ\text{C}$	I_R	10.0 1.0							uA mA
Operating temperature range	T_J	-55 to +125							°C
Storage temperature range	T_{STG}	-55 to +150							°C

Notes:

* Unit mounted on metal chassis

** Unit mounted on P.C. board

RATINGS AND CHARACTERISTIC CURVES

Fig. 1 — MAXIMUM FORWARD SURGE CURRENT




Fig. 2 — DERATING CURVE FOR OUTPUT RECTIFIED CURRENT




Fig. 3 — TYPICAL FORWARD CHARACTERISTICS




Fig. 4 — TYPICAL REVERSE CHARACTERISTICS

