



# 1.7GHz to 2.5GHz, Direct I/Q Modulator with VGA and PA Driver

## General Description

The MAX2720/MAX2721 are low-cost, high-performance, direct I/Q modulators designed for use in wideband-CDMA and wireless local-loop (WLL) systems. Their direct-upconversion architecture reduces system cost, component count, and board space compared to devices with dual-conversion architectures.

The MAX2720/MAX2721 include an I/Q modulator, a variable gain amplifier (VGA), and a power amplifier (PA) driver. The quadrature modulator accepts differential baseband I/Q signals and directly modulates an RF carrier in the 1.7GHz to 2.1GHz range (MAX2720) or the 2.1GHz to 2.5GHz range (MAX2721). The VGA provides 35dB of output power control. The modulator's amplitude and phase balance yield 35dBc of sideband suppression and 30dBc of carrier suppression. These devices feature an LO frequency doubler that allows the external LO source to operate at half-frequency or full-frequency when disabled.

The MAX2720/MAX2721 operate from a single +2.7V to +3.3V supply and require only 77mA (MAX2720) or 86mA (MAX2721) of supply current. An additional 20mA of supply current is saved by disabling the stand-alone PA driver. A low-power shutdown mode further reduces supply current to less than 0.1μA. The device is packaged in the small 20-pin TSSOP-EP with exposed paddle to improve RF performance.

## Applications

Wireless Local Loop (WLL)  
Wideband CDMA Systems  
LMDS/MMDS  
2.4GHz Broadband ISM Radios  
DCS/PCS Base Stations

Pin Configuration appears at end of data sheet.

## Features


- ◆ RF Frequency Range
  - 1.7GHz to 2.1GHz (MAX2720)
  - 2.1GHz to 2.5GHz (MAX2721)
- ◆ Integrated I/Q Modulator, LO Doubler, VGA, and PA Driver
- ◆ 35dB VGA Gain Control Range
- ◆ 35dBc Sideband Suppression
- ◆ 30dBc Carrier Suppression
- ◆ Low Supply Current
  - 77mA (MAX2720), 86mA (MAX2721)
  - 20mA Reduction with PA Driver Disabled
- ◆ 0.1μA Supply Current in Shutdown Mode
- ◆ +2.7V to +3.3V Single-Supply Operation

## Ordering Information

| PART       | TEMP. RANGE    | PIN-PACKAGE  |
|------------|----------------|--------------|
| MAX2720EUP | -40°C to +85°C | 20 TSSOP-EP* |
| MAX2721EUP | -40°C to +85°C | 20 TSSOP-EP* |

\*Exposed paddle.

## Functional Diagram



# 1.7GHz to 2.5GHz, Direct I/Q Modulator with VGA and PA Driver

## ABSOLUTE MAXIMUM RATINGS

|                                                          |                                   |
|----------------------------------------------------------|-----------------------------------|
| V <sub>CC</sub> to GND .....                             | -0.3V to +6V                      |
| ENX2, SHDN, PC, I+, I-, Q+, Q-, LO,<br>DRIN to GND ..... | -0.3V to (V <sub>CC</sub> + 0.3V) |
| ENX2, SHDN Continuous Current .....                      | ±10mA                             |
| PC Continuous Current .....                              | ±10mA                             |
| I+ to I-, Q+ to Q- .....                                 | ±2V                               |
| MODOUT, DROUT to GND Short-Circuit Duration .....        | 10s                               |

|                                                                                                               |                 |
|---------------------------------------------------------------------------------------------------------------|-----------------|
| Continuous Power Dissipation (T <sub>A</sub> = +70°C)<br>20-Pin TSSOP-EP (derate 21.7mW/°C above +70°C) ..... | 1.74W           |
| Operating Temperature Range .....                                                                             | -40°C to +85°C  |
| Junction Temperature .....                                                                                    | +150°C          |
| Storage Temperature Range .....                                                                               | -65°C to +150°C |
| Lead Temperature (soldering 10s) .....                                                                        | +300°C          |

Stresses beyond those listed under "Absolute Maximum Ratings" may cause permanent damage to the device. These are stress ratings only, and functional operation of the device at these or any other conditions beyond those indicated in the operational sections of the specifications is not implied. Exposure to absolute maximum rating conditions for extended periods may affect device reliability.

## DC ELECTRICAL CHARACTERISTICS

(V<sub>CC</sub> = +2.7V to +3.3V; SHDN = V<sub>CC</sub>; ENX2 = GND; V<sub>PC</sub> = 0.5V; no input AC signals applied to I+, I-, Q+, Q-, LO, DRIN. MODOUT and DROUT = V<sub>CC</sub>, T<sub>A</sub> = -40°C to +85°C. Typical values are at V<sub>CC</sub> = +3V, T<sub>A</sub> = +25°C, unless otherwise noted.)

| PARAMETER                              | CONDITIONS                                | MIN | TYP | MAX | UNITS |
|----------------------------------------|-------------------------------------------|-----|-----|-----|-------|
| Supply Voltage                         |                                           | 2.7 |     | 3.3 | V     |
| Supply Current                         | MAX2720                                   |     | 77  | 119 | mA    |
|                                        | MAX2721                                   |     | 86  | 129 |       |
| Supply Current with PA Driver Disabled | MAX2720, DRIN = GND                       |     | 59  | 86  | mA    |
|                                        | MAX2721, DRIN = GND                       |     | 67  | 96  |       |
| Shutdown Supply Current                | SHDN = GND                                |     | 0.1 | 10  | μA    |
| Logic Input High Voltage               |                                           | 2.0 |     |     | V     |
| Logic Input Low Voltage                |                                           |     |     | 0.5 | V     |
| Logic Input Bias Current               |                                           | -1  |     | 1   | μA    |
| PC Input Bias Current                  | 0.5V < V <sub>PC</sub> < 2.5V             | -5  |     | 5   | μA    |
|                                        | 0.5V < V <sub>PC</sub> < 2.5V, SHDN = GND |     | 2.5 |     |       |

## AC ELECTRICAL CHARACTERISTICS

(MAX2720/MAX2721 EV Kit, V<sub>CC</sub> = +3.0V, SHDN = V<sub>CC</sub>, ENX2 = GND, V<sub>PC</sub> = 2.5V, input I/Q signals driven in quadrature, from a 1kΩ source impedance, single-ended, f<sub>I+</sub> = f<sub>Q+</sub> = 500kHz, V<sub>I+</sub> = V<sub>Q+</sub> = 200mVp-p, P<sub>LO</sub> = -13dBm, f<sub>LO</sub> = 950MHz (MAX2720), f<sub>LO</sub> = 1157.5MHz (MAX2721), P<sub>DRIN</sub> = -12dBm, f<sub>DRIN</sub> = 1900MHz (MAX2720), f<sub>DRIN</sub> = 2315MHz (MAX2721), MODOUT and DROUT ports are matched to a 50Ω load, T<sub>A</sub> = +25°C, unless otherwise noted.) (Note 1)

| PARAMETER                         | CONDITIONS                                                              | MIN | TYP  | MAX | UNITS   |
|-----------------------------------|-------------------------------------------------------------------------|-----|------|-----|---------|
| <b>I/Q BASEBAND INPUTS</b>        |                                                                         |     |      |     |         |
| I/Q Input -1dB Bandwidth (Note 2) |                                                                         | 14  | 20   |     | MHz     |
| I/Q Input -3dB Bandwidth (Note 2) |                                                                         |     | 40   |     | MHz     |
| I/Q Differential Input Level      |                                                                         |     | 200  | 630 | mVp-p   |
| I/Q Gain Imbalance                | f <sub>I</sub> = f <sub>Q</sub> < BW-3dB, 0.5V < V <sub>PC</sub> < 2.5V |     | ±0.2 |     | dB      |
| I/Q Phase Imbalance               | f <sub>I</sub> = f <sub>Q</sub> < BW-3dB, 0.5V < V <sub>PC</sub> < 2.5V |     | ±1.0 |     | degrees |
| I/Q Input Resistance              | f <sub>I</sub> = f <sub>Q</sub> < BW-1dB                                | 1.6 | 2.0  |     | kΩ      |
| I/Q Input Resistance Mismatch     | f <sub>I</sub> = f <sub>Q</sub> < BW-1dB                                |     | 18   |     | Ω       |
| I/Q Input Capacitance             | f <sub>I</sub> = f <sub>Q</sub> < BW-1dB                                |     | 5    |     | pF      |
| Group Delay Ripple                | 100kHz < f <sub>I+</sub> = f <sub>Q+</sub> < 2MHz                       |     | 1    |     | ns      |
| Group Delay Mismatch              | 100kHz < f <sub>I</sub> = f <sub>Q</sub> < 2MHz                         |     | 1    |     | ns      |

# 1.7GHz to 2.5GHz, Direct I/Q Modulator with VGA and PA Driver

MAX2720/MAX2721

## AC ELECTRICAL CHARACTERISTICS (continued)

(MAX2720/MAX2721 EV Kit,  $V_{CC} = +3.0V$ ,  $\overline{SHDN} = V_{CC}$ ,  $\overline{ENX2} = GND$ ,  $V_{PC} = 2.5V$ , input I/Q signals driven in quadrature, from a  $1k\Omega$  source impedance, single-ended,  $f_{I+} = f_{Q+} = 500kHz$ ,  $V_{I+} = V_{Q+} = 200mVp-p$ ,  $P_{LO} = -13dBm$ ,  $f_{LO} = 950MHz$  (MAX2720),  $f_{LO} = 1157.5MHz$  (MAX2721),  $P_{DRIN} = -12dBm$ ,  $f_{DRIN} = 1900MHz$  (MAX2720),  $f_{DRIN} = 2315MHz$  (MAX2721), MODOUT and DROUT ports are matched to a  $50\Omega$  load,  $T_A = +25^\circ C$ , unless otherwise noted.) (Note 1)

| PARAMETER                                             | CONDITIONS                                                                                                   |                                     | MIN   | TYP   | MAX  | UNITS  |
|-------------------------------------------------------|--------------------------------------------------------------------------------------------------------------|-------------------------------------|-------|-------|------|--------|
| MODULATOR OUTPUT                                      |                                                                                                              |                                     |       |       |      |        |
| Frequency Range (Note 3)                              | MAX2720                                                                                                      |                                     | 1700  |       | 2100 | MHz    |
|                                                       | MAX2721                                                                                                      |                                     | 2100  |       | 2500 |        |
| Output Power, High                                    | MAX2720, V <sub>PC</sub> = 2.5V, $\overline{ENX2}$ = V <sub>CC</sub> or GND, T <sub>A</sub> = +25°C (Note 3) |                                     | -12.5 | -8.5  | -6.0 | dBm    |
|                                                       | MAX2721, V <sub>PC</sub> = 2.5V, $\overline{ENX2}$ = V <sub>CC</sub> or GND, T <sub>A</sub> = +25°C (Note 3) |                                     | -10.5 | -5.0  | -2.5 |        |
| Output Power Variation Over Temperature               | V <sub>PC</sub> = 2.5V, T <sub>A</sub> = -40°C to +85°C                                                      | MAX2720                             |       | ±1.0  | ±1.8 | dB     |
|                                                       |                                                                                                              | MAX2721                             |       | ±0.8  | ±1.5 |        |
| Power Control Range                                   | V <sub>PC</sub> = 0.5V, $\overline{ENX2}$ = V <sub>CC</sub> or GND                                           | MAX2720                             | 29    | 35    |      | dB     |
|                                                       |                                                                                                              | MAX2721                             | 28    | 32    |      |        |
| PC Slope                                              | Slope between V <sub>PC</sub> = 1V and V <sub>PC</sub> = 2V                                                  |                                     |       | 19    | 23   | dB/V   |
| Output 1dB Compression Point                          | V <sub>PC</sub> = 2.5V                                                                                       | MAX2720                             | +1    | +5    |      | dBm    |
|                                                       |                                                                                                              | MAX2721                             | +3    | +6    |      |        |
| Output Third-Order Intercept Point (Note 4)           | V <sub>PC</sub> = 2.5V                                                                                       | MAX2720                             | +8    | +14   |      | dBm    |
|                                                       |                                                                                                              | MAX2721                             | +9    | +14   |      |        |
| Output VSWR                                           | 0.5V < V <sub>PC</sub> < 2.5V                                                                                |                                     |       | 2:1   |      |        |
| Out-of-Band Noise Density                             | V <sub>PC</sub> = 2.5V, I/Q terminated in 50Ω                                                                |                                     |       | -141  | -137 | dBm/Hz |
| Carrier Suppression                                   | MAX2720, 0.5V < V <sub>PC</sub> < 2.5V                                                                       |                                     | 26    | 33    |      | dBc    |
|                                                       | MAX2721                                                                                                      | V <sub>PC</sub> = 2.5V              | 24    | 31    |      |        |
|                                                       |                                                                                                              | V <sub>PC</sub> = 0.5V              | 20    | 25    |      |        |
| Sideband Suppression                                  | 0.5V < V <sub>PC</sub> < 2.5V                                                                                | MAX2720                             | 30    | 40    |      | dBc    |
|                                                       |                                                                                                              | MAX2721                             | 28    | 35    |      |        |
| MODOUT to LO Input Isolation                          |                                                                                                              |                                     |       | 50    | 45   | dB     |
| Power-Supply Ripple Rejection (Note 5)                | V <sub>CC</sub> = +3.0V + 100mVp-p at 10kHz/300kHz                                                           |                                     |       | 41    |      | dBc    |
| LO BUFFER, LO FREQUENCY DOUBLER, QUADRATURE GENERATOR |                                                                                                              |                                     |       |       |      |        |
| LO Frequency Range (Note 3)                           | MAX2720                                                                                                      | $\overline{ENX2}$ = GND             | 850   |       | 1050 | MHz    |
|                                                       |                                                                                                              | $\overline{ENX2}$ = V <sub>CC</sub> | 1700  |       | 2100 |        |
|                                                       | MAX2721                                                                                                      | $\overline{ENX2}$ = GND             | 1050  |       | 1250 |        |
|                                                       |                                                                                                              | $\overline{ENX2}$ = V <sub>CC</sub> | 2100  |       | 2500 |        |
| LO Input VSWR                                         | MAX2720                                                                                                      | $\overline{ENX2}$ = GND             |       | 1.9:1 |      |        |
|                                                       |                                                                                                              | $\overline{ENX2}$ = V <sub>CC</sub> |       | 1.8:1 |      |        |
|                                                       | MAX2721                                                                                                      | $\overline{ENX2}$ = GND             |       | 1.8:1 |      |        |
|                                                       |                                                                                                              | $\overline{ENX2}$ = V <sub>CC</sub> |       | 1.6:1 |      |        |
| LO Input Power (Note 3)                               |                                                                                                              |                                     | -16   | -10   |      | dBm    |

# 1.7GHz to 2.5GHz, Direct I/Q Modulator with VGA and PA Driver

## AC ELECTRICAL CHARACTERISTICS (continued)

(MAX2720/MAX2721 EV Kit,  $V_{CC} = +3.0V$ ,  $\overline{SHDN} = V_{CC}$ ,  $\overline{ENX2} = GND$ ,  $V_{PC} = 2.5V$ , input I/Q signals driven in quadrature, from a  $1k\Omega$  source impedance, single-ended,  $f_{I+} = f_{Q+} = 500kHz$ ,  $V_{I+} = V_{Q+} = 200mVp-p$ ,  $P_{LO} = -13dBm$ ,  $f_{LO} = 950MHz$  (MAX2720),  $f_{LO} = 1157.5MHz$  (MAX2721),  $P_{DRIN} = -12dBm$ ,  $f_{DRIN} = 1900MHz$  (MAX2720),  $f_{DRIN} = 2315MHz$  (MAX2721), MODOUT and DROUT ports are matched to a  $50\Omega$  load,  $T_A = +25^\circ C$ , unless otherwise noted.) (Note 1)

| PARAMETER                          | CONDITIONS                      |         | MIN  | TYP   | MAX  | UNITS |
|------------------------------------|---------------------------------|---------|------|-------|------|-------|
| PA DRIVER                          |                                 |         |      |       |      |       |
| Frequency Range (Note 6)           | MAX2720                         |         | 1700 |       | 2100 | MHz   |
|                                    | MAX2721                         |         | 2100 |       | 2500 |       |
| Gain (Note 6)                      | MAX2720                         |         | 11   | 13.5  | 15.5 | dB    |
|                                    | MAX2721                         |         | 8.5  | 11.5  | 15.5 |       |
| Gain Variation Over Temperature    | T <sub>A</sub> = -40°C to +85°C | MAX2720 |      | ±0.4  | ±0.8 | dB    |
|                                    |                                 | MAX2721 |      | ±0.3  | ±0.8 |       |
| Noise Figure                       | MAX2720                         |         |      | 2.4   |      | dB    |
|                                    | MAX2721                         |         |      | 2.6   |      |       |
| Output 1dB Compression Point       | MAX2720                         |         | +9.5 | +12.5 |      | dBm   |
|                                    | MAX2721                         |         | +8   | +11   |      |       |
| Output Third-Order Intercept Point | MAX2720 (Note 7)                |         | +22  | +24   |      | dBm   |
|                                    | MAX2721 (Note 8)                |         | +20  | +24   |      |       |
| Reverse Isolation                  |                                 |         |      | 19    |      | dB    |
| DROUT to LO Input Isolation        |                                 |         |      | 65    |      | dB    |
| Input VSWR                         |                                 |         |      | 1.5:1 |      |       |
| Output VSWR                        |                                 |         |      | 1.5:1 |      |       |

**Note 1:** Min/max limits are guaranteed by design and characterization and are not production tested.

**Note 2:** I/Q input bandwidth is determined by the baseband source impedance and the I/Q input capacitance. The bandwidth can be increased by lowering the baseband source impedance.

**Note 3:** MODOUT output power specifications are met over this frequency range for  $V_{PC} = 2.5V$  and  $T_A = +25^\circ C$ .

**Note 4:** IP3 measured with two tones,  $f_1 = 500kHz$  and  $f_2 = 600kHz$ , at  $100mVp-p$  each.

**Note 5:** Measured relative to desired upconverted signal level.

**Note 6:** DROUT gain specifications are met over this frequency range at  $T_A = +25^\circ C$ .

**Note 7:** IP3 measured with two tones,  $f_1 = 1900MHz$  and  $f_2 = 1901MHz$ , at  $-18dBm$  each.

**Note 8:** IP3 measured with two tones,  $f_1 = 2315MHz$  and  $f_2 = 2316MHz$ , at  $-18dBm$  each.


# 1.7GHz to 2.5GHz, Direct I/Q Modulator with VGA and PA Driver

## Typical Operating Characteristics


(MAX2720/MAX2721 EV Kit,  $V_{CC} = +3.0V$ ,  $\overline{SHDN} = V_{CC}$ ,  $\overline{ENX2} = GND$ ,  $V_{PC} = 2.5V$ , input I/Q signals driven in quadrature, from a  $1k\Omega$  source impedance, single-ended,  $f_{I+} = f_{Q+} = 500kHz$ ,  $V_{I+} = V_{Q+} = 200mVp-p$ ,  $P_{LO} = -13dBm$ ,  $f_{LO} = 950MHz$  (MAX2720),  $f_{LO} = 1157.5MHz$  (MAX2721),  $P_{DRIN} = -12dBm$ ,  $f_{DRIN} = 1900MHz$  (MAX2720),  $f_{DRIN} = 2315MHz$  (MAX2721), MODOUT and DROUT ports are matched to a  $50\Omega$  load,  $T_A = +25^\circ C$ , unless otherwise noted.) (Note 1)

### MAX2720


**SUPPLY CURRENT vs. SUPPLY VOLTAGE  
WITH PA DRIVER ENABLED**




**SUPPLY CURRENT vs. SUPPLY VOLTAGE  
WITH PA DRIVER DISABLED**




**MODULATOR OUTPUT POWER  
vs. RF FREQUENCY**



**MODULATOR PERFORMANCE  
vs. LO POWER ( $\overline{ENX2} = GND$ )**



**MODULATOR PERFORMANCE  
vs. LO POWER ( $\overline{ENX2} = V_{CC}$ )**




# 1.7GHz to 2.5GHz, Direct I/Q Modulator with VGA and PA Driver

## Typical Operating Characteristics (continued)


(MAX2720/MAX2721 EV Kit,  $V_{CC} = +3.0V$ ,  $\overline{SHDN} = V_{CC}$ ,  $\overline{ENX2} = GND$ ,  $V_{PC} = 2.5V$ , input I/Q signals driven in quadrature, from a  $1k\Omega$  source impedance, single-ended,  $f_{I+} = f_{Q+} = 500kHz$ ,  $V_{I+} = V_{Q+} = 200mV_{p-p}$ ,  $P_{LO} = -13dBm$ ,  $f_{LO} = 950MHz$  (MAX2720),  $f_{LO} = 1157.5MHz$  (MAX2721),  $P_{DRIN} = -12dBm$ ,  $f_{DRIN} = 1900MHz$  (MAX2720),  $f_{DRIN} = 2315MHz$  (MAX2721), MODOUT and DROUT ports are matched to a  $50\Omega$  load,  $T_A = +25^\circ C$ , unless otherwise noted.) (Note 1)

### MAX2720


**MODULATOR OUTPUT POWER  
vs. PC VOLTAGE ( $\overline{ENX2} = GND$ )**




**MODULATOR CARRIER SUPPRESSION  
vs. PC VOLTAGE ( $\overline{ENX2} = GND$ )**




**MODULATION SIDEBAND SUPPRESSION  
vs. PC VOLTAGE ( $\overline{ENX2} = GND$ )**




**MODULATOR OUTPUT POWER  
vs. PC VOLTAGE ( $\overline{ENX2} = V_{CC}$ )**



**MODULATOR CARRIER SUPPRESSION  
vs. PC VOLTAGE ( $\overline{ENX2} = V_{CC}$ )**



**MODULATOR SIDEBAND SUPPRESSION  
vs. PC VOLTAGE ( $\overline{ENX2} = V_{CC}$ )**




# 1.7GHz to 2.5GHz, Direct I/Q Modulator with VGA and PA Driver

## Typical Operating Characteristics (continued)


(MAX2720/MAX2721 EV Kit,  $V_{CC} = +3.0V$ ,  $\overline{SHDN} = V_{CC}$ ,  $\overline{ENX2} = GND$ ,  $V_{PC} = 2.5V$ , input I/Q signals driven in quadrature, from a  $1k\Omega$  source impedance, single-ended,  $f_{I+} = f_{Q+} = 500kHz$ ,  $V_{I+} = V_{Q+} = 200mVp-p$ ,  $P_{LO} = -13dBm$ ,  $f_{LO} = 950MHz$  (MAX2720),  $f_{LO} = 1157.5MHz$  (MAX2721),  $P_{DRIN} = -12dBm$ ,  $f_{DRIN} = 1900MHz$  (MAX2720),  $f_{DRIN} = 2315MHz$  (MAX2721), MODOUT and DROUT ports are matched to a  $50\Omega$  load,  $T_A = +25^\circ C$ , unless otherwise noted.) (Note 1)

### MAX2720


**MODULATOR OUTPUT POWER  
vs. PC VOLTAGE ( $\overline{ENX2} = GND$ )**




**MODULATOR CARRIER SUPPRESSION  
vs. PC VOLTAGE ( $\overline{ENX2} = GND$ )**




**MODULATOR SIDEBAND SUPPRESSION  
vs. PC VOLTAGE ( $\overline{ENX2} = GND$ )**




**MODULATOR OUTPUT POWER  
vs. PC VOLTAGE ( $\overline{ENX2} = V_{CC}$ )**



**MODULATOR CARRIER SUPPRESSION  
vs. PC VOLTAGE ( $\overline{ENX2} = V_{CC}$ )**



**MODULATOR SIDEBAND SUPPRESSION  
vs. PC VOLTAGE ( $\overline{ENX2} = V_{CC}$ )**



MAX2720/MAX2721


# 1.7GHz to 2.5GHz, Direct I/Q Modulator with VGA and PA Driver

## Typical Operating Characteristics (continued)


(MAX2720/MAX2721 EV Kit,  $V_{CC} = +3.0V$ ,  $\overline{SHDN} = V_{CC}$ ,  $\overline{ENX2} = GND$ ,  $V_{PC} = 2.5V$ , input I/Q signals driven in quadrature, from a  $1k\Omega$  source impedance, single-ended,  $f_{I+} = f_{Q+} = 500kHz$ ,  $V_{I+} = V_{Q+} = 200mVp-p$ ,  $P_{LO} = -13dBm$ ,  $f_{LO} = 950MHz$  (MAX2720),  $f_{LO} = 1157.5MHz$  (MAX2721),  $P_{DRIN} = -12dBm$ ,  $f_{DRIN} = 1900MHz$  (MAX2720),  $f_{DRIN} = 2315MHz$  (MAX2721), MODOUT and DROUT ports are matched to a  $50\Omega$  load,  $T_A = +25^\circ C$ , unless otherwise noted.) (Note 1)

### MAX2720


**MODULATOR OUTPUT POWER  
vs. INPUT LEVEL ( $T_A = -40^\circ C$ )**




**MODULATOR OUTPUT POWER  
vs. INPUT LEVEL ( $T_A = +25^\circ C$ )**




**MODULATOR OUTPUT POWER  
vs. INPUT LEVEL ( $T_A = +85^\circ C$ )**




**MODULATOR OUTPUT IP3  
vs. PC VOLTAGE**



**LO PORT VSWR  
vs. LO FREQUENCY ( $\overline{ENX2} = GND$ )**



**LO PORT VSWR  
vs. LO FREQUENCY ( $\overline{ENX2} = V_{CC}$ )**




# 1.7GHz to 2.5GHz, Direct I/Q Modulator with VGA and PA Driver

## Typical Operating Characteristics (continued)


(MAX2720/MAX2721 EV Kit,  $V_{CC} = +3.0V$ ,  $\overline{SHDN} = V_{CC}$ ,  $\overline{ENX2} = GND$ ,  $V_{PC} = 2.5V$ , input I/Q signals driven in quadrature, from a  $1k\Omega$  source impedance, single-ended,  $f_{I+} = f_{Q+} = 500kHz$ ,  $V_{I+} = V_{Q+} = 200mVp-p$ ,  $P_{LO} = -13dBm$ ,  $f_{LO} = 950MHz$  (MAX2720),  $f_{LO} = 1157.5MHz$  (MAX2721),  $P_{DRIN} = -12dBm$ ,  $f_{DRIN} = 1900MHz$  (MAX2720),  $f_{DRIN} = 2315MHz$  (MAX2721), MODOUT and DROUT ports are matched to a  $50\Omega$  load,  $T_A = +25^\circ C$ , unless otherwise noted.) (Note 1)

### MAX2720


PA DRIVER GAIN vs. SUPPLY VOLTAGE




PA DRIVER OUTPUT IP3 vs. SUPPLY VOLTAGE




PA DRIVER OUTPUT P1dB vs. SUPPLY VOLTAGE




PA DRIVER GAIN vs. RF FREQUENCY



PA DRIVER OUTPUT IP3 vs. FREQUENCY



PA DRIVER OUTPUT P1dB COMPRESSION POINT vs. FREQUENCY





MAX2720/MAX2721

# 1.7GHz to 2.5GHz, Direct I/Q Modulator with VGA and PA Driver

## Typical Operating Characteristics (continued)

(MAX2720/MAX2721 EV Kit,  $V_{CC} = +3.0V$ ,  $\overline{SHDN} = V_{CC}$ ,  $\overline{ENX2} = GND$ ,  $V_{PC} = 2.5V$ , input I/Q signals driven in quadrature, from a  $1k\Omega$  source impedance, single-ended,  $f_{I+} = f_{Q+} = 500kHz$ ,  $V_{I+} = V_{Q+} = 200mVp-p$ ,  $P_{LO} = -13dBm$ ,  $f_{LO} = 950MHz$  (MAX2720),  $f_{LO} = 1157.5MHz$  (MAX2721),  $P_{DRIN} = -12dBm$ ,  $f_{DRIN} = 1900MHz$  (MAX2720),  $f_{DRIN} = 2315MHz$  (MAX2721),  $MODOUT$  and  $DROUT$  ports are matched to a  $50\Omega$  load,  $T_A = +25^\circ C$ , unless otherwise noted.) (Note 1)

### MAX2720




# 1.7GHz to 2.5GHz, Direct I/Q Modulator with VGA and PA Driver

## Typical Operating Characteristics (continued)


(MAX2720/MAX2721 EV Kit,  $V_{CC} = +3.0V$ ,  $\overline{SHDN} = V_{CC}$ ,  $\overline{ENX2} = GND$ ,  $V_{PC} = 2.5V$ , input I/Q signals driven in quadrature, from a  $1k\Omega$  source impedance, single-ended,  $f_{I+} = f_{Q+} = 500kHz$ ,  $V_{I+} = V_{Q+} = 200mV_{p-p}$ ,  $P_{LO} = -13dBm$ ,  $f_{LO} = 950MHz$  (MAX2720),  $f_{LO} = 1157.5MHz$  (MAX2721),  $P_{DRIN} = -12dBm$ ,  $f_{DRIN} = 1900MHz$  (MAX2720),  $f_{DRIN} = 2315MHz$  (MAX2721), MODOUT and DROUT ports are matched to a  $50\Omega$  load,  $T_A = +25^\circ C$ , unless otherwise noted.) (Note 1)

### MAX2721


**SUPPLY CURRENT vs. SUPPLY VOLTAGE  
WITH PA DRIVER ENABLED**




**SUPPLY CURRENT vs. SUPPLY VOLTAGE  
WITH PA DRIVER DISABLED**




**MODULATOR OUTPUT POWER  
vs. RF FREQUENCY**



**MODULATOR PERFORMANCE  
vs. LO POWER (ENX2 = GND)**



**MODULATOR PERFORMANCE  
vs. LO POWER (ENX2 = VCC)**









# 1.7GHz to 2.5GHz, Direct I/Q Modulator with VGA and PA Driver

## Typical Operating Characteristics (continued)

(MAX2720/MAX2721 EV Kit,  $V_{CC} = +3.0V$ ,  $\overline{SHDN} = V_{CC}$ ,  $\overline{ENX2} = GND$ ,  $V_{PC} = 2.5V$ , input I/Q signals driven in quadrature, from a  $1k\Omega$  source impedance, single-ended,  $f_{I+} = f_{Q+} = 500kHz$ ,  $V_{I+} = V_{Q+} = 200mVp-p$ ,  $P_{LO} = -13dBm$ ,  $f_{LO} = 950MHz$  (MAX2720),  $f_{LO} = 1157.5MHz$  (MAX2721),  $P_{DRIN} = -12dBm$ ,  $f_{DRIN} = 1900MHz$  (MAX2720),  $f_{DRIN} = 2315MHz$  (MAX2721), MODOUT and DROUT ports are matched to a  $50\Omega$  load,  $T_A = +25^\circ C$ , unless otherwise noted.) (Note 1)

### MAX2721









# 1.7GHz to 2.5GHz, Direct I/Q Modulator with VGA and PA Driver

## Typical Operating Characteristics (continued)

(MAX2720/MAX2721 EV Kit,  $V_{CC} = +3.0V$ ,  $\overline{SHDN} = V_{CC}$ ,  $\overline{ENX2} = GND$ ,  $V_{PC} = 2.5V$ , input I/Q signals driven in quadrature, from a  $1k\Omega$  source impedance, single-ended,  $f_{I+} = f_{Q+} = 500kHz$ ,  $V_{I+} = V_{Q+} = 200mV_{p-p}$ ,  $P_{LO} = -13dBm$ ,  $f_{LO} = 950MHz$  (MAX2720),  $f_{LO} = 1157.5MHz$  (MAX2721),  $P_{DRIN} = -12dBm$ ,  $f_{DRIN} = 1900MHz$  (MAX2720),  $f_{DRIN} = 2315MHz$  (MAX2721), MODOUT and DROUT ports are matched to a  $50\Omega$  load,  $T_A = +25^\circ C$ , unless otherwise noted.) (Note 1)

### MAX2721



MAX2720/MAX2721


# 1.7GHz to 2.5GHz, Direct I/Q Modulator with VGA and PA Driver

## Typical Operating Characteristics (continued)


(MAX2720/MAX2721 EV Kit,  $V_{CC} = +3.0V$ ,  $\overline{SHDN} = V_{CC}$ ,  $\overline{ENX2} = GND$ ,  $V_{PC} = 2.5V$ , input I/Q signals driven in quadrature, from a  $1k\Omega$  source impedance, single-ended,  $f_{I+} = f_{Q+} = 500kHz$ ,  $V_{I+} = V_{Q+} = 200mVp-p$ ,  $P_{LO} = -13dBm$ ,  $f_{LO} = 950MHz$  (MAX2720),  $f_{LO} = 1157.5MHz$  (MAX2721),  $P_{DRIN} = -12dBm$ ,  $f_{DRIN} = 1900MHz$  (MAX2720),  $f_{DRIN} = 2315MHz$  (MAX2721), MODOUT and DROUT ports are matched to a  $50\Omega$  load,  $T_A = +25^\circ C$ , unless otherwise noted.) (Note 1)

### MAX2721


**MODULATOR OUTPUT POWER  
vs. INPUT LEVEL ( $T_A = -40^\circ C$ )**




**MODULATOR OUTPUT POWER  
vs. INPUT LEVEL ( $T_A = +25^\circ C$ )**




**MODULATOR OUTPUT POWER  
vs. INPUT LEVEL ( $T_A = +85^\circ C$ )**




**MODULATOR OUTPUT IP3  
vs. PC VOLTAGE**



**MODULATOR OUTPUT P1dB  
COMPRESSION POINT vs. PC VOLTAGE**



**LO PORT VSWR vs. LO FREQUENCY  
( $ENX2 = V_{CC}$ )**




# 1.7GHz to 2.5GHz, Direct I/Q Modulator with VGA and PA Driver

## Typical Operating Characteristics (continued)


(MAX2720/MAX2721 EV Kit,  $V_{CC} = +3.0V$ ,  $\overline{SHDN} = V_{CC}$ ,  $\overline{ENX2} = GND$ ,  $V_{PC} = 2.5V$ , input I/Q signals driven in quadrature, from a  $1k\Omega$  source impedance, single-ended,  $f_{I+} = f_{Q+} = 500kHz$ ,  $V_{I+} = V_{Q+} = 200mV_{p-p}$ ,  $P_{LO} = -13dBm$ ,  $f_{LO} = 950MHz$  (MAX2720),  $f_{LO} = 1157.5MHz$  (MAX2721),  $P_{DRIN} = -12dBm$ ,  $f_{DRIN} = 1900MHz$  (MAX2720),  $f_{DRIN} = 2315MHz$  (MAX2721), MODOUT and DROUT ports are matched to a  $50\Omega$  load,  $T_A = +25^\circ C$ , unless otherwise noted.) (Note 1)

### MAX2721


LO PORT VSWR vs. FREQUENCY  
( $\overline{ENX2} = GND$ )




PA DRIVER GAIN vs. SUPPLY VOLTAGE




PA DRIVER OUTPUT IP3  
vs. SUPPLY VOLTAGE




PA DRIVER OUTPUT P1dB  
vs. SUPPLY VOLTAGE



PA DRIVER GAIN  
vs. RF FREQUENCY



PA DRIVER OUTPUT IP3  
vs. FREQUENCY






# 1.7GHz to 2.5GHz, Direct I/Q Modulator with VGA and PA Driver

## Typical Operating Characteristics (continued)

(MAX2720/MAX2721 EV Kit,  $V_{CC} = +3.0V$ ,  $\overline{SHDN} = V_{CC}$ ,  $\overline{ENX2} = GND$ ,  $V_{PC} = 2.5V$ , input I/Q signals driven in quadrature, from a  $1k\Omega$  source impedance, single-ended,  $f_{I+} = f_{Q+} = 500kHz$ ,  $V_{I+} = V_{Q+} = 200mVp-p$ ,  $P_{LO} = -13dBm$ ,  $f_{LO} = 950MHz$  (MAX2720),  $f_{LO} = 1157.5MHz$  (MAX2721),  $P_{DRIN} = -12dBm$ ,  $f_{DRIN} = 1900MHz$  (MAX2720),  $f_{DRIN} = 2315MHz$  (MAX2721), MODOUT and DROUT ports are matched to a  $50\Omega$  load,  $T_A = +25^\circ C$ , unless otherwise noted.) (Note 1)

### MAX2721



# 1.7GHz to 2.5GHz, Direct I/Q Modulator with VGA and PA Driver

MAX2720/MAX2721

## Pin Description

| PIN              | NAME                     | FUNCTION                                                                                                                                                                                                                                                                                                                                                                                                                          |
|------------------|--------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| 1, 5, 10, 19, EP | GND                      | Ground. Connect to ground plane with lowest inductance path. Solder exposed paddle evenly to the board ground plane.                                                                                                                                                                                                                                                                                                              |
| 2                | DROUT                    | PA Driver Open-Collector Output Port. Requires an external matching network and a pull-up inductor to $V_{CC}$ for proper biasing. See <i>Typical Application Circuit</i> for recommended component values.                                                                                                                                                                                                                       |
| 3                | $\overline{\text{SHDN}}$ | Shutdown Control Input. Drive with a logic-level high to enable the device. Drive with a logic-level low to disable the device. Bypass with a 1000pF capacitor to ground, as close to the pin as possible to minimize the amount of external noise coupled onto the control line.                                                                                                                                                 |
| 4, 6, 9, 12, 15  | $V_{CC}$                 | Supply Voltage Input. Bypass to ground with the specified capacitor as close to the pin as possible. (See <i>Typical Application Circuit</i> .)                                                                                                                                                                                                                                                                                   |
| 7, 8             | I-, I+                   | In-Phase Differential Input Ports. Requires DC-blocking capacitors. See <i>Typical Application Circuit</i> for recommended component values.                                                                                                                                                                                                                                                                                      |
| 11               | LO                       | Local Oscillator input. Internally matched to $50\Omega$ over the operating frequency band. Requires a DC-blocking capacitor. See <i>Typical Application Circuit</i> for recommended component values.                                                                                                                                                                                                                            |
| 13, 14           | Q+, Q-                   | Quadrature Differential Input Ports. Requires DC-blocking capacitors. See <i>Typical Application Circuit</i> for recommended component values.                                                                                                                                                                                                                                                                                    |
| 16               | $\overline{\text{ENX2}}$ | Logic-Level Enable Input for LO Doubler. Drive with a logic-level low to enable the doubler, allowing the external LO to run at half-frequency, $f_{LO} = f_{OUT} / 2$ . Drive with a logic-level high to disable the doubler, and allow the external LO to run at full-frequency, $f_{LO} = f_{OUT}$ . Bypass with a 1000pF capacitor to ground as close to the pin as possible to minimize noise coupled into the control line. |
| 17               | MODOUT                   | Modulator Open-Collector Output Port. Requires an external matching network and a pull-up inductor to $V_{CC}$ for proper biasing. See <i>Typical Application Circuit</i> for recommended component values.                                                                                                                                                                                                                       |
| 18               | PC                       | Modulator Power Control Input. Apply a voltage between 0.5V to 2.5V to vary the output power of the I/Q modulator over a 30dB range. Bypass with a 1000pF capacitor to ground as close to the pin as possible to minimize noise on the control line.                                                                                                                                                                              |
| 20               | DRIN                     | PA Driver Amplifier Input Port. Requires an external matching network and a DC-blocking capacitor that can be part of the matching network. See <i>Typical Application Circuit</i> for recommended component values. Connect to ground to disable the PA Driver and reduce supply current.                                                                                                                                        |

## Detailed Description

The MAX2720/MAX2721 upconvert in-phase (I) and quadrature (Q) baseband signals directly to RF frequencies of 1700MHz to 2100MHz (MAX2720) or 2100MHz to 2500MHz (MAX2721). They are designed for wideband-CDMA and WLL systems where direct I/Q modulation of the RF carrier reduces system cost, component count, and board space compared to dual-conversion architectures.

Internally, the MAX2720/MAX2721 include an I/Q modulator, a variable gain amplifier (VGA), and a PA driver. Separate modulator output and PA driver input ports allow insertion of a bandpass filter between the modulator and PA driver for increased noise rejection. Disable the stand-alone PA driver to reduce current consumption. A low-power shutdown mode further reduces current consumption to less than 0.1 $\mu$ A. Additionally, a logic-level control disables or enables an internal frequency doubler that allows the external LO to run at full or half frequency.

# 1.7GHz to 2.5GHz, Direct I/Q Modulator with VGA and PA Driver

## I/Q Modulator

The MAX2720/MAX2721 modulator is composed of a pair of matched double-balanced mixers, an active LO quadrature generator, and a summing amplifier. The pair of mixers accept differential I/Q baseband signals that directly modulate the internal 0° and 90° LO signals applied to the I/Q mixers. An external LO source drives an internal LO quadrature generator that shifts the phase of the LO signal applied to the Q mixer by 90° relative to the LO signal applied to the I channel mixer. The modulated output of the I/Q mixers is summed together, and the undesired sideband is suppressed.

The I+, I-, Q+, and Q- input ports feature high-linearity buffer amplifiers with a -1dB bandwidth of 20MHz and a -3dB bandwidth of 38MHz (1k $\Omega$  I/Q source impedance), and accept differential input voltages up to 630mVp-p. Input bandwidth can be extended to beyond 100MHz by lowering the I/Q source impedance. The ports are internally biased and therefore require DC-blocking capacitors. For single-ended operation, bypass the I- and Q- ports with a capacitor to ground equal in value to the DC-blocking capacitors used on the I+ and Q+ ports. See the *Typical Application Circuit* for recommended component values.

## Variable Gain Amplifier (VGA)

A VGA follows the summing amplifier of the I/Q modulator. Apply a voltage between 0.5V and 2.5V to PC to vary the output power of the modulator over a 32dB span.

The open-collector MODOUT output requires a pull-up inductor to VCC for proper biasing, an external matching network for optimum power transfer, and a DC-blocking capacitor. Since the MAX2720/MAX2721 are optimized for different frequency ranges, they require different output matching networks. See the MAX2720 and

MAX2721 *Typical Application Circuit* for recommended component values. See Table 1 for matching to other frequencies.

## LO Buffer and LO Frequency Doubler

The MAX2720/MAX2721 feature an internal LO frequency doubler that allows the external LO source to run at full or half frequency (Table 2). Operating the LO at half frequency reduces injection-pulling of the voltage-controlled oscillator (VCO) from the PA, and reduces the complexity of designing a high-frequency VCO. An internal two-pole bandpass filter is integrated before the LO phase-shift network to help reduce LO harmonic content and spurious mixing.

To enable the LO frequency doubler, drive  $\overline{\text{ENX2}}$  to a logic-level low and operate the external LO source at half the RF carrier frequency. To disable the LO frequency doubler, drive  $\overline{\text{ENX2}}$  to a logic-level high and run the external LO source at the RF carrier frequency. See Table 2 for LO input frequency ranges.

The LO port is a single-ended input that achieves a VSWR of better than 2:1 over the specified LO input frequency range. Since the port is internally terminated with 50 $\Omega$ , it requires a DC-blocking capacitor. See the *Typical Applications Circuits* for recommended component values. For optimum performance, drive the LO port with an input power of -16dBm to -10dBm. Driving the LO port with lower input power levels may affect quadrature performance, while higher input powers may increase LO leakage.

## PA Driver Amplifier

The PA driver provides a gain of 13.5dB for the MAX2720 and 11.5dB for the MAX2721. The DRIN input port requires an external matching network and a

**Table 1. VGA MODOUT S22 Parameters (VCC = 3.0V, VPC = 2.5V, TA = +25°C)**

| MAX2720         |         |                     | MAX2721         |         |                     |
|-----------------|---------|---------------------|-----------------|---------|---------------------|
| FREQUENCY (MHz) | S22 MAG | S22 PHASE (degrees) | FREQUENCY (MHz) | S22 MAG | S22 PHASE (degrees) |
| 1700            | 0.914   | -66.6               | 2100            | 0.861   | -86.5               |
| 1750            | 0.909   | -68.9               | 2150            | 0.861   | -91.3               |
| 1800            | 0.896   | -71.0               | 2200            | 0.832   | -93.8               |
| 1850            | 0.884   | -73.0               | 2250            | 0.811   | -94.4               |
| 1900            | 0.871   | -74.6               | 2300            | 0.807   | -94.7               |
| 1950            | 0.868   | 75.4                | 2350            | 0.834   | -94.8               |
| 2000            | 0.878   | -77.1               | 2400            | 0.866   | -97.1               |
| 2050            | 0.892   | -79.6               | 2450            | 0.891   | -100.5              |
| 2100            | 0.897   | 82.5                | 2500            | 0.905   | -104.5              |

# 1.7GHz to 2.5GHz, Direct I/Q Modulator with VGA and PA Driver

**Table 2. LO Input Frequency Range**

| <b>ENX2<br/>LOGIC LEVEL</b> | <b>LO INPUT FREQUENCY RANGE (MHz)</b> |                |
|-----------------------------|---------------------------------------|----------------|
|                             | <b>MAX2720</b>                        | <b>MAX2721</b> |
| Low                         | 850 to 1050                           | 1050 to 1250   |
| High                        | 1700 to 2100                          | 2100 to 2500   |

DC-blocking capacitor that can be part of the matching network. The DROUT open-collector output port requires an external matching network and a pull-up inductor to VCC for proper biasing. The pull-up inductor is incorporated as part of the matching network. See the MAX2720 and MAX2721 *Typical Application Circuit* for recommended component values. Refer to Table 3 for matching to other frequencies.

If the additional gain of the PA driver is not required, disable the PA driver to reduce current consumption. To disable the PA driver, short pin 20 (DRIN) to ground and leave pin 2 unconnected.

## Shutdown

Apply a logic-level high to the  $\overline{\text{SHDN}}$  pin to enable the MAX2720/MAX2721. Apply a logic-level low voltage to disable the device and reduce supply current to less than 0.1 $\mu$ A.

## Applications Information

### Layout Considerations

A properly designed PC board is an essential part of any RF circuit. A ground plane is essential. Keep RF signal lines as short as possible to reduce losses, radiation, and inductance. Use separate, low-inductance vias to the ground plane for each pin. For best performance, solder the exposed pad on the bottom of the device package evenly to the board ground plane. Remove the ground plane under the external VCO and lowpass filters to reduce the effects of parasitic capaci-

tance. In direct I/Q modulator applications, radiated power from the PA can couple into the VCO tank. To reduce PA injection-pulling, the external VCO should be housed in a separate shielded compartment if possible.

### Power-Supply, Logic, and PC Input Bypassing

Proper voltage supply bypassing is essential for high-frequency circuit stability. With the exception of pin 6, bypass all VCC pins with a 470pF capacitor as close to the VCC pins as possible. The decoupling capacitor for pin 6 also serves as part of an on-chip matching network, so it should be chosen to resonate out series inductance on the board. Some empirical adjustment may yield increased output power. See the MAX2720/MAX2721 *Typical Application Circuit* for suggested values.

Bypass the  $\overline{\text{ENX2}}$ ,  $\overline{\text{SHDN}}$ , and PC inputs with a 1000pF capacitor to ground to minimize noise injected into the device. Use a series resistor (10k $\Omega$  typ) to further reduce coupling of high-frequency signals into the device.

Voltage supply layout is also critical to achieve optimum performance. The IC has several RF processing stages that use the various VCC pins, and while they have on-chip decoupling, off-chip interaction between them may degrade gain, linearity, carrier suppression, and output power control range. The supplies associated with pins 2, 6, 15 (MAX2721 only), and 17 lie directly in the RF signal path. Pins 4, 12, and 15 carry LO signal currents, so it is important to keep them from interacting with the RF signal path to prevent poor carrier suppression. The VGA generates discarded signal currents on pin 4, which also need to be kept away from the signal path supplies. Because there is a great deal of gain following from the first RF stage, it is also important to prevent coupling from pins 2, 4, 15, and 17 to pin 6; excessive coupling may degrade stability.

# 1.7GHz to 2.5GHz, Direct I/Q Modulator with VGA and PA Driver


Table 3. PA Driver S-Parameters ( $V_{CC} = 3.0V$ ,  $T_A = +25^{\circ}C$ )

| FREQUENCY (MHz) | S11 MAG | S11 PHASE | S21 MAG | S21 PHASE | S12 MAG | S21 PHASE | S22 MAG | S22 PHASE |
|-----------------|---------|-----------|---------|-----------|---------|-----------|---------|-----------|
| 1700            | 0.321   | 151.6     | 4.708   | 178.1     | 0.092   | 164.7     | 0.162   | -82.4     |
| 1750            | 0.347   | 152.7     | 4.588   | 171.5     | 0.094   | 154.2     | 0.158   | -90.3     |
| 1800            | 0.383   | 152.0     | 4.389   | 161.7     | 0.097   | 147.2     | 0.142   | -99.5     |
| 1850            | 0.418   | 149.4     | 4.370   | 153.5     | 0.093   | 138.2     | 0.123   | -109.2    |
| 1900            | 0.449   | 145.3     | 4.160   | 144.3     | 0.093   | 129.7     | 0.095   | -118.4    |
| 1950            | 0.421   | 140.1     | 3.946   | 135.2     | 0.091   | 128.7     | 0.082   | -100.8    |
| 2000            | 0.425   | 142.8     | 3.801   | 128.4     | 0.096   | 121.2     | 0.091   | -111.0    |
| 2050            | 0.440   | 142.8     | 3.690   | 120.4     | 0.100   | 112.8     | 0.083   | -120.3    |
| 2100            | 0.452   | 142.9     | 3.567   | 112.3     | 0.105   | 104.9     | 0.082   | -128.8    |
| 2150            | 0.470   | 141.3     | 3.492   | 104.2     | 0.102   | 97.2      | 0.066   | -138.0    |
| 2200            | 0.475   | 139.0     | 3.360   | 96.2      | 0.106   | 88.0      | 0.055   | -142.7    |
| 2250            | 0.473   | 136.9     | 3.268   | 87.4      | 0.106   | 84.2      | 0.046   | -138.9    |
| 2300            | 0.456   | 135.8     | 3.176   | 80.4      | 0.110   | 75.9      | 0.051   | -133.9    |
| 2350            | 0.462   | 135.3     | 3.087   | 71.7      | 0.117   | 67.9      | 0.042   | -153.1    |
| 2400            | 0.447   | 132.9     | 3.013   | 63.5      | 0.118   | 59.7      | 0.031   | -141.0    |
| 2450            | 0.437   | 132.2     | 2.929   | 55.4      | 0.123   | 51.6      | 0.026   | -144.9    |
| 2500            | 0.425   | 130.3     | 2.848   | 47.0      | 0.125   | 40.9      | 0.015   | -97.8     |

# 1.7GHz to 2.5GHz, Direct I/Q Modulator with VGA and PA Driver


## Typical Application Circuit

MAX2720/MAX2721



# 1.7GHz to 2.5GHz, Direct I/Q Modulator with VGA and PA Driver

## Pin Configuration




## Chip Information

TRANSISTOR COUNT: 1041

# 1.7GHz to 2.5GHz, Direct I/Q Modulator with VGA and PA Driver

## Package Information



TSSOP-EP

MAX2720/MAX2721

# 1.7GHz to 2.5GHz, Direct I/Q Modulator with VGA and PA Driver

## NOTES

Maxim cannot assume responsibility for use of any circuitry other than circuitry entirely embodied in a Maxim product. No circuit patent licenses are implied. Maxim reserves the right to change the circuitry and specifications without notice at any time.

24 \_\_\_\_\_ **Maxim Integrated Products, 120 San Gabriel Drive, Sunnyvale, CA 94086 408-737-7600**