



# Low-Cost, Micropower, Low-Dropout, High-Output-Current, SOT23 Voltage References

## General Description

The MAX6100–MAX6106 are low-cost, low-dropout (LDO), micropower voltage references. These three-terminal references are available with output voltage options of 1.25V, 1.8V, 2.048V, 2.5V, 3V, 4.096V, and 5V. They feature a proprietary curvature-correction circuit and laser-trimmed, thin-film resistors that result in a low temperature coefficient of 75ppm/°C (max) and an initial accuracy of  $\pm 0.4\%$  (max). These devices are specified over the extended temperature range ( $-40^{\circ}\text{C}$  to  $+85^{\circ}\text{C}$ ).


These series-mode voltage references draw only 90 $\mu\text{A}$  of supply current and can source 5mA and sink 2mA of load current. Unlike conventional shunt-mode (two-terminal) references that waste supply current and require an external resistor, these devices offer a supply current that is virtually independent of the supply voltage (with only a 4 $\mu\text{A}/\text{V}$  variation with supply voltage) and do not require an external resistor. Additionally, these internally compensated devices do not require an external compensation capacitor and are stable with load capacitance. Eliminating the external compensation capacitor saves valuable board area in space-critical applications. Low dropout voltage and supply-independent, ultra-low supply current make these devices ideal for battery-operated, high-performance, low-voltage systems.

The MAX6100–MAX6106 are available in tiny 3-pin SOT23 packages.

## Applications

Portable Battery-Powered Systems  
 Notebook Computers  
 PDAs, GPSs, DMMs  
 Cellular Phones  
 Hard-Disk Drives

## Typical Operating Circuit



## Features

- ◆ Ultra-Small 3-Pin SOT23 Package
- ◆ Low Cost
- ◆ No Output Capacitor Required
- ◆ Stable with Capacitive Loads
- ◆ Load Regulation (2mA Sink): 8mV/mA (max)  
Load Regulation (5mA Source): 0.9mV/mA (max)
- ◆  $\pm 0.4\%$  (max) Initial Accuracy
- ◆ Low 75ppm/°C Temperature Coefficient
- ◆ 125 $\mu\text{A}$  (max) Quiescent Supply Current
- ◆ 50mV Dropout at 1mA Load Current

## Ordering Information


PART	TEMP. RANGE	PIN-PACKAGE	TOP MARK
MAX6100EUR-T	$-40^{\circ}\text{C}$ to $+85^{\circ}\text{C}$	3 SOT23-3	FZID
MAX6101EUR-T	$-40^{\circ}\text{C}$ to $+85^{\circ}\text{C}$	3 SOT23-3	FZGT
MAX6102EUR-T	$-40^{\circ}\text{C}$ to $+85^{\circ}\text{C}$	3 SOT23-3	FZGU
MAX6103EUR-T	$-40^{\circ}\text{C}$ to $+85^{\circ}\text{C}$	3 SOT23-3	FZGV
MAX6104EUR-T	$-40^{\circ}\text{C}$ to $+85^{\circ}\text{C}$	3 SOT23-3	FZGW
MAX6105EUR-T	$-40^{\circ}\text{C}$ to $+85^{\circ}\text{C}$	3 SOT23-3	FZGX
MAX6106EUR-T	$-40^{\circ}\text{C}$ to $+85^{\circ}\text{C}$	3 SOT23-3	FZJR

**Note:** There is a minimum order increment of 2500 pieces for SOT23 packages.

## Selector Guide

PART	OUTPUT VOLTAGE (V)	INPUT VOLTAGE RANGE (V)
MAX6100	1.800	2.5 to 12.6
MAX6101	1.250	2.5 to 12.6
MAX6102	2.500	( $V_{\text{OUT}} + 200\text{mV}$ ) to 12.6
MAX6103	3.000	( $V_{\text{OUT}} + 200\text{mV}$ ) to 12.6
MAX6104	4.096	( $V_{\text{OUT}} + 200\text{mV}$ ) to 12.6
MAX6105	5.000	( $V_{\text{OUT}} + 200\text{mV}$ ) to 12.6
MAX6106	2.048	2.5 to 12.6

## Pin Configuration



# Low-Cost, Micropower, Low-Dropout, High-Output-Current, SOT23 Voltage References

## ABSOLUTE MAXIMUM RATINGS

(Voltages Referenced to GND)

IN	-0.3V to +13.5V
OUT	-0.3V to ( $V_{IN} + 0.3V$ )
Output Short-Circuit to GND or IN ( $V_{IN} < 6V$ )	Continuous
Output Short-Circuit to GND or IN ( $V_{IN} \geq 6V$ )	.60s

Continuous Power Dissipation ( $T_A = +70^\circ\text{C}$ )

3-Pin SOT23 (derate 4.0mW/ $^\circ\text{C}$ above $+70^\circ\text{C}$ )	320mW
Operating Temperature Range	-40 $^\circ\text{C}$ to +85 $^\circ\text{C}$
Storage Temperature Range	-65 $^\circ\text{C}$ to +150 $^\circ\text{C}$
Lead Temperature (soldering, 10s)	+300 $^\circ\text{C}$

Stresses beyond those listed under "Absolute Maximum Ratings" may cause permanent damage to the device. These are stress ratings only, and functional operation of the device at these or any other conditions beyond those indicated in the operational sections of the specifications is not implied. Exposure to absolute maximum rating conditions for extended periods may affect device reliability.

## ELECTRICAL CHARACTERISTICS—MAX6101, $V_{OUT} = 1.25V$

( $V_{IN} = +5V$ ,  $I_{OUT} = 0$ ,  $T_A = T_{MIN}$  to  $T_{MAX}$ , unless otherwise noted. Typical values are at  $T_A = +25^\circ\text{C}$ .) (Note 1)

PARAMETER	SYMBOL	CONDITIONS	MIN	TYP	MAX	UNITS
Output Voltage	$V_{OUT}$	$T_A = +25^\circ\text{C}$	1.245	1.250	1.255	V
Output Voltage Temperature Coefficient (Notes 2, 3)	$TCV_{OUT}$	0 $^\circ\text{C}$ to +70 $^\circ\text{C}$			65	ppm/ $^\circ\text{C}$
		-40 $^\circ\text{C}$ to +85 $^\circ\text{C}$			75	
Line Regulation	$\frac{\Delta V_{OUT}}{\Delta V_{IN}}$	$2.5V \leq V_{IN} \leq 12.6V$			90	$\mu\text{V}/\text{V}$
Load Regulation	$\frac{\Delta V_{OUT}}{\Delta I_{OUT}}$	Sourcing: $0 \leq I_{OUT} \leq 5\text{mA}$			0.9	mV/mA
		Sinking: $-2\text{mA} \leq I_{OUT} \leq 0$			3.0	
OUT Short-Circuit Current	$I_{SC}$	Short to GND		110		mA
		Short to IN		12		
Long-Term Stability	$\frac{\Delta V_{OUT}}{\text{time}}$	1000hr at +25 $^\circ\text{C}$		50		ppm/1000hr
Output Voltage Hysteresis (Note 4)	$\frac{\Delta V_{OUT}}{\text{cycle}}$			130		ppm
<b>DYNAMIC CHARACTERISTICS</b>						
Noise Voltage	$e_{OUT}$	$f = 0.1\text{Hz}$ to 10Hz		13		$\mu\text{Vp-p}$
		$f = 10\text{Hz}$ to 10kHz		15		$\mu\text{V}_{RMS}$
Ripple Rejection	$\frac{\Delta V_{OUT}}{\Delta V_{IN}}$	$V_{IN} = 5V \pm 100\text{mV}$ , $f = 120\text{Hz}$		86		dB
Turn-On Settling Time	$t_R$	To $V_{OUT} = 0.1\%$ of final value, $C_{OUT} = 50\text{pF}$		50		$\mu\text{s}$
<b>INPUT CHARACTERISTICS</b>						
Supply Voltage Range	$V_{IN}$	Guaranteed by line-regulation test	2.5		12.6	V
Quiescent Supply Current	$I_{IN}$			90	125	$\mu\text{A}$
Change in Supply Current	$I_{IN}/V_{IN}$	$2.5V \leq V_{IN} \leq 12.6V$		4	8	$\mu\text{A}/\text{V}$

# Low-Cost, Micropower, Low-Dropout, High-Output-Current, SOT23 Voltage References

## ELECTRICAL CHARACTERISTICS—MAX6100, V<sub>OUT</sub> = 1.8V

(V<sub>IN</sub> = +5V, T<sub>A</sub> = T<sub>MIN</sub> to T<sub>MAX</sub>, unless otherwise noted. Typical values are at T<sub>A</sub> = +25°C) (Note 1)

PARAMETER	SYMBOL	CONDITIONS	MIN	TYP	MAX	UNITS
Output Voltage	V <sub>OUT</sub>	T <sub>A</sub> = +25°C	1.793	1.800	1.807	V
Output Voltage Temperature Coefficient (Notes 2, 3)	TCV <sub>OUT</sub>	0°C to +70°C			65	ppm/°C
		-40°C to +85°C			75	
Line Regulation	$\frac{\Delta V_{OUT}}{\Delta V_{IN}}$	2.5V ≤ V <sub>IN</sub> ≤ 12.6V			200	μV/V
Load Regulation	$\frac{\Delta V_{OUT}}{\Delta I_{OUT}}$	Sourcing: 0 ≤ I <sub>OUT</sub> ≤ 5mA			0.9	mV/mA
		Sinking: -2mA ≤ I <sub>OUT</sub> ≤ 0			4.0	
OUT Short-Circuit Current	I <sub>SC</sub>	Short to GND		110		mA
		Short to IN		12		
Long-Term Stability	$\frac{\Delta V_{OUT}}{\text{time}}$	1000hr at +25°C		50		ppm/1000hr
Output Voltage Hysteresis (Note 4)	$\frac{\Delta V_{OUT}}{\text{cycle}}$			130		ppm
<b>DYNAMIC CHARACTERISTICS</b>						
Noise Voltage	e <sub>OUT</sub>	f = 0.1Hz to 10Hz		22		μVp-p
		f = 10Hz to 10kHz		25		μV <sub>RMS</sub>
Ripple Rejection	$\frac{\Delta V_{OUT}}{\Delta V_{IN}}$	V <sub>IN</sub> = 5V, ±100mV, f = 120Hz		86		dB
Turn-on Settling Time	t <sub>R</sub>	To V <sub>OUT</sub> = 0.1% of final value, C <sub>OUT</sub> = 50pF		100		μs
<b>INPUT CHARACTERISTICS</b>						
Supply Voltage Range	V <sub>IN</sub>	Guaranteed by line-regulation test	2.5		12.6	V
Quiescent Supply Current	I <sub>IN</sub>			90	125	μA
Change in Supply Current	I <sub>IN</sub> /V <sub>IN</sub>	2.5V ≤ V <sub>IN</sub> ≤ 12.6V		4	8	μA/V

MAX6100-MAX6106

# Low-Cost, Micropower, Low-Dropout, High-Output-Current, SOT23 Voltage References

## ELECTRICAL CHARACTERISTICS—MAX6106, $V_{OUT} = 2.048V$

( $V_{IN} = +5V$ ,  $I_{OUT} = 0$ ,  $T_A = T_{MIN}$  to  $T_{MAX}$ , unless otherwise noted. Typical values are at  $T_A = +25^\circ C$ .) (Note 1)

PARAMETER	SYMBOL	CONDITIONS	MIN	TYP	MAX	UNITS
Output Voltage	$V_{OUT}$	$T_A = +25^\circ C$	2.040	2.048	2.056	V
Output Voltage Temperature Coefficient (Notes 2, 3)	$TCV_{OUT}$	$0^\circ C$ to $+70^\circ C$			65	ppm/ $^\circ C$
		$-40^\circ C$ to $+85^\circ C$			75	
Line Regulation	$\Delta V_{OUT} / \Delta V_{IN}$	$2.5V \leq V_{IN} \leq 12.6V$			200	$\mu V/V$
Load Regulation	$\Delta V_{OUT} / \Delta I_{OUT}$	Sourcing: $0 \leq I_{OUT} \leq 5mA$			0.9	mV/mA
		Sinking: $-2mA \leq I_{OUT} \leq 0$			4.0	
OUT Short-Circuit Current	$I_{SC}$	Short to GND		110		mA
		Short to IN		12		
Long-Term Stability	$\Delta V_{OUT} / \text{time}$	1000hr at $+25^\circ C$		50		ppm/1000hr
Output Voltage Hysteresis (Note 4)	$\Delta V_{OUT} / \text{cycle}$			130		ppm
<b>DYNAMIC CHARACTERISTICS</b>						
Noise Voltage	$e_{OUT}$	$f = 0.1Hz$ to $10Hz$		22		$\mu Vp-p$
		$f = 10Hz$ to $10kHz$		25		$\mu V_{RMS}$
Ripple Rejection	$\Delta V_{OUT} / \Delta V_{IN}$	$V_{IN} = 5V \pm 100mV$ , $f = 120Hz$		86		dB
Turn-On Settling Time	$t_R$	To $V_{OUT} = 0.1\%$ of final value, $C_{OUT} = 50pF$		100		$\mu s$
<b>INPUT CHARACTERISTICS</b>						
Supply Voltage Range	$V_{IN}$	Guaranteed by line-regulation test	2.5		12.6	V
Quiescent Supply Current	$I_{IN}$			90	125	$\mu A$
Change in Supply Current	$I_{IN} / V_{IN}$	$2.5 \leq V_{IN} \leq 12.6V$		4	8	$\mu A/V$

# Low-Cost, Micropower, Low-Dropout, High-Output-Current, SOT23 Voltage References

## ELECTRICAL CHARACTERISTICS—MAX6102, V<sub>OUT</sub> = 2.50V

(V<sub>IN</sub> = +5V, I<sub>OUT</sub> = 0, T<sub>A</sub> = T<sub>MIN</sub> to T<sub>MAX</sub>, unless otherwise noted. Typical values are at T<sub>A</sub> = +25°C.) (Note 1)

PARAMETER	SYMBOL	CONDITIONS	MIN	TYP	MAX	UNITS
Output Voltage	V <sub>OUT</sub>	T <sub>A</sub> = +25°C	2.490	2.50	2.510	V
Output Voltage Temperature Coefficient (Notes 2, 3)	TCV <sub>OUT</sub>	0°C to +70°C			65	ppm/°C
		-40°C to +85°C			75	
Line Regulation	$\frac{\Delta V_{OUT}}{\Delta V_{IN}}$	(V <sub>OUT</sub> + 0.2V) ≤ V <sub>IN</sub> ≤ 12.6V			300	μV/V
Load Regulation	$\frac{\Delta V_{OUT}}{\Delta I_{OUT}}$	Sourcing: 0 ≤ I <sub>OUT</sub> ≤ 5mA			0.9	mV/mA
		Sinking: -2mA ≤ I <sub>OUT</sub> ≤ 0			5.0	
Dropout Voltage (Note 5)	$V_{IN} - V_{OUT}$	I <sub>OUT</sub> = 1mA		50	200	mV
OUT Short-Circuit Current	I <sub>SC</sub>	Short to GND		110		mA
		Short to IN		12		
Long-Term Stability	$\frac{\Delta V_{OUT}}{\text{time}}$	1000hr at +25°C		50		ppm/1000hr
Output Voltage Hysteresis (Note 4)	$\frac{\Delta V_{OUT}}{\text{cycle}}$			130		ppm
<b>DYNAMIC CHARACTERISTICS</b>						
Noise Voltage	e <sub>OUT</sub>	f = 0.1Hz to 10Hz		27		μVp-p
		f = 10Hz to 10kHz		30		μV <sub>RMS</sub>
Ripple Rejection	$\frac{\Delta V_{OUT}}{\Delta V_{IN}}$	V <sub>IN</sub> = 5V ± 100mV, f = 120Hz		86		dB
Turn-On Settling Time	t <sub>R</sub>	To V <sub>OUT</sub> = 0.1% of final value, C <sub>OUT</sub> = 50pF		115		μs
<b>INPUT CHARACTERISTICS</b>						
Supply Voltage Range	V <sub>IN</sub>	Guaranteed by line-regulation test	V <sub>OUT</sub> + 0.2		12.6	V
Quiescent Supply Current	I <sub>IN</sub>			90	125	μA
Change in Supply Current	I <sub>IN</sub> /V <sub>IN</sub>	(V <sub>OUT</sub> + 0.2V) ≤ V <sub>IN</sub> ≤ 12.6V		4	8	μA/V

MAX6100-MAX6106

# Low-Cost, Micropower, Low-Dropout, High-Output-Current, SOT23 Voltage References

## ELECTRICAL CHARACTERISTICS—MAX6103, $V_{OUT} = 3.0V$

( $V_{IN} = +5V$ ,  $I_{OUT} = 0$ ,  $T_A = T_{MIN}$  to  $T_{MAX}$ , unless otherwise noted. Typical values are at  $T_A = +25^\circ C$ .) (Note 1)

PARAMETER	SYMBOL	CONDITIONS	MIN	TYP	MAX	UNITS
Output Voltage	$V_{OUT}$	$T_A = +25^\circ C$	2.988	3.000	3.012	V
Output Voltage Temperature Coefficient (Notes 2, 3)	$TCV_{OUT}$	$0^\circ C$ to $+70^\circ C$			65	ppm/ $^\circ C$
		$-40^\circ C$ to $+85^\circ C$			75	
Line Regulation	$\frac{\Delta V_{OUT}}{\Delta V_{IN}}$	$(V_{OUT} + 0.2V) \leq V_{IN} \leq 12.6V$			400	$\mu V/V$
Load Regulation	$\frac{\Delta V_{OUT}}{\Delta I_{OUT}}$	Sourcing: $0 \leq I_{OUT} \leq 5mA$			0.9	mV/mA
		Sinking: $-2mA \leq I_{OUT} \leq 0$			6.0	
Dropout Voltage (Note 5)	$V_{IN} - V_{OUT}$	$I_{OUT} = 1mA$		50	200	mV
OUT Short-Circuit Current	$I_{SC}$	Short to GND		110		mA
		Short to IN		12		
Long-Term Stability	$\frac{\Delta V_{OUT}}{\text{time}}$	1000hr at $+25^\circ C$		50		ppm/1000hr
Output Voltage Hysteresis (Note 4)	$\Delta V_{OUT}/\text{cycle}$			130		ppm
<b>DYNAMIC CHARACTERISTICS</b>						
Noise Voltage	$e_{OUT}$	$f = 0.1Hz$ to $10Hz$		35		$\mu Vp-p$
		$f = 10Hz$ to $10kHz$		40		$\mu V_{RMS}$
Ripple Rejection	$\frac{\Delta V_{OUT}}{\Delta V_{IN}}$	$V_{IN} = 5V \pm 100mV$ , $f = 120Hz$		76		dB
Turn-On Settling Time	$t_R$	To $V_{OUT} = 0.1\%$ of final value, $C_{OUT} = 50pF$		115		$\mu s$
<b>INPUT CHARACTERISTICS</b>						
Supply Voltage Range	$V_{IN}$	Guaranteed by line-regulation test	$V_{OUT} + 0.2$		12.6	V
Quiescent Supply Current	$I_{IN}$			90	125	$\mu A$
Change in Supply Current	$I_{IN}/V_{IN}$	$(V_{OUT} + 0.2V) \leq V_{IN} \leq 12.6V$		4	8	$\mu A/V$

# Low-Cost, Micropower, Low-Dropout, High-Output-Current, SOT23 Voltage References

## ELECTRICAL CHARACTERISTICS—MAX6104, V<sub>OUT</sub> = 4.096V

(V<sub>IN</sub> = +5V, I<sub>OUT</sub> = 0, T<sub>A</sub> = T<sub>MIN</sub> to T<sub>MAX</sub>, unless otherwise noted. Typical values are at T<sub>A</sub> = +25°C.) (Note 1)

PARAMETER	SYMBOL	CONDITIONS	MIN	TYP	MAX	UNITS
Output Voltage	V <sub>OUT</sub>	T <sub>A</sub> = +25°C	4.080	4.096	4.112	V
Output Voltage Temperature Coefficient (Notes 2, 3)	TCV <sub>OUT</sub>	0°C to +70°C			65	ppm/°C
		-40°C to +85°C			75	
Line Regulation	$\frac{\Delta V_{OUT}}{\Delta V_{IN}}$	(V <sub>OUT</sub> + 0.2V) ≤ V <sub>IN</sub> ≤ 12.6V			430	μV/V
Load Regulation	$\frac{\Delta V_{OUT}}{\Delta I_{OUT}}$	Sourcing: 0 ≤ I <sub>OUT</sub> ≤ 5mA			0.9	mV/mA
		Sinking: -2mA ≤ I <sub>OUT</sub> ≤ 0			8.0	
Dropout Voltage (Note 5)	$\frac{V_{IN} - V_{OUT}}{V_{OUT}}$	I <sub>OUT</sub> = 1mA		50	200	mV
OUT Short-Circuit Current	I <sub>SC</sub>	Short to GND		110		mA
		Short to IN		12		
Long-Term Stability	$\frac{\Delta V_{OUT}}{\text{time}}$	1000hr at +25°C		50		ppm/1000hr
Output Voltage Hysteresis (Note 4)	$\frac{\Delta V_{OUT}}{\text{cycle}}$			130		ppm
<b>DYNAMIC CHARACTERISTICS</b>						
Noise Voltage	e <sub>OUT</sub>	f = 0.1Hz to 10Hz		50		μVp-p
		f = 10Hz to 10kHz		50		μV <sub>RMS</sub>
Ripple Rejection	$\frac{\Delta V_{OUT}}{\Delta V_{IN}}$	V <sub>IN</sub> = 5V ±100mV, f = 120Hz		72		dB
Turn-On Settling Time	t <sub>R</sub>	To V <sub>OUT</sub> = 0.1% of final value, C <sub>OUT</sub> = 50pF		190		μs
<b>INPUT CHARACTERISTICS</b>						
Supply Voltage Range	V <sub>IN</sub>	Guaranteed by line-regulation test	V <sub>OUT</sub> + 0.2		12.6	V
Quiescent Supply Current	I <sub>IN</sub>			90	125	μA
Change in Supply Current	I <sub>IN</sub> /V <sub>IN</sub>	(V <sub>OUT</sub> + 0.2V) ≤ V <sub>IN</sub> ≤ 12.6V		4	8	μA/V

MAX6100-MAX6106

# Low-Cost, Micropower, Low-Dropout, High-Output-Current, SOT23 Voltage References

## ELECTRICAL CHARACTERISTICS—MAX6105, $V_{OUT} = 5.000V$

( $V_{IN} = +5.5V$ ,  $I_{OUT} = 0$ ,  $T_A = T_{MIN}$  to  $T_{MAX}$ , unless otherwise noted. Typical values are at  $T_A = +25^\circ C$ .) (Note 1)

PARAMETER	SYMBOL	CONDITIONS	MIN	TYP	MAX	UNITS
Output Voltage	$V_{OUT}$	$T_A = +25^\circ C$	4.980	5.000	5.020	V
Output Voltage Temperature Coefficient (Notes 2, 3)	$TCV_{OUT}$	$0^\circ C$ to $+70^\circ C$			65	ppm/ $^\circ C$
		$-40^\circ C$ to $+85^\circ C$			75	
Line Regulation	$\frac{\Delta V_{OUT}}{\Delta V_{IN}}$	$(V_{OUT} + 0.2V) \leq V_{IN} \leq 12.6V$			550	$\mu V/V$
Load Regulation	$\frac{\Delta V_{OUT}}{\Delta I_{OUT}}$	Sourcing: $0 \leq I_{OUT} \leq 5mA$			0.9	mV/mA
		Sinking: $-2mA \leq I_{OUT} \leq 0$			10	
Dropout Voltage (Note 5)	$V_{IN} - V_{OUT}$	$I_{OUT} = 1mA$		50	200	mV
OUT Short-Circuit Current	$I_{SC}$	Short to GND		110		mA
		Short to IN		12		
Long-Term Stability	$\frac{\Delta V_{OUT}}{\text{time}}$	1000hr at $+25^\circ C$		50		ppm/1000hr
Output Voltage Hysteresis (Note 4)	$\frac{\Delta V_{OUT}}{\text{cycle}}$			130		ppm
<b>DYNAMIC CHARACTERISTICS</b>						
Noise Voltage	$e_{OUT}$	$f = 0.1Hz$ to $10Hz$		60		$\mu V_{p-p}$
		$f = 10Hz$ to $10kHz$		60		$\mu V_{RMS}$
Ripple Rejection	$\frac{\Delta V_{OUT}}{\Delta V_{IN}}$	$V_{IN} = 6V \pm 100mV$ , $f = 120Hz$		65		dB
Turn-On Settling Time	$t_R$	To $V_{OUT} = 0.1\%$ of final value, $C_{OUT} = 50pF$		300		$\mu s$
<b>INPUT CHARACTERISTICS</b>						
Supply Voltage Range	$V_{IN}$	Guaranteed by line-regulation test	$V_{OUT} + 0.2$		12.6	V
Quiescent Supply Current	$I_{IN}$			90	125	$\mu A$
Change in Supply Current	$I_{IN}/V_{IN}$	$(V_{OUT} + 0.2V) \leq V_{IN} \leq 12.6V$		4	8	$\mu A/V$

**Note 1:** Devices are 100% production tested at  $T_A = +25^\circ C$  and are guaranteed by design from  $T_A = T_{MIN}$  to  $T_{MAX}$  by correlation to sample units characterized over temperature.

**Note 2:** Temperature coefficient is specified by the “box” method; i.e., the maximum  $\Delta V_{OUT}$  is divided by the maximum  $\Delta t$ .

**Note 3:** Not production tested. Guaranteed by design.

**Note 4:** Thermal hysteresis is defined as the change in  $+25^\circ C$  output voltage before and after temperature cycling of the device from  $T_A = T_{MIN}$  to  $T_{MAX}$ .










**Note 5:** Dropout voltage is the minimum input voltage at which  $V_{OUT}$  changes  $\leq 0.2\%$  from  $V_{OUT}$  at  $V_{IN} = 5.0V$  ( $V_{IN} = 5.5V$  for MAX6105).

# Low-Cost, Micropower, Low-Dropout, High-Output-Current, SOT23 Voltage References

## Typical Operating Characteristics

( $T_A = +25^\circ\text{C}$ , unless otherwise noted.)










MAX6100-MAX6106



# Low-Cost, Micropower, Low-Dropout, High-Output-Current, SOT23 Voltage References

## Typical Operating Characteristics (continued)

( $T_A = +25^\circ\text{C}$ , unless otherwise noted.)









# Low-Cost, Micropower, Low-Dropout, High-Output-Current, SOT23 Voltage References

## Typical Operating Characteristics (continued)

( $T_A = +25^\circ\text{C}$ , unless otherwise noted.)


MAX6100-MAX6106



# Low-Cost, Micropower, Low-Dropout, High-Output-Current, SOT23 Voltage References

## Typical Operating Characteristics (continued)

( $T_A = +25^\circ\text{C}$ , unless otherwise noted.)



### Pin Description

PIN	NAME	FUNCTION
1	IN	Input Voltage
2	OUT	Reference Output
3	GND	Ground

### Applications Information

#### Input Bypassing

For the best line-transient performance, decouple the input with a 0.1µF ceramic capacitor as shown in the *Typical Operating Circuit*. Locate the capacitor as close to IN as possible. Where transient performance is less important, no capacitor is necessary.

#### Output/Load Capacitance

Devices in the MAX6100 family do not require an output capacitance for frequency stability. They are stable for any capacitive load when sourcing less than 200µA. When sourcing greater than 200µA, the output may become unstable with capacitive loads between 0.5nF and 50nF. In applications where the load or the supply can experience step changes, an output capacitor will reduce the amount of overshoot (undershoot) and improve the circuit's transient response. Many applications do not require an external capacitor, and the MAX6100 family can offer a significant advantage in these applications when board space is critical.

#### Supply Current

The quiescent supply current of the series-mode MAX6100 family is typically 90µA and is virtually independent of the supply voltage, with only a 8µA/V (max) variation with supply voltage. Unlike series references, shunt-mode references operate with a series resistor connected to the power supply. The quiescent current of a shunt-mode reference is thus a function of the input voltage. Additionally, shunt-mode references have to be biased at the maximum-expected load current, even if the load current is not present at the time. In the MAX6100 family, the load current is drawn from the input voltage only when required, so supply current is not wasted and efficiency is maximized at all input voltages. This improved efficiency reduces power dissipation and extends battery life. When the supply voltage is below the minimum specified input voltage (as during turn-on), the devices can draw up to 400µA beyond the nominal supply current. The input voltage source must be capable of providing this current to ensure reliable turn-on.

#### Output Voltage Hysteresis

Output voltage hysteresis is the change of output voltage at  $T_A = +25^\circ\text{C}$  before and after the device is cycled over its entire operating temperature range. Hysteresis is caused by differential package stress appearing across the bandgap core transistors. The typical temperature hysteresis value is 130ppm.

# Low-Cost, Micropower, Low-Dropout, High-Output-Current, SOT23 Voltage References

## Turn-On Time

These devices typically turn on and settle to within 0.1% of their final value in 50 $\mu$ s to 300 $\mu$ s. The turn-on time can increase up to 1.5ms with the device operating at the minimum dropout voltage and the maximum load.

## Chip Information

TRANSISTOR COUNT: 117

## Package Information

NOTES:  
 1. D&E DO NOT INCLUDE MOLD FLASH.  
 2. MOLD FLASH OR PROTRUSIONS NOT TO EXCEED .15mm (.006")  
 3. CONTROLLING DIMENSION: MILLIMETER

DIM	INCHES		MILLIMETERS	
	MIN	MAX	MIN	MAX
A	0.031	0.047	0.787	1.194
A1	0.001	0.005	0.025	0.127
B	0.014	0.022	0.356	0.559
C	0.0034	0.006	0.086	0.152
D	0.105	0.120	2.667	3.048
E	0.047	0.055	1.194	1.397
e	0.070	0.080	1.778	2.032
H	0.082	0.098	2.083	2.489
L	0.004	0.012	0.102	0.305
S	0.017	0.022	0.432	0.559
$\alpha$	0°	8°	0°	8°

**MAXIM**

PROPRIETARY INFORMATION

TITLE: PACKAGE OUTLINE, SOT-23, 3L

APPROVAL	DOCUMENT CONTROL NO.	REV	1/1
	21-0051	C	

SOTF03LEPS

Maxim cannot assume responsibility for use of any circuitry other than circuitry entirely embodied in a Maxim product. No circuit patent licenses are implied. Maxim reserves the right to change the circuitry and specifications without notice at any time.

Maxim Integrated Products, 120 San Gabriel Drive, Sunnyvale, CA 94086 408-737-7600 13