

MN1873265

Type			MN1873265
ROM (x8-bit)			32K
RAM (x8-bit)			480
Minimum Instruction Execution Time			0.5µs at 2/3 frequency dividing (at 4.5 to 5.5V, 12MHz)
Interrupts			• RESET • External 0 • External 1 • Timer 0 • Timer 1 • Timer 2 • Remote Control • Line 21 • COSD
Timer Counter			Timer Counter 0 : 8-bit x 1 Clock Source 1/1, 1/4, 1/16, 1/64 of System Clock Interrupt Source Overflow of Timer Counter 0 Timer Counter 1 : 8-bit x 1 Clock Source 1/2, 1/16, 1/64, 1/256, 1/512 of System Clock Interrupt Source Overflow of Timer Counter 1 Time Base Counter Clock Source 1/4096 of System Clock Interrupt Source 1/1, 1/2, 1/4, 1/8 of Timer Counter 2 Watchdog
I/O Pins	I/O	21	• Common use 3
	Input	1	• Common use 1
	High Voltage Output	7	• Nch Open-drain (Breakdown Voltage 12V) 7
A/D Inputs			5-bit x 7ch (without S/H)
PWM			14-bit x 1ch (Repetition Cycle 16µs, at 12MHz), 8-bit x 8ch (Repetition Cycle 32µs, at 12MHz), 7-bit x 1ch (Repetition Cycle 16µs, at 12MHz)
Special Ports			Remote Control Reception
CRTC			Single OSD built-in (Caption OSD 12 x 26, 176 letters)
Notes			Remote Control Data Detection Circuit built-in
Package			SDIP064-P-0750

Electrical Characteristics


A/D Converter Characteristics

Parameter	Symbol	Condition	Limit			Unit
			min	typ	max	
A/D Conversion Time	TAD	fosc=12MHz	9			µs
Analog Input Voltage	VAD		VSS		VDD	V

(Ta= -20 to +70°C, VDD=5.0V, VSS=0V)

Support Tool

In-Circuit Emulator	PX-ICE1870 / 80 + PX-PRB1876476
EPROM built-in Type	Type MN18P76476
	ROM (x 8-bit) 64K
	RAM (x 8-bit) 928
	Minimum Instruction Execution Time 0.5μs (at 4.5 to 5.5V, 12MHz)
	Package SDIP064-P-0750
Pin Assignment	



SDIP064-P-0750