

MN1874083

Type		MN1874083	
ROM (x8-bit)		40K	
RAM (x8-bit)		640	
Minimum Instruction Execution Time		0.5µs at 2/3 frequency dividing (at 4.5 to 5.5V, 12MHz)	
Interrupts		• RESET • External 0 • External 1 • Timer 0 • Timer 1 • Timer 2 • I ² C • Remote Control • Line 21 • COSD	
Timer Counter		Timer Counter 0 : 8-bit x 1 Clock Source 1/1, 1/4, 1/16, 1/64 of System Clock Interrupt Source Overflow of Timer Counter 0 Timer Counter 1 : 8-bit x 1 Clock Source 1/2, 1/16, 1/64, 1/256, 1/512 of System Clock Interrupt Source . . . Overflow of Timer Counter 1 Time Base Counter Clock Source 1/4096 of System Clock Interrupt Source 1/1, 1/2, 1/4, 1/8 of Timer Counter 2 Watchdog	
Serial Interface		I²C x 1 (Two bus line system)	
I/O Pins	I/O	21	• Common use 5
	Input	1	• Common use 1
	Output	7	• Nch Open-drain 7
A/D Inputs		5-bit x 7ch (without S/H)	
PWM		14-bit x 1ch (Repetition Cycle 16µs, at 12MHz), 8-bit x 8ch (Repetition Cycle 32µs, at 12MHz), 7-bit x 1ch (Repetition Cycle 16µs, at 12MHz) (All PWM are 5V , not connectable to 12V systems)	
Special Ports		Remote Control Reception	
CRTC		Single OSD built-in (Caption OSD 12 x 26, 256 letters)	
Notes		Remote Control Data Detection Circuit built-in, On-chip synchronous separator for caption decoder, ROM Correction Circuit built-in	
Package		SDIP064-P-0750	

Electrical Characteristics

A/D Converter Characteristics


Parameter	Symbol	Condition	Limit			Unit
			min	typ	max	
A/D Conversion Time	TAD	fosc=12MHz	9			µs
Analog Input Voltage	VAD		VSS		VDD	V

(Ta= -20 to +70°C, VDD=5.0V, VSS=0V)

Support Tool

In-Circuit Emulator	PX-ICE1870 / 80 + PX-PRB1879682	
EPROM built-in Type	Type	MN18P79682
	ROM (x 8-bit)	96K
	RAM (x 8-bit)	1248
	Minimum Instruction Execution Time	0.333μs (at 4.5 to 5.5V, 12MHz)
	Package	SDIP064-P-0750

Pin Assignment



SDIP064-P-0750