

MN1879682

Type			MN1879682
ROM (x8-bit)			96K
RAM (x8-bit)			1248
Minimum Instruction Execution Time			0.5µs / 0.333µs (at 4.5 to 5.5V, 12MHz) selectable
Interrupts			• RESET • External 0 • External 1 • External 2 • External 3 • Timer 0 • Timer 1 • Timer 2 • I²C • Serial • Remote Control • Line 21 • MOSD • COSD
Timer Counter			Timer Counter 0 : 8-bit x 1 Clock Source 1/1, 1/4, 1/16, 1/64 of System Clock, Counts external input (P54 input) Interrupt Source Overflow of Timer Counter 0 Timer Counter 1 : 8-bit x 1 Clock Source 1/2, 1/16, 1/64, 1/256, 1/512 of System Clock Interrupt Source Overflow of Timer Counter 1 Time Base Counter Clock Source 1/4096 of System Clock Interrupt Source 1/1, 1/2, 1/4, 1/8 of Timer Counter 2 Watchdog Counter for Clock (Clock function) AC Counter
Serial Interface			Serial 0 : 8-bit x 1 (Transmission/Reception of variable bit length, Transfer direction of MSB/LSB selectable, Clock Polarity selectable, Start Condition function, Data flow unidirectional / bidirectional selectable) Clock Source System Clock I²C x 1 (Two bus line system)
I/O Pins	I/O	40	• Common use 33
	Input	3	• Common use 3
	Output	7	• Nch Open-drain 7
A/D Inputs			5/7-bit x 10ch (without S/H)
PWM			14-bit x 1ch (Repetition Cycle 16µs, at 12MHz), 8-bit x 8ch (Repetition Cycle 32µs, at 12MHz), 7-bit x 1ch (Repetition Cycle 16µs, at 12MHz) (All PWM are 5V , not connectable to 12V systems)
Special Ports			Hsync Detection, Remote Control Reception
CRTC			Double OSD built-in (Menu OSD 12 x 18, 512 letters, Caption OSD 12 x 26, 176 letters)
Notes			Remote Control Data Detection Circuit built-in, On-chip synchronous separator for caption decoder
Package			SDIP064-P-0750

Electrical Characteristics

A/D Converter Characteristics

Parameter	Symbol	Condition	Limit			Unit
			min	typ	max	
A/D Conversion Time	TAD	fosc=12MHz	9/12			μs
Analog Input Voltage	VAD		VSS		VDD	V

(Ta= -20 to +70°C, VDD=5.0V, VSS=0V)

Support Tool


In-Circuit Emulator

PX-ICE1870 / 80 + PX-PRB1879682

EPROM built-in Type

Type	MN18P79682
ROM (x 8-bit)	96K
RAM (x 8-bit)	1248
Minimum Instruction Execution Time	0.5μs / 0.333μs (at 4.5 to 5.5V, 12MHz) Selectable
Package	SDIP064-P-0750

Pin Assignment



SDIP064-P-0750

※ P04 • IRQ0 pin

TYPE A	Stand-by function is available	Input pin
TYPE B	Stand-by function is not available	I/O pin